

**NEW MEXICO OIL CONSERVATION COMMISSION  
WELL LOCATION AND ACREAGE DEDICATION PLAT**

Form C-102  
Supersedes C-128  
Effective 1-1-65

All distances must be from the outer boundaries of the Section.

|  |  |                             |  |  |                      |
|--|--|-----------------------------|--|--|----------------------|
| Operator<br><b>YATES PETROLEUM CORPORATION</b>   |  |                             | Lease<br><b>Hill View AHE Federal</b>    |  | Well No.<br><b>8</b> |
| Unit Letter<br><b>P</b>  | Section<br><b>14</b>                       | Township<br><b>20 South</b> | Range<br><b>24 East</b>                  | County<br><b>Eddy County, N.M.</b>     |                      |
| Actual Footage Location of Well:<br><b>660</b> feet from the <b>South</b> line and <b>660</b> feet from the <b>East</b> line |  |                             |  |  |                      |
| Ground Level Elev.<br><b>3613.</b>   | Producing Formation<br><b>Cisco Canyon</b> |                             | Pool<br><b>S. Dagger Draw Upper Penn</b> | Dedicated Acreage:<br><b>320</b> Acres |                      |

1. Outline the acreage dedicated to the subject well by colored pencil or hachure marks on the plat below.
2. If more than one lease is dedicated to the well, outline each and identify the ownership thereof (both as to working interest and royalty).
3. If more than one lease of different ownership is dedicated to the well, have the interests of all owners been consolidated by communitization, unitization, force-pooling, etc?

☐ Yes ☐ No If answer is "yes," type of consolidation \_\_\_\_\_

If answer is "no," list the owners and tract descriptions which have actually been consolidated. (Use reverse side of this form if necessary.) \_\_\_\_\_

No allowable will be assigned to the well until all interests have been consolidated (by communitization, unitization, forced-pooling, or otherwise) or until a non-standard unit, eliminating such interests, has been approved by the Commission.

|  |  |  |  |
|--|--|--|--|
|  |  |  |  |
|--|--|--|--|

**CERTIFICATION**

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief.

*Ken Beardemphl*


Name  
**Ken Beardemphl**

Position  
**Landman**

Company  
**Yates Petroleum Corporation**

Date  
**12-4-90**

I hereby certify that the well location shown on this plat was obtained from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my knowledge and belief.



Date Surveyed  
**November 28, 1990**


Registered Professional Engineer and/or Land Surveyor

*Dan R. Reddy*

Certificate No.

**NM PE&PS NO. 5412**

0 330 660 990 1320 1650 1980 2310 2640 2000 1500 1000 500 0



THE FOLLOWING CONSTITUTE MINIMUM BLOWOUT PREVENTER REQUIREMENTS

1. All preventers to be hydraulically operated with secondary manual control installed prior to drilling out from under casing.
2. Choke outlet to be a minimum of 3" diameter.
3. Kill line to be of all steel construction of 2" minimum diameter.
4. All connections from operating manifolds to preventers to be all steel. hole or tube a minimum of one inch in diameter.
5. The available closing pressure shall be at least 15% in excess of that required with sufficient volume to operate the B.O.P.'s.
6. All connections to and from preventer to have a pressure rating equivalent to that of the B.O.P.'s.
7. Inside blowout preventer to be available on rig floor.
8. Operating controls located a safe distance from the rig floor.
9. Hole must be kept filled on trips below intermediate casing.

EXHIBIT  
B