

OIL CONSERVATION DIVISION

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.

30-007-20085

5. Indicate Type of Lease

STATE ☐

FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☐

GAS
WELL ☐

OTHER Coal methane

2. Name of Operator

Pennzoil Exploration and Production Company

3. Address of Operator

P.O. Box 2967, Houston, TX 77252

7. Lease Name or Unit Agreement Name

Van Bremmer Canyon
3019

8. Well No.

311G

9. Pool name or Wildcat

Wildcat

4. Well Location

Unit Letter G : 1633 Feet From The east Line and 2193 Feet From The north Line

Section 31

Township 30N

Range 19E

NMPM

Colfax

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

7692 GR

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☒

OTHER: Completed drilling ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

6-01-89 Spud

6-02-89 Drilled 14 3/4" hole to 44'. Set and cement 2 jts (43'), 11 3/4", 42 lb, H-40, ST&C conductor w/60 sks, class "G" w/2% CaCl @ 15.8 PPG. Cement to surface.

6-04-89 Drilled 11" hole to 333'. Set and cement 12 jts (327') 8 5/8", 24 lb, J-55, ST&C w/300sks, class "G" w/2% CaCl @ 15.8 PPG cement to surface.

6-18-89 Test casing and BOP w/600 psi for 30 min. No pressure drop.

6-21-89 Drill to 1675' on air. Switch to mud, 7 7/8 hole.

6-23-89 Drill to 2018' on mud, 7 7/8" hole.

6-24-89 Cored 2018' to 2042'.

6-25-89 Drill 7 7/8" hole to 2200'.

6-26-89 Set and cement 81 jts (2174.54') 5 1/2" 17 lbs, J-55, LT&C casing w/462 sks silicalite cement @ 11 PPG. Cement to surface. Bump plug w/1000 psi. Well shut in waiting on completion.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE L. D. Williamson TITLE OPERATIONS Supt DATE 6-29-89

TYPE OR PRINT NAME LARRY D. WILLIAMSON TELEPHONE NO. 505-376-2817

(This space for State Use)

APPROVED BY R. E. Johnson DISTRICT SUPERVISOR DATE 7-14-89

CONDITIONS OF APPROVAL, IF ANY: