

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 87240
District II
811 South First, Artesia, NM 87210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised March 25, 1999

OIL CONSERVATION DIVISION
2040 South Pacheco
Santa Fe, NM 87505

WELL API NO.

30-007-20103

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name:

VPR 'A'

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH
PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☒ Other COALBED METHANE

2. Name of Operator

EL PASO ENERGY RATON, L.L.C.

3. Address of Operator

P.O. BOX 190; RATON, NM 87740

8. Well No. 25

9. Pool name or Wildcat

4. Well Location

Unit Letter A: 660' feet from the NORTH line and 990' feet from the EAST line

Section 34 Township 32N Range 19E NMPM COLFAX County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)
8058' (GR)

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: RE-ENTRY & COMPLETION ☒

12.

1/14-15/00 Drill out cement plugs. Clean out to 2420'.

3/27-30/00 Perforate 1490'-1491'. Cement squeezed with 131 sxs. Ran CBL.

5/09-22/00 Perforate 600'-601' & 1120'-1121'. Cement sqzd with 42 sxs via tubing & 52 sxs via casing. Clean out to 2420'
Perforate 910'-911'. Cement sqzd with 50 sxs. Repeated cement squeeze with 50 sxs. Ran CBL 1500'-surface.
Clean out to 2410'

5/28/00 Perforate: 2332' - 2334' & 2316' - 2318'. All 4 spf.

6/11/00 Perforate: 2307' - 2311', 2266' - 2270', 2212' - 2218'. All 4spf.

6/13/00 Stimulate: 30000# 20/40 & 90000# 12/20 Sand with 680000 scf N2 70 Quality foam.

6/14/00 Perforate: 1354' - 1358', 1281' - 1285', 1272' - 1276'. All 4spf.

6/15/00 Stimulate: 20000# 20/40 & 50000# 12/20 Sand with 220000 scf N2 70 Quality foam.

6/16/00 Perforate: 1197'-1201', 1154'-1158', 1097'-1101', 1060'-1068', 974'-979', 936'-942', & 930'-932'. All 4 spf.
Stimulate: 40000# 20/40 & 155000# 12/20 Sand with 1025000 scf N2 70 Quality foam.

6/25/00 Perforate: 722'-726', 693'-697', 659'-663'. All 4spf.

6/27/00 Stimulate: 20000# 20/40 & 80000# 12/20 Sand with 545000 scf N2 70 Quality foam.

7/11-13/00 Clean out to 2410'. Ran tubing & rods. Well ready for production.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Joel L. Pettit TITLE WELL SITE SUPERVISOR DATE 09/01/00

Type or print name: JOEL L. PETTIT

Telephone No.: (505) 445-4620

(This space for State use)

APPROVED BY R. E. Johnson TITLE DISTRICT SUPERVISOR DATE 9/6/00

Conditions of approval, if any: