

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 87240
District II
811 South First, Artesia, NM 87210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised March 25, 1999

OIL CONSERVATION DIVISION
2040 South Pacheco
Santa Fe, NM 87505

WELL API NO. 30-007-20124
5. Indicate Type of Lease STATE ☐ FEE ☒
6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		7. Lease Name or Unit Agreement Name: VPR 'A'
1. Type of Well: Oil Well ☐ Gas Well ☐ Other Coalbed Methane		
2. Name of Operator SONAT RATON, L.L.C.	8. Well No. - 10	
3. Address of Operator P.O. Box 190; Raton, NM 87740	9. Pool name or Wildcat	
4. Well Location Unit Letter T : 1453.55 feet from the South line and 993.42 feet from the East line Section 1 Township 31 N Range 19 E NMPM Colfax County		
10. Elevation (Show whether DR, RKB, RT, GR, etc.) 8214.6'(GR)		

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data			
NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	MULTIPLE COMPLETION ☐	CASING TEST AND CEMENT JOB ☐	
OTHER: ☐		OTHER: ☐	COMPLETION ☒

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

Perforate casing 1836' - 1839' W/4 SPF and frac W/ 50,000 lbs. of sand.
Set RBF @ 1700'
Perforate casing 1396' - 1399' W/4 SPF and frac w/50,000 lbs. of sand.
Set RBF @ 1360'
Perforate casing 1346' - 1349' W/4 SPF and frac w/25,000 lbs. of sand.
Set RBP @ 1260'
Perforate casing 1146 - 1148, 1182 - 1186 W/4 SPF and frac W/50,000 lbs. of sand.
Set RBF @ 1128'
Perforate casing 1111-1121 W/4 SPF and frac W/75,000 lbs of sand
ITES mixed & Pumped 94 sks of Midcon 2 plus additives down the annules, clean out to 1890'
Run production equipment (PC Pump).

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE DR Lankford TITLE Senior Petroleum Engineer DATE 9/29/99

Type or print name: Donald R. Lankford Telephone No. (505) 425-1620

(This space for State use)
APPROVED BY Ry Ephum TITLE **DISTRICT SUPERVISOR** DATE 9/30/99
Conditions of approval, if any: