




AREA 640 ACRES
LOCATE WELL CORRECTLY

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

WELL RECORD

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPPLICATE.

General Crude Oil Company
(Company or Operator)

R. L. Spires
(Lease)

Well No. 1, in NW 1/4 of SE 1/4 of Sec. 22, T-10-N, R-22-E, NMPM.
Wildcat Pool, Guadalupe County.

Well is 1980 feet from East line and 198 feet from South line
of Section 22. If State Land the Oil and Gas Lease No. is Not applicable

Drilling Commenced April 1, 1956. Drilling was Completed June 28, 1956.

Name of Drilling Contractor La Mance Drilling Company
Address Box 2686, Midland, Texas

Elevation above sea level at Top of Tubing Head 4959 Derrick Floor. The information given is to be kept confidential until
Not applicable, 19

OIL SANDS OR ZONES

No. 1, from None to No. 4, from to
No. 2, from to No. 5, from to
No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from None to feet.
No. 2, from to feet.
No. 3, from to feet.
No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
13 3/8	54.5	New	265	Halliburton	None	None	Surface
9 5/8	32.3	New	3082	Halliburton	None	None	Intermediate

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
17 1/2	13 3/8	265	300	Pump & Plug	9.0#/gal.	Circ. cement to surf.
12 1/4	9 5/8	3082	1200	Pump & Plug	11.7#/gal.	---

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

Well was non-productive.

Result of Production Stimulation

Depth Cleaned Out

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0 feet to 7667 feet, and from feet to feet.
Cable tools were used from None feet to feet, and from feet to feet.

PRODUCTION

Put to Producing None, 19

OIL WELL: The production during the first 24 hours was barrels of liquid of which was oil; % was emulsion; % water; and % was sediment. A.P.I. Gravity

GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of liquid Hydrocarbon. Shut in Pressure lbs.

Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):
Central Eastern New Mexico Northwestern New Mexico

T. Any		T. Record		T. Ojo Alamo
T. Salt Santa Rosa	561	T. XXXXX		T. Kirtland-Fruitland
B. Salt Permian	862	T. XXXXXX		T. Farmington
T. XXXXX		T. XXXXXX		T. Pictured Cliffs
T. XXXXX		T. XXXXX		T. Menefee
T. XXXXX		T. XXXXXX		T. Point Lookout
T. XXXXXX		T. XXXXXX		T. Mancos
T. San Andres	1065	T. XXXXXX		T. Dakota
T. Glorieta	1564	T. Limestone (?)	6460	T. Morrison
T. XXXXXX Yaso	1920	T. Greenstone Schist	7440	T. Penn
T. Tubbs	2856	T.		T.
T. XXXX Granite Wash	3492	T.		T.
T. Penn	4933(?)	T.		T.
T. XXXXX		T.		T.

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	25	25	Surface Soil	5205	5640	435	Layers of Granite Wash with interbedded shale
25	150	125	Sand and Shale				
150	165	151	Red Shale	5640	5720	80	Limestone
165	310	145	Sand w/shale stringers	5720	6460	740	Alternate beds granite wash and shale.
310	540	250	Shale w/gyp stringers				
540	565	25	Sand	6460	7440	980	Alternate beds shale, sandy shale, limestone and granite wash.
565	590	25	Shale				
590	680	91	Sand w/shale and lime stringers.				
680	1065	385	Shale w/sandy shale and lime stringers.	7440	7667		Greenstone schist
1065	1330	265	Lime, dolomite & anhydrite				
1330	1420	90	Sand w/shale & dolomite				
1420	1565	145	Dolomite				
1565	1920	255	Sand w/shale, dolomite				
1920	2855	935	Salt, Anhydrite & shale				
2855	3495	640	Shaly sand with occasional anhydrite stringers.				
3495	4930	1435	Alternate shale and shaly sand (granite Wash)				
4930	5205	275	Limestone with stringers of shale and granite wash				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

June 29, 1956

Company or Operator General Crude Oil Company
Name F. A. Hunter

Address 314 Commerce Building, Abilene, Texas
Position or Title District Production Superintendent