



Form C-103
 Supersedes Old
 C-102 and C-103
 Effective 1-1-65

NEW MEXICO OIL CONSERVATION COMMISSION

SEP 12 1977

| | | |
|-----------------------|--|-------------------------------------|
| N. OF COPIES RECEIVED | | |
| DISTRIBUTION | | |
| SANTA FE | | |
| FILE | | <input checked="" type="checkbox"/> |
| U.S.G.S. | | |
| LAND OFFICE | | |
| OPERATOR | | |

5a. Indicate Type of Lease
 State Fee
 5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
 (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT ..." (FORM C-101) FOR SUCH PROPOSALS.)

| | |
|---|---|
| 1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER _____ | 7. Unit Agreement Name |
| 2. Name of Operator H. Axelrod (Kenneth M. Axelrod) | 8. Farm or Lease Name Beller (Libby) |
| 3. Address of Operator Drawer A, Borger, Texas 79007 | 9. Well No. |
| 4. Location of Well UNIT LETTER 0 545 N FEET FROM THE S LINE AND 480 W FEET FROM THE E LINE, SECTION SW/4 SE/4 1 20 RANGE 30 E NMPM. | 10. Field and Pool, or Wildcat Wildcat |
| 11. Elevation (Show whether DF, RT, GR, etc.) | 12. County Harding |

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

| | | | |
|--|---|---|--|
| PERFORM REMEDIAL WORK <input type="checkbox"/> | PLUG AND ABANDON <input type="checkbox"/> | REMEDIAL WORK <input type="checkbox"/> | ALTERING CASING <input type="checkbox"/> |
| TEMPORARILY ABANDON <input type="checkbox"/> | CHANGE PLANS <input type="checkbox"/> | COMMENCE DRILLING OPNS. <input type="checkbox"/> | PLUG AND ABANDONMENT <input checked="" type="checkbox"/> |
| PULL OR ALTER CASING <input type="checkbox"/> | OTHER <input type="checkbox"/> | CASING TEST AND CEMENT JOB <input type="checkbox"/> | |

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Mix and pump 25 sacks Class A Cement from T.D. to 820'. Filled 8-1/4" casing with 8.5 lb. Drilling mud with 4% Gel up to approximately 15' of ground level topped with 5 sacks Class A Cement with marker installed in cement. Location was cleaned and restored.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Kenneth M. Axelrod TITLE operator DATE 5 Sept 77

APPROVED BY Carl Wang TITLE SENIOR PETROLEUM GEOLOGIST DATE 9/12/77

CONDITIONS OF APPROVAL, IF ANY: