

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA-FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

10 13.8

5a. Indicate Type of Lease  
State  Fee

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT ..." (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Carbon Dioxide	7. Unit Agreement Name
2. Name of Operator Cities Service Company	8. Farm or Lease Name Fort Union
3. Address of Operator P.O. Box 1919 Midland, TX 79702	9. Well No. 2
4. Location of Well UNIT LETTER <u>H</u> , <u>1980</u> FEET FROM THE <u>North</u> LINE AND <u>660</u> FEET FROM THE <u>East</u> LINE, SECTION <u>18</u> TOWNSHIP <u>19N</u> RANGE <u>19E</u> N.M.P.M.	10. Field and Pool, or Wildcat Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) 6675' GR	12. County Mora

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

T.D. 2725', sand.

Set 66 joints (2700.70') of 5-1/2" 14#, K55, 8rd, ST&C Casing at 2715' and cemented with 200 sacks Class C Thick set w/10# Gilsonite, 1/2# Flocele and 2% CaCl<sub>2</sub>, 480 sacks HOWCO Lite w/5# Gil & 1/4# Flocele & tailed in with 285 sacks 50-50 Pozmix w/5# salt per sack. PD at 1600 MST, 1-7-78. Bumped plug w/1200# - OK. WOC 6 hours. Tested casing to 800# - OK.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature] TITLE Region Operations Manager DATE January 12, 1978

APPROVED BY [Signature] TITLE SENIOR PETROLEUM GEOLOGIST DATE 1-18-78

CONDITIONS OF APPROVAL, IF ANY