

N. M. C. C.
Hobbs

UNITED STATES
DEPARTMENT OF THE INTERIOR

GEOLOGICAL SURVEY
P. O. Box 297
Roswell, New Mexico
April 26, 1943

Re: J. W. Fuller No. 1

Stanolind Oil & Gas Company
Box "F"
Hobbs, New Mexico

Re: Santa Fe 053941

Gentlemen:

Receipt is acknowledged of your "Subsequent Report of Abandonment", dated April 6, 1943, covering your Fuller No. 1 well, located on the subject land in the NE 1/4 Sec. 25, T. 8 N., R. 30 E., Quay County, New Mexico.

The above referred to location was inspected by a representative of this office on April 21, 1943.

The attached report is approved as of this date.

Very truly yours,

John A. Barnett
JOHN A. BARNETT,
District Engineer.

JAD:1c



Indian Agency.....

(SUBMIT IN TRIPLICATE)

U. S. Land Office..... Santa Fe, N. M.

053941

Lease or permit No.....

Allottee.....

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Lease No.....

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF REDRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL.....	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

J. W. Fuller Inc.

April 6, 1943

Well No. 1 is located 660 ft. from $\begin{Bmatrix} N \\ S \end{Bmatrix}$ line and 660 ft. from $\begin{Bmatrix} E \\ W \end{Bmatrix}$ line of sec. 25

NE 4 of Section 25

(1/4 Sec. and Sec. No.)

8 North

(Twp.)

30 East

(Range)

NMPM

(Meridian)

Frio Dome (Wildcat)

(Field)

Quay

(County or Subdivision)

New Mexico

(State or Territory)

The elevation of the derrick floor above sea level is 4459 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

In accordance with approved notice of Intention to Abandon subject well, this work has been completed in the following manner: Bottom of well bore was filled with very heavy mud-laden fluid. 9-5/8" csg. was shot off and 5354' of this was recovered. A 20' cement plug was placed in bottom of 9-5/8 at 4980. Two 20' plugs were placed in open hole at 2790 and 2420, respectively. A 20' cement plug was placed in bottom of 13" csg. at 1084. A 15' cement plug was placed 15' to surface. All intervening space was filled up with heavy mud-laden fluid. A 4" pipe marker extends 5' above the ground level which was cemented in top of the surface csg. The cellar and pits were filled and location graded. Work completed April 3, 1943.

No 13" or 16" csg. was recovered, In as much as these csg. strings were cemented to surface.

In our Notice of Intention to Abandon, we proposed acidizing and testing the San Andres

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. (OVER)

Company STANOLIND OIL AND GAS COMPANY

Address Box "F"

Hobbs, New Mexico

Ralph L. Hendrickson
Title Field Superintendent

UNITED STATES

Section from 2460 - 2670. However, upon further investigation of sample cuttings and core analysis and reviewing drill stem tests previously taken, this procedure was considered unwarranted. Therefore, no test was made.

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	
NOTICE OF INTENTION TO CHANGE PLANS	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	
NOTICE OF INTENTION TO PULL OR ALTER CASING	
NOTICE OF INTENTION TO ABANDON WELL	
SUBSEQUENT REPORT OF WATER SHUT-OFF	
SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
SUBSEQUENT REPORT ON ALTERING CASING	
SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
SUBSEQUENT REPORT ON ABANDONMENT	X
SUPPLEMENTARY WELL HISTORY	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE OR OTHER DATA)

Well No. 1 is located 600 ft. from [2] line and 600 ft. from [E] line of sec. 25

10 23

Section 25	8 North (Twp)	12 East (Range)	10 23
State of Texas	County of Subdivision	City	10 23

The elevation of the derrick floor above sea level is 4480 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casing; indicate mudlogging jobs, cementing points, and all other important proposed work)

In accordance with approved notice of intention to abandon subject well, this work has been completed in the following manner: Bottom of well bore was filled with very heavy mud-laden fluid. 9-7/8" casing was shot off and 8 3/4" casing was placed in open hole at 4280' and 4290'. The 8 3/4" casing was placed in open hole at 4280'. 12" cement plug was placed in bottom of 12" casing at 4280'. 12" cement plug was placed in bottom of 12" casing at 4280'. All intervening space was filled with heavy mud-laden fluid. A 4" line was extended 5' above the ground level which was cemented in top of the casing. The collar and pipe were filled and location marked. Work completed April 5, 1943.

No 12" or 16" casing was recovered. Inasmuch as these casings were cemented to surface.

In our Notice of Intention to Abandon, we proposed acidizing and testing the San Andres formation. It is understood that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. (OVER)

Company: SEYMOUR OIL AND GAS COMPANY

Address: Fort Worth

State: New Mexico

Title: Field Superintendent