

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from.....0.....feet to.....4992.....feet, and from.....feet to.....feet.
Cable tools were used from.....feet to.....feet, and from.....feet to.....feet.

PRODUCTION

Put to Producing.....Plugged & Abandoned 19.....

OIL WELL: The production during the first 24 hours was.....barrels of liquid of which.....% was
was oil;% was emulsion;% water; and.....% was sediment. A.P.I.
Gravity.....

GAS WELL: The production during the first 24 hours was.....M.C.F. plus.....barrels of
liquid Hydrocarbon. Shut in Pressure.....lbs.

Length of Time Shut in.....

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico Drilled as Tight Hole Northwestern New Mexico

T. Anhy.....	T. Devonian.....	T. Ojo Alamo.....
T. Salt.....	T. Silurian.....	T. Kirtland-Fruitland.....
B. Salt.....	T. Montoya.....	T. Farmington.....
T. Yates.....	T. Simpson.....	T. Pictured Cliffs.....
T. 7 Rivers.....	T. McKee.....	T. Menefee.....
T. Queen.....	T. Ellenburger.....	T. Point Lookout.....
T. Grayburg.....	T. Gr. Wash.....	T. Mancos.....
T. San Andres.....	T. Granite.....	T. Dakota.....
T. Glorieta.....	T.	T. Morrison.....
T. Drinkard.....	T.	T. Penn.....
T. Tubbs.....	T.	T.
T. Abo.....	T.	T.
T. Penn.....	T.	T.
T. Miss.....	T.	T.

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	385	385	Sand Redbeds & Shales				
385	1480	1095	Sand & Redbeds				
1480	2111	631	Shale, Anhydrite & Gyp.				
2111	2210	99	Lost Circulation - no samples				
2210	2368	158	Shale & Dolomite				
2368	2398	30	Sand & Dolomite				
2398	2423	25	Sand				
2423	2501	78	Sand and Dolomite				
2501	2558	57	Sand				
2558	2865	307	Sand, Shale & Dolomite				
2865	2886	21	Dolomite				
2886	3365	495	Dolomite, Shale & Anhydrite				
3365	3500	135	Sand, Shale & Lime				
3500	3606	106	Sand, some Dolomite streaks.				
3606	3813	207	Sand and Dolomite				
3813	3858	45	Sand				
3858	4615	757	Shale & Dolomite				
4615	4890	275	Lime, Shale & Dolomite				
4890	4992	102	Lime, Shale & Granite Wash				
4992			Granite P & A				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

August 30, 1959

Company or Operator: A. N. Spanel - W. O. Heinza Address: Rm 6420 - 350 Fifth Ave., New York
Name: W. O. Heinza Date: The Author: L. Ne