## Form 3160-5 (August 1999)

## **UNITED STATES** DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

MAR 1 1 2004

RECEIVED

FORM APPROVED OMB No. 1004-0135 Expires November 30, 2000

SUNDRY NOTICES AND REPORTS ON WELLS CD-ARTESIA

5. Lease Serial No.

662	NM - 9566
-----	-----------

abandoned well. Use Form 3160-3 (APD) for such proposals.		abandoned well. Use Form 3160-3 (APD) for such proposals.  6. If Indian, Allottee or Tribe Name		
SUBMIT IN TR	(PLICATE - Other Inst	ructions an reverse	<b>side.</b> 7. If t	Jnit or CA/Agreement, Name and/or No.
. Type of Well				
Oil Well 🗓 Gas Well 🚨 Other				ell Name and No.
2. Name of Operator				Mescalero 28 Fed #1
Threshold Development Company  3a. Address and an Ct. Ponthouse II 3b. Phone No. (include area code)				PI Well No. 30-035-20033
Ra. Address August 11 St Penthouse II Solution 11 St Penthouse II 817-870-1483				eld and Pool, or Exploratory Area
Location of Well (Footage, Sec.	, T., R., M., or Survey Description			Wildcat Exploratory
660' FNL & 1525'			11. Co	ounty or Parish, State
Unit C, NENW				Otero Co., NM
12. CHECK AP	PROPRIATE BOX(ES)	O INDICATE NATU	RE OF NOTICE, REPORT	T, OR OTHER DATA
TYPE OF SUBMISSION	1	TY	PE OF ACTION	
	Acidize	Deepen Deepen	Production (Start/Resume	) Water Shut-Off
Notice of Intent	Alter Casing	Fracture Treat	Reclamation	☐ Well Integrity
Subsequent Report	Casing Repair	New Construction	Recomplete	Other Spud, surface
	Change Plans	Plug and Abandon	☐ Temporarily Abandon	casing & cement
Final Abandonment Notice	Convert to Injection	Plug Back	Water Disposal	
casing set at 620 Cemented with 200 14.0), 250 sacks 1.99, weight 12. weight 14.8) and Bumped plug to 3 Ran Temperature Spotted 35 sacks 1". Tagged ceme	8'. 1-standard go sacks Premium For Howco Lite with 5). Tailed in with 185 sacks Premius 48 psi for 5 minus Survey and found Premium Plus with at 195'. Spot	guide shoe set Plus, 1% thixse .25% flocele, ith 200 sacks FumPlus (yield lates, held okay top of cement th 2% CaCl2. Itted 50 sacks F	at 628'. Stand f t, .25% thickset 5#/sack gilsonite remium Plus and 2 .32, weight 14.8) Cement did not at 220'. Ran 1". D 3:15 AM 9-8-200 remium Plus with	1/4" 42# J-55 (628') of float shoe set at 585'.  13 (yield 1.51, weight and 2% CaCl2 (yield 2% CaCl2 (yield 1.34,  PD 5:00 PM 9-7-2003.  circulate. WOC 6 hours Tagged cement at 214'.  13. WOC 2 hours. Ran  2% CaCl2. PD 5:55 AM  28 d 95 sacks Premium Plus
14. I hereby certify that the forego			CONTINUED OF	NEXT PAGE:
Name (Printed/Typed)	,	Tist-		·
Rusty Klein	1/1	Title	Agent	
Signature Visit	Her	Date	November 30, 200	)3
	) / / THIS SPACE	FOR FEDERALTOR	STATE OFFICE USE	A TANAS MENTAL OF THE PROPERTY
Approved by		,	· Fitle	Date
Conditions of approval, if any, are certify that the applicant holds les		otice does not warrant or		
which would entitle the applicant to		Burne in any subject lease	Office	

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

THRESHOLD DEVELOPMENT COMPANY Mescalero 28 Federal #1 Section 28-T25S-R18E Otero County, New Mexico

## SUNDRY NOTICE CONTINUED:

with 2% CaCl2. PD 8:48 AM 9-8-2003. Cement circulated to surface. WOC. Drilled out at 4:00 AM 9-9-2003. WOC 35 hours. Reduced hole to 10-5/8". Resumed drilling. NOTE: Casing and cement job witnessed by J. R. Hogwood w/BLM-Roswell.

November 30, 2003