Submit 3 Copies To Appropriate District State of New Mexico Form C-103 Office Energy, Minerals and Natural Resources Revised June 10, 2003 District I WELL API NO. 1625 N. French Dr., Hobbs, NM 88240 30-005-63410 District II OIL CONSERVATION DIVISION 1301 W. Grand Ave., Artesia, NM 88210 5. Indicate Type of Lease District III 1220 South St. Francis Dr. STATE X FEE 1000 Rio Brazos Rd., Aztec, NM 87410 Santa Fe, NM 87505 6. State Oil & Gas Lease No. District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505 VO-5657 7. Lease Name or Unit Agreement Name SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH Roulette AXR State PROPOSALS.) 8. Well Number 1. Type of Well: RECEIVED Oil Well Gas Well X Other 2. Name of Operator JUN 0 9 2004 9. OGRID Number 025575 Yates Petroleum Corporation OCP ARTESIA 3. Address of Operator 10. Pool name or Wildcat 105 S. 4th Street, Artesia, NM 88210 Wildcat Basement 4. Well Location Unit Letter E: 1775 feet from the North line and 788 feet from the West line 10S Range Township 26E NMPM County 11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3779'GR 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data SUBSEQUENT REPORT OF: NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING [ COMMENCE DRILLING OPNS. **TEMPORARILY ABANDON CHANGE PLANS** PLUG AND **ABANDONMENT PULL OR ALTER CASING MULTIPLE** CASING TEST AND COMPLETION **CEMENT JOB** OTHER:  $\overline{X}$ OTHER: Production casing 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 5/31/04 - Reached TD 6480' at 8:00 AM. Set 7" 26# J-55 LT&C 8rd casing at 6480'. Set float collar at 5453'. Cemented 1st stage with 850 sx Pecos Valley Lite with additives. Cement circulated to surface. Cemented 2<sup>nd</sup> stage with 1100 sx 35:65:6 Class "C" with additives. Tailed in with 150 sx Class "C" Neat. Cement circulated to surface. Tested casing to 1000 psi for 30 mins. I hereby certify that the information above is true and complete to the best of my knowledge and belief. TITLE: Regulatory Compliance Supervisor DATE: June 8, 2004 E-mail address: <u>tinah@ypcnm.com</u> Telephone No. <u>505-748-1471</u> Type or print name Tina Huerta (This space for State use) DATE JUN 0 9 2004 FOR RECORDS TONLY

Conditions of approval, if any:

APPPROVED BY