Form 3160-5 (August 1999)

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

RECEIVED

FORM APPROVED OMB NO. 1004-0135 Expires: November 30, 2000

SUNDRY NOTICES AND REPORTS ON WELLS

MAY 2 4 7004

NM025503

5. Lease Serial No.

Do not	use	this	form for	proposals to	o drill or t	o re-enter	and on a	40TE014
				·			\$4.5 to 10.7 "	

6. If Indian, Allottee or Tribe Name

abandoned well. Ose For	=======================================					
SUBMIT IN TRIPLICATE -	Other instruction	s on reverse side		7. If Unit of	r CA/Agreement, Name and/or N	
Type of Well Oil Well Gas Well Other Other				8. Well Nar		
2. Name of Operator OXY USA WTP Limited Partnership		192463		9. API Well	l No.	
3a Address P.O. Box 50250, Midland, TX 79710-	3b. Phone No. (include area code) 432-685-5717		30-015-33651-3364 10. Field and Pool, or Exploratory Area Undsg. Hackberry Morrow, N. 11. County or Parish, State			
4. Location of Well (Footage, Sec., T., R., M., or Survey 760 FSL 2020 FEL SWSE(0)) Sec 26						
12. CHECK APPROPRIATE	BOX(ES) TO INI	DICATE NATURE OF	NOTICE, REF	LEddy PORT, OR O	THER DATA	
TYPE OF SUBMISSION	TY	PE OF ACTION				
Notice of Intent	Acidize	Deepen]	n (Start/Resume)	Water Shut-Off	
X Subsequent Report	Alter Casing Casing Repair	Fracture Treat New Construction	Reclamati Recomple		Well Integrity X Other Spud.	
Final Abandonment Notice	Change Plans Convert to Injection	Plug and Abandon Plug Back	Temporarily Abandon Water Disposal		Set Csq & Cmt	
13. Describe Proposed or Completed Operation (clearly lift the proposal is to deepen directionally or recomm						

Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the final site is ready for final inspection.)

See Attached

14 I hereby certify that the foregoing is true and correct Name (Printed Typed)	Title		
David_Stewart	Sr. Regulato	ry Analyst	
C. Stat	Date 5/21	104	
THIS SPACE F	OR FEDERAL OR STATE OFFICE US	SE .	
Approved by	Title	Date	
Conditions of approval, if any, are attached. Approval of this notice of certify that the applicant holds legal or equitable title to those rights in which would entitle the applicant to conduct operations thereon.			

States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

OXY PAL FEDERAL #1

05/14/2004 CMIC:

LOCATION STAKED BY JOHN WEST SURVEYORS AT 760' FSL, 2020' FEL, SECTION 26, T18S, R30E, EDDY CTY NM. BUILT ROAD & LOCATION. DUG & LINED RESERVE PITS. SET 20" CONDUCTOR AT 40' & CEMENTED W/ REDI-MIX. MIRU PATTERSON 508. HELD PRE SPUD SAFETY MEETING & RIG INSPECTION. SPUDED 17 1/2" HOLE AT 10:00 PM 5-13-04. DRILLING F/ 40' TO 109' & LOST RETURNS. BUILD & PUMP LCM PILLS. REGAIN CIRCULATION, DRILLING TO 140'. RESET ROATARY TABLE AT REPORT TIME. DON W/ BLM NOTIFIED OF SPUD AT 3:30 PM MST 5-13-04.

05/15/2004 CMIC: LANGE

BOWKER

RESET ROTARY TABLE.DRILLING F/ 140' TO 150'. LOST RETURNS, MIX & PUMP 2 LCM PILLS, REGAINED CIRCULATION. DRILLING F/ 150' TO 181' LOST RETURNS, MIX & PUMP LCM PILL. DRILLING F/ 181' TO 184'. GROUND CRACKING FROM CELLAR OUT TO PIPE RACKS & F/ CELLAR OUT TO MUD TANKS. FLUID COMING OUT OF CRACKS AND UP CELLAR. MIX & PUMP GW-27 & LCM PILL. DRILLING W/ RETURNS F/ 184' TO 560' W/ SURVEYS. PUT LEVEL ON SUB TO WATCH FOR ANY SETTLING, SUB STAYING LEVEL. CRACKS ARE NOT SEEPING FLUID, STILL HAVE MUD COMING UP AROUND CONDUCTOR PIPE.

05/16/2004 CMIC: BOWKER

DRILLING F/ 560' TO 645'. PUMP SWEEP & CIRCULATE OUT OF HOLE. POOH TO RUN CASING. RU CASING CREW & RUN CASING. HIT HARD BRIDGE AT 577', COULD NOT GET THRU IT. TALKED W/ PAUL SCHWARTZ & JIM AMOS W/ BLM, THEY AGRRED TO LET US CEMENT THE CASING AT 577'. RU HALLIBURTON & CEMENT CASING W/ 150 SX THIXOTROPIC, 360 SX HALLIBURTON LITE TAILED W/ 250 SX PREMIUM PLUS. DISPLACED W/ 90 BBLS FW. BUMPED PLUG W/ 600 PSI AT 2:15 PM 4-15-04. CIRCULATED 175 SX TO RESERVE. WOC 6 HOURS. CUT OFF CONDUCTOR & CASING & WELD ON STARTING HEAD. TESTED HEAD TO 500 PSI OK. NIPPLE UP BOPE AT REPORT TIME. PAUL SCHWARTZ W/ BLM NOTIFIED & WITNESSED CEMENT JOB.

05/17/2004 CMIC: BOWKER

FINISH NIPPLE UP BOPE. PU BHA & TRIP IN HOLE. TAG CEMENT. TEST CASING & BOPE TO 500 PSI. DRILL CEMENT & BAFFLE PLATE. DRILLING AHEAD W/ NO PROBLEMS AT REPORT TIME.

05/18/2004 CMIC: LANGE

DRILLING F/ 1372' TO 1990' W/ SURVEYS. NO PROBLEMS AT REPORT TIME.

05/19/2004 CMIC: LANGE

DRILLING F/ 1990' TO 2490' W/ SURVEYS. NO PROBLEMS AT REPORT TIME.

05/20/2004 CMIC: BOWKER

DRILLED TO 2817' AND CRACKED SUCTION LINE ON PUMP. POOH WITH BIT TO CASING. REPAIRED SUCTION LINE. TBIH WITH BIT, DRILLING AHEAD AT REPORT TIME WITH NO PROBLEMS.

05/21/2004 CMIC: BOWKER

DRILLING AHEAD WITH NO PROBLEMS.