

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

2040 Pacheco St.
Santa Fe, NM 87505

WELL API NO. 30-015-32589
Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
State Oil & Gas Lease No.
Lease Name or Unit Agreement Name Otis 35 Fee Com
Well No. 1
Pool name or Wildcat Carlsbad East Morrow

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK IN A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER	
Name of Operator Mewbourne Oil Company 14744	
Address of Operator PO Box 5270, Hobbs, NM 88241	
Well Location Unit Letter <u>P</u> <u>660</u> Feet From The <u>South</u> Line and <u>660</u> Feet From The <u>East</u> Line Section <u>35</u> Township <u>21S</u> Range <u>27E</u> NMPM <u>Eddy</u> County	
Elevation (Show whether DF, RKB, RT, GR, etc.) 3098' GL	

11

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ANBANDONMENT ☐
CASING TEST AND CEMENT JOB ☒
OTHER: ☐

12 Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

02-01-03...Spud 17 1/2" hole. TD'ed @ 425'. Ran 425' of 13 3/8" 48# H-40 ST/C csg. Cemented w/ 250 sks BJ Lite 'C' Poz w/ additives. Mixed @ 12.5 #/g & 1.98 yd. Tailed w/ 200 sks 'C' w/ 2% CaCl2. Mixed @ 14.8 #/g & 1.34 yd. Circ 65 sks to pit. WOC 18 hrs. Test BOP to 500 psi. OK. Drill out w/ 12 1/4" bit.

02-09-02...TD'ed 12 1/4" hole @ 2628'. Ran 2628' of 8 5/8" 32# J-55 ST/C csg. Cemented w/ 950 sks BJ Lite 'C' Poz w/ additives. Mixed @ 12.5 #/g & 1.96 yd. Tailed w/ 200 sks 'C' w/ 2% CaCl2. Mixed @ 14.8 #/g & 1.34 yd. Circ 68 sks to pit. WOC 18 hrs. Test BOP to 2000 psi. OK. Drilled out w/ 7 7/8" bit. Will test BOP equipment with 3rd party on trip before Wolfcamp.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE [Signature] TITLE District Manager DATE 02-17-03

TYPE OR PRINT NAME N.M. Young TELEPHONE NO. 505-393-5905

(This space for State Use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

**ORIGINAL SIGNED BY TIM W. GUM
DISTRICT II SUPERVISOR**

DATE

FEB 21 2003