

Submit 3 Copies To Appropriate District  
Office  
District I  
1625 N. French Dr., Hobbs, NM 88240  
District II  
811 South First, Artesia, NM 88210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
1220 S. St. Francis Dr., Santa Fe, NM  
87505

State of New Mexico  
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

Form C-103  
Revised March 25, 1999

WELL API NO.  
30-005-63480

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name:

Johnson IL

7. Well No.

5

8. Pool name or Wildcat  
Pecos Slope Abo

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☒ Other ☐

2. Name of Operator

Yates Petroleum Corporation

3. Address of Operator

105 S. 4<sup>th</sup> Street Artesia, NM 88210

4. Well Location

Unit Letter O : 660 feet from the South line and 1850 feet from the East line

Section 30 Township 6S Range 26E NMPM Chaves County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

3695' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

REMEDIAL WORK ☐

ALTERING CASING ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETION ☐

CASING TEST AND CEMENT JOB ☐

OTHER:

☐ OTHER: Recompletion to Abo

☒

Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Set composite plug at 4600'. Perforate Abo 3670'-3692', 3757'-3772', 3776'-3782', 3812'-3832', 3918'-3922' (1 SPF) with 72 - .42" holes. Spotted 500g 7-1/2 IC HCL over Abo perms. Frac Abo with 2000g 7-1/2% IC HCL and 118,000g 55Q CO2 foamed 35% x-linked gelled 7% KCL water carrying 313,000# 16/30 Brady sand. Set wireline packer at 3620'.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Tina Huerta TITLE Regulatory Compliance Supervisor DATE March 28, 2003

Type or print name Tina L. Huerta

Telephone No. 505-748-1471

(This space for State use)

APPROVED BY

TITLE

Jim W. Gunn District Supervisor

DATE

APR 01 2003

Conditions of approval, if any: