

Submit 3 Copies To Appropriate District Office

District I

1625 N. French Dr., Hobbs, NM 88240

District II

1301 W. Grand Avenue, Artesia, NM 87210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION

1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103

Revised March 25, 1999

WELL API NO.

30-015-26348

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name:

**SOUTH CANYON BLUFF
"23"**

8. Well No. **7**

9. Pool name or Wildcat
E. LOVING (BRUSHY CANYON)

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☒ Gas Well ☐ Other

2. Name of Operator **RAM ENERGY, INC.**

3. Address of Operator **5100 E. SKELLY DR., STE 650, TULSA, OK 74115**

4. Well Location

Unit Letter **J** : **1950** feet from the **SOUTH** line and **1750** feet from the **EAST** line

Section **23** Township **23S** Range **28E** NMPM County **EDDY**

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

3000' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: **RECOMPLETE**



SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

A) WIPR WSH. TOH W/PUMP & RODS. NU BOPE. REL TAC & TOH WITH TBG.

B) RUN & SET A 5 1/2" CIBP. TEST CSG TO 2500' SG. PERF U. BRUSHY CANYON 4791-94', 4782-88', 4772-78', 4758-68', 4740-46' & 4685-4700' W/4" CSG GUN, 2 SPT, FOR A TOTAL OF 104 HOLES.

C) TIH W/PKR & SET AT 4630'. ND BOPE & NU TREE. SWAB & TEST.

D) ACIDIZE W/ 2000 GAL 7.5% HCL & 150 BALL SEALERS. SWAB TEST.

E) FRAC TREAT W/ 57,000 GAL XL GEL & 113,000 #16/30 BEAD. SD & 44,000 #16/30 REGN COATED SD. TOH W/PKR. TIH W/PKR ASSBL. TOP.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Mike Kaiser

NAME

MIKE KAISER

DATE

03/24/03

Type or print name

OF ENGR

Telephone No.

918/652800

(This space for State use)

APPROVED BY

Jim W. Gurn

TITLE

District Supervisor

DATE

MAR 28 2003

Conditions of approval, if any: