

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 South First, Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

5
Form C-103

Revised March 25, 1999

WELL API NO.

30-015-32001

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name:

Lucy ALC State

8. Well No.

5

9. Pool name or Wildcat

Undesignated Lost Tank
Delaware West

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH
PROPOSALS.)

1. Type of Well:

Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator

Yates Petroleum Corporation

3. Address of Operator

105 S. 4th Street Artesia, NM 88210

4. Well Location

Unit Letter H : 1650 feet from the North line and 330 feet from the East line

Section 34 Township 21S Range 31E NMPM Eddy County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

3502' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

MULTIPLE
COMPLETION ☐

OTHER:

☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING
CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND
ABANDONMENT ☐

CASING TEST AND
CEMENT JOB ☐

OTHER: Spud, set surface and intermediate casing

☒

Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

3/7/03 - Spudded well at 10:00 AM. Set 40' of 20" conductor and redi-mix.

3/9/03 - Resumed drilling at 6:00 PM.

3/10/03 - Set 13-3/8" 48# casing set at 858'. Cemented with 470 sx Halliburton Lite Premium Plus with additives. Tailed in with 200 sx Premium Plus cement with additives. Cement circulated to surface. WOC 23 hrs.

3/18/03 - Set 8-5/8" 32# casing set at 4100'. Stage 1: cemented with 800 sx Interfill "C" with additives and tailed in with 200 sx Premium Plus cement with additives. Stage 2: cemented with 225 sx Interfill "C" with additives. Cement circulated to surface. WOC 29 hrs 30 mins. Reduced hole to 7-7/8" and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Tina Huerta TITLE Regulatory Compliance Supervisor DATE March 20, 2003

Type or print name Tina Huerta

Telephone No. 505-748-1471

(This space for State use)

APPROVED BY Simon W. Green TITLE District Supervisor DATE MAR 26 2003

Conditions of approval, if any: