Form 3160-5 (August 1999)

N.M. Oil Cons. DIV-Dist. 2

DEPARTMENT OF THE INTERIOR W. Grand Avenue

BUREAU OF LAND MANAGEMENTESIA, NM 88210

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an

FORM APPROVED OMB NO. 1004-0135

	Expires. November 30, 2000	
5.	Lease Serial No.	
NM	LC026874F	
6.	If Indian, Allottee or Tribe Name	

abandoned well. Use ron	1					
SUBMIT IN TRIPLICATE -	7. If Unit or CA/Agreement, Name and/or No.					
1. Type of Well Oil Well X Gas Well Other 2. Name of Operator Occidental Permian Limited Partners 3a. Address P.O. Box 50250. Midland. TX 79710- 4. Location of Well (Footage, Sec., T., R., M., or Survey III) 1387 FNL 1062 FEL SENE(H) Sec 6 T	157984 3b. Phone No. (include area code) 432 - 685 - 5717		8. Well Name and No. West Ribbon #1 Federal 9. API Well No. 30-015-32717 10. Field and Pool, or Exploratory Area Empire Morrrow, South 11. County or Parish, State Eddy NM			
12. CHECK APPROPRIATE	BOX(ES) TO INDI	CATE NATURE OF N	OTICE, REP		HER DATA	
TYPE OF SUBMISSION		TYF	TYPE OF ACTION			
Notice of Intent X Subsequent Report Final Abandonment Notice 13. Describe Proposed or Completed Operation (clearly If the proposal is to deepen directionally or recomp Attach the Bond under which the work will be per following completion of the involved operations. It testing has been completed. Final Abandonment Metermined that the final site is ready for final inspection.	blete horizontally, give sub formed or provide the Bo If the operation results in a Notices shall be filed only	surface locations and meas and No. on file with BLM/ a multiple completion or re	Recomple Recomple Temporar Water Dis	ily Abandon sposal roposed work and ritical depths of a subsequent report new interval, a F	Il pertinent markers and zones. Is shall be filed within 30 days form 3160-4 shall be filed once	
RECEIVED ANG 2 4 2004		Attached	ALEX	TED FOR R JG 2 3 200 KIS C. SWOB DLEUM ENGI	4 ODA	
14. I hereby certify that the foregoing is true and correct Name (Printed/Typed)		Title				
Name (Printed/Typed) David Stewart	Sr. Re	gulatory Ar	alyst			
Vi Stat		Date &	راعاصر			
THIS	S SPACE FOR FEDE	RAL OR STATE OFF	ICE USE			
Approved by		Title		D	ate	

Title 18 U.S.C. Section 1001, and Title 43 U.S.C. Section 1212, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

Office

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

WEST RIBBON FEDERAL #1

07/11/2004 CMIC: BOWKER

DRILLING AHEAD WIYH NO PROBLEMS

07/12/2004 CMIC: BOWKER

DRILLING AHEAD AT REPORT TIME WITH NO PROBLEMS

07/13/2004 CMIC: LANGE

DRILLED TO 5220' AND BIT QUIT. DROPPED TOTCO AND TOOH. CHANGED BIT. TBIH WITH BIT AND BHA AT

REPORT TIME.

07/14/2004 CMIC: LANGE

FTIH WITH BIT AND BHA. WASHED 30' TO BOTTOM. DRILLING AHEAD AT REPORT TIME WITH NO PROBLEMS.

07/15/2004 CMIC: LANGE

DRILLING AHEAD AT REPORT TIME WITH NO PROBLEMS.

07/16/2004 CMIC: BOWKER

DRILLING AHEAD WITH NO PROBLEMS.

07/17/2004 CMIC: BOWKER

DRILLED TO 6839' AND LOST 200# PUMP PRESSURE. PUMPED SOFT LINE. TOOH AND FOUND SPLIT IN THE MIDDLE OF THE 63RD STAND. TBIH WITH BIT. WASHED 38' TO BOTTOM. DRILLING AHEAD AT REPORT TIME WITH NO PROBLEMS.

07/18/2004 CMIC: BOWKER

DRILLED TO 6974' AND LOST 150# PUMP PRESSURE. PUMPED SOFT LINE. TOOH AND FOUND SPLIT IN THE MIDDLE OF THE 64TH STAND. TBIH WITH BIT. WASHED 60' TO BOTTOM, DRILLING AHEAD AT REPORT TIME WITH NO PROBLEMS.

07/19/2004 CMIC: BOWKER

DRILLING AHEAD AT REPORT TIME WITH NO PROBLEMS. MUDDING UP AT REPORT TIME FOR PENN SHALE.

07/20/2004 CMIC: BOWKER

DRILLED TO 7714'. DROPPED TOTCO AND TOOH. CHANGED BIT AND BHA. TIH WITH BIT AND BHA. CUT DRILLING LINE. FTIH WITH BIT. WASHED AND REAMED 48' TO BOTTOM. DRILLING AHEAD AT REPORT TIME WITH NO PROBLEMS.

07/21/2004 CMIC: BOWKER

DRILLING AHEAD WITH NO PROBLEMS.

07/22/2004 CMIC: BOWKER

DRILLING AHEAD WITH NO PROBLEMS.

07/23/2004 CMIC: BOWKER

DRILLING AHEAD AT REPORT TIME WITH NO PROBLEMS.

07/24/2004 CMIC: BOWKER

DRILLED TO 8966' AND LOST 200# PUMP PRESSURE. PUMPED SOFT LINE. TOOH AND FOUND HOLE IN THE TOP OF THE 70TH STAND. TBIH WITH BIT. WASHED 30' TO BOTTOM. DRILLING AHEAD AT REPORT TIME WITH NO PROBLEMS.

07/25/2004 CMIC: BOWKER

DRILLED TO 9116' AND LOST 200# PUMP PRESSURE. PUMPED SOFT LINE. TOOH AND FOUND SPLIT IN THE MIDDLE OF THE 55TH STAND. TBIH WITH BIT. DRILLED TO 9184' AND LOST 150# PUMP PRESSURE. PUMPED SOFT LINE. TOOH AND FOUND SPLIT IN THE TOP OF THE 88TH STAND. TOOH WITH BIT. CHANGED BIT. TIH WITH BIT AND BHA AT REPORT TIME.

07/26/2004 CMIC: BOWKER

FTIH WITH BIT AND BHA. WASHED 30' TO BOTTOM. DRILLING AHEAD AT REPORT TIME WITH NO PROBLEMS.

07/27/2004 CMIC: LANGE

DRILLING AHEAD AT REPORT TIME WITH NO PROBLEMS.

07/28/2004 CMIC: BOWKER

DRILLING F/ 9485' TO 9550'. REACHED TD AT 3:30 AM 7-28-04. CIRCULATE FOR SHORT TRIP.

07/29/2004 CMIC: BOWKER

SHORT TRIP 20 STANDS. CIRCULATE BOTTOMS UP. HAD INCREASE OF GAS F/ 500U TO 3200U & FLOW INCREASE F/ 50% TO 60%. WT UP SYSTEM F/ 10.3 PPG TO 10.7 PPG. SHORT TRIP 20 STANDS & WAIT FOR 1 HOUR, TRIP IN HOLE. HAD 1150U GAS ON BOTTOMS UP & 2-3' FLARE. BRING WT UP TO 10.8 PPG. GAS DOWN TO 225 UNITS. STRAP OUT OF HOLE FOR LOGS. RU LOGGERS AT REPORT TIME.

07/30/2004 CMIC: BOWKER

LOGGING W/ BAKER ATLAS. LOGGERS TD 9553'

07/31/2004 CMIC: LANGE

LOGGING. RIG DOWN LOGGERS & TRIP IN HOLE. CUT DRILLING LINE. FINISH TRIP IN HOLE. CIRCULATE & CONDITION HOLE FOR CASING. HAD 10' FLARE ON BOTTOMS UP. LAY DOWN DRILL PIPE AT REPORT TIME.

08/01/2004 CMIC: LANGE

FINISH LAYING DOWN DRILL PIPE & DRILL COLLARS. SAFETY MEETING BEFORE RUNNING CASING. RU CASING. CREW & RUN 235 JOINTS 5 1/2", 17# L-80 & P-110. TOTAL PIPE 9569', SET AT 9553'. RU HOWCO CEMENTING HEAD & CIRCULATE W/ RIG PUMP FOR 2 HOURS. HAD LAZY 4' FLARE ON BOTTOMS UP THEN WENT OUT. CEMENT W/ HOWCO W/ 725 SX INTERFILL. H & TAILED W/ 300 SX SUPER "H" W/ ADDITIVES. DISPLACED W/ 220 BBLS FW. BUMPED PLUG W/ 2250 PSI, PLUG DOWN AT 12:00 AM MST 8-1-04. RELEASED PRESSURE, FLOATS HELD. NIPPLE DOWN & PU STACK. SET SLIPS W/ FULL STRING WT. (110,000#). CUT OFF CASING. SET OUT BOP & NIPPLE UP "C" SECTION AT REPORT TIME.

08/02/2004 CMIC: LANGE

FINISH NIPPLE UP "C" SECTION. TEST TO 5000# OK. RUN TEMPERATURE SURVEY, TOP OF CEMENT AT 1845'.
JET & CLEAN PITS. RIG RELEASED AT 1:00 PM 8-1-04. IAST REPORT.