

Submit 3 Copies To Appropriate District  
Office  
District I  
1625 N. French Dr., Hobbs, NM 88240  
District II  
1301 W. Grand Ave., Artesia, NM 88210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
1220 S. St. Francis Dr., Santa Fe, NM  
87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103  
Revised March 25, 1999

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

WELL API NO.  
30-015-33452

5. Indicate Type of Lease  
STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement  
Name:

Herradura 25

8. Well No.  
#1

9. Pool name or Wildcat  
Burton Flat Morrow

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH  
PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☒ Other ☐

RECEIVED

2. Name of Operator  
Mewbourne Oil Company 14744

AUG 27 2004

3. Address of Operator  
PO Box 5270 Hobbs, NM 88241

OCD-ARTESIA

4. Well Location

Unit Letter B : 990 feet from the North line and 1980 feet from the East line

Section 25 Township 22S Range 27E NMPM Eddy County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)  
3080' GL

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE  
COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND  
ABANDONMENT ☐

CASING TEST AND  
CEMENT JOB ☒

OTHER:

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

08/12/04...MI & spud 17 1/2" hole. TD'd 17 1/2" hole @ 440'. Ran 440' - 13 3/4" H40 ST&C csg. Cemented with 250 sks BJ Lite "C" with additives. Mixed @ 12.5 #/g with 1.98 cf/sk yd. Tail with 200 sks Class "C" with 2% CaCl2. Mixed @ 14.8 #/g with 1.34 cf/sk yd. Circ 70 sks to pit. WOC 18 hrs. At 2:30 pm, test BOPE and 13 3/4" casing to 1000# for 30 mins, held OK. Drilled out with 12 1/4" bit.

08/19/04...TD'd 12 1/4" hole @ 4317'. Called OCD and received verbal permission to change 9 3/4" setting depth from 4500' as permitted to 4317'. Ran 4317' - 9 3/4" 40# HCK55/N80 LT&C csg. Cemented with 1850 sks 35:65:6 Poz C with additives. Mixed @ 12.5 #/g with 1.98 cf/sk yd. Tailed with 200 sks Class C with 2% CaCl2. Mixed @ 14.8 #/g with 1.34 cf/sk yd. Circ 125 sks cmt to pit. WOC 18 hrs. At 7:45 pm, test BOPE and 9 3/4" casing to 2000# for 30 mins, held OK. Drilled out with 8 3/4" bit.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Kristi Green TITLE Hobbs Regulatory DATE 08/23/04

Type or print name Kristi Green Telephone No. 505-393-5905

(This space for State use)

APPROVED BY FOR RECORDS ONLY DATE AUG 30 2004

Conditions of approval, if any: