Form 3160-5 (September 2001)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB No. 1004-0135 Expires: January 31, 2004

SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

5. Lease Serial No. NM - 25363

6. If Indian, Allottee or Tribe Name

SUBMIT IN TRIPLICATE - Other instructions on reverse side						7. If Unit or CA/Agreement, Name and/or No.		
I. Type of Well ☐ Oil Well ☑ Gas Well ☐ Other					8. Well Name and No.			
2. Name of Operator				Champeau Fed No. 1				
Nadel and Gussman Permian, L. I		RECEIVED			9. API Well No.			
Sa. Address	3b. Phone No. (include area code)			30-005-00518				
			SEP 1 6 2004		10. Field and Pool, or Exploratory Area			
601 N. Marienfeld, Suite 508, Mi	432-682-4429 OCD-AHTESIA			Little Lucky Lake Morrow				
I. Location of Well (Footage, Sec., 560' FNL & 1980' FWL Unit C, SEc 31-15S-30E				11. County or Parish, State				
					Chaves Co., N	<u>M</u>		
12. CHECK APP	PROPRIATE BOX(ES) TO	INDICATE NA	TURE O	F NOTICE, RE	EPORT, OR O	THER DATA		
TYPE OF SUBMISSION				F ACTION				
	Acidize [Deepen		Production (Start/	Resume)	Water Shut-Off		
Notice of Intent	Alter Casing	Fracture Treat	ā	Reclamation	´ ¬	Well Integrity		
	Casing Repair	New Constructi	<u> </u>	Recomplete		Other		
✓ Subsequent Report		Plug and Aband		Temporarily Aba	undon	Other		
Final Abandonment Notice	=	= ~			ingon			
That Avandonment Protect	Convert to Injection	Plug Back	لا	Water Disposal				
determined that the site is ready f 8-23-04 Spot 30 sxs @ 9302-9302 8/26/04 Perf @ 8000', test to 800 Perf @ 6400, test to 800 8/27/04 Perf @ 4550 test to 700 p 8/31/04 Cut and pull 3500' of 4" o 9/01/04 Set CICR @ 3170 and sp 9/02/04 Spot 20 sxs 2925 -2733 ' 9/03/04 Cut and pull 2009' of 5-1/ Spot 50 sxs @ 2072-1852	2 & tag. Resport 30sxs 9302-8; psi spot 25 sxs @ 8109-7312 & psi spot 25 sxs plug @ 6474 to si. Spot 25 sxs 4580 - 3806 an asg; Spot 35 sxs @ 3549 - 3174 ot 35 sxs @ 3170 -2925' and tag /2 csg 2' and tag 00 psi. Spot 60 sxs @ 597 - 365 ace	861' & tag & tag; o 5996 & tag. d tag & tag g	equirements	s, including reclan	nation, have been	completed, and the operato	ir has	
14. 1 hereby certify that the foregoin Name (Printed Typed)	g is true and correct		<u></u>	B				
Kem E. McCready	Title	^e Operation	ns Engeleer	· · · · · · · · · · · · · · · · · · ·	. <u> </u>			
Signature K, S.	Jose Creaty	Dat	e 9/14/200	AP.				
	THIS SPACE FO	topical and the second of the second of the second	N. P. Sh. M. P. Waller, C. P. L. P.	OFFICE USE				
Approved by (Signature)			Name (Printed/T)	yped)	Tit	le		
Conditions of approval, if any, are certify that the applicant holds legs which would entile the applicant to come the condition of the conditions of the co	does not warrant of in the subject leas	Office se			Date			

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NADEL AND GUSSMAN PERMIAN

Champeau Federal #1

660' FNL, 1980' FWL, UnitC, Sec 31, T15S, R30E, Chaves County, NM API # 30-005-00518


Elev: 3932' GL

13-3/8", 48# @ 493' 500 sx, circulated 17-1/2" hole

8-5/8", 32# @ 2929' 1300 sx, DNC 1" from 250' to surface w/ 100 sx 11" hole

5-1/2", 15.5 & 17# @ 4406' 275 sx, TOC @ 2835', calc 75% 7-7/8" hole

4", 12.93# N-80 @ 10,032' 425 sx, TOC @ 8500' by T.S.



20 sx plug at 60' - surface

60 sx plug 597'- 363' tagged Perf @ 543'.

50 sx plug 2072-1852' tagged Cut 5-1/2" csg @ 2009'.

20 sx plug @ 2925-2733' tagged Cmt Ret @ 3170' spot 35 sxs 3170-2925 tagged 35 sx @ 3549-3174 tagged Cut 4"casing at 3500'

San Andres Perfs: 3666' - 3738' @ 2 SPF, 15/15 LO frac SQZD w/ 250 sx (3/85)

25 sx plug: 4580' - 3806' tagged across production casing shoe Perf @ 4550'

25 sx plg @ 6474- 5996 tagged Perf @ 6400'

25 sx plug @ 8109-7312 tagged Perf @ 8000'

60 sx plug: 9302' - 8861' tagged Spotted 2 30 sxs plugs twice tag solid @ 9302' Strawn Perfs: 9334' - 9359' @ 2 SPF, 38 holes, 2500 gals 7 1/2% NEFE

cmt ret @ 9882'

Morrow Perfs: 9894' - 9946' @ 2 SPF

50 sx plug: 11,000' - 10,900'

PBTD @ 9978'
TD @ 11,250'

Former Well Name: Texaco - Shell Champeau Federal #1 Spud Date: 05/03/62, P&A 7/05/68, reentered 3/27/85