

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103
Revised March 25, 1999

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-015-32845
1. Type of Well: Oil Well <input type="checkbox"/> Gas Well <input checked="" type="checkbox"/> Other		5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
2. Name of Operator Mewbourne Oil Company 14744		6. State Oil & Gas Lease No. E-5073
3. Address of Operator PO Box 5270 Hobbs, NM 88241		7. Lease Name or Unit Agreement Name: Winchester 36 State Com
4. Well Location Unit Letter <u>K</u> : <u>1880</u> feet from the <u>South</u> line and <u>1980</u> feet from the <u>West</u> line Section <u>36</u> Township <u>19S</u> Range <u>28E</u> NMPM Eddy County		8. Well No. 1
10. Elevation (Show whether DR, RKB, RT, GR, etc.) 3294' GL		9. Pool name or Wildcat Winchester Morrow

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

- PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

- REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: Add additional Morrow Perfs ☒

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

07/29/04...Spot sand to isolate Morrow perforations at 11010 to 11366'. Perforate Upper Morrow at 10751'-10840' (Total 12', 26 holes, 2 SPF, 6.5 GC, 0.24" EHD, 21.4" Penetration & 120 phasing).

08/01/04...Acidized with 2000 gals 7 1/2% HCl Morrow Acid. Flowed back. PWOL.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Kristi Green TITLE Hobbs Regulatory DATE 10/08/04

Type or print name Kristi Green

Telephone No. 505-393-5905

(This space for State use)

APPROVED BY FOR RECORDS ONLY DATE OCT 13 2004

Conditions of approval, if any: