# District I 1625 N. French Dr., Hobbs, NM 88240 District II 1301 W. Grand Avenue, Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

# State of New Mexico Energy Minerals and Natural Resources

Form C-101 May 27, 2004

Oil Conservation Division **RECEIVED** Submit to appropriate District Office

1220 South St. Francis Dr.

DEC 1 4 2004

☐ AMENDED REPORT

Santa Fe, NM 87505

APPL	ICATI	ON FO				ENTER, D	<u>EEPEN</u>	, PLUGBACI		
		Operator Name					<sup>2</sup> OGRID Number 14744			
		Mewbourne O Po Box Hobbs, NM	5270	ıy		30 - 015 - 33773				
<sup>3</sup> Prope		Tiobos, IVIV	1 66240	<sup>5</sup> Property	Name		150 013	°We	ll No.	
			<u> </u>		Empire 18	State				5
		l les	<sup>9</sup> Proposed Pool 1 des East Empire Yo					10 Proposed	d Pool 2	
		Un	ues East Emphe 10	cso	7 Surface	Location	<del></del>			
UL or lot no.	Section	Township	Range	T 10	Idn Feet fro		North/South line Feet from the		East/West line	County
P P	18	178	29E		99		S	330	E	Eddy
			No <sup>8</sup> Prop	osed Bo	ttom Hole Loca	tion If Differe	nt From S	Surface		
UL or lot no.	Section	Township	Range	Lo	Idn Feet fro	om the North/S	South line Feet from the Ea		East/West line	County
				A	dditional We		on			
	Гуре Code N		<sup>12</sup> Well Type Co O	ode		e/Rotary R	14 Lease Type Code S		15 Ground Level Elevation 3634'	
	ultiple No		<sup>17</sup> Proposed Dep 4500	oth		mation pire Yeso	<sup>19</sup> Contractor TBA		<sup>20</sup> Spud Date ASAP	
	roundwater e but less th		No	Distance from nearest fresh water well Less than 1000 from all other wtr sources No				Distance from nearest surface water 1000' or more Yes		
Pit: Liner:	Synthetic	X _12_	_mils thick Clay	y 🔲 Pi	Volume:_24000	bbls	Drillir	ng Method: Production	<u>n</u>	
Close	d-Loop Sys	tem	21					X Brine X Diesel/C	Oil-based [ ] (	Gas/Air
			21	Propo	sed Casing a	nd Cement	Progran	1		
Hole S	ize	С	asing Size	Casii	Casing weight/foot Sett		g Depth Sacks of Cer		nt	Estimated TOC
12 1/4	····		8 5/8"		32#	400'	400'			Surface
7 1/8"		BW	Tie back		17# 45				Coverall oil, water & gas bearing zones	
22 Describe the proposed program. If this application is to DEEPEN or PLUG BACK, give the data on the present productive zone and proposed new productive Describe the blowout prevention program, if any. Use additional sheets if necessary.										
	•	•				•	bit #2A) fro	om surface casing to t	total depth.	
Mud Program	:		•		•	,	ŕ	_	•	
	0' to 400'				PH and LCM as ne		•			
	400' to TI	D Brine	Water, lime for P	H and LC	M as needed for se	eepage.				·
		***				DXA.				
		on given above is further certify th			OIL CONSERVATION DIVISION					
		D guidelines X, a			Approved by:					
(attached) alt	ernative C	OCD-appr	oved plan .					ማግጹ ብ	101 0110	e e
Printed name:	en	Frist	i gu	en .	Tim W. GUM  DISTRICT II SUPERVISOR					
Title: Hobbs Production						Approval Date:	DEC 1		ration Date:	DEC 1 7 200
E-mail Addres	E-mail Address: kgreen@mewbourne.com									<u> </u>
Date: 12/10/0	)4		Phone: 505-	393-5905		Conditions of A	pproval Att	ached		

DISTRICȚ I 1625 M. French Dr., Hobbs, NM 88240 DISTRICT II

State of New Mexico

Energy, Minerals and Natural Resources Department

Form C-102 Revised March 17, 1999 Instruction on back Submit to Appropriate District Office

State Lease - 4 Copies

Fee Lease - 3 Copies

811 South First, Artesia, NM 88210 DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87410 DISTRICT IV 2040 South Pacheco, Santa Fe, NM 87505

# OIL CONSERVATION DIVISION P.O. Box 2088

Santa Fe, New Mexico 87504-2088

☐ AMENDED REPORT

#### WELL LOCATION AND ACREAGE DEDICATION PLAT

API Number	Pool Code	Pool Name				
		Undes East	Empire Yeso			
Property Code	Propi	erty Name	Well Number			
	EMPIRE "18"	STATE	6			
OGRID No. 14744	Opera	ator Name	Elevation			
	MEWBOURNE (	DIL COMPANY	3634			

#### Surface Location

	UL or lot No.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
ĺ	P	18	17S	29E		990	SOUTH	330	EAST	EDDY

#### Bottom Hole Location If Different From Surface

UL or lot No.	Section	Township	Range	Lot idn	Feet from the	North/South line	Feet from the	East/West line	County
Dedicated Acres	Joint or	infili Co	nsolidation (	Code Or	der No.	<u> </u>		1.11.1.0	
40				_					

#### NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION

	OPERATOR CERTIFICATION  / hereby certify the the information
	contained herein is true and complete to the best of my knowledge and belief.
	Honste green
	Signature   Kristi Green
	Printed Name
	Hobbs Regulatory
	12/08/04
	Date
	SURVEYOR CERTIFICATION
	I hereby certify that the well location shown
	on this plat was plotted from field notes of actual surveys made by me or under my
	supervison, and that the same is true and correct to the best of my belief.
	12/06/2004 Date Surveyed
	Signature & Scal of
	Lease' #V05082
	N.32°49'48.1"
	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \
	E.569778.2 Certificate No. Hersefiel L. Joges RLS 3640
	CAMPIRE 19 STATE 6 GENERALE SOMEWHING COMPANY
0 330' 660' 990' 1650' 1980' 2310'	2310' 1980'1650 990' 660' 330' 0'

# MULTI-POINT SURFACE USE AND OPERATIONS PLAN MEWBOURNE OIL COMPANY

Empire 18 St #6 990' FSL & 330' FEL Section 18-T17S-R29E Eddy County, New Mexico

This plan is submitted with Form C101, Application for Permit to Drill, covering the above described well. The purpose of this plan is to describe the location of the proposed well, the proposed construction activities and operations plan, the magnitude of the surface disturbance involved, and the procedures to be followed in restoring the surface so that a complete appraisal can be made of the environmental impact associated with the proposed operations.

#### 1. Existing Roads:

- A. Exhibit #3 is a topographic map showing the location of the proposed well and access road.
- B. Directions to location from Loco Hills: Continue west on Hwy 82, approx 7.7 miles. Between mile marker 124 and 125 turn right thru yellow cattle guard, proceed north for 0.6 miles. Turn left (north/NW) at "Y" for 7/10 mile. Turn right at "Y". Proceed NE for 0.5 miles. Turn right (east) proceed 0.3 miles thru "18" #3 location. Turn left (north) 0.1 miles to location.

# 2. Proposed Access Road:

A 600' of new lease road will be needed.

## 3. Location of Existing and/or Proposed Facilities:

- A. There are no production facilities on this lease at the present time.
- B. In the event that the well is productive, production facilities will be located on the well pad.

#### 4. Location and Type of Water Supply

The well will be drilled with a combination of fresh water and brine water based mud systems. The water will be obtained from commercial suppliers in the area and/or hauled to the location by transport trucks over existing and proposed roads as indicated in Exhibit #3.

#### 5. Source of Construction Materials

All material required for construction of the drill pad and access roads will be obtained from private, state, or federal pits. The construction contractor will be solely responsible for securing construction materials required for this operation and paying any royalties that may be required on those materials.

# MULTI-POINT SURFACE USE AND OPERATIONS PLAN

MEWBOURNE OIL COMPANY

Empire 18 St #6

Page 2

# 6. Methods of Handling Waste Disposal:

- A. Drill cuttings not retained for evaluation purposed will be disposed of in the reserve pit.
- B. Drilling fluids will be allowed to evaporate in the reserve pit prior to closure.
- C. Water produced during operations will be disposed of in the reserve pit.
- D. If any liquid hydrocarbons are produced during operations, those liquids will be stored in suitable tanks until sold.
- E. Current regulations regarding the proper disposal of human waste will be followed.
- F. All trash, junk, and other waste materials will be stored in proper containers to prevent dispersal and will be removed to an appropriate facility within one week of cessation of drilling and completion activities.

### 7. Ancillary Facilities

There are no ancillary facilities within the immediate vicinity of the proposed well site.

#### 8. Well Site Layout

- A diagram of the drill pad is shown in Exhibit #5. Dimensions of the pad, pits, and location of major rig components are shown.
- B. The reserve pit will be lined with a high quality plastic sheeting to prevent migration of fluids as per OCD regulations.
- C. The pad dimension of 400' X 250' have been staked and flagged.

#### 9. Plans for Restoration of Surface

- A. Upon cessation of the proposed operations, if the well is abandoned, the location and road will be ripped and re-seeded. The reserve pit area, after allowing to dry will be leveled. The entire location will be restored to the original contour as much as reasonable possible. All trash, garbage, and pit lining will be hauled to appropriate disposal to assure the location is aesthetically pleasing as reasonable possible. All restoration work will be completed within 180 days of cessation of activities.
- B. The disturbed area will be restored by re-seeding during the proper growing season.
- C. Three sides of the reserve pit will be fenced prior to and during drilling operations. The reserve pit will be fenced on the fourth side after the drilling rig is removed to prevent the endangerment of livestock. The fence will remain in place until the pit area has been leveled and restored.

# MULTI-POINT SURFACE USE AND OPERATIONS PLAN

MEWBOURNE OIL COMPANY

Empire 18 St #6 Page 3

- D. Upon cessation of the proposed operations, if the well is not abandoned, the reserve pit area will be restored as per OCD guidelines. Any additional caliche required for production facilities will be obtained from a source as described in Section 6.
- E. Within 90 days of cessation of drilling and completion operations, all equipment not necessary for production operations will be removed. The location will be cleaned of all trash and junk to assure the well site is left as aesthetically pleasing as reasonably possible

## 10. Surface Ownership:

The surface is owned by:

State of New Mexico

#### 11. Other Information

- A. Topography: Refer to the archaeological report for a detailed description of flora, fauna, soil characteristics, dwellings, and historical or cultural sites.
- B. The primary use of the surface at the location is for grazing of livestock.

#### 12. Operator's Representative:

A. Through APD approval and drilling operations:

N.M. Young, District Manager Mewbourne Oil Company PO Box 5270 Hobbs, NM 88241 505-393-5905

B. Through completion and production operations:

N.M. Young, District Manager Mewbourne Oil Company PO Box 5270 Hobbs, NM 88241 505-393-5905

# MULTI-POINT SURFACE USE AND OPERATIONS PLAN MEWBOURNE OIL COMPANY

Empire 18 St #6 Page 4

#### 13. Certification

I hereby certify that I, or persons under my direct supervision, have inspected the proposed drill site and access route; that I am familiar with the conditions which currently exist; that the statements made in this plan are to the best of my knowledge, true and correct; and the work associated with the operations proposed herein will be performed by Mewbourne Oil Company, its contractors and subcontractors, in accordance with this plan and the terms and conditions under which it is approved. This statement is subject to the provisions of 18 U.S.C. 1001 for the filing of a false statement.

Date: 12/10/04

Signature:

NM Young Mewbourne Oil Company PO Box 5270 Hobbs, NM 88241 (505) 393-5905

# Hydrogen Sulfide Drilling Operations Plan Mewbourne Oil Company

Empire 18 St #6 990' FSL & 330' FEL Section 18-T17S-R29E Eddy County, New Mexico

## 1. Hydrogen Sulfide Training

All personnel, whether regularly assigned, contracted, or employed on an unscheduled basis, will have received training from a qualified instructor in the following areas prior to entering the drilling pad area of the well:

- 1 The hazards and characteristics of hydrogen sulfide gas.
- 2 The proper use of personal protective equipment and life support systems.
- The proper use of hydrogen sulfide detectors, alarms, warning systems, briefing areas, evacuation procedures.
- 4 The proper techniques for first aid and rescue operations.

Additionally, supervisory personnel will be trained in the following areas:

- The effects of hydrogen sulfide on metal components. If high tensile tubular systems are utilized, supervisory personnel will be trained in their special maintenance requirements.
- 2 Corrective action and shut in procedures, blowout prevention, and well control procedures while drilling a well.
- 3 The contents of the Hydrogen Sulfide Drilling Operations Plan.

There will be an initial training session prior to encountering a know hydrogen sulfide source. The initial training session shall include a review of the site specific Hydrogen Sulfide Drilling Operations Plan.

#### 2. Hydrogen Sulfide Safety Equipment and Systems

All hydrogen sulfide safety equipment and systems will be installed, tested, and operational prior to drilling below the intermediate casing.

# 1. Well Control Equipment

- A. Flare line with automatic igniter or continuous ignition source.
- B. Choke manifold with minimum of one adjustable choke.
- C. Blowout preventers equipped with blind rams and pipe rams to accommodate all pipe sizes with properly sized closing unit
- D. Auxiliary equipment including rotating head and annular type blowout preventer.

# 2. Protective Equipment for Essential Personnel

Thirty minute self contained work unit located at briefing area as indicated on wellsite diagram.

# 3. Hydrogen Sulfide Protection and Monitoring Equipment

Two portable hydrogen sulfide monitors positioned on location for optimum coverage and detection. The units shall have audible sirens to notify personnel when hydrogen sulfide levels exceed 20 ppm.

#### 4. Visual Warning Systems

- A. Wind direction indicators as indicated on the wellsite diagram.
- B. Caution signs shall be posted on roads providing access to location. Signs shall be painted a high visibility color with lettering of sufficient size to be readable at reasonable distances from potentially contaminated areas.

#### 3. Mud Program

The mud program has been designed to minimize the amount of hydrogen sulfide entrained in the mud system. Proper mud weight, safe drilling practices, and the use of hydrogen sulfide scavengers will minimize hazards while drilling the well.

## 4. Metallurgy

All tubular systems, wellheads, blowout preventers, drilling spools, kill lines, choke manifolds, and valves shall be suitable for service in a hydrogen sulfide environment when chemically treated.

#### 5. Communications

State & County Officials phone numbers are posted on rig floor and supervisors trailer. Communications in company vehicles and toolpushers are either two way radios or cellular phones.

#### 6. Well Testing

Drill stem testing is not an anticipated requirement for evaluation of this well. A drill stem test is required, it will be conducted with a minimum number of personnel in the immediate vicinity. The test will be conducted during daylight hours only.

#### 7. General Requirements


MOC has researched this area and no high concentrations of H2S was found. MOC will have on location and working all H2S safety equipment before Yates formation.

# Notes Regarding Blowout Preventer Mewbourne Oil Company

Empire 18 St #6 990' FSL & 330' FEL Section 18-T17S-R29E Eddy County, New Mexico

- 1. Drilling nipple (bell nipple) to be constructed so that it can be removed without the use of a welder through the opening of the rotary table, with minimum internal diameter equal to blowout preventer bore.
- 2. Blowout preventer and all fittings must be in good condition with a minimum 3000 psi working pressure.
- 3. Safety valve must be available on the rig floor at all times with proper connections to install in the drill string. Valve must be full bore with minimum 3000 psi working pressure.
- 4. Equipment through which bit must pass shall be at least as large as internal diameter of the casing.
- 5. A kelly cock shall be installed on the kelly at all times.
- 6. Blowout preventer closing equipment to include and accumulator of at least 40 gallon capacity, two independent sources of pressure on closing unit, and meet all other API specifications.

## Mewbourne Oil Company BOP Scematic for 8 3/4" or 7 7/8" Hole



Empire 18 St #6 Sec 18-T17S-R29E 990' FSL & 330' FEL Eddy County, NM

SECTION 18, TOWNSHIP 17 SOUTH, RANGE 29 EAST, NMPM, EDDY COUNTY, NEW MEXICO. 3706 3647 0 3680 **36**95 MEWBOURNE PIPELINE 165' FROM PIPELINE 140' FROM #10 PIPELINE Oil Well 365 STATE EMPIRE "18" STATE #1 #6 122' FROM POWERLINE Ò **EMPIRE** STATE #3 Ü.S.A. 673 3635 Exhibit 3 <u> 2</u>000' 1000' 1000 Scale 1" = 1000' THE PREPARATION OF THIS PLAT AND THE PERFORMANCE OF THE SURVEY UPON THE PREPARATION OF THIS PLAT AND THE PENFORMANCE OF THE SURVEY UNDER MY DIRECTION AND THE PLAT WHICH IT IS BASED WERE DONE UNDER MY DIRECTION AND THE PLAT ACCURATELY DEPICTS THE RESULTS OF FAIR SURVEYS IN NEW MEXICO AS REQUIREMENTS OF THE STANDARDS FOR LAND SURVEYS IN NEW MEXICO AS ADOPTED BY THE NEW MEXICO STATE TOWN OF REGISTRATION FOR PROFESSIONAL ENGINEERS AND UNDERSTORMS. MEWBOURNE COMPANY LEASE ROAD TO ACCESS THE MEWBOURNE EMPIRE "18" STATE #6, 7, 8, 9, & 10 WELLS, LOCATED IN SECTION 18, TOWNSHIP 17 SOUTH, RANGE 29 EAST, NMPM, EDDY COUNTY, NEW MEXICO. vo.3640 Survey Date: 12/06/2004 Sheet 1 Sheets of WING COMPANY GENERAL SUR P.O. BOX 1928 Drawn By: Ed Blevins W.O. Number NEW MEXICO 88260 Date: 12/06/04 LOVINGTON. Scale 1" = 1000' EMPIRE

Rig Location Schematic

