

Submit to Appropriate District Office
State Lease - 6 copies
Fee Lease - 5 copies

District I

1625 N. French, Hobbs, NM 88240

District II

1301 W. Grand Avenue, Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION

1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-105

Revised June 10, 2003

WELL API NO.

30-015-33315

5. Indicate Type Of Lease
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. Type of Well:
OIL WELL ☒ GAS WELL ☐ DRY ☐ OTHER _____
b. Type of Completion:
NEW WELL ☒ WORK OVER ☐ DEEPEN ☐ PLUG BACK ☐ DIFF. RESVR. ☐ OTHER _____

RECEIVED

DEC 22 2004

000-ARTESIA

7. Lease Name or Unit Agreement Name

Big Walt 2 State

2. Name of Operator

Nearburg Producing Company

8. Well No.

8

3. Address of Operator

3300 N A St., Bldg 2, Ste 120, Midland, TX 79705

9. Pool name or Wildcat

Indian Basin; Upper Penn, Ass.

4. Well Location

Unit Letter H : 2018 Feet From The North Line and 723 Feet From The East Line

Section 2 Township 22S Range 24E NMPM Eddy County

10. Date Spudded 10/19/04 11. Date T.D. Reached 11/18/04 12. Date Compl. (Ready to Prod.) 12/3/04 13. Elevations (DF & RKB, RT, GR, etc.) 3862' 14. Elev. Casinghead

15. Total Depth 8340 16. Plug Back T.D. 8295 17. If Multiple Compl. How Many Zones? _____ 18. Intervals Drilled By _____ Rotary Tools X Cable Tools

19. Producing Interval(s), of this completion - Top, Bottom, Name
7914-7991 (OA)

20. Was Directional Survey Made
Yes

21. Type Electric and Other Logs Run
Litho Density; Comp Neutron

22. Was Well Cored
No

23. CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
9-5/8	36#	1490	14-3/4	1300	250
7	23 & 26#	8340	8-3/4	960	245

24. LINER RECORD

SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	SIZE	DEPTH SET	PACKER SET
					2-7/8	8027	

25. TUBING RECORD

26. Perforation record (interval, size, and number)

7914-7991 (OA) 4 JSPF (308 Holes)

27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.

DEPTH INTERVAL AMOUNT AND KIND MATERIAL USED
7914-7991 352 bbls 20% HCL

28. PRODUCTION

Date First Production 12/3/04 Production Method (Flowing, gas lift, pumping - Size and type pump) Pumping Well Status (Prod. or Shut-in) Producing

Date of Test 12/15/04 Hours Tested 24 Choke Size _____ Prod'n For Test Period _____ Oil - Bbl. 612 Gas - MCF 279 Water - Bbl. 3610 Gas - Oil Ratio 4561

Flow Tubing Press. 300 Casing Pressure 230 Calculated 24-Hour Rate _____ Oil - Bbl. 612 Gas - MCF 279 Water - Bbl. 3610 Oil Gravity - API -(Corr.) 39.1

29. Disposition of Gas (Sold, used for fuel, vented, etc.)

Sold

Test Witnessed By

Bill Young

30. List Attachments

C104 Logs; Surveys

31. I hereby certify that the information shown on both sides of this form is true and complete to the best of my knowledge and belief

Signature

Printed Name

Sarah Jordan

Title Production Analyst Date 12/21/04

E-mail address

sjordan@nearburg.com

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico		Northeastern New Mexico	
T. Anhy	T. Canyon	T. Ojo Alamo	T. Penn. "B"
T. Salt	T. Strawn	T. Kirtland-Fruitland	T. Penn. "C"
B. Salt	T. Atoka	T. Pictured Cliffs	T. Penn. "D"
T. Yates	T. Miss	T. Cliff House	T. Leadville
T. 7 Rivers	T. Devonian	T. Menefee	T. Madison
T. Queen	T. Silurian	T. Point Lookout	T. Elbert
T. Grayburg	T. Montoya	T. Mancos	T. McCracken
T. San Andres	T. Simpson	T. Gallup	T. Ignacio Otzte
T. Glorieta	T. McKee	Base Greenhorn	T. Granite
T. Paddock	T. Ellenburger	T. Dakota	T.
T. Blinbry	T. Gr. Wash	T. Morrison	T.
T. Tubb	T. Delaware Sand	T. Todilto	T.
T. Drinkard	T. Bone Springs	T. Entrada	T.
T. Abo	T.	T. Wingate	T.
T. Wolfcamp 7456		T. Chinle	T.
T. Penn	T. 3 Bone Spring 7029	T. Permian	T.
T. Cisco (Bough C) 7914	T.	T. Penn "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from 7914 to 7991
 No. 2, from to

No. 3, from to
 No. 4, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet
 No. 2, from to feet
 No. 3, from to feet

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology	From	To	Thickness in Feet	Lithology
1500	2000	500	Dolo				
2000	2760	760	Sand				
2760	7100	4340	Dolo				
7100	7470	370	Sand				
7470	7914	444	Shale				
7914	7951	37	Dolo				
7951	8340	389	Lost Returns				

Survey Report



Report Date: November 18, 2004	Survey / DLS Computation Method: Minimum Curvature / Lubinski
Client: Nearburg Producing	Vertical Section Azimuth: 201.070°
Field: Eddy County, NM	Vertical Section Origin: N 0.000 ft, E 0.000 ft
Structure / Slot: Big Walt 2 St #8 / Big Walt 2 St #8	TVD Reference Datum: RKB
Well: Big Walt 2 St #8	TVD Reference Elevation: 0.0 ft relative to
Borehole: Big Walt 2 St #8	Sea Bed / Ground Level Elevation: 0.000 ft relative to
UWI/API#:	Magnetic Declination: 8.999°
Survey Name / Date: Big Walt 2-8_sur / October 28, 2004	Total Field Strength: 49471.377 nT
Tort / AHD / DDI / ERD ratio: 83.507° / 968.03 ft / 4.911 / 0.117	Magnetic Dip: 60.450°
Grid Coordinate System: NAD27 New Mexico State Planes, Eastern Zone, US Feet	Declination Date: October 28, 2004
Location Lat/Long: N 32 25 21.765, W 104 27 44.502	Magnetic Declination Model: IGRF 2000
Location Grid N/E Y/X: N 517520.900 ftUS, E 460186.500 ftUS	North Reference: Grid North
Grid Convergence Angle: -0.06918006°	Total Corr Mag North -> Grid North: +9.068°
Grid Scale Factor: 0.99991091	Local Coordinates Referenced To: Well Head

Comments	Survey Type (Markers)	Measured Depth (ft)	Inclination (deg)	Azimuth (deg)	TVD (ft)	Vertical Section (ft)	NS (ft)	EW (ft)	Closure (ft)	Closure Azimuth (deg)	DLS (deg/100 ft)	Tool Face (deg)
SL	***	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	55.60M
	***	183.00	0.30	55.60	183.00	-0.39	0.27	0.40	0.48	55.60	0.16	54.70M
	***	271.00	0.40	54.70	271.00	-0.84	0.58	0.84	1.02	55.33	0.11	81.70M
	***	360.00	0.30	81.70	360.00	-1.21	0.79	1.32	1.54	59.06	0.21	48.30M
	***	391.00	0.30	48.30	391.00	-1.33	0.86	1.46	1.69	59.60	0.56	40.30M
	***	421.00	0.30	40.30	421.00	-1.47	0.97	1.57	1.85	58.32	0.14	-1.90M
	***	451.00	0.10	358.10	450.99	-1.57	1.06	1.62	1.93	56.92	0.79	63.30M
	***	482.00	0.10	63.30	481.99	-1.61	1.09	1.64	1.97	56.34	0.35	34.10M
	***	513.00	0.30	34.10	512.99	-1.71	1.17	1.71	2.08	55.58	0.70	21.70M
	***	544.00	0.30	21.70	543.99	-1.87	1.32	1.79	2.22	53.65	0.21	72.80M
	***	577.00	0.20	72.80	576.99	-1.99	1.41	1.88	2.35	52.99	0.71	13.70M
	***	608.00	0.20	13.70	607.99	-2.08	1.48	1.94	2.44	52.62	0.64	-88.20M
	***	639.00	0.30	271.80	638.99	-2.11	1.54	1.87	2.42	50.60	1.27	-143.20M
	***	670.00	0.90	216.80	669.99	-1.85	1.35	1.65	2.13	50.73	2.48	-147.00M
	***	701.00	0.80	213.00	700.99	-1.40	0.97	1.38	1.69	54.96	0.37	-133.20M
	***	732.00	1.20	226.80	731.98	-0.90	0.56	1.03	1.17	61.18	1.50	-137.50M
	***	762.00	1.60	222.50	761.97	-0.22	0.04	0.51	0.52	85.43	1.38	-145.60M
	***	793.00	1.60	214.40	792.96	0.60	-0.64	-0.02	0.64	181.98	0.73	-149.80M
	***	824.00	2.30	210.20	823.94	1.64	-1.53	-0.58	1.64	200.74	2.30	-148.40M
	***	854.00	2.50	211.60	853.92	2.87	-2.61	-1.22	2.88	205.17	0.69	-157.10M
	***	885.00	2.70	202.90	884.89	4.27	-3.86	-1.86	4.28	205.79	1.43	-159.00M
	***	915.00	3.00	201.00	914.85	5.76	-5.24	-2.42	5.77	204.79	1.05	-158.60M
	***	945.00	3.60	201.40	944.80	7.49	-6.85	-3.04	7.50	203.97	2.00	-157.80M
	***	975.00	3.90	202.20	974.74	9.45	-8.67	-3.77	9.46	203.52	1.02	-160.30M
	***	1005.00	4.20	199.70	1004.66	11.57	-10.65	-4.53	11.57	203.04	1.16	-158.60M
	***	1036.00	4.60	201.40	1035.57	13.94	-12.88	-5.37	13.95	202.62	1.36	-159.30M
	***	1066.00	4.70	200.70	1065.47	16.38	-15.15	-6.24	16.38	202.39	0.38	-158.70M
	***	1097.00	4.80	201.30	1096.36	18.94	-17.54	-7.16	18.95	202.20	0.36	-160.10M
	***	1127.00	5.10	199.90	1126.25	21.53	-19.97	-8.07	21.53	202.01	1.08	55.10G
	***	1157.00	5.50	205.50	1156.12	24.30	-22.52	-9.14	24.30	202.10	2.18	-31.47G
	***	1186.00	5.80	203.70	1184.98	27.15	-25.11	-10.33	27.15	202.36	1.20	-11.57G
	***	1216.00	6.40	202.60	1214.81	30.33	-28.04	-11.58	30.34	202.44	2.04	4.65G
	***	1247.00	7.00	203.00	1245.60	33.95	-31.38	-12.98	33.96	202.48	1.94	-3.59G
	***	1277.00	7.20	202.90	1275.37	37.65	-34.79	-14.43	37.67	202.52	0.67	-26.52G
	***	1308.00	7.60	201.40	1306.11	41.65	-38.49	-15.93	41.66	202.49	1.43	-17.43G
	***	1338.00	8.00	200.50	1335.83	45.72	-42.29	-17.39	45.73	202.35	1.39	90.00G
	***	1398.00	8.00	200.70	1395.25	54.07	-50.11	-20.33	54.08	202.08	0.05	-90.00G
	***	1448.00	8.00	199.10	1444.76	61.02	-56.65	-22.69	61.03	201.83	0.45	32.38G
	SS	1595.00	9.00	203.07	1590.15	82.74	-76.90	-30.55	82.74	201.67	0.79	149.67G
	SS	1734.00	8.50	205.07	1727.53	103.85	-96.21	-39.16	103.87	202.15	0.42	-121.25G

Comments	Survey Type (Markers)	Measured Depth (ft)	Inclination (deg)	Azimuth (deg)	TVD (ft)	Vertical Section (ft)	NS (ft)	EW (ft)	Closure (ft)	Closure Azimuth (deg)	DLS (deg/100 ft)	Tool Face (deg)
	SS	1889.00	8.25	202.07	1880.88	126.40	-116.89	-48.19	126.43	202.41	0.32	151.88G
	SS	2015.00	7.75	204.07	2005.65	143.92	-133.02	-55.05	143.97	202.48	0.45	123.61G
	SS	2225.00	7.50	207.07	2213.80	171.69	-158.15	-67.07	171.79	202.98	0.22	90.00G
	SS	2391.00	7.50	210.07	2378.38	193.17	-177.18	-77.43	193.36	203.60	0.24	117.94G
	SS	2514.00	7.25	214.07	2500.36	208.66	-190.55	-85.80	208.98	204.24	0.46	114.42G
	SS	2704.00	7.00	219.07	2688.89	231.35	-209.47	-99.81	232.04	205.48	0.35	-45.77G
	SS	2881.00	7.25	217.07	2864.53	252.34	-226.76	-113.34	253.51	206.56	0.20	156.80G
	SS	3051.00	6.25	221.07	3033.35	271.35	-242.29	-125.88	273.04	207.45	0.65	90.00G
	SS	3206.00	6.25	223.07	3187.43	287.10	-254.82	-137.19	289.40	208.30	0.14	180.00G
	SS	3372.00	5.75	223.07	3352.52	303.19	-267.49	-149.04	306.21	209.13	0.30	-60.59G
	SS	3589.00	6.00	219.07	3568.38	324.06	-284.24	-163.61	327.96	209.92	0.22	0.00G
	SS	3707.00	6.23	219.07	3685.71	336.01	-294.00	-171.53	340.38	210.26	0.19	80.07G
	SS	3904.00	6.25	220.07	3881.54	356.32	-310.50	-185.17	361.53	210.81	0.06	90.00G
	SS	4291.00	6.25	221.07	4266.24	396.03	-342.51	-212.57	403.11	211.83	0.03	140.51G
	SS	4516.00	6.00	223.07	4489.96	418.44	-360.33	-228.65	426.75	212.40	0.15	-51.43G
	SS	4734.00	8.50	205.07	4706.22	445.08	-383.25	-243.26	453.94	212.40	1.54	115.10G
	SS	4965.00	8.75	259.07	4934.96	471.47	-402.08	-267.78	483.09	213.66	3.38	-151.25G
	SS	5090.00	8.00	256.07	5058.63	481.49	-405.98	-285.56	496.35	215.12	0.69	16.51G
	SS	5228.00	8.50	257.07	5195.20	492.71	-410.57	-304.82	511.36	216.59	0.38	180.00G
	SS	5268.00	8.25	257.07	5234.78	495.96	-411.87	-310.50	515.80	217.01	0.62	-141.62G
	SS	5404.00	7.75	254.07	5369.45	506.94	-416.57	-328.83	530.72	218.29	0.48	0.00G
	SS	5467.00	8.00	254.07	5431.86	512.13	-418.94	-337.13	537.74	218.82	0.40	49.50G
	SS	5520.00	8.25	256.07	5484.33	516.53	-420.87	-344.37	543.80	219.29	0.71	0.00G
	SS	5585.00	8.25	256.07	5548.65	521.88	-423.12	-353.42	551.30	219.87	0.00	-151.88G
	SS	5646.00	7.75	254.07	5609.06	526.87	-425.30	-361.62	558.26	220.37	0.94	-90.00G
	SS	5782.00	7.75	242.07	5743.83	539.31	-432.11	-378.54	574.47	221.22	1.19	104.85G
	***	5904.00	7.50	260.10	5864.77	549.62	-437.33	-393.66	588.41	221.99	1.96	-161.12G
	***	5936.00	6.60	257.40	5896.52	551.71	-438.09	-397.51	591.56	222.22	3.00	-114.34G
	***	5967.00	6.30	250.40	5927.33	553.81	-439.05	-400.85	594.51	222.40	2.71	-80.07G
	***	5999.00	6.50	243.00	5959.13	556.30	-440.46	-404.12	597.76	222.54	2.65	-78.79G
	***	6031.00	6.90	231.70	5990.91	559.30	-442.48	-407.24	601.36	222.63	4.30	-76.63G
	***	6062.00	7.30	221.90	6021.67	562.74	-445.10	-410.02	605.17	222.65	4.11	-69.93G
	***	6093.00	7.60	216.40	6052.41	566.56	-448.21	-412.55	609.17	222.63	2.49	-109.18G
	***	6125.00	7.30	207.70	6084.14	570.62	-451.72	-414.75	613.24	222.56	3.64	-74.86G
	***	6156.00	7.50	202.80	6114.89	574.60	-455.33	-416.45	617.05	222.45	2.13	-119.65G
	***	6187.00	7.10	196.50	6145.64	578.53	-459.03	-417.78	620.68	222.31	2.88	-58.54G
	***	6218.00	7.70	189.80	6176.38	582.48	-462.91	-418.68	624.16	222.13	3.39	-74.57G
	***	6249.00	8.00	183.30	6207.09	586.57	-467.11	-419.15	627.60	221.90	3.02	-102.86G
	***	6280.00	7.80	171.60	6237.80	590.46	-471.35	-418.97	630.64	221.63	5.22	-81.95G
	***	6312.00	8.00	164.50	6269.49	594.13	-475.64	-418.06	633.25	221.31	3.11	-112.32G
	***	6344.00	7.70	158.20	6301.19	597.49	-479.78	-416.67	635.45	220.97	2.85	-109.10G
	***	6376.00	7.40	149.60	6332.92	600.35	-483.54	-414.83	637.10	220.63	3.65	-90.00G
	***	6405.00	7.40	137.90	6361.68	602.36	-486.54	-412.63	637.95	220.30	5.19	-90.00G
	***	6437.00	7.40	132.30	6393.41	604.03	-489.46	-409.72	638.31	219.93	2.25	-78.76G
	***	6468.00	7.70	124.00	6424.14	605.22	-491.96	-406.53	638.19	219.57	3.65	-22.73G
	***	6499.00	8.00	123.10	6454.85	606.13	-494.30	-403.00	637.76	219.19	1.05	42.96G
	***	6532.00	8.40	125.60	6487.51	607.22	-496.96	-399.11	637.38	218.77	1.62	43.09G
	***	6563.00	8.80	128.00	6518.17	608.48	-499.74	-395.40	637.24	218.35	1.73	12.69G
	***	6595.00	9.70	129.20	6549.75	610.03	-502.95	-391.39	637.29	217.89	2.88	56.10G
	***	6627.00	10.20	133.20	6581.27	611.93	-506.59	-387.23	637.64	217.39	2.66	180.00G
	***	6657.00	10.10	133.20	6610.80	613.93	-510.21	-383.38	638.19	216.92	0.33	123.50G
	***	6689.00	9.90	135.00	6642.31	616.10	-514.08	-379.39	638.91	216.43	1.16	-26.07G
	***	6721.00	10.50	133.40	6673.81	618.32	-518.02	-375.32	639.70	215.92	2.07	-71.94G
	***	6753.00	10.60	131.80	6705.27	620.47	-521.99	-371.01	640.41	215.40	0.97	137.77G
	***	6784.00	10.50	132.30	6735.74	622.50	-525.79	-366.80	641.09	214.90	0.44	-5.40G

Comments	Survey Type (Markers)	Measured Depth (ft)	Inclination (deg)	Azimuth (deg)	TVD (ft)	Vertical Section (ft)	NS (ft)	EW (ft)	Closure (ft)	Closure Azimuth (deg)	DLS (deg/100 ft)	Tool Face (deg)
	***	6814.00	10.90	132.10	6765.22	624.51	-529.53	-362.67	641.82	214.41	1.34	-85.54G
	***	6846.00	11.00	127.60	6796.64	626.47	-533.42	-358.01	642.42	213.87	2.69	-30.82G
	***	6878.00	11.40	126.40	6828.03	628.17	-537.16	-353.04	642.79	213.31	1.45	-45.40G
	***	6909.00	11.60	125.40	6858.41	629.75	-540.79	-348.03	643.10	212.76	0.91	-161.26G
	***	6941.00	11.20	124.70	6889.78	631.28	-544.42	-342.86	643.38	212.20	1.32	172.00G
	***	6972.00	10.80	125.00	6920.21	632.69	-547.80	-338.00	643.68	211.68	1.30	105.99G
	***	7004.00	10.70	127.00	6951.64	634.23	-551.31	-333.17	644.16	211.15	1.21	-10.81G
	***	7036.00	11.00	126.70	6983.07	635.86	-554.92	-328.35	644.79	210.61	0.95	64.13G
	***	7068.00	11.30	129.70	7014.47	637.69	-558.75	-323.49	645.64	210.07	2.04	35.02G
	***	7100.00	11.50	130.40	7045.84	639.75	-562.82	-318.65	646.76	209.52	0.76	25.57G
	***	7131.00	11.80	131.10	7076.20	641.85	-566.90	-313.91	648.01	208.97	1.07	180.00G
	***	7163.00	11.50	131.10	7107.54	644.07	-571.15	-309.04	649.40	208.42	0.94	-103.03G
	***	7195.00	11.40	128.70	7138.90	646.12	-575.22	-304.17	650.69	207.87	1.52	-103.13G
	***	7226.00	11.30	126.30	7169.30	647.84	-578.94	-299.33	651.74	207.34	1.56	-177.29G
	***	7258.00	10.90	126.20	7200.70	649.46	-582.58	-294.36	652.73	206.81	1.25	17.96G
	***	7289.00	11.20	126.70	7231.12	651.03	-586.11	-289.58	653.75	206.29	1.02	-35.36G
	***	7320.00	11.60	125.30	7261.51	652.61	-589.71	-284.63	654.81	205.76	1.57	0.00G
	***	7352.00	11.70	125.30	7292.85	654.20	-593.45	-279.35	655.91	205.21	0.31	100.15G
	***	7383.00	11.60	128.60	7323.21	655.91	-597.21	-274.35	657.21	204.67	2.17	-90.00G
	***	7414.00	11.60	127.70	7353.58	657.74	-601.06	-269.45	658.69	204.15	0.58	-175.79G
	***	7445.00	10.60	127.30	7384.00	659.43	-604.69	-264.72	660.10	203.64	3.24	-174.91G
	***	7476.00	8.20	125.80	7414.58	660.79	-607.71	-260.65	661.25	203.21	7.78	169.47G
	***	7508.00	6.60	128.40	7446.31	661.92	-610.19	-257.36	662.24	202.87	5.11	-172.47G
	***	7539.00	5.70	127.20	7477.14	662.88	-612.23	-254.74	663.11	202.59	2.93	139.56G
	***	7571.00	5.30	131.00	7508.99	663.82	-614.16	-252.36	663.98	202.34	1.69	107.95G
	***	7603.00	5.10	140.30	7540.86	665.02	-616.22	-250.33	665.13	202.11	2.70	37.15G
	***	7635.00	5.50	143.40	7572.72	666.53	-618.55	-248.51	666.60	201.89	1.54	43.22G
Last MWD Survey	***	7660.00	6.10	148.50	7597.59	667.98	-620.64	-247.10	668.02	201.71	3.16	-114.43G
	SS	7910.00	5.75	139.07	7846.26	681.94	-641.43	-231.96	682.08	199.88	0.41	111.46G
TD	SS	8312.00	5.50	174.07	8246.44	708.56	-675.82	-216.77	709.73	197.78	0.84	0.00G

TD