Submit 1 Copy To Appropriate District Office		ate of New Me						orm C-103	
Office Energy, Minerals and Natural Resources District 1625 N French Dr, Hobbs, NM 88240						October 13, 2009 WELL API NO.			
DISTRICT OUL CONSERVATION DIVISION						30-015-39034			
District III 1220 South St. Francis Dr.						5. Indicate Type of Lease			
1000 Rio Brazos Rd, Aztec, NM 87410 Santa Fe, NM 87505 District IV						STATE X FEE			
1220 S St Francis Dr, Santa Fe, NM 87505					6. State O	il & Gas l 648	Lease No.		
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)					7. Lease Name or Unit Agreement Name: East Millman Unit				
1. Type of Well: Oil Well 🗓 Gas Well 🗋 Other					8. Well Number 238				
2. Name of Operator Stephens & Johnson Operating Co						Number 0199	58		
3. Address of Operator						10. Pool name or Wildcat			
P 0 Box 2249, Wichita Falls, TX 76307  4. Well Location						Millman: Yates-SR-QN-GB-SA, East			
	1981 feet fro	om the Nor	<u>rth</u> 1	ine and	572	feet from	n the Ea	stline	
Section 14	Towns	hip 19S	Range	28E	NMPM		County	Eddy	
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3414' KB; 3402' GR									
12. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data									
					SEQUENT REPORT OF:				
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK							ALTERING	CASING	
TEMPORARILY ABANDON					NG OPNS.	X	P AND A		
PULL OR ALTER CASING					OB				
DOWNHOLE COMMINGLE									
OTHER:			OTHER:						
13. Describe proposed or completed of starting any proposed work). Sproposed completion or recompleted proposed completion or recompleted proposed completion or recompleted proposed completion or recompleted proposed completed proposed p	SEE RULE 19.1								
Spudded 12 1/4" hole 3:45 pm 6-22-11. Drilled to 300' KB & ran 7 jts 8 5/8" 24 #/ft surface csg and cemented w/200 sx cement. Cement circulated to surface (circulate 40 sx to pit). WOC 18 hrs. Pressure test BOP and 8 5/8" surface csg to 1500 psig for 30 minutes. Held OK. Drilled 7 7/8" hole to 2738' KB. Ran 64 jts 5 1/2" 15.50 #/ft csg, set at 2731' KB. Cemented w/675 sx cement. Plug down 10:51 pm 6-28-11. Circulated cement to surface (circulate 75 sx to pit).									
0-20-11. Chiculated cement	, to surrace	(Circulate /	5 5X tO 1	) ( ) .			RECE	IVED	
							JUL O	<b>5</b> 2011	
Spud Date: 6/22/2011		Rig Relea	ase Date:	(	5/29/2011		NMOCD	ARTESIA	
I hereby certify that the information ab	nove is true	complete to the	hest of m	v knowledge	e and helief				
1.1.00.1.1 8		-		_				100 10011	
SIGNATURE With M. M. TITLE Petroleum							DATE6	/30/2011	
Type or print name William M. Kind	caid	mkincaid@sjoc E-mail address:					PHONE <u>940</u>	0-723-2166	
APPROVED BY Conditions of Arrange (if any)	Vay	TIT	F TLE	Field Supe	ervisor	, D.	ATE <u>7-1</u>	5-11	
Conditions of Approval (if any):									