Form 3169-5 (Aug&st 2007)

## UNITED STATES DEPARTMENT OF THE INTERIOR

FORM APPROVED OMB NO. 1004-0135

OCD Artesia Expires. July 31, 2010 BUREAU OF LAND MANAGEMENT Lease Serial No. SUNDRY NOTICES AND REPORTS ON WELLS NMLC028731B Do not use this form for proposals to drill or to re-enter an 6 If Indian, Allottee or Tribe Name abandoned well. Use form 3160-3 (APD) for such proposals. If Unit or CA/Agreement, Name and/or No. SUBMIT IN TRIPLICATE - Other instructions on reverse side. Well Name and No. Type of Well DODD FEDERAL UNIT 37 Oil Well Gas Well Other: **UNKNOWN OTH** Contact. KANICIA CASTILLO API Well No COG OPERATING LLC E-Mail: kcastillo@conchoresources.com 30-015-25175 3a. Address b Phone No (include area code) 10. Field and Pool, or Exploratory 550 WEST TEXAS AVE, STE 100 Ph: 432-685-4332 GRBG JACKSON SR Q GRBG SA MIDLAND, TX 79701 4 Location of Well (Footage, Sec., T., R., M., or Survey Description) 11 County or Parish, and State Sec 14 T17S R29E 2310FNL 25FWL EDDY COUNTY, NM JUL 15 2011 12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF ACTION TYPE OF SUBMISSION □ Acidize □ Deepen Production (Start/Resume) Water Shut-Off □ Notice of Intent ☐ Alter Casing Fracture Treat □ Reclamation Well Integrity Subsequent Report Casing Repair New Construction ☐ Other ☐ Recomplete Final Abandonment Notice Change Plans Plug and Abandon ☐ Temporarily Abandon Convert to Injection Plug Back ■ Water Disposal 13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones Attach the Bond under which the work will be performed or provide the Bond No on file with BLM/BIA Required subsequent reports shall be filed within 30 days following completion of the involved operations If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.) 5/04/11 MIRU. 5/05/11 Sheared pkr trying to release, POOH w/pkr.
5/08/11 RIH w/workstring, RBP @ 4011, pkr @ 3990. Test RBP to 1500 PSI, good test. Release pkr.
Test csg to 600# for 30 min, good test. Retreive RBP. POOH.
5/09/11 Redressed prod pkr. Test tbg in fole. 5000 PSI abid. Set align. Finish testing in hole, no further failers. Circ 60 bbls pkr fluid. Set pkr @ 4027. Perform MIT, Darold Gray w/ OCD witnessed. Passed test. 5/10/11 RDMO. SEE ATTACHED FOR CONDITIONS OF APPROVAL 14. Thereby certify that the foregoing is true and correct Electronic Submission #108654 verified by the BLM Well Information System For COG OPERATING LLC, sent to the Carlsbad Name (Printed/Typed) KANICIA CASTILLO **PREPARER** 

<u>CFPTED FOR RFCORD</u> (Electronic Submission) 05/19/2011 Signature THIS SPACE FOR FEDERAL OR STATE OFFICE USE JUN 2 4 2011 Approved By Title BUREAU OF LAND MANAGEMENT Conditions of approval, if any, are attached Approval of this notice does not warrant or CARLSBAD FIELD OFFICE certify that the applicant holds legal or equitable title to those rights in the subject lease

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

which would entitle the applicant to conduct operations thereon

Office

## Conditions of Approval: Wells with Packers\*

## COG Operating LLC Dodd Federal Unit 37

June 23, 2011

- 1. Conduct a Mechanical Integrity Test of the tubing/casing annulus after a tubing, packer or casing seal is established. Repair that seal any time more than five barrels of packer fluid is replaced within 30 days.
  - a. The minimum test pressure should be 500 psig for 30 minutes or 300 psig for 60 minutes, with 200 psig differentials between tubing and casing pressure (at test time) but no more than 70% of casing burst pressure as described by Onshore Order 2.III.B.1.h. (The tubing or reservoir pressure may need to be reduced). An alternate method for a BLM approved MIT is to have the fluid filled system open to atmospheric pressure and have a loss of less than five barrels in 30 days witnessed by a BLM authorized officer.
  - b. Document the pressure test on a calibrated recorder chart registering within 25 to 85 per cent of its full range. Greater than 10% pressure leakoff will be viewed as a failed MIT. Less than 10% pressure leakoff will be evaluated site specifically and may restrict injection approval.
  - c. Notify Paul R. Swartz at 575-234-5985 and/or 575-200-7902 at least 24 hours before the test. If there is no response, notify the BLM on call drilling phone, 575-361-2822.
  - d. Submit a subsequent Sundry Form 3160-5 relating the MIT activity. List the name of the BLM witness, or the notified person and date of notification. NMOCD is to retain the original recorded MIT chart.
  - e. Use of tubing internal protection, on/off tubing equipment just above the packer, and a profile nipple installation is required. The setting depths and descriptions of each are to be included in the subsequent sundry. List (by date) descriptions of daily activity of any previously unreported wellbore work.
  - f. Submit the original subsequent sundry with three copies to BLM Carlsbad.
- 2. Compliance with a NMOCD Administrative Order is required, submit documentation of that authorization.
  - a. Approved injection pressure compliance is required.
  - b. If injection pressure exceeds the approved pressure you are required to reduce that pressure and notify the BLM within 24 hours.
  - c. When injection pressure is within 50 psig of the maximum pressure, install automation equipment that will prevent exceeding that maximum.
  - i. Submit a subsequent report (Sundry Form 3160-5) describing the installed automation equipment.
  - e. Other unexplained significant variations of rate or pressure to be reported within 5 days of notice.

- 3. The casing/tubing annulus is required to be monitored for communication with injection fluid or loss of casing integrity.
  - a. The annulus is to be maintained full of packer fluid at atmospheric pressure. Installation of equipment that will display on site, continuous open to the air fluid level is required. A BLM inspector may request verification of this fluid level at any time.
  - b. Loss of packer fluid above five barrels per month requires notification of the BLM authorized officer within 5 days.
  - c. Gain of annular fluid requires notification within 24 hours. Cease injection and maintain a production casing pressure of Opsia. Notify the BLM's authorized officer (Paul R. Swartz at 575-200-7902). If there is no response, notify the BLM on call drilling phone, 575-361-2822.
  - d. Also submit to this office a (Sundry Form 3160-5) Notice of Intent (NOI) for approval by BLM and NMOCD with a detailed plan for correction and the anticipated date of correction. Verbal approval for the plan may be given by a BLM authorized officer, with the NOI filed within five business days.
  - e. After the repairs submit a (Sundry Form 3160-5) Subsequent report, describing the repair(s) and Mechanical Integrity Test as per item 1 above.
  - f. The operator shall keep accurate and current records documenting that the casing annulus is fluid filled. A suggested format for these records is available from the BLM Carlsbad Field Office. Copies of those records shall be furnished at the request of a BLM authorized officer.

\*COA's prepared by Paul R Swartz