Form 3160-5 (August 2007)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

OCD Artesia

FORM APPROVED

OMB N	O 10	004-	0135
Expires:	July	31,	2010

Lease Serial No.

SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.			NMLC029395B				
			6. If Indian, Allottee or Tribe Name				
SUBMIT IN TRIPLICATE - Other instructions on reverse side.				7 If Unit or CA/Agreement, Name and/or No.			
1. Type of Well					8 Well Name and No. TURNER B 59		
Oil Well Gas Well Other INTECTION						<u>.</u>	
2. Name of Operator Contact TERRY CALLAHAN LINN OPERATING INCORPORATED E-Mail: tcallahan@linnenergy.com					9. API Well No 30-015-05446-00-S1		
3a Address 600 TRAVIS STREET SUITE 5100 HOUSTON, TX 77002 3b. Phone No (include area code) Ph: 281-840-4272				e)	10 Field and Pool, or Exploratory GRAYBURG		
4 Location of Well (Footage, Sec., T, R., M, or Survey Description)					11 County or Parish, and State		
Sec 29 T17S R31E NENE 560FNL 660FEL 🗡					EDDY COUNTY, NM		
ULA					· _		
12. CHECK APP	ROPRIATE BOX(ES) TO	OINDICATE	E NATURE OF	NOTICE, RI	EPORT, OR OTHER	DATA	
TYPE OF SUBMISSION	TYPE OF ACTION						
Notice of Intent	☐ Acidize	□ Dee	pen		ion (Start/Resume)	Water Shut-Off	
_	Alter Casing Fracture Treat		□ Reclam	ation	☐ Well Integrity		
Subsequent Report	□ Casing Repair	□ Nev	☐ New Construction		plete		
Final Abandonment Notice Change Plans		□ Plug	g and Abandon	□ Tempor	arily Abandon		
_ ,	Convert to Injection	Plug	Plug Back Water		Pisposal		
If the proposal is to deepen direction Attach the Bond under which the wo following completion of the involved testing has been completed. Final Aldetermined that the site is ready for f RETURN TO INJECTION.	rk will be performed or provide operations. If the operation re candonment Notices shall be file	the Bond No o sults in a multip	n file with BLM/BI le completion or rec	A. Required su completion in a	bsequent reports shall be fil- new interval, a Form 3160-4	ed within 30 days I shall be filed once	
6/23/2011 - FLOWED BACK 2	250 BBLS				•		
SEE ATTACHED CONDITIONS O	F APPROVAL Accepted for NMOC		AUG	EIVEI 4 2011 D ARTES			
14 Thereby certify that the foregoing is	Electronic Submission # For LINN OPERA	112883 verifie	d by the BLM We ORATED. sent to	ell Information	n System d		
Committed to AFMSS for processing by DEBORAH MCKINNEY on 07/15/2011					(11DLM1063SE)		
Name(Printed/Typed) TERRY C	ALLAHAN		Title REGUL	_ATORY SPE	ECIALIST III	•	
Signature (Electronic S	Submission)		Date 07/13/2	2011			
	THIS SPACE FO	OR FEDERA	L OR STATE	OFFICE US	SE		
Approved By ACCEPT			DUNCAN WHITLOCK Title LEAD PETROLEUM ENGINEERING TECH Date 08/01/201				
Conditions of approval, if any, are attached certify that the applicant holds legal or equivalent would entitle the applicant to conditions.	ntable title to those rights in th		Office Carlsbad				

Title 18 U S C Section 1001 and Title 43 U S C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

Conditions of Approval: Wells with Packers*

Linn Operating, Inc. Turner B - 059

July 25, 2011

- Conduct a Mechanical Integrity Test of the tubing/casing annulus after a tubing, packer or casing seal is established. Repair that seal any time more than five barrels of packer fluid is replaced within 30 days.
 - a. The minimum test pressure should be 500 psig for 30 minutes or 300 psig for 60 minutes, with 200 psig differentials between tubing and casing pressure (at test time) but no more than 70% of casing burst pressure as described by Onshore Order 2.III.B.1.h. (The tubing or reservoir pressure may need to be reduced). An alternate method for a BLM approved MIT is to have the fluid filled system open to atmospheric pressure and have a loss of less than five barrels in 30 days witnessed by a BLM authorized officer.
 - b. Document the pressure test on a calibrated recorder chart registering within 25 to 85 per cent of its full range. Greater than 10% pressure leakoff will be viewed as a failed MIT. Less than 10% pressure leakoff will be evaluated site specifically and may restrict injection approval.
 - c. Notify Paul R. Swartz at 575-234-5985 and/or 575-200-7902 at least 24 hours before the test. If there is no response, notify the BLM on call drilling phone, 575-361-2822.
 - d. Submit a subsequent Sundry Form 3160-5 relating the MIT activity. List the name of the BLM witness, or the notified person and date of notification. NMOCD is to retain the original recorded MIT chart.
 - e. Use of tubing internal protection, on/off tubing equipment just above the packer, and a profile nipple installation is required. The setting depths and descriptions of each are to be included in the subsequent sundry. List (by date) descriptions of daily activity of any previously unreported wellbore work.
 - f. Submit the original subsequent sundry with three copies to BLM Carlsbad.
- 2. Compliance with a NMOCD Administrative Order is required, submit documentation of that authorization.
 - a. Approved injection pressure compliance is required.
 - b. If injection pressure exceeds the approved pressure you are required to reduce that pressure and notify the BLM within 24 hours.
 - c. When injection pressure is within 50 psig of the maximum pressure, install automation equipment that will prevent exceeding that maximum.
 - i. Submit a subsequent report (Sundry Form 3160-5) describing the installed automation equipment within 30 days.
 - e. Other unexplained significant variations of rate or pressure to be reported within 5 days of notice.

- 3. The casing/tubing annulus is required to be monitored for communication with injection fluid or loss of casing integrity.
 - a. The annulus is to be maintained full of packer fluid at atmospheric pressure. Installation of equipment that will display on site, continuous open to the air fluid level is required. A BLM inspector may request verification of this fluid level at any time.
 - b. **Submit a subsequent report (Sundry Form 3160-5)** describing the installation of packer fluid level monitoring equipment within 30 days of this approval.
 - The operator shall keep monthly records documenting that the casing annulus is fluid filled.
 A suggested format for these records is available from the BLM Carlsbad Field Office.
 Copies of those records shall be furnished at the request of a BLM authorized officer.
 - d. Loss of packer fluid above five barrels per month requires notification of the BLM authorized officer within 5 days.
 - e. Gain of annular fluid requires notification within 24 hours. Cease injection and maintain a production casing pressure of Opsia. Notify the BLM's authorized officer (Paul R. Swartz at 575-200-7902). If there is no response, notify the BLM on call drilling phone, 575-361-2822.
 - f. Also submit to this office a (Sundry Form 3160-5) Notice of Intent (NOI) for approval by BLM and NMOCD with a detailed plan for correction and the anticipated date of correction. Verbal approval for the plan may be given by a BLM authorized officer, with the NOI filed within five business days.
 - g. After the repairs submit a (Sundry Form 3160-5) Subsequent report, describing the repair(s) and Mechanical Integrity Test as per item 1 above.

^{*}COA's prepared by Paul R. Swartz