Form 3160-5 (August 2007)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE - Other instructions on reverse side.

OCD-	そんさい
FORM A	APPROVED
OMB NO	O. 1004-0135
Expires:	July 31, 2010

Lease Serial No

SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.

NMNM0437523 6. If Indian, Allottee or Tribe Name

7. If Unit or CA/Agreement, Name and/or No.

1 Type of Well					8. Well Name and No. GRATEFUL BOD FEDERAL COM 1H		
					9. API Well No		
2. Name of Operator Contact. TINA HUERTA YATES PETROLEUM CORPORATIONE-Mail: tinah@yatespetroleum com				30-015-38990-00-X1			
3a. Address 3b. Phone No 105 SOUTH FOURTH STREET Ph: 575-748 ARTESIA, NM 88210 Fx: 575-748-							
4 Location of Well (Footage, Sec., T., R., M., or Survey Description)			11. County or Parish, and State				
Sec 13 T18S R29E NENE Lot A 786FNL 545FEL /					EDDY COUNTY, NM		
12. CHECK APPE	ROPRIATE BOX(ES) TO	O INDICATE	NATURE OF	NOTICE, R	EPORT, OR OTHER	R DATA	
TYPE OF SUBMISSION	TYPE OF ACTION						
☐ Notice of Intent Subsequent Report Final Abandonment Notice	☐ Acidize ☐ Alter Casing ☐ Casing Repair ☐ Change Plans ☐ Convert to Injection	□ New	ture Treat Reclamation Construction Recomplete and Abandon Temporarily Abandon		ation plete rarily Abandon	☐ Water Shut-Off ☐ Well Integrity ☑ Other Drilling Operations	
Attach the Bond under which the worfollowing completion of the involved testing has been completed. Final At determined that the site is ready for f 7/15/11 - Resumed drilling at at 381'. Cemented with 150 s Poly-E-Flake + 1% CaCl (yld "C" + 2% CaCl (yld 1.35, wt 14 tagged cement at 185'. NOTE Ran 1" and tagged at 185'. C WOC. Ran 1" and tagged at 14.8). WOC. Ran 1" and tag wt 14.8). WOC. Ran 1" and tag wt 14.8). WOC. Ran 1" and tag. wt 14.8). WOC. Ran 1" and tag. wt 14.8). Circulated hrs. Reduced hole to 11" and	operations. If the operation repandonment Notices shall be filinal inspection.) 5:00 AM. TD 14-3/4" hole x Thixotropic + 10#/bbl C 1.63, wt 14.2). Tailed in v 4.8). Ran temperature stemperature stemperature with BLN emented with 80 sx Premented with 80 sx Premented with 80 sx Premented with 75 ged at 165'. Cemented with 75 ged at 165'. Cemented with 30 ged at 160'. Cemented and tagged at 120'. Cer 10 sx to surface. Tested resumed drilling.	e to 381'. Set all set of all set	e completion or re equirements, incl 11-3/4" 42# H bbl Gilsonite + illiburton Lite F nd TOC at 124 emperature su + 3% CaCl (yl- lus "C" + 3% (nium Plus "C" remium Plus "C" remium Plus "24 sx Premiun	I-40 ST&C ca 0.25#/bbl Premium Plus Premium Plus Premium Plus Premium Plus Premium Plus Premium Plus Premium Plus CaCl (yld 1.35 +3% CaCl ('C" + 3% CaCl	new interval, a Form 316 on, have been completed,	0-4 shall be filed once	
14 Thereby certify that the foregoing is Con Name (Printed/Typed) TINA HUE	# Electronic Submission For YATES PETRO nmitted to AFMSS for proc	OLEUM CORP	DRÅTION, sent RT SIMMONS o	t to the Carlsb n 07/19/2011 (ad		
Signature (Electronic Submission)			Date 07/19/2011				
	THIS SPACE FO	OR FEDERA	L OR STATE	OFFICE U	SE		
Approved By ACCEPT	ED		JAMES / TitleSUPER\	A AMOS /ISOR EPS		Date 07/23/2011	
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.			Office Carlsbad				
Title 18 U.S.C. Section 1001 and Title 43 States any false, fictitious or fraudulent					nake to any department or	r agency of the United	
					· · · · · · · · · · · · · · · · · · ·		