

Form 3160-3  
(June 2015)FORM APPROVED  
OMB No. 1004-0137  
Expires: January 31, 2018

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT  
**APPLICATION FOR PERMIT TO DRILL OR REENTER**

1a. Type of work: <input checked="" type="checkbox"/> DRILL <input type="checkbox"/> REENTER 1b. Type of Well: <input checked="" type="checkbox"/> Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other 1c. Type of Completion: <input type="checkbox"/> Hydraulic Fracturing <input checked="" type="checkbox"/> Single Zone <input type="checkbox"/> Multiple Zone		5. Lease Serial No. <b>NMNM136870</b> 6. If Indian, Allottee or Tribe Name  7. If Unit or CA Agreement, Name and No.  8. Lease Name and Well No. <b>CORRAL CANYON FEDERAL 11H</b>
2. Name of Operator <b>XTO ENERGY INCORPORATED</b>		9. API Well No. <b>3001547217</b>
3a. Address <b>22777 Springwoods Village Parkway Spring TX 77389</b>	3b. Phone No. (include area code) <b>(432)620-6700</b>	10. Field and Pool, or Exploratory <b>WILLOW LAKE BONE SPRING SE</b>
4. Location of Well (Report location clearly and in accordance with any State requirements. *) At surface <b>NWNE / 5 FNL / 2155 FEL / LAT 32.151941 / LONG -103.970702</b> At proposed prod. zone <b>NENE / 200 FNL / 1650 FEL / LAT 32.180513 / LONG -103.969269</b>		11. Sec., T. R. M. or Blk. and Survey or Area <b>SEC 10 / T25S / R29E / NMP</b>
14. Distance in miles and direction from nearest town or post office* <b>8.3 miles</b>		12. County or Parish <b>EDDY</b>
15. Distance from proposed* location to nearest property or lease line, ft. (Also to nearest drig. unit line, if any) <b>5 feet</b>		16. No of acres in lease <b>1280</b>
17. Spacing Unit dedicated to this well <b>320</b>		18. Distance from proposed location* to nearest well, drilling, completed, applied for, on this lease, ft. <b>50 feet</b>
19. Proposed Depth <b>8832 feet / 19142 feet</b>		20. BLM/BIA Bond No. in file <b>FED: UTB000138</b>
21. Elevations (Show whether DF, KDB, RT, GL, etc.) <b>3024 feet</b>	22. Approximate date work will start* <b>02/03/2021</b>	23. Estimated duration <b>25 days</b>
24. Attachments		

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No. 1, and the Hydraulic Fracturing rule per 43 CFR 3162.3-3 (as applicable)

- |   |   |
|---|---|
| 1. Well plat certified by a registered surveyor.<br>2. A Drilling Plan.<br>3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO must be filed with the appropriate Forest Service Office). | 4. Bond to cover the operations unless covered by an existing bond on file (see Item 20 above).<br>5. Operator certification.<br>6. Such other site specific information and/or plans as may be requested by the BLM. |
|---|---|

25. Signature (Electronic Submission)  Title <b>Geologist</b>	Name (Printed/Typed) <b>Elizabeth Zastoupil / Ph: (817)885-6750</b>	Date <b>10/06/2017</b>
Approved by (Signature) (Electronic Submission)  Title <b>Assistant Field Manager Lands &amp; Minerals</b>	Name (Printed/Typed) <b>Cody Layton / Ph: (575)234-5959</b>  Office <b>CARLSBAD</b>	Date <b>06/23/2020</b>

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.  
 Conditions of approval, if any, are attached.

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.



(Continued on page 2)

Entered - KMS NMOCD

\*(Instructions on page 2)

DISTRICT I  
1625 N. French Dr., Hobbs, NM 88240  
Phone: (575) 393-6161 Fax: (575) 393-0720

DISTRICT II  
811 S. First St., Artesia, NM 88210  
Phone: (575) 748-1283 Fax: (575) 748-9720

DISTRICT III  
1000 Rio Brazos Road, Aztec, NM 87410  
Phone: (505) 334-6178 Fax: (505) 334-6170

DISTRICT IV  
1220 S. St. Francis Dr., Santa Fe, NM 87505  
Phone: (505) 476-3460 Fax: (505) 476-3462

State of New Mexico  
Energy, Minerals & Natural Resources Department  
OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, New Mexico 87505

Form C-102  
Revised August 1, 2011  
Submit one copy to appropriate  
District Office

AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT


API Number <b>3001547217</b>	Pool Code <b>96217</b>	Pool Name <b>Willow Lake; Bone Spring SE</b>
Property Code <b>314121</b>	Property Name <b>CORRAL CANYON FEDERAL</b>	Well Number <b>11H</b>
OGRID No. <b>005380</b>	Operator Name <b>XTO ENERGY</b>	Elevation <b>3024'</b>

UL or lot No.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
<b>B</b>	<b>10</b>	<b>25-S</b>	<b>29-E</b>		<b>5</b>	<b>NORTH</b>	<b>2155</b>	<b>EAST</b>	<b>EDDY</b>

UL or lot No.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
<b>B</b>	<b>34</b>	<b>24-S</b>	<b>29-E</b>		<b>200</b>	<b>NORTH</b>	<b>1650</b>	<b>EAST</b>	<b>EDDY</b>

Dedicated Acres <b>320.0</b>	Joint or Infill <b>319.97</b>	Consolidation Code	Order No.
---------------------------------	----------------------------------	--------------------	-----------

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION



SCALE: 1"=2000'

BOTTOM HOLE LOCATION

NAD 27 NME  
Y= 429537.1 N  
X= 612787.4 E  
LAT.=32.180389° N  
LONG.=103.968782° W

LAST TAKE POINT  
NAD 27 NME  
Y= 429407.1 N  
X= 612789.8 E  
LAT.=32.180032° N  
LONG.=103.968776° W

BOTTOM HOLE LOCATION

NAD 83 NME  
Y= 429595.7 N  
X= 653971.7 E  
LAT.=32.180513° N  
LONG.=103.969269° W

LAST TAKE POINT  
NAD 83 NME  
Y= 429465.8 N  
X= 653974.1 E  
LAT.=32.180155° N  
LONG.=103.969263° W

CORNER COORDINATES TABLE

NAD 27 NME  
A - Y= 429738.2 N, X= 611801.1 E  
B - Y= 429736.7 N, X= 613117.3 E  
C - Y= 424447.5 N, X= 611866.9 E  
D - Y= 424452.9 N, X= 613199.5 E  
E - Y= 419144.2 N, X= 611882.0 E  
F - Y= 419151.7 N, X= 613207.6 E

CORNER COORDINATES TABLE

NAD 83 NME  
A - Y= 429796.8 N, X= 652985.4 E  
B - Y= 429795.3 N, X= 654301.6 E  
C - Y= 424506.0 N, X= 653051.3 E  
D - Y= 424511.4 N, X= 654383.9 E  
E - Y= 419202.6 N, X= 653066.6 E  
F - Y= 419210.1 N, X= 654392.2 E

FIRST TAKE POINT

NAD 27 NME  
Y= 419479.8 N  
X= 612883.6 E  
LAT.=32.152741° N  
LONG.=103.968582° W

GEODETIC COORDINATES

NAD 27 NME  
SURFACE LOCATION  
Y=419141.9 N  
X=612378.7 E  
LAT.=32.151817° N  
LONG.=103.970217° W

FIRST TAKE POINT

NAD 83 NME  
Y= 419538.2 N  
X= 654068.1 E  
LAT.=32.152865° N  
LONG.=103.969068° W

GEODETIC COORDINATES

NAD 83 NME  
SURFACE LOCATION  
Y=419200.4 N  
X=653563.3 E  
LAT.=32.151941° N  
LONG.=103.970702° W

OPERATOR CERTIFICATION

I hereby certify that the information herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location or has a right to drill this well at this location pursuant to a contract with an owner of such mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.

Signature: *Elizabeth Zastoupil* Date: **10/6/2017**  
Printed Name: **Elizabeth Zastoupil**  
E-mail Address: **Xtoenergy.com**

SURVEYOR CERTIFICATION

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.

MAY 5, 2014

Date of Survey  
Signature & Seal of Professional Surveyor:

*Ronald J. Eidson*  
Certificate Number: **3239**  
Gary G. Eidson 12641  
Ronald J. Eidson 3239  
ACK REL. W.O.: 14110434 JWSC W.O.: 17.13.0107

Intent ☒ As Drilled ☐

API #								
Operator Name: XTO ENERGY INC			Property Name: CORRAL CANYON FEDERAL			Well Number 11H		

Kick Off Point (KOP)

UL B	Section 10	Township 25S	Range 29E	Lot	Feet 5	From N/S NORTH	Feet 2155	From E/W EAST	County EDDY
Latitude 32.151941					Longitude -103.970702				NAD 83

First Take Point (FTP)

UL O	Section 3	Township 25S	Range 30E	Lot	Feet 330	From N/S SOUTH	Feet 1650	From E/W EAST	County EDDY
Latitude 32.152865					Longitude -103.969068				NAD 83

Last Take Point (LTP)

UL B	Section 34	Township 24S	Range 29E	Lot	Feet 330	From N/S NORTH	Feet 1650	From E/W EAST	County EDDY
Latitude 32.180155					Longitude -103.969263				NAD 83

Is this well the defining well for the Horizontal Spacing Unit?

Is this well an infill well?

If infill is yes please provide API if available, Operator Name and well number for Defining well for Horizontal Spacing Unit.

API #								
Operator Name:			Property Name:			Well Number		

KZ 06/29/2018

# PECOS DISTRICT

## DRILLING CONDITIONS OF APPROVAL

<b>OPERATOR'S NAME:</b>	XTO Energy Incorporated
<b>WELL NAME &amp; NO.:</b>	Corral Canyon Federal 11H
<b>LOCATION:</b>	Sec 10-25S-29E-NMP
<b>COUNTY:</b>	Eddy County, New Mexico

COA

H2S	<input type="radio"/> Yes	<input checked="" type="radio"/> No	
Potash	<input checked="" type="radio"/> None	<input type="radio"/> Secretary	<input type="radio"/> R-111-P
Cave/Karst Potential	<input type="radio"/> Low	<input checked="" type="radio"/> Medium	<input type="radio"/> High
Cave/Karst Potential	<input type="radio"/> Critical		
Variance	<input type="radio"/> None	<input checked="" type="radio"/> Flex Hose	<input type="radio"/> Other
Wellhead	<input type="radio"/> Conventional	<input checked="" type="radio"/> Multibowl	<input type="radio"/> Both
Other	<input type="checkbox"/> 4 String Area	<input type="checkbox"/> Capitan Reef	<input type="checkbox"/> WIPP
Other	<input type="checkbox"/> Fluid Filled	<input type="checkbox"/> Cement Squeeze	<input type="checkbox"/> Pilot Hole
Special Requirements	<input type="checkbox"/> Water Disposal	<input type="checkbox"/> COM	<input type="checkbox"/> Unit

### A. HYDROGEN SULFIDE

Hydrogen Sulfide (H2S) monitors shall be installed prior to drilling out the surface shoe. If H2S is detected in concentrations greater than 100 ppm, the Hydrogen Sulfide area shall meet Onshore Order 6 requirements, which includes equipment and personnel/public protection items. If Hydrogen Sulfide is encountered, provide measured values and formations to the BLM.

### B. CASING

1. The **13-3/8** inch surface casing shall be set at approximately 785 feet (a minimum of 70 feet (Eddy County) into the Rustler Anhydrite and above the salt) and cemented to the surface.
  - a. If cement does not circulate to the surface, the appropriate BLM office shall be notified and a temperature survey utilizing an electronic type temperature survey with surface log readout will be used or a cement bond log shall be run to verify the top of the cement. Temperature survey will be run a minimum of six hours after pumping cement and ideally between 8-10 hours after completing the cement job.
  - b. Wait on cement (WOC) time for a primary cement job will be a minimum of **8 hours** or 500 pounds compressive strength, whichever is greater. (This is to include the lead cement)
  - c. Wait on cement (WOC) time for a remedial job will be a minimum of 4 hours

after bringing cement to surface or 500 pounds compressive strength, whichever is greater.

- d. If cement falls back, remedial cementing will be done prior to drilling out that string.
2. The minimum required fill of cement behind the **9-5/8** inch intermediate casing is:
    - Cement to surface. If cement does not circulate see B.1.a, c-d above.  
**Wait on cement (WOC) time for a primary cement job is to include the lead cement slurry due to cave/karst or potash.**
    - ❖ In Medium Cave/Karst Areas if cement does not circulate to surface on the first two casing strings, the cement on the 3rd casing string must come to surface.
  3. The minimum required fill of cement behind the **5-1/2** inch production casing is:
    - Cement should tie-back at least **200 feet** into previous casing string. Operator shall provide method of verification.

### **C. PRESSURE CONTROL**

1. Variance approved to use flex line from BOP to choke manifold. Manufacturer's specification to be readily available. No external damage to flex line. Flex line to be installed as straight as possible (no hard bends).'
2. Operator has proposed a multi-bowl wellhead assembly. This assembly will only be tested when installed on the surface casing. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the surface casing shoe shall be **5000 (5M)** psi.
  - a. Wellhead shall be installed by manufacturer's representatives, submit documentation with subsequent sundry.
  - b. If the welding is performed by a third party, the manufacturer's representative shall monitor the temperature to verify that it does not exceed the maximum temperature of the seal.
  - c. Manufacturer representative shall install the test plug for the initial BOP test.
  - d. If the cement does not circulate and one inch operations would have been possible with a standard wellhead, the well head shall be cut off, cementing operations performed and another wellhead installed.
  - e. Whenever any seal subject to test pressure is broken, all the tests in OOGO2.III.A.2.i must be followed.

## **GENERAL REQUIREMENTS**

The BLM is to be notified in advance for a representative to witness:

- a. Spudding well (minimum of 24 hours)
- b. Setting and/or Cementing of all casing strings (minimum of 4 hours)
- c. BOPE tests (minimum of 4 hours)

☒ Eddy County

Call the Carlsbad Field Office, 620 East Greene St., Carlsbad, NM 88220,  
(575) 361-2822

☒ Lea County

Call the Hobbs Field Station, 414 West Taylor, Hobbs NM 88240, (575)  
393-3612

1. Unless the production casing has been run and cemented or the well has been properly plugged, the drilling rig shall not be removed from over the hole without prior approval.
  - a. In the event the operator has proposed to drill multiple wells utilizing a skid/walking rig. Operator shall secure the wellbore on the current well, after installing and testing the wellhead, by installing a blind flange of like pressure rating to the wellhead and a pressure gauge that can be monitored while drilling is performed on the other well(s).
  - b. When the operator proposes to set surface casing with Spudder Rig
    - Notify the BLM when moving in and removing the Spudder Rig.
    - Notify the BLM when moving in the 2<sup>nd</sup> Rig. Rig to be moved in within 90 days of notification that Spudder Rig has left the location.
    - BOP/BOPE test to be conducted per Onshore Oil and Gas Order No. 2 as soon as 2nd Rig is rigged up on well.
2. Floor controls are required for 3M or Greater systems. These controls will be on the rig floor, unobstructed, readily accessible to the driller and will be operational at all times during drilling and/or completion activities. Rig floor is defined as the area immediately around the rotary table; the area immediately above the substructure on which the draw works are located, this does not include the dog house or stairway area.
3. The record of the drilling rate along with the GR/N well log run from TD to surface (horizontal well – vertical portion of hole) shall be submitted to the BLM office as well as all other logs run on the borehole 30 days from completion. If available, a digital copy of the logs is to be submitted in addition to the paper copies. The Rustler top and top and bottom of Salt are to be recorded on the Completion Report.

A. CASING

1. Changes to the approved APD casing program need prior approval if the items substituted are of lesser grade or different casing size or are Non-API. The Operator

can exchange the components of the proposal with that of superior strength (i.e. changing from J-55 to N-80, or from 36# to 40#). Changes to the approved cement program need prior approval if the altered cement plan has less volume or strength or if the changes are substantial (i.e. Multistage tool, ECP, etc.). The initial wellhead installed on the well will remain on the well with spools used as needed.

2. Wait on cement (WOC) for Potash Areas: After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi for all cement blends, 2) until cement has been in place at least 24 hours. WOC time will be recorded in the driller's log. The casing integrity test can be done (prior to the cement setting up) immediately after bumping the plug.
3. Wait on cement (WOC) for Water Basin: After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi at the shoe, 2) until cement has been in place at least 8 hours. WOC time will be recorded in the driller's log. See individual casing strings for details regarding lead cement slurry requirements. The casing integrity test can be done (prior to the cement setting up) immediately after bumping the plug.
4. Provide compressive strengths including hours to reach required 500 pounds compressive strength prior to cementing each casing string. Have well specific cement details onsite prior to pumping the cement for each casing string.
5. No pea gravel permitted for remedial or fall back remedial without prior authorization from the BLM engineer.
6. On that portion of any well approved for a 5M BOPE system or greater, a pressure integrity test of each casing shoe shall be performed. Formation at the shoe shall be tested to a minimum of the mud weight equivalent anticipated to control the formation pressure to the next casing depth or at total depth of the well. This test shall be performed before drilling more than 20 feet of new hole.
7. If hardband drill pipe is rotated inside casing, returns will be monitored for metal. If metal is found in samples, drill pipe will be pulled and rubber protectors which have a larger diameter than the tool joints of the drill pipe will be installed prior to continuing drilling operations.
8. Whenever a casing string is cemented in the R-111-P potash area, the NMOCD requirements shall be followed.

#### B. PRESSURE CONTROL

1. All blowout preventer (BOP) and related equipment (BOPE) shall comply with well control requirements as described in Onshore Oil and Gas Order No. 2 and API RP 53 Sec. 17.

2. If a variance is approved for a flexible hose to be installed from the BOP to the choke manifold, the following requirements apply: The flex line must meet the requirements of API 16C. Check condition of flexible line from BOP to choke manifold, replace if exterior is damaged or if line fails test. Line to be as straight as possible with no hard bends and is to be anchored according to Manufacturer's requirements. The flexible hose can be exchanged with a hose of equal size and equal or greater pressure rating. Anchor requirements, specification sheet and hydrostatic pressure test certification matching the hose in service, to be onsite for review. These documents shall be posted in the company man's trailer and on the rig floor.
3. 5M or higher system requires an HCR valve, remote kill line and annular to match. The remote kill line is to be installed prior to testing the system and tested to stack pressure.
4. If the operator has proposed a multi-bowl wellhead assembly in the APD. The following requirements must be met:
  - a. Wellhead shall be installed by manufacturer's representatives, submit documentation with subsequent sundry.
  - b. If the welding is performed by a third party, the manufacturer's representative shall monitor the temperature to verify that it does not exceed the maximum temperature of the seal.
  - c. Manufacturer representative shall install the test plug for the initial BOP test.
  - d. Whenever any seal subject to test pressure is broken, all the tests in OOGO2.III.A.2.i must be followed.
  - e. If the cement does not circulate and one inch operations would have been possible with a standard wellhead, the well head shall be cut off, cementing operations performed and another wellhead installed.
5. The appropriate BLM office shall be notified a minimum of 4 hours in advance for a representative to witness the tests.
  - a. In a water basin, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. The casing cut-off and BOP installation can be initiated four hours after installing the slips, which will be approximately six hours after bumping the plug. For those casing strings not using slips, the minimum wait time before cut-off is eight hours after bumping the plug. BOP/BOPE testing can begin after cut-off or once cement reaches 500 psi compressive strength (including lead when specified), whichever is greater. However, if the float does not hold, cut-off cannot be initiated until cement reaches 500 psi compressive strength (including lead when specified).



- b. In potash areas, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. For all casing strings, casing cut-off and BOP installation can be initiated at twelve hours after bumping the plug. However, **no tests** shall commence until the cement has had a minimum of 24 hours setup time, except the casing pressure test can be initiated immediately after bumping the plug (only applies to single stage cement jobs).
- c. The tests shall be done by an independent service company utilizing a test plug not a cup or J-packer. The operator also has the option of utilizing an independent tester to test without a plug (i.e. against the casing) pursuant to Onshore Order 2 with the pressure not to exceed 70% of the burst rating for the casing. Any test against the casing must meet the WOC time for water basin (8 hours) or potash (24 hours) or 500 pounds compressive strength, whichever is greater, prior to initiating the test (see casing segment as lead cement may be critical item).
- d. The test shall be run on a 5000 psi chart for a 2-3M BOP/BOP, on a 10000 psi chart for a 5M BOP/BOPE and on a 15000 psi chart for a 10M BOP/BOPE. If a linear chart is used, it shall be a one hour chart. A circular chart shall have a maximum 2 hour clock. If a twelve hour or twenty-four hour chart is used, tester shall make a notation that it is run with a two hour clock.
- e. The results of the test shall be reported to the appropriate BLM office.
- f. All tests are required to be recorded on a calibrated test chart. A copy of the BOP/BOPE test chart and a copy of independent service company test will be submitted to the appropriate BLM office.
- g. The BOP/BOPE test shall include a low pressure test from 250 to 300 psi. The test will be held for a minimum of 10 minutes if test is done with a test plug and 30 minutes without a test plug. This test shall be performed prior to the test at full stack pressure.
- h. BOP/BOPE must be tested by an independent service company within 500 feet of the top of the Wolfcamp formation if the time between the setting of the intermediate casing and reaching this depth exceeds 20 days. This test does not exclude the test prior to drilling out the casing shoe as per Onshore Order No. 2.

#### C. DRILLING MUD

Mud system monitoring equipment, with derrick floor indicators and visual and audio alarms, shall be operating before drilling into the Wolfcamp formation, and shall be used until production casing is run and cemented.

#### D. WASTE MATERIAL AND FLUIDS

All waste (i.e. drilling fluids, trash, salts, chemicals, sewage, gray water, etc.) created as a result of drilling operations and completion operations shall be safely contained and disposed of properly at a waste disposal facility. No waste material or fluid shall be disposed of on the well location or surrounding area.

Porto-johns and trash containers will be on-location during fracturing operations or any other crew-intensive operations.

APD ID: 10400023039

Submission Date: 10/06/2017

Highlighted data  
reflects the most  
recent changes

Operator Name: XTO ENERGY INCORPORATED

Well Name: CORRAL CANYON FEDERAL

Well Number: 11H

[Show Final Text](#)

Well Type: OIL WELL

Well Work Type: Drill

## Section 1 - Geologic Formations

Formation ID	Formation Name	Elevation	True Vertical Depth	Measured Depth	Lithologies	Mineral Resources	Producing Formation
127160	---	3024	0	0	ALLUVIUM, OTHER : Quaternary	NONE	N
127161	RUSTLER	2575	449	449	SANDSTONE	USEABLE WATER	N
127167	TOP SALT	2211	813	813	SALT	USEABLE WATER	N
127168	BASE OF SALT	130	2894	2894	SALT	USEABLE WATER	N
127162	DELAWARE	-78	3102	3102	SANDSTONE	NATURAL GAS, OIL, OTHER : Produced Water	N
127163	BRUSHY CANYON	-2569	5593	5593	SANDSTONE	NATURAL GAS, OIL, USEABLE WATER	N
127164	BONE SPRING	-3823	6847	6847	SANDSTONE	NATURAL GAS, OIL, OTHER : Produced Water	N
127165	BONE SPRING 1ST	-4769	7793	7793	SANDSTONE	NATURAL GAS, OIL, OTHER : Produced Water	N
127166	2ND BONE SPRING LIME	-5059	8083	8083	LIMESTONE	NATURAL GAS, OIL, OTHER : Produced Water	N
127169	BONE SPRING 2ND	-5564	8588	8688	SANDSTONE	NATURAL GAS, OIL, OTHER : Produced Water	Y
127170	BONE SPRING 3RD	-5850	8874	8874	SANDSTONE	NATURAL GAS, OIL, OTHER : Produced Water	N

## Section 2 - Blowout Prevention

Pressure Rating (PSI): 5M

Rating Depth: 10000

**Equipment:** The blow out preventer equipment (BOP) for this well consists of a 13-5/8" minimum 5M Hydril and a 13-5/8" minimum 5M Double Ram BOP. Max bottom hole pressure should not exceed 4409 psi. With a Maximum Absolute Surface Pressure (MASP) = 2466psi

**Requesting Variance?** YES

**Variance request:** A variance is requested to allow use of a flex hose as the choke line from the BOP to the Choke Manifold. If this hose is used, a copy of the manufacturer's certification and pressure test chart will be kept on the rig. Attached is an example of a certification and pressure test chart. The manufacturer does not require anchors.

**Testing Procedure:** All BOP testing will be done by an independent service company. Annular pressure tests will be limited to 50% of the working pressure. When nipping up on the 13-5/8" 5M flange, the BOP test will be limited to 5000 psi. All BOP tests will include a low pressure test as per BLM regulations. The 5M BOP diagrams are attached. Blind rams will be

**Operator Name:** XTO ENERGY INCORPORATED

**Well Name:** CORRAL CANYON FEDERAL

**Well Number:** 11H

functioned tested each trip, pipe rams will be functioned tested each day.

**Choke Diagram Attachment:**

CorralCanyon11H\_CkMani\_20171006073608.pdf

**BOP Diagram Attachment:**

CorralCanyon11H\_5MBOP\_20171006073615.pdf

### Section 3 - Casing

Casing ID	String Type	Hole Size	Csg Size	Condition	Standard	Tapered String	Top Set MD	Bottom Set MD	Top Set TVD	Bottom Set TVD	Top Set MSL	Bottom Set MSL	Calculated casing length MD	Grade	Weight	Joint Type	Collapse SF	Burst SF	Joint SF Type	Joint SF	Body SF Type	Body SF
1	SURFACE	17.5	13.375	NEW	API	N	0	785	0	785	-5793	-6608	785	H-40	48	ST&C	2.06	5.77	DRY	8.55	DRY	8.55
2	INTERMEDIATE	12.25	9.625	NEW	API	N	0	6922	0	6922	-5793	-8843	6922	HCL-80	40	BUTT	1.15	1.57	DRY	3.36	DRY	3.36
3	PRODUCTION	8.75	5.5	NEW	API	N	0	19142	0	8832	-5793	-14618	19142	OTHER	17	BUTT	1.69	1.12	DRY	2.62	DRY	2.62

### Casing Attachments

**Casing ID:** 1      **String Type:** SURFACE

**Inspection Document:**

**Spec Document:**

**Tapered String Spec:**

**Casing Design Assumptions and Worksheet(s):**

CorralCanyon11H\_CaseAssump\_20171006073722.pdf

**Operator Name:** XTO ENERGY INCORPORATED

**Well Name:** CORRAL CANYON FEDERAL

**Well Number:** 11H

#### Casing Attachments

**Casing ID:** 2      **String Type:** INTERMEDIATE

**Inspection Document:**

**Spec Document:**

**Tapered String Spec:**

**Casing Design Assumptions and Worksheet(s):**

CorralCanyon11H\_CaseAssump\_20171006073925.pdf

**Casing ID:** 3      **String Type:** PRODUCTION

**Inspection Document:**

**Spec Document:**

**Tapered String Spec:**

**Casing Design Assumptions and Worksheet(s):**

CorralCanyon11H\_CaseAssump\_20171006073931.pdf

#### Section 4 - Cement

String Type	Lead/Tail	Stage Tool Depth	Top MD	Bottom MD	Quantity(sx)	Yield	Density	Cu Ft	Excess%	Cement type	Additives
SURFACE	Lead		0	785	810	1.35	14.8	1134	100	HalCem-C	2% CaCl

INTERMEDIATE	Lead		0	6922	2110	2.49	11.9	1531.35	100	EconoCem-C	3 lbm/sk Kol-Seal + 0.25 lbm D-air 5000
INTERMEDIATE	Tail				285	1.33	14.8	385.7	100	HalCem-C	none
PRODUCTION	Lead		3400	19142	520	2.77	10.8	1939	50	Tuned Light	2 lbm/sk Kol-Seal + 0.3 lbm/sk CFR-3

**Operator Name:** XTO ENERGY INCORPORATED

**Well Name:** CORRAL CANYON FEDERAL

**Well Number:** 11H

String Type	Lead/Tail	Stage Tool Depth	Top MD	Bottom MD	Quantity(sx)	Yield	Density	Cu Ft	Excess%	Cement type	Additives
PRODUCTION	Tail				2440	1.22	14.5	3513.6	30	VersaCem-H	3 lbm/sk Kol-Seal + 0.4% Halad 344 + 0.3% CFR-3 + 0.3% Super CBL + 0.25 lbm/sk D-air 5000

## Section 5 - Circulating Medium

**Mud System Type:** Closed

**Will an air or gas system be Used?** NO

**Description of the equipment for the circulating system in accordance with Onshore Order #2:**

**Diagram of the equipment for the circulating system in accordance with Onshore Order #2:**

**Describe what will be on location to control well or mitigate other conditions:** The necessary mud products for weight addition and fluid loss control will be on location at all times. Spud with fresh water/native mud. Drill out from under 13-3/8" surface casing with brine solution. A 9.8ppg - 10.2ppg brine mud will be used while drilling through the salt formation. Cut brine will be used to drill the 8-3/4" section. A polymer water will be used to drill the 8-1/2" lateral. Pump speed will be recorded on a daily drilling report after mudding up.

**Describe the mud monitoring system utilized:** A Pason or Totco will be used to detect changes in loss or gain of mud volume. A mud test will be performed every 24 hours to determine: density, viscosity, strength, filtration and pH as necessary. Solids control equipment will be used to operate as a closed loop system.

## Circulating Medium Table

Top Depth	Bottom Depth	Mud Type	Min Weight (lbs/gal)	Max Weight (lbs/gal)	Density (lbs/cu ft)	Gel Strength (lbs/100 sqft)	PH	Viscosity (CP)	Salinity (ppm)	Filtration (cc)	Additional Characteristics
0	785	OTHER : FW/Native	8.4	8.8							A mud test will be performed every 24 hours to determine: density, viscosity, strength, filtration and pH as necessary. Solids control equipment will be used to operate as a closed loop system.
6922	9332	OTHER : FW/Cut Brine	8.6	9.4							A mud test will be performed every 24 hours to determine: density, viscosity, strength, filtration and pH as necessary. Solids control equipment will be used to operate as a closed loop

**Operator Name:** XTO ENERGY INCORPORATED

**Well Name:** CORRAL CANYON FEDERAL

**Well Number:** 11H

Top Depth	Bottom Depth	Mud Type	Min Weight (lbs/gal)	Max Weight (lbs/gal)	Density (lbs/cu ft)	Gel Strength (lbs/100 sqft)	PH	Viscosity (CP)	Salinity (ppm)	Filtration (cc)	Additional Characteristics
system.											
9332	1914 2	OIL-BASED MUD	9.2	9.6							A mud test will be performed every 24 hours to determine: density, viscosity, strength, filtration and pH as necessary. Solids control equipment will be used to operate as a closed loop system.
785	6922	OTHER : Brine/Gel Sweeps	9.8	10.2							A mud test will be performed every 24 hours to determine: density, viscosity, strength, filtration and pH as necessary. Solids control equipment will be used to operate as a closed loop system.

## Section 6 - Test, Logging, Coring

**List of production tests including testing procedures, equipment and safety measures:**

Mud Logger: Mud Logging Unit (2 man) on below intermediate casing.

Open hole logging to include Density/Neutron/PE/Dual Laterlog/Spectral Gamma from kick-off point to intermediate casing shoe.

**List of open and cased hole logs run in the well:**

CBL,CNL,DS,DLL,GR,MUDLOG

**Coring operation description for the well:**

No coring will take place on this well

## Section 7 - Pressure

**Anticipated Bottom Hole Pressure:** 4409

**Anticipated Surface Pressure:** 2465.96

**Anticipated Bottom Hole Temperature(F):** 175

**Anticipated abnormal pressures, temperatures, or potential geologic hazards?** NO

**Describe:**

**Contingency Plans geohazards description:**

**Operator Name:** XTO ENERGY INCORPORATED

**Well Name:** CORRAL CANYON FEDERAL

**Well Number:** 11H

**Contingency Plans geohazards attachment:**

**Hydrogen Sulfide drilling operations plan required?** YES

**Hydrogen sulfide drilling operations plan:**

CorralCanyon11H\_H2S\_20171006074639.pdf

CorralCanyon11H\_H2SRigLayout\_20171006074646.pdf

## Section 8 - Other Information

**Proposed horizontal/directional/multi-lateral plan submission:**

CorralCanyon11H\_Directional\_20171006074707.pdf

**Other proposed operations facets description:**

**Other proposed operations facets attachment:**

Corral\_Fed\_GCP\_20190806063410.pdf

**Other Variance attachment:**

Corral\_Fed\_FH\_20190806063446.pdf



Corral Canyon 11H

19142 ft TD

5/24/2017

13 3/8"	785 MD/TVD	8.8 # mud			
48#, H-40, ST&C	collapse =	740	Burst =	1730	Tension = 322000
(8.8)(0.052)(785) =	359 psi	740/359=	2.06	SF for collapse	
Max exp. surf pressure	300 psi	1730/300=	5.77	SF for burst	
(785)(48) =	37680 lb	322/37.7 =	8.55	SF for tension	

9-5/8"	6922 MD/TVD	10.2 # mud			
40#, HCL-80, BTC	collapse =	4230	burst =	5750	tension = 837000
Max expected surf pressure =		3671 psi			
(10.2)(0.052)(6922) =	2170 psi	4230/2170=	1.95	SF for collapse	
*Less internal fluid height		5750/3671.428	1.57	SF for burst	
(6922)(36)=	249192 lb	837/249.192=	3.36	SF for tension	

5 1/2"	0 Top	19142 Shoe (MD)	8832 TVD	10.4 # mud
	0.35 FF	9332 LP (MD)	9810 Lat Length	
17#, P-110, BTC	collapse=	7460	burst=	10640 tension= 568000
Max expected surf pressure =		9500 psi	*for frac	
(10.4)(0.052)(8832) =	4776 psi	7460/4776=	1.56	SF for collapse
Maximum Absolute Surface Pressure (MASP)				
(10.4)(0.052)(8832) - (.22*8832) =	2833 psi	10640/9500=	1.12	SF for burst
(9332*17)+(9810*0.35*17)=	217014 lb	568/217.0135=	2.62	SF for tension

Corral Canyon 11H

19142 ft TD

5/24/2017

13 3/8"	785 MD/TVD	8.8 # mud			
48#, H-40, ST&C	collapse =	740	Burst =	1730	Tension = 322000
(8.8)(0.052)(785) =	359 psi	740/359=	2.06	SF for collapse	
Max exp. surf pressure	300 psi	1730/300=	5.77	SF for burst	
(785)(48) =	37680 lb	322/37.7 =	8.55	SF for tension	

9-5/8"	6922 MD/TVD	10.2 # mud			
40#, HCL-80, BTC	collapse =	4230	burst =	5750	tension = 837000
Max expected surf pressure =		3671 psi			
(10.2)(0.052)(6922) =	2170 psi	4230/2170=	1.95	SF for collapse	
*Less internal fluid height		5750/3671.428	1.57	SF for burst	
(6922)(36)=	249192 lb	837/249.192=	3.36	SF for tension	

5 1/2"	0 Top	19142 Shoe (MD)	8832 TVD	10.4 # mud
	0.35 FF	9332 LP (MD)	9810 Lat Length	
17#, P-110, BTC	collapse=	7460	burst=	10640 tension= 568000
Max expected surf pressure =		9500 psi *for frac		
(10.4)(0.052)(8832) =	4776 psi	7460/4776=	1.56	SF for collapse
Maximum Absolute Surface Pressure (MASP)				
(10.4)(0.052)(8832) - (.22*8832) =	2833 psi	10640/9500=	1.12	SF for burst
(9332*17)+(9810*0.35*17)=	217014 lb	568/217.0135=	2.62	SF for tension

Corral Canyon 11H

19142 ft TD

5/24/2017

13 3/8"	785 MD/TVD	8.8 # mud			
48#, H-40, ST&C	collapse =	740	Burst =	1730	Tension = 322000
(8.8)(0.052)(785) =	359 psi	740/359=	2.06	SF for collapse	
Max exp. surf pressure	300 psi	1730/300=	5.77	SF for burst	
(785)(48) =	37680 lb	322/37.7 =	8.55	SF for tension	

9-5/8"	6922 MD/TVD	10.2 # mud			
40#, HCL-80, BTC	collapse =	4230	burst =	5750	tension = 837000
Max expected surf pressure =		3671 psi			
(10.2)(0.052)(6922) =	2170 psi	4230/2170=	1.95	SF for collapse	
*Less internal fluid height		5750/3671.428	1.57	SF for burst	
(6922)(36)=	249192 lb	837/249.192=	3.36	SF for tension	

5 1/2"	0 Top	19142 Shoe (MD)	8832 TVD	10.4 # mud		
	0.35 FF	9332 LP (MD)	9810 Lat Length			
17#, P-110, BTC	collapse=	7460	burst=	10640	tension=	568000
Max expected surf pressure =		9500 psi *for frac				
(10.4)(0.052)(8832) =		4776 psi	7460/4776=		1.56	SF for collapse
Maximum Absolute Surface Pressure (MASP)						
(10.4)(0.052)(8832) - (.22*8832) =		2833 psi	10640/9500=		1.12	SF for burst
(9332*17)+(9810*0.35*17)=		217014 lb	568/217.0135=		2.62	SF for tension



## **HYDROGEN SULFIDE (H<sub>2</sub>S) CONTINGENCY PLAN**

**Assumed 100 ppm ROE = 3000'**

100 ppm H<sub>2</sub>S concentration shall trigger activation of this plan.

### **Emergency Procedures**

In the event of a release of gas containing H<sub>2</sub>S, the first responder(s) must

- Isolate the area and prevent entry by other persons into the 100 ppm ROE.
- Evacuate any public places encompassed by the 100 ppm ROE.
- Be equipped with H<sub>2</sub>S monitors and air packs in order to control the release.
- Use the "buddy system" to ensure no injuries occur during the response
- Take precautions to avoid personal injury during this operation.
- Contact operator and/or local officials to aid in operation. See list of phone numbers attached.
- Have received training in the
  - o Detection of H<sub>2</sub>S, and
  - o Measures for protection against the gas,
  - o Equipment used for protection and emergency response.

### **Ignition of Gas source**

Should control of the well be considered lost and ignition considered, take care to protect against exposure to Sulfur Dioxide (SO<sub>2</sub>). Intentional ignition must be coordinated with the NMOCD and local officials. Additionally the NM State Police may become involved. NM State Police shall be the Incident Command on scene of any major release. Take care to protect downwind whenever this is an ignition of the gas.

### **Characteristics of H<sub>2</sub>S and SO<sub>2</sub>**

<b>Common Name</b>	<b>Chemical Formula</b>	<b>Specific Gravity</b>	<b>Threshold Limit</b>	<b>Hazardous Limit</b>	<b>Lethal Concentration</b>
<b>Hydrogen Sulfide</b>	<b>H<sub>2</sub>S</b>	<b>1.189 Air = 1</b>	<b>10 ppm</b>	<b>100 ppm/hr</b>	<b>600 ppm</b>
<b>Sulfur Dioxide</b>	<b>SO<sub>2</sub></b>	<b>2.21 Air = 1</b>	<b>2 ppm</b>	<b>N/A</b>	<b>1000 ppm</b>

### **Contacting Authorities**

XTO Energy Inc's personnel must liaison with local and state agencies to ensure a proper response to a major release. Additionally, the OCD must be notified of the release as soon as possible but no later than 4 hours. Agencies will ask for information such as type and volume of release, wind direction, location of release, etc. Be prepared with all information available including directions to site. The following call list of essential and potential responders has been prepared for use during a release. (Operator Name)'s response must be in coordination with the State of New Mexico's "Hazardous Materials Emergency Response Plan" (HMER).

## **EUNICE OFFICE – EDDY & LEA COUNTIES**

EMSU @ Oil Center, NM, 8/10ths mile west of Hwy 8 on Hwy 175  
Eunice, NM

575-394-2089

### **XTO ENERGY INC PERSONNEL:**

Logan Farmar, Drilling Engineer	432-234-9872
Milton Turman, Drilling Superintendent	817-524-5107
Jeff Raines, Construction Foreman	432-557-3159
Dudley McMinn, EH & S Manager	432-557-7976
Wes McSpadden, Production Foreman	575-441-1147

### **SHERIFF DEPARTMENTS:**

Eddy County	575-887-7551
Lea County	575-396-3611

### **NEW MEXICO STATE POLICE:**

575-392-5588

### **FIRE DEPARTMENTS:**

	911
Carlsbad	575-885-2111
Eunice	575-394-2111
Hobbs	575-397-9308
Jal	575-395-2221
Lovington	575-396-2359

### **HOSPITALS:**

	911
Carlsbad Medical Emergency	575-885-2111
Eunice Medical Emergency	575-394-2112
Hobbs Medical Emergency	575-397-9308
Jal Medical Emergency	575-395-2221
Lovington Medical Emergency	575-396-2359

### **AGENT NOTIFICATIONS:**

Bureau of Land Management	575-393-3612
New Mexico Oil Conservation Division	575-393-6161
Mosaic Potash - Carlsbad	575-887-2871

### **CONTRACTORS:**

ABC Rental – Light Towers	575-394-3155
Bulldog Services – Trucking/Forklift	575-391-8543
Champion – Chemical	575-393-7726
Indian Fire & Safety	575-393-3093
Key – Dirt Contractor	575-393-3180
Key Tools – Light Towers	575-393-2415
Sweatt – Dirt Contractor	575-397-4541
RWI – Contract Gang	575-393-5305



October 6, 2017

Elizabeth Zastoupil  
XTO Energy Inc.  
810 Houston St.  
Fort Worth, TX 76102  
817-885-6750  
Elizabeth\_zastoupil@xtoenergy.com

Bureau of Land Management  
620 E. Greene  
Carlsbad, NM 88220  
575-887-6544

Dear Sirs:

XTO Energy Inc. does not anticipate encountering H<sub>2</sub>S while drilling the Corral Canyon Federal #11H located in Section 10, T25S, R29E, in Eddy County, New Mexico. As a precaution, I have attached an H<sub>2</sub>S contingency plan along with a gas analysis of our well stream. If you need anything further, please contact me at the telephone number or email listed above.


Thank you,

Elizabeth Zastoupil  
Geologist

↑  
S  
|

Prevailing Winds  
Direction SW

## H<sub>2</sub>S Briefing Areas and Alarm Locations





## **XTO ENERGY, INC.**

**Eddy County, NM**

**Sec 10, T25S, R29E**

**Corral Canyon Federal 11H**

**Wellbore #1**

**Plan: Plan #2**

## **QES Well Planning Report**

**23 May, 2017**





<b>Database:</b>	EDM5002	<b>Local Co-ordinate Reference:</b>	Well Corral Canyon Federal 11H
<b>Company:</b>	XTO ENERGY, INC.	<b>TVD Reference:</b>	RKB @ 3049.0usft (Frontier #27)
<b>Project:</b>	Eddy County, NM	<b>MD Reference:</b>	RKB @ 3049.0usft (Frontier #27)
<b>Site:</b>	Sec 10, T25S, R29E	<b>North Reference:</b>	Grid
<b>Well:</b>	Corral Canyon Federal 11H	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	Wellbore #1		
<b>Design:</b>	Plan #2		

<b>Project</b>	Eddy County, NM		
<b>Map System:</b>	US State Plane 1927 (Exact solution)	<b>System Datum:</b>	Mean Sea Level
<b>Geo Datum:</b>	NAD 1927 (NADCON CONUS)		
<b>Map Zone:</b>	New Mexico East 3001		

<b>Site</b>	Sec 10, T25S, R29E		
<b>Site Position:</b>		<b>Northing:</b>	418,642.60 usft
<b>From:</b>	Map	<b>Easting:</b>	611,643.50 usft
<b>Position Uncertainty:</b>	0.0 usft	<b>Slot Radius:</b>	13-3/16 "
		<b>Latitude:</b>	32° 9' 1.624 N
		<b>Longitude:</b>	103° 58' 21.351 W
		<b>Grid Convergence:</b>	0.19 °

<b>Well</b>	Corral Canyon Federal 11H		
<b>Well Position</b>	<b>+N/-S</b>	499.3 usft	<b>Northing:</b> 419,141.90 usft
	<b>+E/-W</b>	735.2 usft	<b>Easting:</b> 612,378.70 usft
<b>Position Uncertainty</b>	0.0 usft	<b>Wellhead Elevation:</b>	0.0 usft
		<b>Latitude:</b>	32° 9' 6.541 N
		<b>Longitude:</b>	103° 58' 12.780 W
		<b>Ground Level:</b>	3,024.0 usft

<b>Wellbore</b>	Wellbore #1				
<b>Magnetics</b>	<b>Model Name</b>	<b>Sample Date</b>	<b>Declination (°)</b>	<b>Dip Angle (°)</b>	<b>Field Strength (nT)</b>
	IGRF2015	5/23/2017	7.14	59.93	47,863

<b>Design</b>	Plan #2			
<b>Audit Notes:</b>				
<b>Version:</b>	<b>Phase:</b>	PLAN	<b>Tie On Depth:</b>	0.0
<b>Vertical Section:</b>	<b>Depth From (TVD) (usft)</b>	<b>+N/-S (usft)</b>	<b>+E/-W (usft)</b>	<b>Direction (°)</b>
	0.0	0.0	0.0	2.25

<b>Plan Sections</b>										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	TFO (°)	Target
0.0	0.00	0.00	0.0	0.0	0.0	0.00	0.00	0.00	0.00	
8,040.0	0.00	0.00	8,040.0	0.0	0.0	0.00	0.00	0.00	0.00	
8,455.1	41.52	86.06	8,419.7	9.9	143.6	10.00	10.00	0.00	86.06	
9,332.3	90.00	359.45	8,832.0	585.6	502.5	10.00	5.53	-9.87	-87.46	
19,142.3	90.00	359.45	8,832.0	10,395.2	408.7	0.00	0.00	0.00	0.00	PBHL - Corral Canyon

<b>Database:</b>	EDM5002	<b>Local Co-ordinate Reference:</b>	Well Corral Canyon Federal 11H
<b>Company:</b>	XTO ENERGY, INC.	<b>TVD Reference:</b>	RKB @ 3049.0usft (Frontier #27)
<b>Project:</b>	Eddy County, NM	<b>MD Reference:</b>	RKB @ 3049.0usft (Frontier #27)
<b>Site:</b>	Sec 10, T25S, R29E	<b>North Reference:</b>	Grid
<b>Well:</b>	Corral Canyon Federal 11H	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	Wellbore #1		
<b>Design:</b>	Plan #2		

Planned Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
0.0	0.00	0.00	0.0	0.0	0.0	0.0	0.00	0.00	0.00
100.0	0.00	0.00	100.0	0.0	0.0	0.0	0.00	0.00	0.00
200.0	0.00	0.00	200.0	0.0	0.0	0.0	0.00	0.00	0.00
300.0	0.00	0.00	300.0	0.0	0.0	0.0	0.00	0.00	0.00
400.0	0.00	0.00	400.0	0.0	0.0	0.0	0.00	0.00	0.00
Rustler									
449.0	0.00	0.00	449.0	0.0	0.0	0.0	0.00	0.00	0.00
500.0	0.00	0.00	500.0	0.0	0.0	0.0	0.00	0.00	0.00
600.0	0.00	0.00	600.0	0.0	0.0	0.0	0.00	0.00	0.00
700.0	0.00	0.00	700.0	0.0	0.0	0.0	0.00	0.00	0.00
800.0	0.00	0.00	800.0	0.0	0.0	0.0	0.00	0.00	0.00
Top Salt									
813.0	0.00	0.00	813.0	0.0	0.0	0.0	0.00	0.00	0.00
900.0	0.00	0.00	900.0	0.0	0.0	0.0	0.00	0.00	0.00
1,000.0	0.00	0.00	1,000.0	0.0	0.0	0.0	0.00	0.00	0.00
1,100.0	0.00	0.00	1,100.0	0.0	0.0	0.0	0.00	0.00	0.00
1,200.0	0.00	0.00	1,200.0	0.0	0.0	0.0	0.00	0.00	0.00
1,300.0	0.00	0.00	1,300.0	0.0	0.0	0.0	0.00	0.00	0.00
1,400.0	0.00	0.00	1,400.0	0.0	0.0	0.0	0.00	0.00	0.00
1,500.0	0.00	0.00	1,500.0	0.0	0.0	0.0	0.00	0.00	0.00
1,600.0	0.00	0.00	1,600.0	0.0	0.0	0.0	0.00	0.00	0.00
1,700.0	0.00	0.00	1,700.0	0.0	0.0	0.0	0.00	0.00	0.00
1,800.0	0.00	0.00	1,800.0	0.0	0.0	0.0	0.00	0.00	0.00
1,900.0	0.00	0.00	1,900.0	0.0	0.0	0.0	0.00	0.00	0.00
2,000.0	0.00	0.00	2,000.0	0.0	0.0	0.0	0.00	0.00	0.00
2,100.0	0.00	0.00	2,100.0	0.0	0.0	0.0	0.00	0.00	0.00
2,200.0	0.00	0.00	2,200.0	0.0	0.0	0.0	0.00	0.00	0.00
2,300.0	0.00	0.00	2,300.0	0.0	0.0	0.0	0.00	0.00	0.00
2,400.0	0.00	0.00	2,400.0	0.0	0.0	0.0	0.00	0.00	0.00
2,500.0	0.00	0.00	2,500.0	0.0	0.0	0.0	0.00	0.00	0.00
2,600.0	0.00	0.00	2,600.0	0.0	0.0	0.0	0.00	0.00	0.00
2,700.0	0.00	0.00	2,700.0	0.0	0.0	0.0	0.00	0.00	0.00
2,800.0	0.00	0.00	2,800.0	0.0	0.0	0.0	0.00	0.00	0.00
Base Salt									
2,894.0	0.00	0.00	2,894.0	0.0	0.0	0.0	0.00	0.00	0.00
2,900.0	0.00	0.00	2,900.0	0.0	0.0	0.0	0.00	0.00	0.00
3,000.0	0.00	0.00	3,000.0	0.0	0.0	0.0	0.00	0.00	0.00
3,100.0	0.00	0.00	3,100.0	0.0	0.0	0.0	0.00	0.00	0.00
Delaware									
3,102.0	0.00	0.00	3,102.0	0.0	0.0	0.0	0.00	0.00	0.00
3,200.0	0.00	0.00	3,200.0	0.0	0.0	0.0	0.00	0.00	0.00
3,300.0	0.00	0.00	3,300.0	0.0	0.0	0.0	0.00	0.00	0.00
3,400.0	0.00	0.00	3,400.0	0.0	0.0	0.0	0.00	0.00	0.00
3,500.0	0.00	0.00	3,500.0	0.0	0.0	0.0	0.00	0.00	0.00
3,600.0	0.00	0.00	3,600.0	0.0	0.0	0.0	0.00	0.00	0.00
3,700.0	0.00	0.00	3,700.0	0.0	0.0	0.0	0.00	0.00	0.00
3,800.0	0.00	0.00	3,800.0	0.0	0.0	0.0	0.00	0.00	0.00
3,900.0	0.00	0.00	3,900.0	0.0	0.0	0.0	0.00	0.00	0.00
Cherry Canyon									
3,971.0	0.00	0.00	3,971.0	0.0	0.0	0.0	0.00	0.00	0.00
4,000.0	0.00	0.00	4,000.0	0.0	0.0	0.0	0.00	0.00	0.00
4,100.0	0.00	0.00	4,100.0	0.0	0.0	0.0	0.00	0.00	0.00
4,200.0	0.00	0.00	4,200.0	0.0	0.0	0.0	0.00	0.00	0.00
4,300.0	0.00	0.00	4,300.0	0.0	0.0	0.0	0.00	0.00	0.00

<b>Database:</b>	EDM5002	<b>Local Co-ordinate Reference:</b>	Well Corral Canyon Federal 11H
<b>Company:</b>	XTO ENERGY, INC.	<b>TVD Reference:</b>	RKB @ 3049.0usft (Frontier #27)
<b>Project:</b>	Eddy County, NM	<b>MD Reference:</b>	RKB @ 3049.0usft (Frontier #27)
<b>Site:</b>	Sec 10, T25S, R29E	<b>North Reference:</b>	Grid
<b>Well:</b>	Corral Canyon Federal 11H	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	Wellbore #1		
<b>Design:</b>	Plan #2		

Planned Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
4,400.0	0.00	0.00	4,400.0	0.0	0.0	0.0	0.00	0.00	0.00
4,500.0	0.00	0.00	4,500.0	0.0	0.0	0.0	0.00	0.00	0.00
4,600.0	0.00	0.00	4,600.0	0.0	0.0	0.0	0.00	0.00	0.00
4,700.0	0.00	0.00	4,700.0	0.0	0.0	0.0	0.00	0.00	0.00
4,800.0	0.00	0.00	4,800.0	0.0	0.0	0.0	0.00	0.00	0.00
4,900.0	0.00	0.00	4,900.0	0.0	0.0	0.0	0.00	0.00	0.00
5,000.0	0.00	0.00	5,000.0	0.0	0.0	0.0	0.00	0.00	0.00
5,100.0	0.00	0.00	5,100.0	0.0	0.0	0.0	0.00	0.00	0.00
5,200.0	0.00	0.00	5,200.0	0.0	0.0	0.0	0.00	0.00	0.00
5,300.0	0.00	0.00	5,300.0	0.0	0.0	0.0	0.00	0.00	0.00
5,400.0	0.00	0.00	5,400.0	0.0	0.0	0.0	0.00	0.00	0.00
5,500.0	0.00	0.00	5,500.0	0.0	0.0	0.0	0.00	0.00	0.00
Brushy Canyon									
5,593.0	0.00	0.00	5,593.0	0.0	0.0	0.0	0.00	0.00	0.00
5,600.0	0.00	0.00	5,600.0	0.0	0.0	0.0	0.00	0.00	0.00
5,700.0	0.00	0.00	5,700.0	0.0	0.0	0.0	0.00	0.00	0.00
5,800.0	0.00	0.00	5,800.0	0.0	0.0	0.0	0.00	0.00	0.00
5,900.0	0.00	0.00	5,900.0	0.0	0.0	0.0	0.00	0.00	0.00
6,000.0	0.00	0.00	6,000.0	0.0	0.0	0.0	0.00	0.00	0.00
6,100.0	0.00	0.00	6,100.0	0.0	0.0	0.0	0.00	0.00	0.00
6,200.0	0.00	0.00	6,200.0	0.0	0.0	0.0	0.00	0.00	0.00
6,300.0	0.00	0.00	6,300.0	0.0	0.0	0.0	0.00	0.00	0.00
6,400.0	0.00	0.00	6,400.0	0.0	0.0	0.0	0.00	0.00	0.00
6,500.0	0.00	0.00	6,500.0	0.0	0.0	0.0	0.00	0.00	0.00
6,600.0	0.00	0.00	6,600.0	0.0	0.0	0.0	0.00	0.00	0.00
6,700.0	0.00	0.00	6,700.0	0.0	0.0	0.0	0.00	0.00	0.00
6,800.0	0.00	0.00	6,800.0	0.0	0.0	0.0	0.00	0.00	0.00
Bone Spring									
6,847.0	0.00	0.00	6,847.0	0.0	0.0	0.0	0.00	0.00	0.00
6,900.0	0.00	0.00	6,900.0	0.0	0.0	0.0	0.00	0.00	0.00
7,000.0	0.00	0.00	7,000.0	0.0	0.0	0.0	0.00	0.00	0.00
7,100.0	0.00	0.00	7,100.0	0.0	0.0	0.0	0.00	0.00	0.00
7,200.0	0.00	0.00	7,200.0	0.0	0.0	0.0	0.00	0.00	0.00
7,300.0	0.00	0.00	7,300.0	0.0	0.0	0.0	0.00	0.00	0.00
7,400.0	0.00	0.00	7,400.0	0.0	0.0	0.0	0.00	0.00	0.00
7,500.0	0.00	0.00	7,500.0	0.0	0.0	0.0	0.00	0.00	0.00
7,600.0	0.00	0.00	7,600.0	0.0	0.0	0.0	0.00	0.00	0.00
1st Bone Spring Lm									
7,654.0	0.00	0.00	7,654.0	0.0	0.0	0.0	0.00	0.00	0.00
7,700.0	0.00	0.00	7,700.0	0.0	0.0	0.0	0.00	0.00	0.00
1st Bone Spring Ss									
7,793.0	0.00	0.00	7,793.0	0.0	0.0	0.0	0.00	0.00	0.00
7,800.0	0.00	0.00	7,800.0	0.0	0.0	0.0	0.00	0.00	0.00
7,900.0	0.00	0.00	7,900.0	0.0	0.0	0.0	0.00	0.00	0.00
8,000.0	0.00	0.00	8,000.0	0.0	0.0	0.0	0.00	0.00	0.00
Build 10°/100'									
8,040.0	0.00	0.00	8,040.0	0.0	0.0	0.0	0.00	0.00	0.00
8,050.0	1.00	86.06	8,050.0	0.0	0.1	0.0	10.00	10.00	0.00
2nd Bone Spring Lm									
8,083.0	4.31	86.06	8,083.0	0.1	1.6	0.2	10.00	10.00	0.00
8,100.0	6.00	86.06	8,099.9	0.2	3.1	0.3	10.00	10.00	0.00
8,150.0	11.00	86.06	8,149.3	0.7	10.5	1.1	10.00	10.00	0.00
8,200.0	16.01	86.06	8,197.9	1.5	22.2	2.4	10.00	10.00	0.00

<b>Database:</b>	EDM5002	<b>Local Co-ordinate Reference:</b>	Well Corral Canyon Federal 11H
<b>Company:</b>	XTO ENERGY, INC.	<b>TVD Reference:</b>	RKB @ 3049.0usft (Frontier #27)
<b>Project:</b>	Eddy County, NM	<b>MD Reference:</b>	RKB @ 3049.0usft (Frontier #27)
<b>Site:</b>	Sec 10, T25S, R29E	<b>North Reference:</b>	Grid
<b>Well:</b>	Corral Canyon Federal 11H	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	Wellbore #1		
<b>Design:</b>	Plan #2		

Planned Survey										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	
8,250.0	21.01	86.06	8,245.3	2.6	38.0	4.1	10.00	10.00	0.00	
8,300.0	26.01	86.06	8,291.2	4.0	57.9	6.3	10.00	10.00	0.00	
8,350.0	31.01	86.06	8,335.1	5.6	81.7	8.8	10.00	10.00	0.00	
8,400.0	36.01	86.06	8,376.8	7.5	109.2	11.8	10.00	10.00	0.00	
8,450.0	41.02	86.06	8,415.9	9.7	140.3	15.2	10.00	10.00	0.00	
<b>EOB @ 41.52° Inc / 86.06° Azm - Build/Turn 10°/100'</b>										
8,455.1	41.52	86.06	8,419.7	9.9	143.6	15.5	10.00	10.00	0.00	
8,500.0	41.92	79.33	8,453.2	13.7	173.2	20.5	10.00	0.88	-14.98	
8,550.0	42.81	72.02	8,490.2	22.0	205.8	30.1	10.00	1.79	-14.61	
8,600.0	44.15	65.01	8,526.5	34.6	237.8	44.0	10.00	2.68	-14.01	
8,650.0	45.90	58.39	8,561.9	51.4	268.9	61.9	10.00	3.49	-13.26	
<b>2nd Bone Spring Ss</b>										
8,688.1	47.47	53.61	8,588.0	66.9	291.8	78.3	10.00	4.13	-12.52	
8,700.0	48.00	52.17	8,596.0	72.2	298.8	83.9	10.00	4.46	-12.10	
8,750.0	50.42	46.39	8,628.7	96.9	327.5	109.7	10.00	4.84	-11.57	
8,800.0	53.11	41.01	8,659.6	125.3	354.6	139.2	10.00	5.37	-10.75	
8,850.0	56.02	36.02	8,688.6	157.2	379.9	172.0	10.00	5.82	-9.99	
8,900.0	59.11	31.37	8,715.5	192.3	403.3	208.0	10.00	6.20	-9.31	
8,950.0	62.37	27.01	8,739.9	230.4	424.5	246.9	10.00	6.51	-8.71	
9,000.0	65.75	22.91	8,761.8	271.2	443.5	288.4	10.00	6.76	-8.20	
<b>2nd Bone Spring "B" Ss</b>										
9,012.9	66.64	21.89	8,767.0	282.1	448.0	299.5	10.00	6.90	-7.91	
9,050.0	69.24	19.03	8,780.9	314.3	460.0	332.1	10.00	7.00	-7.71	
9,100.0	72.81	15.32	8,797.2	359.4	473.9	377.8	10.00	7.14	-7.41	
9,150.0	76.44	11.76	8,810.4	406.3	485.2	425.0	10.00	7.27	-7.13	
9,200.0	80.13	8.30	8,820.6	454.5	493.7	473.5	10.00	7.37	-6.91	
9,250.0	83.84	4.92	8,827.6	503.7	499.4	522.9	10.00	7.44	-6.76	
9,300.0	87.58	1.59	8,831.3	553.4	502.2	572.7	10.00	7.48	-6.66	
<b>EOBT @ 90.00° Inc / 359.45° Azm</b>										
9,332.3	90.00	359.45	8,832.0	585.6	502.5	604.9	10.00	7.49	-6.63	
9,400.0	90.00	359.45	8,832.0	653.4	501.9	672.6	0.00	0.00	0.00	
9,500.0	90.00	359.45	8,832.0	753.4	500.9	772.5	0.00	0.00	0.00	
9,600.0	90.00	359.45	8,832.0	853.4	500.0	872.4	0.00	0.00	0.00	
9,700.0	90.00	359.45	8,832.0	953.4	499.0	972.2	0.00	0.00	0.00	
9,800.0	90.00	359.45	8,832.0	1,053.4	498.1	1,072.1	0.00	0.00	0.00	
9,900.0	90.00	359.45	8,832.0	1,153.4	497.1	1,172.0	0.00	0.00	0.00	
10,000.0	90.00	359.45	8,832.0	1,253.4	496.1	1,271.9	0.00	0.00	0.00	
10,100.0	90.00	359.45	8,832.0	1,353.3	495.2	1,371.8	0.00	0.00	0.00	
10,200.0	90.00	359.45	8,832.0	1,453.3	494.2	1,471.6	0.00	0.00	0.00	
10,300.0	90.00	359.45	8,832.0	1,553.3	493.3	1,571.5	0.00	0.00	0.00	
10,400.0	90.00	359.45	8,832.0	1,653.3	492.3	1,671.4	0.00	0.00	0.00	
10,500.0	90.00	359.45	8,832.0	1,753.3	491.4	1,771.3	0.00	0.00	0.00	
10,600.0	90.00	359.45	8,832.0	1,853.3	490.4	1,871.2	0.00	0.00	0.00	
10,700.0	90.00	359.45	8,832.0	1,953.3	489.4	1,971.0	0.00	0.00	0.00	
10,800.0	90.00	359.45	8,832.0	2,053.3	488.5	2,070.9	0.00	0.00	0.00	
10,900.0	90.00	359.45	8,832.0	2,153.3	487.5	2,170.8	0.00	0.00	0.00	
11,000.0	90.00	359.45	8,832.0	2,253.3	486.6	2,270.7	0.00	0.00	0.00	
11,100.0	90.00	359.45	8,832.0	2,353.3	485.6	2,370.6	0.00	0.00	0.00	
11,200.0	90.00	359.45	8,832.0	2,453.3	484.7	2,470.4	0.00	0.00	0.00	
11,300.0	90.00	359.45	8,832.0	2,553.3	483.7	2,570.3	0.00	0.00	0.00	
11,400.0	90.00	359.45	8,832.0	2,653.3	482.7	2,670.2	0.00	0.00	0.00	
11,500.0	90.00	359.45	8,832.0	2,753.3	481.8	2,770.1	0.00	0.00	0.00	
11,600.0	90.00	359.45	8,832.0	2,853.3	480.8	2,870.0	0.00	0.00	0.00	

<b>Database:</b>	EDM5002	<b>Local Co-ordinate Reference:</b>	Well Corral Canyon Federal 11H
<b>Company:</b>	XTO ENERGY, INC.	<b>TVD Reference:</b>	RKB @ 3049.0usft (Frontier #27)
<b>Project:</b>	Eddy County, NM	<b>MD Reference:</b>	RKB @ 3049.0usft (Frontier #27)
<b>Site:</b>	Sec 10, T25S, R29E	<b>North Reference:</b>	Grid
<b>Well:</b>	Corral Canyon Federal 11H	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	Wellbore #1		
<b>Design:</b>	Plan #2		

Planned Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
11,700.0	90.00	359.45	8,832.0	2,953.3	479.9	2,969.8	0.00	0.00	0.00
11,800.0	90.00	359.45	8,832.0	3,053.3	478.9	3,069.7	0.00	0.00	0.00
11,900.0	90.00	359.45	8,832.0	3,153.3	478.0	3,169.6	0.00	0.00	0.00
12,000.0	90.00	359.45	8,832.0	3,253.3	477.0	3,269.5	0.00	0.00	0.00
12,100.0	90.00	359.45	8,832.0	3,353.3	476.1	3,369.4	0.00	0.00	0.00
12,200.0	90.00	359.45	8,832.0	3,453.3	475.1	3,469.3	0.00	0.00	0.00
12,300.0	90.00	359.45	8,832.0	3,553.2	474.1	3,569.1	0.00	0.00	0.00
12,400.0	90.00	359.45	8,832.0	3,653.2	473.2	3,669.0	0.00	0.00	0.00
12,500.0	90.00	359.45	8,832.0	3,753.2	472.2	3,768.9	0.00	0.00	0.00
12,600.0	90.00	359.45	8,832.0	3,853.2	471.3	3,868.8	0.00	0.00	0.00
12,700.0	90.00	359.45	8,832.0	3,953.2	470.3	3,968.7	0.00	0.00	0.00
12,800.0	90.00	359.45	8,832.0	4,053.2	469.4	4,068.5	0.00	0.00	0.00
12,900.0	90.00	359.45	8,832.0	4,153.2	468.4	4,168.4	0.00	0.00	0.00
13,000.0	90.00	359.45	8,832.0	4,253.2	467.4	4,268.3	0.00	0.00	0.00
13,100.0	90.00	359.45	8,832.0	4,353.2	466.5	4,368.2	0.00	0.00	0.00
13,200.0	90.00	359.45	8,832.0	4,453.2	465.5	4,468.1	0.00	0.00	0.00
13,300.0	90.00	359.45	8,832.0	4,553.2	464.6	4,567.9	0.00	0.00	0.00
13,400.0	90.00	359.45	8,832.0	4,653.2	463.6	4,667.8	0.00	0.00	0.00
13,500.0	90.00	359.45	8,832.0	4,753.2	462.7	4,767.7	0.00	0.00	0.00
13,600.0	90.00	359.45	8,832.0	4,853.2	461.7	4,867.6	0.00	0.00	0.00
13,700.0	90.00	359.45	8,832.0	4,953.2	460.8	4,967.5	0.00	0.00	0.00
13,800.0	90.00	359.45	8,832.0	5,053.2	459.8	5,067.3	0.00	0.00	0.00
13,900.0	90.00	359.45	8,832.0	5,153.2	458.8	5,167.2	0.00	0.00	0.00
14,000.0	90.00	359.45	8,832.0	5,253.2	457.9	5,267.1	0.00	0.00	0.00
14,100.0	90.00	359.45	8,832.0	5,353.2	456.9	5,367.0	0.00	0.00	0.00
14,200.0	90.00	359.45	8,832.0	5,453.2	456.0	5,466.9	0.00	0.00	0.00
14,300.0	90.00	359.45	8,832.0	5,553.2	455.0	5,566.7	0.00	0.00	0.00
14,400.0	90.00	359.45	8,832.0	5,653.2	454.1	5,666.6	0.00	0.00	0.00
14,500.0	90.00	359.45	8,832.0	5,753.1	453.1	5,766.5	0.00	0.00	0.00
14,600.0	90.00	359.45	8,832.0	5,853.1	452.1	5,866.4	0.00	0.00	0.00
14,700.0	90.00	359.45	8,832.0	5,953.1	451.2	5,966.3	0.00	0.00	0.00
14,800.0	90.00	359.45	8,832.0	6,053.1	450.2	6,066.1	0.00	0.00	0.00
14,900.0	90.00	359.45	8,832.0	6,153.1	449.3	6,166.0	0.00	0.00	0.00
15,000.0	90.00	359.45	8,832.0	6,253.1	448.3	6,265.9	0.00	0.00	0.00
15,100.0	90.00	359.45	8,832.0	6,353.1	447.4	6,365.8	0.00	0.00	0.00
15,200.0	90.00	359.45	8,832.0	6,453.1	446.4	6,465.7	0.00	0.00	0.00
15,300.0	90.00	359.45	8,832.0	6,553.1	445.4	6,565.6	0.00	0.00	0.00
15,400.0	90.00	359.45	8,832.0	6,653.1	444.5	6,665.4	0.00	0.00	0.00
15,500.0	90.00	359.45	8,832.0	6,753.1	443.5	6,765.3	0.00	0.00	0.00
15,600.0	90.00	359.45	8,832.0	6,853.1	442.6	6,865.2	0.00	0.00	0.00
15,700.0	90.00	359.45	8,832.0	6,953.1	441.6	6,965.1	0.00	0.00	0.00
15,800.0	90.00	359.45	8,832.0	7,053.1	440.7	7,065.0	0.00	0.00	0.00
15,900.0	90.00	359.45	8,832.0	7,153.1	439.7	7,164.8	0.00	0.00	0.00
16,000.0	90.00	359.45	8,832.0	7,253.1	438.8	7,264.7	0.00	0.00	0.00
16,100.0	90.00	359.45	8,832.0	7,353.1	437.8	7,364.6	0.00	0.00	0.00
16,200.0	90.00	359.45	8,832.0	7,453.1	436.8	7,464.5	0.00	0.00	0.00
16,300.0	90.00	359.45	8,832.0	7,553.1	435.9	7,564.4	0.00	0.00	0.00
16,400.0	90.00	359.45	8,832.0	7,653.1	434.9	7,664.2	0.00	0.00	0.00
16,500.0	90.00	359.45	8,832.0	7,753.1	434.0	7,764.1	0.00	0.00	0.00
16,600.0	90.00	359.45	8,832.0	7,853.1	433.0	7,864.0	0.00	0.00	0.00
16,700.0	90.00	359.45	8,832.0	7,953.0	432.1	7,963.9	0.00	0.00	0.00
16,800.0	90.00	359.45	8,832.0	8,053.0	431.1	8,063.8	0.00	0.00	0.00
16,900.0	90.00	359.45	8,832.0	8,153.0	430.1	8,163.6	0.00	0.00	0.00
17,000.0	90.00	359.45	8,832.0	8,253.0	429.2	8,263.5	0.00	0.00	0.00

<b>Database:</b>	EDM5002	<b>Local Co-ordinate Reference:</b>	Well Corral Canyon Federal 11H
<b>Company:</b>	XTO ENERGY, INC.	<b>TVD Reference:</b>	RKB @ 3049.0usft (Frontier #27)
<b>Project:</b>	Eddy County, NM	<b>MD Reference:</b>	RKB @ 3049.0usft (Frontier #27)
<b>Site:</b>	Sec 10, T25S, R29E	<b>North Reference:</b>	Grid
<b>Well:</b>	Corral Canyon Federal 11H	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	Wellbore #1		
<b>Design:</b>	Plan #2		

Planned Survey										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	
17,100.0	90.00	359.45	8,832.0	8,353.0	428.2	8,363.4	0.00	0.00	0.00	
17,200.0	90.00	359.45	8,832.0	8,453.0	427.3	8,463.3	0.00	0.00	0.00	
17,300.0	90.00	359.45	8,832.0	8,553.0	426.3	8,563.2	0.00	0.00	0.00	
17,400.0	90.00	359.45	8,832.0	8,653.0	425.4	8,663.0	0.00	0.00	0.00	
17,500.0	90.00	359.45	8,832.0	8,753.0	424.4	8,762.9	0.00	0.00	0.00	
17,600.0	90.00	359.45	8,832.0	8,853.0	423.5	8,862.8	0.00	0.00	0.00	
17,700.0	90.00	359.45	8,832.0	8,953.0	422.5	8,962.7	0.00	0.00	0.00	
17,800.0	90.00	359.45	8,832.0	9,053.0	421.5	9,062.6	0.00	0.00	0.00	
17,900.0	90.00	359.45	8,832.0	9,153.0	420.6	9,162.4	0.00	0.00	0.00	
18,000.0	90.00	359.45	8,832.0	9,253.0	419.6	9,262.3	0.00	0.00	0.00	
18,100.0	90.00	359.45	8,832.0	9,353.0	418.7	9,362.2	0.00	0.00	0.00	
18,200.0	90.00	359.45	8,832.0	9,453.0	417.7	9,462.1	0.00	0.00	0.00	
18,300.0	90.00	359.45	8,832.0	9,553.0	416.8	9,562.0	0.00	0.00	0.00	
18,400.0	90.00	359.45	8,832.0	9,653.0	415.8	9,661.9	0.00	0.00	0.00	
18,500.0	90.00	359.45	8,832.0	9,753.0	414.8	9,761.7	0.00	0.00	0.00	
18,600.0	90.00	359.45	8,832.0	9,853.0	413.9	9,861.6	0.00	0.00	0.00	
18,700.0	90.00	359.45	8,832.0	9,953.0	412.9	9,961.5	0.00	0.00	0.00	
18,800.0	90.00	359.45	8,832.0	10,053.0	412.0	10,061.4	0.00	0.00	0.00	
18,900.0	90.00	359.45	8,832.0	10,152.9	411.0	10,161.3	0.00	0.00	0.00	
19,000.0	90.00	359.45	8,832.0	10,252.9	410.1	10,261.1	0.00	0.00	0.00	
19,100.0	90.00	359.45	8,832.0	10,352.9	409.1	10,361.0	0.00	0.00	0.00	
<b>TD @ 19142.3' MD / 8832.0' TVD</b>										
19,142.3	90.00	359.45	8,832.0	10,395.2	408.7	10,403.2	0.00	0.00	0.00	

Design Targets										
Target Name	Dip Angle (°)	Dip Dir. (°)	TVD (usft)	+N/-S (usft)	+E/-W (usft)	Northing (usft)	Easting (usft)	Latitude	Longitude	
LTP - Corral Canyon Fex - hit/miss target - Shape - Point	0.00	0.00	8,832.0	10,265.2	411.1	429,407.10	612,789.80	32° 10' 48.114 N	103° 58' 7.594 W	
- plan misses target center by 1.2usft at 19012.2usft MD (8832.0 TVD, 10265.2 N, 409.9 E)										
PBHL - Corral Canyon F - plan hits target center - Point	0.00	0.00	8,832.0	10,395.2	408.7	429,537.10	612,787.40	32° 10' 49.401 N	103° 58' 7.616 W	
FTP - Corral Canyon Fe - plan misses target center by 51.3usft at 9100.0usft MD (8797.2 TVD, 359.4 N, 473.9 E) - Point	0.00	0.00	8,832.0	337.9	504.9	419,479.80	612,883.60	32° 9' 9.868 N	103° 58' 6.894 W	

<b>Database:</b>	EDM5002	<b>Local Co-ordinate Reference:</b>	Well Corral Canyon Federal 11H
<b>Company:</b>	XTO ENERGY, INC.	<b>TVD Reference:</b>	RKB @ 3049.0usft (Frontier #27)
<b>Project:</b>	Eddy County, NM	<b>MD Reference:</b>	RKB @ 3049.0usft (Frontier #27)
<b>Site:</b>	Sec 10, T25S, R29E	<b>North Reference:</b>	Grid
<b>Well:</b>	Corral Canyon Federal 11H	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	Wellbore #1		
<b>Design:</b>	Plan #2		

Formations						
Measured Depth (usft)	Vertical Depth (usft)	Name	Lithology	Dip (°)	Dip Direction (°)	
449.0	449.0	Rustler				
813.0	813.0	Top Salt				
2,894.0	2,894.0	Base Salt				
3,102.0	3,102.0	Delaware				
3,971.0	3,971.0	Cherry Canyon				
5,593.0	5,593.0	Brushy Canyon				
6,847.0	6,847.0	Bone Spring				
7,654.0	7,654.0	1st Bone Spring Lm				
7,793.0	7,793.0	1st Bone Spring Ss				
8,083.0	8,083.0	2nd Bone Spring Lm				
8,688.1	8,588.0	2nd Bone Spring Ss				
9,012.9	8,767.0	2nd Bone Spring "B" Ss				

Plan Annotations					
Measured Depth (usft)	Vertical Depth (usft)	Local Coordinates			
		+N/-S (usft)	+E/-W (usft)	Comment	
8,040.0	8,040.0	0.0	0.0	Build 10°/100'	
8,455.1	8,419.7	9.9	143.6	EOB @ 41.52° Inc / 86.06° Azm - Build/Turn 10°/100'	
9,332.3	8,832.0	585.6	502.5	EOBT @ 90.00° Inc / 359.45° Azm	
19,142.3	8,832.0	10,395.2	408.7	TD @ 19142.3' MD / 8832.0' TVD	



Sec 10, T25S, R29E  
Corral Canyon Federal 11H  
Q170\*\*\* & WT-170\*\*\*  
Plan #2






Company Name: XTO ENERGY, INC.  
Corral Canyon Federal 11H  
Eddy County, NM  
Rig: Frontier #27  
Created By: Keith Noack  
Date: 5/23/2017

PROJECT DETAILS: Eddy County, NM  
Geodetic System: US State Plane 1927 (Exact solution)  
Datum: NAD 1927 (NADCON CONUS)  
Ellipsoid: Clarke 1866  
Zone: New Mexico East 3001  
System Datum: Mean Sea Level

WELL DETAILS: Corral Canyon Federal 11H						
+N/-S	+E/-W	Northing	Ground Level: Easting	3024.0	Latitude	Longitude
0.0	0.0	419141.90	612378.70		32° 9' 6.541 N	103° 58' 12.780 W

ANNOTATIONS									
MD	Inc	Azi	TVD	+N/-S	+E/-W	VSect	Departure	Annotation	
8040.0	0.00	0.00	8040.0	0.0	0.0	0.0	0.0	Build 10°/100'	
8455.1	41.52	86.06	8419.7	9.9	143.6	15.5	143.9	EOB @ 41.52° Inc / 86.06° Azm - Build/Turn 10°/100'	
9332.3	90.00	359.45	8832.0	585.6	502.5	604.9	884.7	EOBT @ 90.00° Inc / 359.45° Azm	
19142.3	90.00	359.45	8832.0	10395.2	408.7	10403.2	10694.7	TD @ 19142.3' MD / 8832.0' TVD	

DESIGN TARGET DETAILS						
Name	TVD	+N/-S	+E/-W	Northing	Easting	Latitude
FTP - Corral Canyon Fed 11H	8832.0	337.9	504.9	419479.80	612883.60	32° 9' 9.866 N
LTP - Corral Canyon Fed 11H	8832.0	10265.2	411.1	429407.10	612789.80	32° 10' 48.114 N
PBHL - Corral Canyon Fed 11H	8832.0	10395.2	408.7	429537.10	612787.40	32° 10' 49.401 N





District I  
1625 N. French Dr., Hobbs, NM 88240  
District II  
811 S. First St., Artesia, NM 88210  
District III  
1000 Rio Brazos Road, Aztec, NM 87410  
District IV  
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources Department  
Oil Conservation Division  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

Submit Original  
to Appropriate  
District Office

## GAS CAPTURE PLAN

Date: 05/01/2018

☒ Original Operator & OGRID No.: XTO Energy, Inc [005380] \_\_\_\_\_  
☐ Amended - Reason for Amendment: \_\_\_\_\_

This Gas Capture Plan outlines actions to be taken by the Operator to reduce well/production facility flaring/venting for new completion (new drill, recomple to new zone, re-frac) activity.

*Note: Form C-129 must be submitted and approved prior to exceeding 60 days allowed by Rule (Subsection A of 19.15.18.12 NMAC).*

### Well(s)/Production Facility – Name of facility: Corral Canyon 10 East CTB

The well(s) that will be located at the production facility are shown in the table below.

Well Name	API	Well Location (ULSTR)	Footages	Expected MCF/D	Flared or Vented	Comments
Corral Canyon Federal 10H		C-10-25S-29E	500'FNL & 2410'FWL	4500MCF/D	Flared/Sold	CTB Connected
Corral Canyon Federal 11H		B-10-25S-29E	5'FNL & 2155'FEL	4500MCF/D	Flared/Sold	CTB Connected
Corral Canyon Federal 22H		C-10-25S-29E	500'FNL & 2460'FWL	4500MCF/D	Flared/Sold	CTB Connected
Corral Canyon Federal 23H		B-10-25S-29E	5-FNL & 2205'FEL	4500MCF/D	Flared/Sold	CTB Connected

### Gathering System and Pipeline Notification

Well(s) will be connected to a production facility after flowback operations are complete, if gas transporter system is in place. The gas produced from production facility is dedicated to Enlink and will be connected to Enlink low/high pressure gathering system located in Loving County, Texas. It will require 0' of pipeline to connect the facility to low/high pressure gathering system. XTO Energy, Inc. provides (periodically) to Enlink a drilling, completion and estimated first production date for wells that are scheduled to be drilled in the foreseeable future. In addition, XTO Energy, Inc. and Enlink have periodic conference calls to discuss changes to drilling and completion schedules. Gas from these wells will be processed at Enlink Processing Plant located in Block 27, Section 4, Loving County, Texas. The actual flow of the gas will be based on compression operating parameters and gathering system pressures.

### Flowback Strategy

After the fracture treatment/completion operations, well(s) will be produced to temporary production tanks and gas will be flared or vented. During flowback, the fluids and sand content will be monitored. When the produced fluids contain minimal sand, the wells will be turned to production facilities. Gas sales should start as soon as the wells start flowing through the production facilities, unless there are operational issues on Enlink system at that time. Based on current information, it is XTO Energy, Inc.'s belief the system can take this gas upon completion of the well(s).

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

### Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

- Power Generation – On lease
  - Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas – On lease
  - Gas flared would be minimal, but might be uneconomical to operate when gas volume declines

- NGL Removal – On lease
  - Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines