

UNITED STATES NMOCD Rec'd: 9/28/2020
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENTFORM APPROVED
OMB NO. 1004-0137
Expires: January 31, 2018**SUNDRY NOTICES AND REPORTS ON WELLS**
Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.5. Lease Serial No.
NMNM56428

6. If Indian, Allottee or Tribe Name

7. If Unit or CA/Agreement, Name and/or No.

SUBMIT IN TRIPLICATE - Other instructions on page 2

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

8. Well Name and No.

PAVO FRIO 29/30 B3CD FED COM 1H

2. Name of Operator

MEWBOURNE OIL COMPANY

Contact: JACKIE LATHAN

E-Mail: jlathan@mewbourne.com

9. API Well No.

30-015-45406-00-X1

3a. Address

P O BOX 5270
HOBBS, NM 88241

3b. Phone No. (include area code)

Ph: 575-393-5905

10. Field and Pool or Exploratory Area

PALMILLO-BONE SPRING, EAST

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Sec 29 T18S R29E NWNE 550FNL 2600FEL
32.724186 N Lat, 104.096786 W Lon

11. County or Parish, State

EDDY COUNTY, NM

12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Hydraulic Fracturing	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input checked="" type="checkbox"/> Other
	<input type="checkbox"/> Change Plans	<input type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	Drilling Operations
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleat horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleat in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.

02/28/20 TD 12 1/4" hole @ 1377'. Ran 1362' of 9 5/8" 36# J55 LT&C csg. Cemented with 225 sks Class C w/additives. Mixed @ 13.5#/g w/1.73 yd. Tail w/200 sks Class C w/1.0% CaCl2. Mixed @ 14.8#/g w/1.33 yd. Displaced w/102 bbls of FW. Plug down @ 6:00 P.M. 02/27/20. Circ 84 sks of cmt to the pit. WOC. Set Cameron Mandrel hanger through BOP w/70k#. Set pack-off & test to 5000#. At 6:45 A.M. 02/28/20, tested csg to 1500# for 30 minutes, held OK. Drilled out with 8 3/4" bit. FIT test to EMW of 9.5 PPG.

03/05/20 TD 8 3/4" hole @ 8861'. Ran 8846' of 7" 29# HCP110 LT&C csg. Cemented with 500 sks 50:50 PliteH w/additives. Mixed @ 11.5#/g w/2.63 yd. Tail w/400 sks Class H w/0.5% fluid loss & 0.15% Retarder. Mixed @ 15.6#/g w/1.18 yd. Displaced w/326 bbls of OBM. Plug down @ 10:15 A.M. 03/05/20. Circ 115 sks of cmt to the pit. WOC. Set Cameron Mandrel hanger through BOP w/265k#. Set pack-off & test to 5000#. Test Annular & upper pipe rams to 1500#. At 10:00 P.M. 03/05/20, tested csg to 1500#

14. I hereby certify that the foregoing is true and correct.

Electronic Submission #530987 verified by the BLM Well Information System
For MEWBOURNE OIL COMPANY, sent to the Carlsbad
Committed to AFMSS for processing by PRISCILLA PEREZ on 09/22/2020 (20PP4238SE)

Name (Printed/Typed) JACKIE LATHAN

Title REGULATORY

Signature (Electronic Submission)

Date 09/22/2020

Accepted for record – NMOCD gc 10/2/2020

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved By

ACCEPTEDJONATHON SHEPARD
Title PETROLEUM ENGINEER

Date 09/25/2020

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office Carlsbad

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

**** BLM REVISED ** BLM REVISED ** BLM REVISED ** BLM REVISED ** BLM REVISED ****

Missing Approved Spud Sundry Notice. accepted/entered 10/26/2020 ab

Additional data for EC transaction #530987 that would not fit on the form

32. Additional remarks, continued

for 30 minutes, held OK. Drilled out with 6 1/8" bit. FIT test to EMW of 10.5 PPG.

03/16/20 TD'ed 6 1/8" hole @ 16063' MD. Ran 16062' of 4 1/2" 13.5# HCP110 BPNQ csg. Cement w/700 sks Lite Class H 35:65:6 w/additives. Mixed @ 13.5#/g w/1.60 yd. Followed w/5 bbls FW. Released dart. Displaced w/207 bbls sugar FW. Plug down @ 5:30 P.M. 03/17/20. Bump plug w/3300#. Set packer w/80k#. Sting out of PBR w/2000# on DP. Displaced 7" csg w/255 bbls sugar FW. Circ 280 sks of cmt off of liner top to the pit. Circ 360 bbls FW w/polymer sweep. At 6:30 P.M., 03/17/20, tested csg to 1500# for 30 mins, held OK. Top of liner @ 7901'.

Rig released on 03/18/2020 @ 9:00 P.M.

Bond on file: NM1693 nationwide & NMB000919

Revisions to Operator-Submitted EC Data for Sundry Notice #530987

	Operator Submitted	BLM Revised (AFMSS)
Sundry Type:	DRG SR	DRG SR
Lease:	NMNM56428	NMNM56428
Agreement:		
Operator:	MEWBOURNE OIL COMPANY PO BOX 5270 HOBBS, NM 88241 Ph: 575-393-5905	MEWBOURNE OIL COMPANY P O BOX 5270 HOBBS, NM 88241 Ph: 575.393.5905
Admin Contact:	JACKIE LATHAN AUTHORIZED REPRESENTATIVE E-Mail: jlathan@mewbourne.com Ph: 575-393-5905	JACKIE LATHAN REGULATORY E-Mail: jlathan@mewbourne.com Ph: 575-393-5905
Tech Contact:	JACKIE LATHAN AUTHORIZED REPRESENTATIVE E-Mail: jlathan@mewbourne.com Ph: 575-393-5905	JACKIE LATHAN REGULATORY E-Mail: jlathan@mewbourne.com Ph: 575-393-5905
Location:		
State:	NM	NM
County:	EDDY	EDDY
Field/Pool:	PALMILLO;BONE SPRING EAST	PALMILLO-BONE SPRING, EAST
Well/Facility:	PAVO FRIO 29/30 B3CD FED COM 1H Sec 29 T18S R29E Mer NMP NWNE 550FNL 2600FEL	PAVO FRIO 29/30 B3CD FED COM 1H Sec 29 T18S R29E NWNE 550FNL 2600FEL 32.724186 N Lat, 104.096786 W Lon