n.	JD Murchi State of New Me	son Interests	,	Ø 002 Form C-10
and the state of	rgy, Minerals and Natu		_	May 27, 20
N. French Dr., Hobbs, NM 88240			ELL APT NO.	. 14th Z1, Z0
Shriet II 1301 W. Grand Ave., Artesia, NM EE210 OI	L CONSERVATION	DIVISION	30-015-33477	
District III	1220 South St. Fra	4	5. Indicate Type of Le	
1000 Rio Brazos Rd., Azteo, NM 87410 District IV	Santa Fe, NM 8		STATE	FEE 🗵
1220 S. St. Francis Dr., Santa Fe, NM	Danie I 0, 14141 0	7505	6. State Oil & Gas Le	ase No.
57505	<i>t</i>			<u> </u>
SUNDRY NOTICES AND DO NOT USE THIS FORM FOR PROPOSALS TO DI	O REPORTS ON WELLS	G PACT TO A	7. Lease Name or Um	t Agreement Name
DIFFERENT RESERVOIR. OSK "APPLICATION FOI	R PERMIT" (FORM C-101) FO	R SUCH	TTATAY	76
PROFOSALS.) 1. Type of Well: Oil Well 🔲 Gas Wel	l 🕅 Other		* Well Number 1	
. Name of Operator	M Ome		9. OGRID Number	· · · · · · · · · · · · · · · · · · ·
MURCHISON	OIL & GAS, INC.	•	A. OCKID Nimber	015363
3. Address of Operator	1		10. Pool name or Wil	
1100 MIRA VISTA BLVD., PLANO, TX. 75093-4698			UNDES. LOGAN DRAW; MORROW	
Well Location				
Unit Letter F: 1980	fcet from theNOR	TH line and	1980 feet from t	he WEST line
Section 19	Township 17-S	Range 27-E	NMPM	County EDD
11. Ele	vation (Show whether DR	, RKB, RT, GR, etc		
t or Below-grade Pank Application or Closure	3302' CH			
·	=		:	
	Distance from nearest fresh w	 :	nice from nearest surface wa	ter
	Grade Tank: Volume		truction Material	
12. Check Appropri	ate Box to Indicate N	ature of Notice,	Report or Other Dat	a.
NOTICE OF INTENTION	ON TO:	هاره ا	OFOUENT BEROS	
	AND ABANDON []		SEQUENT REPOR	
 - -	SE PLANS	REMEDIAL WOR		ERING CASING [
	PLE COMPL	COMMENCE DRI		ND A
WOLIN	THE COMPLE	CASING/CEMEN	T JOB 🛛	
OTHER:	🗀	OTHER:		г
13. Describe proposed or completed oper	ations. (Clearly state all	pertinent details, ap	d give pertinent dates; in	cluding estimated
or agarding and brobosed MOLK). SEE	RULE 1103. For Multip	ale Completions: A	ttach wellbore diagram o	of proposed comple
or recompletion.			, ,	•
			1	
	to smudding small Canal	107 L-1		
Contacted Van Barron w/ NMOCD prior		l /-1/2" Dole with P	merson UTI Rig #510 @	
Contacted Van Barron w/ NMOCD prior and drill to 310'. Rnn 11 joints of 13-3/8	" 68 #/FT N_20 Posteroco	coming to 2001 and	O	2300 HRS 2/20/0
and current to 210. Knm 11 lonnes of 13-3/9	" 68 #/F1 N-80 Buttress	casing to 300' and .	set. Cemented with 340	SYS Mass "C" +
CaCl. Bumped plug w/ 490 PSI. Did no TOC @ 225'. Ran 1" tubing to 210'. Co	" 68 #/FT N-80 Buttress circulate cement to surf intacted Van Barton w/ N	casing to 300' and acce. WOC 10.5 HR	set. Comented with 340 S. Ran temperature sure	SXS Class "C" + ; vey (Copy attached
CaCl. Bumped plug w/ 490 PSI. Did no TOC @ 225'. Ran 1" tubing to 210'. Co Pumped 50 SXS of Class "C" + 3% CaCl.	" 68 #/F.I' N-80 Buttress I circulate cement to surfice intacted Van Barton w/ N I. WOC 3.5 HRS. Cemen	casing to 300' and acce. WOC 10.5 HR MOCD and obtain	set. Comented with 340 S. Ran temperature sured approval to circulate approval to circul	SXS Class "C" + ; vey (Copy attached cement through 1"
CaCl. Bumped plug w/ 490 PSI. Did no TOC @ 225'. Ran 1" tubing to 210'. Co Pumped 50 SXS of Class "C" + 3% CaCl. Contacted Van Barton w/ NMOCD and of the contacted Van Barton w/ NMOCD and of the cacle	" 68 #/FT N-80 Buttress I circulate cement to surficentacted Van Barton w/ N L. WOC 3.5 HRS. Cement Obtained approval to circulate the circulate surficence of the circula	casing to 300' and ace. WOC 10.5 HR MOCD and obtains at top at bottom of a late, exament through	set. Comented with 340 S. Ran temperature sur- ed approval to circulate of conductor pipe. Ran 1" 1 a linch. Circulated com-	SXS Class "C" + vey (Copy attached cement through 1" thing to 50'.
CaCl. Bumped plug w/ 490 PSI. Did no TOC @ 225'. Ran 1" tubing to 210'. Co Pumped 50 SXS of Class "C" + 3% CaCl. Contacted Van Barton w/ NMOCD and c SXS Class "C" + 2% CaCl. WOC 23.5 I	" 68 #/FT N-80 Buttress I circulate cement to surficentacted Van Barton w/ N I. WOC 3.5 HRS. Cements to circulate approval to circulate Weld on wellheads.	casing to 300' and ace. WOC 10.5 HR MOCD and obtains at top at bottom of a late, exament through	set. Comented with 340 S. Ran temperature sur- ed approval to circulate of conductor pipe. Ran 1" 1 a linch. Circulated com-	SXS Class "C" +: vey (Copy attached cement through 1" ching to 50".
CaCl. Bumped plug w/ 490 PSI. Did no TOC @ 225'. Ran 1" tubing to 210'. Co Pumped 50 SXS of Class "C" + 3% CaCl	" 68 #/FT N-80 Buttress I circulate cement to surficentacted Van Barton w/ N I. WOC 3.5 HRS. Cements to circulate approval to circulate Weld on wellheads.	casing to 300' and ace. WOC 10.5 HR MOCD and obtains at top at bottom of a late, exament through	set. Comented with 340 S. Ran temperature sur- ed approval to circulate of conductor pipe. Ran 1" 1 a linch. Circulated com-	SXS Class "C" +: vey (Copy attached cement through 1" ching to 50".
CaCl. Bumped plug w/ 490 PSI. Did no TOC @ 225'. Ran 1" tubing to 210'. Co Pumped 50 SXS of Class "C" + 3% CaCl. Contacted Van Barton w/ NMOCD and c SXS Class "C" + 2% CaCl. WOC 23.5 I	" 68 #/FT N-80 Buttress I circulate cement to surficentacted Van Barton w/ N I. WOC 3.5 HRS. Cements to circulate approval to circulate Weld on wellheads.	casing to 300' and ace. WOC 10.5 HR MOCD and obtains at top at bottom of a late, exament through	set. Comented with 340 S. Ran temperature sured approval to circulate conductor pipe. Ran 1" in 1 inch. Ciruclated com in hole with 12-1/4" bit	SXS Class "C" + ; rey (Copy attached cement through 1" mbing to 50'. cout to surface w/ 1 and drill out ceme
CaCl. Bumped plug w/ 490 PSI. Did no TOC @ 225'. Ran 1" tubing to 210'. Co Pumped 50 SXS of Class "C" + 3% CaCl. Contacted Van Barton w/ NMOCD and c SXS Class "C" + 2% CaCl. WOC 23.5 I	" 68 #/FT N-80 Buttress I circulate cement to surficentacted Van Barton w/ N I. WOC 3.5 HRS. Cements to circulate approval to circulate Weld on wellheads.	casing to 300' and ace. WOC 10.5 HR MOCD and obtains at top at bottom of a late, exament through	set. Comented with 340 S. Ran temperature sured approval to circulate conductor pipe. Ran 1" 1 inch. Circulated comin hole with 12-1/4" bit	SXS Class "C" + ; vey (Copy attached cement through 1" mbing to 50'. cout to surface w/ 1 and drill out ceme
CaCl. Bumped plug w/ 490 PSI. Did no TOC @ 225'. Ran 1" tubing to 210'. Co Pumped 50 SXS of Class "C" + 3% CaCl. Contacted Van Barton w/ NMOCD and c SXS Class "C" + 2% CaCl. WOC 23.5 I	" 68 #/FT N-80 Buttress I circulate cement to surficentacted Van Barton w/ N I. WOC 3.5 HRS. Cements to circulate approval to circulate Weld on wellheads.	casing to 300' and ace. WOC 10.5 HR MOCD and obtains at top at bottom of a late, exament through	set. Comented with 340 S. Ran temperature sured approval to circulate conductor pipe. Ran 1" in 1 inch. Ciruclated com in hole with 12-1/4" bit	SXS Class "C" + ; rey (Copy attached cement through 1" mbing to 50' cout to surface w/ 1 and drill out ceme 4 TO 400 PS
CaCl. Bumped plug w/ 490 PSI. Did no TOC @ 225'. Ran 1" tubing to 210'. Co Pumped 50 SXS of Class "C" + 3% CaCl. Contacted Van Barton w/ NMOCD and c SXS Class "C" + 2% CaCl. WOC 23.5 I	" 68 #/FT N-80 Buttress I circulate cement to surficentacted Van Barton w/ N I. WOC 3.5 HRS. Cements to circulate approval to circulate Weld on wellheads.	casing to 300' and ace. WOC 10.5 HR MOCD and obtains at top at bottom of a late, exament through	set. Comented with 340 S. Ran temperature sured approval to circulate conductor pipe. Ran 1" 1 inch. Circulated comin hole with 12-1/4" bit	SXS Class "C" + vey (Copy attached cement through 1" mbing to 50'. cent to surface w/ 1 and drill out ceme
CaCl. Bumped plug w/ 490 PSI. Did no TOC @ 225'. Ran 1" tubing to 210'. Co Pumped 50 SXS of Class "C" + 3% CaCl. Contacted Van Barton w/ NMOCD and c SXS Class "C" + 2% CaCl. WOC 23.5 I	" 68 #/FT N-80 Buttress I circulate cement to surficentacted Van Barton w/ N I. WOC 3.5 HRS. Cements to circulate approval to circulate Weld on wellheads.	casing to 300' and ace. WOC 10.5 HR MOCD and obtains at top at bottom of a late, exament through	set. Comented with 340 S. Ran temperature sured approval to circulate conductor pipe. Ran 1" 1 inch. Circulated comin hole with 12-1/4" bit	SXS Class "C" + ; rey (Copy attached cement through 1" mbing to 50' cout to surface w/ 1 and drill out ceme 4 TO 400 PS
CaCl. Bumped plug w/ 490 PSI. Did no TOC @ 225'. Ran 1" tubing to 210'. Co Pumped 50 SXS of Class "C" + 3% CaCl Confacted Van Barton w/ NMOCD and of SXS Class "C" + 2% CaCl. WOC 23.5 Resume drilling formation with 12-1/4" to the state of t	" 68 #/F.I' N-80 Buttress I circulate cement to surficient Van Barton w/ N . WOC 3.5 HRS. Cement to circulate approval to circulate approval to circulate. Weld on wellhead soft.	casing to 300' and ace. WOC 10.5 HR IMOCD and obtains at top at bottom of a late coment through and mipple up. Ran	set. Comented with 340 S. Ran temperature sured approval to circulate conductor pipe. Ran 1" 1 1 inch. Circulated comin hole with 12-1/4" bit TEST CASIN HBLD FOR 30	SXS Class "C" + ; vey (Copy attached cement through 1" mbing to 50', cont to surface w/ 1 and drill out ceme A TO 400 PSE MIN.
CaCl. Bumped plug w/ 490 PSI. Did no TOC @ 225'. Ran 1" tubing to 210'. Co Pumped 50 SXS of Class "C" + 3% CaCl Contacted Van Barton w/ NMOCD and of SXS Class "C" + 2% CaCl. WOC 23.5 I Resume drilling formation with 12-1/4" to be the contacted Van Barton with 12-1/4" to be the contacte	to circulate cement to surficient Van Barton w/ N. WOC 3.5 HRS. Cement to circulate approval to circulate approval to circulate well bead approval.	casing to 300' and ace. WOC 10.5 HR IMOCD and obtains at top at bottom of a late coment through and nipple up. Ran	set. Comented with 340 S. Ran temperature sured approval to circulate conductor pipe. Ran 1" 1 1 inch. Circulated comin hole with 12-1/4" bit TEST CASIN HBLD FOR 30	SXS Class "C" + ; rey (Copy attached cement through 1" mbing to 50' cont to surface w/ 1 and drill out ceme L TO 400 PSE MIN.
CaCl. Bumped plug w/ 490 PSI. Did no TOC @ 225'. Ran 1" tubing to 210'. Co Pumped 50 SXS of Class "C" + 3% CaCl Contacted Van Barton w/ NMOCD and of SXS Class "C" + 2% CaCl. WOC 23.5 I Resume drilling formation with 12-1/4" to the contacted Van Barton with 12-1/4" to the contacted v	to circulate cement to surficient Van Barton w/ N. WOC 3.5 HRS. Cement to circulate approval to circulate approval to circulate well bead approval.	casing to 300' and ace. WOC 10.5 HR IMOCD and obtains at top at bottom of a late coment through and nipple up. Ran	set. Comented with 340 S. Ran temperature sured approval to circulate conductor pipe. Ran 1" 1 1 inch. Circulated comin hole with 12-1/4" bit TEST CASIN HBLD FOR 30	SXS Class "C" + ; rey (Copy attached cement through 1" mbing to 50', cut to surface w/ 1 and drill out ceme 4 TO 400 PS
CaCl. Bumped plug w/ 490 PSI. Did no TOC @ 225'. Ran 1" tubing to 210'. Co Pumped 50 SXS of Class "C" + 3% CaCl. Confacted Van Barton w/ NMOCD and of SXS Class "C" + 2% CaCl. WOC 23.5 I Resume drilling formation with 12-1/4" to the confact of the	to the land complete to the land of MAOCD guidelines I	casing to 300' and ace. WOC 10.5 HR MOCD and obtains at top at bottom of a late coment through and nipple up. Ran pest of my knowled; l, a general permit [] of	set. Comented with 340 S. Ran temperature sured approval to circulate conductor pipe. Ran 1" in 1 inch. Circulated comin hole with 12-1/4" bit TEST CASIN HBLD FOR 30 TEST CASIN HBLD FOR 30 TEST CASIN HBLD FOR 30	SXS Class "C" + ; rey (Copy attached cement through 1" mbing to 50', cont to surface w/ 1 and drill out ceme A TO 400 PSE WIN. MID thy that any pit or bel CD-approved plan [].
CaCl. Bumped plug w/ 490 PSI. Did no TOC @ 225'. Ran 1" tubing to 210'. Co Pumped 50 SXS of Class "C" + 3% CaCl. Confacted Van Barton w/ NMOCD and of SXS Class "C" + 2% CaCl. WOC 23.5 I Resume drilling formation with 12-1/4" to the confact of the	to circulate cement to surficient Van Barton w/ N. WOC 3.5 HRS. Cement to circulate approval to circulate approval to circulate well be well head a soft. TYPLE	casing to 300' and ace. WOC 10.5 HR IMOCD and obtains at top at bottom of a late coment through and nipple up. Ran	set. Comented with 340 S. Ran temperature sured approval to circulate conductor pipe. Ran 1" in 1 inch. Circulated comin hole with 12-1/4" bit TEST CASIN HBLD FOR 30 TEST CASIN HBLD FOR 30 TEST CASIN HBLD FOR 30	SXS Class "C" + ; rey (Copy attached cement through 1" mbing to 50' cont to surface w/ 1 and drill out ceme L TO 400 PSE MIN.
CaCl. Bumped plug w/ 490 PSI. Did no TOC @ 225'. Ran 1" tubing to 210'. Co Pumped 50 SXS of Class "C" + 3% CaCl. Contacted Van Barton w/ NMOCD and of SXS Class "C" + 2% CaCl. WOC 23.5 I Resume drilling formation with 12-1/4" to the contacted by the contact of t	TYPLE	casing to 300' and ace. WOC 10.5 HR MOCD and obtains at top at bottom of a late coment through and nipple up. Ran Dest of my knowled; J. n. general permit V.P. OPHRATION	set. Comented with 340 S. Ran temperature sured approval to circulate conductor pipe. Ran 1" in a 1 inch. Ciruclated coming the conductor pipe. Ran 1" in hole with 12-1/4" bit. TEST CASIN HBLD FOR 30	SXS Class "C" + 2 rey (Copy attached cement through 1" mbing to 50' cent to surface w/ 1 and drill out ceme A TO 400 (SS MIN. MIN. TE 3/16/2005
CaCl. Bumped plug w/ 490 PSI. Did no TOC @ 225'. Ran 1" tubing to 210'. Co Pumped 50 SXS of Class "C" + 3% CaCl. Contacted Van Barton w/ NMOCD and of SXS Class "C" + 2% CaCl. WOC 23.5 I Resume drilling formation with 12-1/4" to the contacted by the contact of t	TYPLE	casing to 300' and ace. WOC 10.5 HR MOCD and obtains at top at bottom of a late coment through and nipple up. Ran Dest of my knowled; J. n. general permit V.P. OPHRATION	set. Comented with 340 S. Ran temperature sured approval to circulate conductor pipe. Ran 1" in 1 inch. Circulated comin hole with 12-1/4" bit TEST CASIN HBLD FOR 30 TEST CASIN HBLD FOR 30 TEST CASIN HBLD FOR 30	SXS Class "C" + 2 vey (Copy attached cement through 1" mbing to 50' cont to surface w/ 1 and drill out cemen A TO 400 (SS) WIN. MIN. TE 3/16/2005 TE 3/16/2005
CaCl. Bumped plug w/ 490 PSI. Did no TOC @ 225'. Ran 1" tubing to 210'. Co Pumped 50 SXS of Class "C" + 3% CaCl. Contacted Van Barton w/ NMOCD and of SXS Class "C" + 2% CaCl. WOC 23.5 I Resume drilling formation with 12-1/4" to the contacted by short account of the contact of	TITLE Tire Barry Barry Buttress Circulate cement to surfice to the latest Van Barton w/ N WOC 3.5 HRS. Cement to circulate approval to circulate approval to circulate to the latest value and complete to the latest	casing to 300' and ace. WOC 10.5 HR MOCD and obtains at top at bottom of a late coment through and nipple up. Ran Dest of my knowled; J. n. general permit V.P. OPHRATION	set. Comented with 340 S. Ran temperature sured approval to circulate conductor pipe. Ran 1" in 1 inch. Circulated comin hole with 12-1/4" bit TEST CASIN HBLD FOR 30 TEST CASIN HBLD FOR 30 TEST CASIN HBLD FOR 30 Company of the conductor of the conductor pipe. TEST CASIN HBLD FOR 30 Company of the conductor of the conducto	SXS Class "C" + 2 rey (Copy attached cement through 1" mbing to 50'. cont to surface w/ 1 and drill out cemes A TO 400 PSS WIN. MIN. TE 3/16/2005 E No. (972) 931-0' MAR 2 3 200
CaCl. Bumped plug w/ 490 PSI. Did no TOC @ 225'. Ran 1" tubing to 210'. Co Pumped 50 SXS of Class "C" + 3% CaCl. Contacted Van Barton w/ NMOCD and of SXS Class "C" + 2% CaCl. WOC 23.5 I Resume drilling formation with 12-1/4" to the contacted by short account of the contacted by	TYPLE	casing to 300' and ace. WOC 10.5 HR MOCD and obtains at top at bottom of a late coment through and nipple up. Ran Dest of my knowled; J. n. general permit V.P. OPHRATION	set. Comented with 340 S. Ran temperature sured approval to circulate conductor pipe. Ran 1" in 1 inch. Circulated comin hole with 12-1/4" bit TEST CASIN HBLD FOR 30 TEST CASIN HBLD FOR 30 TEST CASIN HBLD FOR 30 Company of the conductor of the conductor pipe. TEST CASIN HBLD FOR 30 Company of the conductor of the conducto	SXS Class "C" + 2 vey (Copy attached cement through 1" mbing to 50' cont to surface w/ 1 and drill out ceme A TO 400 PS MIN. MSO thy that any pit or belico- co-approved plan []. TE 3/16/2005 se No. (972) 931-0'
CaCl. Bumped plug w/ 490 PSI. Did no TOC @ 225'. Ran 1" tubing to 210'. Co Pumped 50 SXS of Class "C" + 3% CaCl. Contacted Van Barton w/ NMOCD and of SXS Class "C" + 2% CaCl. WOC 23.5 I Resume drilling formation with 12-1/4" to the constructed or closed according to the constructed or closed according to print name MICHAEL S. DAUGHER of State Use Only PPROVED BY: PPROVED BY: PORT TO THE TOTAL TO THE PROVED BY: PORT TO THE TOTAL TO THE PROVED BY: PORT TO THE TOTAL TO THE PROVED BY: PORT TO THE TOTAL THE PROVED BY: PORT TO	TITLE Tire Barry Barry Buttress Circulate cement to surfice to the latest Van Barton w/ N WOC 3.5 HRS. Cement to circulate approval to circulate approval to circulate to the latest value and complete to the latest	casing to 300' and ace. WOC 10.5 HR MOCD and obtains at top at bottom of a late coment through and nipple up. Ran Dest of my knowled; J. n. general permit V.P. OPHRATION	set. Comented with 340 S. Ran temperature sured approval to circulate conductor pipe. Ran 1" in 1 inch. Circulated comin hole with 12-1/4" bit TEST CASIN HBLD FOR 30 TEST CASIN HBLD FOR 30 TEST CASIN HBLD FOR 30 Company of the conductor of the conductor pipe. TEST CASIN HBLD FOR 30 Company of the conductor of the conducto	SXS Class "C" + 2 rey (Copy attached cement through 1" mbing to 50'. cont to surface w/ 1 and drill out cemes A TO 400 PSS WIN. MIN. TE 3/16/2005 E No. (972) 931-0' MAR 2 3 200

-.