

OCD-ARTESIA

Form 3160-5
(August 2007)UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENTFORM APPROVED
OMB No. 1004-0137
Expires: July 31, 2010

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

SUBMIT IN TRIPLICATE - Other instructions on page 2.

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Murchison Oil Gas, Inc.

3a. Address

P.O. Box 627
Carlsbad, New Mexico 88221

3b. Phone No. (include area code)

(575) 628 - 3932

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Sec. 35, T-18S, R-24E
Unit O 990' FSL & 1980 FEL

5. Lease Serial No.

NM 33661

6. If Indian, Allottee or Tribe Name

7. If Unit of CA/Agreement, Name and/or No.

NM/01384 / Penasco Draw Fed Com

8. Well Name and No.

Penasco Draw Federal #1

9. API Well No.

30-015-25959

10. Field and Pool or Exploratory Area

11. Country or Parish, State

Eddy, New Mexico

12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
☒ Notice of Intent	☐ Acidize	☐ Deepen	☐ Production (Start/Resume)	☐ Water Shut-Off
☐ Subsequent Report	☐ Alter Casing	☐ Fracture Treat	☐ Reclamation	☐ Well Integrity
☐ Final Abandonment Notice	☐ Casing Repair	☐ New Construction	☐ Recomplete	☐ Other
	☐ Change Plans	☒ Plug and Abandon	☐ Temporarily Abandon	
	☐ Convert to Injection	☐ Plug Back	☐ Water Disposal	

13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleat horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleat in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.)

See attached p & a Proposed Procedure.

RECLAMATION PROCEDURE
ATTACHEDSEE ATTACHED FOR
CONDITIONS OF APPROVAL

14. I hereby certify that the foregoing is true and correct Name (Printed/Typed)

Tommy W. Folsom

Title Operations Manager

Signature

Date 07/11/2011

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Title

SEAS

Date

8-29-11

Office

CFO

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

Accepted for record
NMOCD

9/1/2011

MURCHISON OIL AND GAS, INC.
PENASCO DRAW FEDERAL #1
SEC.35, T-18S, R-24E
Unit O 990' FSL AND 1980' FEL
EDDY COUNTY, NEW MEXICO

P&A

June 27, 2011

CASING:

Surface	13 3/8" - 48# K -55 @	388'	Cmt Cir.
Intermediate	9 5/8" - 40# K-55 @	1,216'	Cmt Cir.
Production Csg	5 1/2" - 17# N-80 @	8,840'	Cmt Top @ 5,970'

LOGS:

ND& DLL Dated 8-19-88

ELEVATION:

KB - 3735' GL - 3717

EQUIPMENT:

Tubing - 2 7/8" N-80 Tbg 6.5# estimated 7,400'

EXSITING PERFORATIONS:

Morrow - 8,641' to 8,662'
CIBP at 8590' capped with 15' Cmt
Atoka - 8272' to 8,276'
Strawn - 8,125' to 8,134' and 8184' to 8,188'
Wolfcamp Canyon - 7,466' to 7,472'

Procedure:

1. Start work when procedure is approved by BLM and plugging rig located. MI and RUPU and NUBOP. Notify BLM at 575-887-6544 before starting any work.
2. POOH w/ tbg and control well as needed. Tally out of hole and remove any tools from bottom of tbg. (Pkr, plunger equipment) TIH and tag w/ wireline.
3. CIBP was reported to be set at 8,050' w/ 30' cmt placed on top of plug.

- a. If CIBP is not at 8,050' POOH and set CIBP at 8,050' and cap w/ ~~20'~~ ^{35' (Dump Bar)} cmt continue procedure.
- b. If CIBP is at 8,050' continue procedure
4. Set CIBP above Canyon perforations 7,466' to 7,472' at 7,400' and cap w/ ~~30'~~ ^{35' (Dump Bar)} of cmt.
5. Free point csg and cut off and POOH w/ 5 1/2" csg. 5280 +/-
6. TIH w/ open ended tbg and spot class H cmt plug 50' below and 100' above 5 1/2" csg stub. WOC and tag plug. This plug should be above top of Wolfcamp.
7. Circulate hole w/ 10# salt gel
8. PUH and set 140' class C cmt plug at ~~4,000'~~ ^{4110' - 3970'} top of Abo, WOC and tag.
9. PUH and set 110' class C cmt plug at 1900' top of Glorieta, WOC and tag.
10. PUH and set 110' class C cmt plug 50' below and 60' above 9 5/8" csg shoe at 1,216'. WOC and tag.
11. PUH and set 100' class C cmt plug across 13 3/8" shoe inside 9 5/8" csg 438' to 338'.
12. Dig out and cut off well head 4' below ground level and spot 50' surface plug. Weld on P&A Marker with the following information, four foot above ground level.

MURCHISON OIL AND GAS, INC.
PENASCO FEDERAL #1
SEC.35, T-18S, R-24E
990' FSL AND 1980' FEL
EDDY COUNTY, NEW MEXICO
API # 30-015-25959
Lease# NM 33661
Date well is plugged

13. Fill in cellar, remove all equipment, clean and restore location as required by BLM, seed with seed mixture #4.

Penasco Federal #1
P & A Procedure
June 27, 2011
Page 3 of 3

FORMATION TOPS:


GLORIETA	1977
YESO	2116
TUBB	3361
ABO	4040
WOLFCAMP	5230
STRAWN	7884
ATOKA	8211
MORROW	8625
CHESTER LIME	8830

Tommy W. Folsom
Operations Manager

Murchison Oil and Gas, Inc.
Penasco Federal #1
Sec. 35, T-18S, R-24E
Eddy County, New Mexico
API # 30-015-25959

TOPS

Glorieta	1,977'
Yeso	2,116'
Tubb	3,361'
Abo	4,040'
Wolfcamp	5,230'
Burson	6,378'
Cisco	6,892'
Canyon	7,422'
Strawn	7,884'
Atoka	8,211'
Morrow	8,625'
Chester	8,830'



17 1/2" Hole
13 3/8" 48# K-55 @ 388'

12 1/4" hole
9 5/8" 40# K-55 @ 1,216'

Perforations 7,466' to 7,472' Canyon

CIBP at 8,050' Capped w/ 30' cmt
Perforations 8,125' to 8,134' Strawn

Perforations 8,184' to 8,188' Strawn

Perforations 8,272' to 8,276' Atoka

CIBP at 8,590' capped w/ 30' cmt
Perforations 8,641' to 8,662' Morrow

7 7/8" hole
5 1/2" 17# N-80 @ 8,840'
Cmt Top at 5,970'

HOLE SIZE 17 1/2"

1" To Surf,

CASING SIZE 13 3/8" 48# J-55

TD 388

HOLE SIZE 12 1/4"

Circi

CASING SIZE 9 5/8" 36# J-55

TD 1216

HOLE SIZE 7 7/8"

575 SY.

TDC 5970

CASING SIZE 5 1/2" # K-55

TD 8840

SALT SECTIONS TOP
BASE
RIILP

CAVE / KARST

SPEC. WATER

TDC SURF Surf

INT Surf

PROD

⑥ shoe
woc tag

FORMATIONS Yeso 2116

Abd 4040

Wolfcamp 5230 CISD 7008

Cyn 7425

ST 7697

AT 7991

MR 8625

⑤ shoe-woc tag

④ Gbrieta - woc tag

③ Abd - woc tag

② Wolfcamp / stub.

Cut/Pull 5280 +/-

CMT-5330 - 5180, woc tag 5180 or lower

① CIBP @ 7400' + 35' cmt

Cyn - 7466 - 7472 CIBP 8050 + 3.

ST - 8125 - 8188

AT - 8272 - 8276

CIBP + 15' cmt
8570

MR
8641 -
8662

DVT

PERFORATIONS 8641 - 8662

8125 - 8274

7466 - 7472

BUREAU OF LAND MANAGEMENT
Carlsbad Field Office
620 East Greene Street
Carlsbad, New Mexico 88220
575-234-5972

**Permanent Abandonment of Federal Wells
Conditions of Approval**

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within ninety (90) days from the approval date of this Notice of Intent to Abandon.

If you are unable to plug the well by the 90th day provide this office, prior to the 90th day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.

The rig used for the plugging procedure cannot be released and moved off without the prior approval of the authorized officer. Failure to do so may result in enforcement action.

2. **Notification:** Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Eddy County, call 575-361-2822; Lea County, call 575-393-3612.

3. **Blowout Preventers:** A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The BOP must be installed and maintained as per API and manufacturer recommendations. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.

4. **Mud Requirement:** Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of **brine** water. Minimum nine (9) pounds per gallon.

5. **Cement Requirement:** Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. Any plug that requires a tag will have a minimum WOC time of 4 hours.

In lieu of a cement plug across perforations in a cased hole (not for any other plugs), a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient. **Before pumping or bailing cement on top of CIBP, tag will be required to verify depth. Based on depth, a tag of the cement may be deemed necessary.**

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

6. Dry Hole Marker: All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). **The BLM is to be notified a minimum of 4 hours prior to the wellhead being cut off to verify that cement is to surface in the casing and all annuluses. Wellhead cut off shall commence within ten (10) calendar days of the well being plugged. If the cut off cannot be done by the 10th day, the BLM is to be contacted with justification to receive an extension for completing the cut off.**

The well bore shall then be capped with a 4-inch pipe, 10-feet in length, 4 feet above ground and embedded in cement, unless otherwise noted in COA (requirements will be attached). The following information shall be permanently inscribed on the dry hole marker: well name and number, name of the operator, lease serial number, surveyed location (quarter-quarter section, section, township and range or other authorized survey designation acceptable to the authorized officer such as metes and bounds).

7. Subsequent Plugging Reporting: Within 30 days after plugging work is completed, file one original and three copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. **Show date well was plugged.**

8. Trash: All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration will be required. See attached reclamation procedure.

J. Amos 3/6/11



United States Department of the Interior

BUREAU OF LAND MANAGEMENT

Carlsbad Field Office
620 E. Greene St
Carlsbad, New Mexico 88220-6292
www.blm.gov/nm



In Reply Refer To: 1310

Reclamation Objectives and Procedures

Reclamation Objective: Oil and gas development is one of many uses of the public lands and resources. While development may have a short- or long-term effect on the land, successful reclamation can ensure the effect is not permanent. During the life of the development, all disturbed areas not needed for active support of production operations should undergo "interim" reclamation in order to minimize the environmental impacts of development on other resources and uses. At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and productivity of the land and water are restored.

The long-term objective of final reclamation is to set the course for eventual ecosystem restoration, including the restoration of the natural vegetation community, hydrology, and wildlife habitats. In most cases this means returning the land to a condition approximating or equal to that which existed prior to the disturbance. The final goal of reclamation is to restore the character of the land and water to its pre-disturbance condition. The operator is generally not responsible for achieving full ecological restoration of the site. Instead, the operator must achieve the short-term stability, visual, hydrological, and productivity objectives of the surface management agency and take steps necessary to ensure that long-term objectives will be reached through natural processes.

To achieve these objectives, remove any and all contaminants, scrap/trash, equipment, pipelines and powerlines. Strip and remove caliche, contour the location to blend with the surrounding landscape, re-distribute the native soils, provide erosion control as needed, rip and seed as specified in the original APD COA. This will apply to well pads, facilities, and access roads. Barricade access road at the starting point. If reserve pits have not reclaimed due to salts or other contaminants, submit a plan for approval, as to how you propose to provide adequate restoration of the pit area.

1. The Application for Permit to Drill or Reenter (APD, Form 3160-3), Surface Use Plan of Operations must include adequate measures for stabilization and reclamation of disturbed lands. Oil and Gas operators must plan for reclamation, both interim and final, up front in the APD process as per Onshore Oil and Gas Order No. 1.
2. For wells and/or access roads not having an approved plan, or an inadequate plan for surface reclamation (either interim or final reclamation), the operator must submit a proposal describing the procedures for reclamation. For interim reclamation, the appropriate time for submittal would be when filing the Well Completion or Recompletion Report and Log (Form 3160-4). For final reclamation, the appropriate time for submittal would be when filing the Notice of Intent, or the Subsequent Report of Abandonment, Sundry Notices and Reports on Wells (Form 3160-5). Interim reclamation is to be completed within 6 months of well completion, and final reclamation is to be completed within 6 months of well abandonment.
3. The operator must file a Subsequent Report Plug and Abandonment (Form 3160-5) following the plugging of a well.
4. Previous instruction had you waiting for a BLM specialist to inspect the location and provide you with reclamation requirements. If you have an approved Surface Use Plan of Operation and/or an approved Sundry Notice, you are free to proceed with reclamation as per approved APD. If you have issues or concerns, contact a BLM specialist to assist you. It would be in your interest to have a BLM specialist look at the location and access road prior to the removal of reclamation

equipment to ensure that it meets BLM objectives. Upon conclusion submit a Form 3160-5, Subsequent Report of Reclamation. This will prompt a specialist to inspect the location to verify work was completed as per approved plans.

5. The approved Subsequent Report of Reclamation will be your notice that the native soils, contour and seedbed have been reestablished. If the BLM objectives have not been met the operator will be notified and corrective actions may be required.
6. It is the responsibility of the operator to monitor these locations and/or access roads until such time as the operator feels that the BLM objective has been met. If after two growing seasons the location and/or access roads are not showing the potential for successful revegetation, additional actions may be needed. When you feel the BLM objectives have been met submit a Final Abandonment Notice (FAN), Form 3160-5, stating that all reclamation requirements have been achieved and the location and/or access road is ready for a final abandonment inspection.
7. At this time the BLM specialist will inspect the location and/or access road. If the native soils and contour have been restored, and the revegetation is successful, the FAN will be approved, releasing the operator of any further liability of the location and/or access road. If the location and/or access road have not achieved the objective, you will be notified as to additional work needed or additional time being needed to achieve the objective.

If there are any questions, please feel free to contact any of the following specialists:

Jim Amos
Supervisory Environmental Protection Specialist
575-234-5909, 575-361-2648 (Cell)

Cody Layton
Natural Resource Specialist
575-234-5959

Terry Gregston
Environmental Protection Specialist
575-234-5958

Trishia Bad Bear
Natural Resource Specialist
575-393-3612

Bobby Ballard
Environmental Protection Specialist
575-234-2230

Todd Suter
Surface Protection Specialist
575-234-5987

Randy Rust
Environmental Protection Specialist
575-234-5943

Doug Hoag
Civil Engineering Technician
575-234-5979

Linda Denniston
Environmental Protection Specialist
575-234-5974

Jennifer Van Curen
Environmental Protection Specialist
575-234-5905

Justin Frye
Environmental Protection Specialist
575-234-5922