Submit 3 Copies To Appropriate District	State of New M	exico	Form C-103
Office District 1* Least No. French Dr. Hobbs NM 88240		ural Resources	June 19, 2008
1625 N. French Dr., Hobbs, NM 88240			WELL API NO.
District II 1301 W Grand Ave , Artesia, NM 88210 OIL CONSERVATION DIVISION		30-015-39264	
District III 1220 South St. Francis Dr.			5. Indicate Type of Lease
1000 Rio Brazos Rd., Aztec, NM 87410 District IV Santa Fe, NM 87505		STATE FEE 6. State Oil & Gas Lease No.	
1220 S St Francis Dr., Santa Fe, NM	Santa I of I iii o	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	6. State Off & Gas Lease No.
87505 SUNDRY NOTICES AND REPORTS ON WELLS			7. Lease Name or Unit Agreement Name
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH			_
PROPOSALS.)		Hearse 36 State \checkmark 8. Well Number	
1. Type of Well: Oil Well Gas Well Other		8. Well Number 4H	
2. Name of Operator			9. OGRID Number 229137
COG Operating LLC 3. Address of Operator			10. Pool name or Wildcat
3. Address of Operator 550 W. Texas Ave., Suite 100 Midland, TX 79701		N Seven Rivers; Glorieta-Yeso 97565	
4. Well Location			
	feet from the North	line and <u>1700</u> _	feet from the <u>East</u> line
Section 36	Township 19S Range	25E NM	
	11. Elevation (Show whether Di 3401' G)
<u> 18 de la marca de la companya de l</u>	J401 U	IX.	Rich State of the
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data			
NOTICE OF IN	ITENITION TO:	- CLIB	SEQUENT REPORT OF:
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WOR	
PULL OR ALTER CASING	MULTIPLE COMPL	CASING/CEMEN	T JOB \square
DOWNHOLE COMMINGLE			
→ →	_		
OTHER:		OTHER:	
OTHER:		OTHER:	
OTHER: 2011 COG Opera	ting LLC respectfully request	OTHER:	nove this location to:
OTHER: RECEIVED RECEIVED COG OPERA	ting LLC respectfully request	OTHER:	nove this location to:
OTHER: RECEIVED OCT 19 2011 COG Opera	ting LLC respectfully request	OTHER: ts permission to nection 36, T19S, R	nove this location to:
OTHER: RECEIVED OCI 19 2011 COG OPERA OCI 19 2011 COG OPERA	ting LLC respectfully request SHL: 330' FSL & 1700' FEL, So BHL: 330' FNL & 1700' FEL, So	OTHER: ts permission to n ection 36, T19S, R ection 36, T19S, F	nove this location to: 25E, UL O 25E, UL B
OTHER: RECEIVED OCT 19 2011 COG Opera	ting LLC respectfully request SHL: 330' FSL & 1700' FEL, So BHL: 330' FNL & 1700' FEL, So	OTHER: ts permission to n ection 36, T19S, R ection 36, T19S, R	nove this location to: 225E, UL O 225E, UL B
	inded plat and new Directions	ai i iaii is attaciiet	i for your review.
Allallic	ting LLC respectfully request SHL: 330' FSL & 1700' FEL, So SHL: 330' FNL & 1700' FEL, So ended plat and new Directions ove is requested due to hous	ai i iaii is attaciiet	i for your review.
Allallic	inded plat and new Directions	es being too clos	i for your review.
This location m COG proposes to drill a 12 1/4" hole	Additional Drilling	g Plan Changes: 36# J-55 and cement	e to the original location. to surface. Drill a 8 3/4" hole to 2298' MD and
This location m COG proposes to drill a 12 ¼" hole kick off and drill curve to 3048' ME	Additional Drilling to 825' w/ fresh water, run 9 5/8". Drill a 7 7/8" lateral to new BH.	g Plan Changes: 36# J-55 and cement L @ 2775' TVD 71	e to the original location. to surface. Drill a 8 3/4" hole to 2298' MD and 80' MD. Run 7180' of 7" 26# L-80 x 5 1/2"
This location m COG proposes to drill a 12 ¼" hole kick off and drill curve to 3048' ME 17# L-80 casing to TD with DV/EC	Additional Drilling to 825' w/ fresh water, run 9 5/8". D. Drill a 7 7/8" lateral to new BH P Combo Tool at 2775' and isolati	g Plan Changes: 36# J-55 and cement L @ 2775' TVD 71	e to the original location. to surface. Drill a 8 3/4" hole to 2298' MD and
This location m COG proposes to drill a 12 ¼" hole kick off and drill curve to 3048' ME	Additional Drilling to 825' w/ fresh water, run 9 5/8". D. Drill a 7 7/8" lateral to new BH P Combo Tool at 2775' and isolati	g Plan Changes: 36# J-55 and cement L @ 2775' TVD 71	e to the original location. to surface. Drill a 8 3/4" hole to 2298' MD and 80' MD. Run 7180' of 7" 26# L-80 x 5 1/2"
This location m COG proposes to drill a 12 ¼" hole kick off and drill curve to 3048' ME 17# L-80 casing to TD with DV/EC DV tool and cement from 2775' to s Proposed casing and cement program	Additional Drilling to 825' w/ fresh water, run 9 5/8": D. Drill a 7 7/8" lateral to new BH. P Combo Tool at 2775' and isolatiurface.	p Plan Changes: 36# J-55 and cement L @ 2775' TVD 71 on packers in the ope	e to the original location. to surface. Drill a 8 3/4" hole to 2298' MD and 80' MD. Run 7180' of 7" 26# L-80 x 5 1/2"
This location m COG proposes to drill a 12 ¼" hole kick off and drill curve to 3048' ME 17# L-80 casing to TD with DV/EC DV tool and cement from 2775' to s	Additional Drilling to 825' w/ fresh water, run 9 5/8": D. Drill a 7 7/8" lateral to new BH. P Combo Tool at 2775' and isolatiurface.	p Plan Changes: 36# J-55 and cement L @ 2775' TVD 71 on packers in the ope	to surface. Drill a 8 ¾" hole to 2298' MD and 80' MD. Run 7180' of 7" 26# L-80 x 5 ½" en hole. Set isolation packers and ECP. Open
This location m COG proposes to drill a 12 ¼" hole kick off and drill curve to 3048' ME 17# L-80 casing to TD with DV/EC DV tool and cement from 2775' to s Proposed casing and cement program 300.	Additional Drilling to 825' w/ fresh water, run 9 5/8": D. Drill a 7 7/8" lateral to new BH: P Combo Tool at 2775' and isolatiurface. m: change the casing type from 5.5	p Plan Changes: 36# J-55 and cement L @ 2775' TVD 71 on packers in the ope	to surface. Drill a 8 ¾" hole to 2298' MD and 80' MD. Run 7180' of 7" 26# L-80 x 5 ½" en hole. Set isolation packers and ECP. Open
This location m COG proposes to drill a 12 ¼" hole kick off and drill curve to 3048' ME 17# L-80 casing to TD with DV/EC DV tool and cement from 2775' to s Proposed casing and cement program	Additional Drilling to 825' w/ fresh water, run 9 5/8": D. Drill a 7 7/8" lateral to new BH: P Combo Tool at 2775' and isolatiurface. m: change the casing type from 5.5	p Plan Changes: 36# J-55 and cement L @ 2775' TVD 71 on packers in the ope	to surface. Drill a 8 ¾" hole to 2298' MD and 80' MD. Run 7180' of 7" 26# L-80 x 5 ½" en hole. Set isolation packers and ECP. Open
This location m COG proposes to drill a 12 ¼" hole kick off and drill curve to 3048' ME 17# L-80 casing to TD with DV/EC DV tool and cement from 2775' to s Proposed casing and cement program 300.	Additional Drilling to 825' w/ fresh water, run 9 5/8": D. Drill a 7 7/8" lateral to new BH. P Combo Tool at 2775' and isolatiurface. n: change the casing type from 5.5 cole after we land the curve.	p Plan Changes: 36# J-55 and cement L @ 2775' TVD 71 on packers in the ope	to surface. Drill a 8 ¾" hole to 2298' MD and 80' MD. Run 7180' of 7" 26# L-80 x 5 ½" en hole. Set isolation packers and ECP. Open ge the sacks of cement on the production to
This location m COG proposes to drill a 12 ¼" hole kick off and drill curve to 3048' ME 17# L-80 casing to TD with DV/EC DV tool and cement from 2775' to s Proposed casing and cement program 300. Also, we will downsize to a 7 7/8" h I hereby certify that the information	Additional Drilling to 825' w/ fresh water, run 9 5/8": D. Drill a 7 7/8" lateral to new BH P Combo Tool at 2775' and isolatiurface. In: change the casing type from 5.5 cole after we land the curve.	pes being too closes pelan Changes: 36# J-55 and cement L @ 2775' TVD 71 on packers in the open to 7 x 5.5 and change best of my knowledge	to surface. Drill a 8 ¾" hole to 2298' MD and 80' MD. Run 7180' of 7" 26# L-80 x 5 ½" en hole. Set isolation packers and ECP. Open ge the sacks of cement on the production to e and belief.
This location m COG proposes to drill a 12 ¼" hole kick off and drill curve to 3048' ME 17# L-80 casing to TD with DV/EC DV tool and cement from 2775' to s Proposed casing and cement program 300. Also, we will downsize to a 7 7/8" h I hereby certify that the information SIGNATURE	Additional Drilling to 825' w/ fresh water, run 9 5/8" D. Drill a 7 7/8" lateral to new BH P Combo Tool at 2775' and isolati urface. TITLE TITLE	pes being too clos per Plan Changes: 36# J-55 and cement L @ 2775' TVD 71 on packers in the ope to 7 x 5.5 and chang best of my knowledg	to surface. Drill a 8 3/4" hole to 2298' MD and 80' MD. Run 7180' of 7" 26# L-80 x 5 1/2" en hole. Set isolation packers and ECP. Open ge the sacks of cement on the production to e and belief. DATE 10/17/2011
This location m COG proposes to drill a 12 ¼" hole kick off and drill curve to 3048' ME 17# L-80 casing to TD with DV/EC DV tool and cement from 2775' to s Proposed casing and cement program 300. Also, we will downsize to a 7 7/8" h I hereby certify that the information SIGNATURE Type or print name Kelly J. Ho	Additional Drilling to 825' w/ fresh water, run 9 5/8" D. Drill a 7 7/8" lateral to new BH P Combo Tool at 2775' and isolati urface. TITLE TITLE	pes being too closes pelan Changes: 36# J-55 and cement L @ 2775' TVD 71 on packers in the open to 7 x 5.5 and change best of my knowledge	to surface. Drill a 8 ¾" hole to 2298' MD and 80' MD. Run 7180' of 7" 26# L-80 x 5 ½" en hole. Set isolation packers and ECP. Open ge the sacks of cement on the production to e and belief.
This location m COG proposes to drill a 12 ¼" hole kick off and drill curve to 3048' ME 17# L-80 casing to TD with DV/EC DV tool and cement from 2775' to s Proposed casing and cement program 300. Also, we will downsize to a 7 7/8" h I hereby certify that the information SIGNATURE	Additional Drilling to 825' w/ fresh water, run 9 5/8" D. Drill a 7 7/8" lateral to new BH P Combo Tool at 2775' and isolati urface. TITLE TITLE	pes being too clos per Plan Changes: 36# J-55 and cement L @ 2775' TVD 71 on packers in the ope to 7 x 5.5 and chang best of my knowledg	to surface. Drill a 8 3/4" hole to 2298' MD and 80' MD. Run 7180' of 7" 26# L-80 x 5 1/2" en hole. Set isolation packers and ECP. Open ge the sacks of cement on the production to e and belief. DATE 10/17/2011 PHONE: 432-685-4384
This location m COG proposes to drill a 12 ¼" hole kick off and drill curve to 3048' ME 17# L-80 casing to TD with DV/EC DV tool and cement from 2775' to s Proposed casing and cement program 300. Also, we will downsize to a 7 7/8" h I hereby certify that the information SIGNATURE Type or print name Kelly J. Ho	Additional Drilling to 825' w/ fresh water, run 9 5/8" D. Drill a 7 7/8" lateral to new BH P Combo Tool at 2775' and isolati urface. TITLE TITLE	pes being too clos per Plan Changes: 36# J-55 and cement L @ 2775' TVD 71 on packers in the ope to 7 x 5.5 and chang best of my knowledg	to surface. Drill a 8 3/4" hole to 2298' MD and 80' MD. Run 7180' of 7" 26# L-80 x 5 1/2" en hole. Set isolation packers and ECP. Open ge the sacks of cement on the production to e and belief. DATE 10/17/2011