

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S St Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised August 1, 2011

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-015-39483
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. LG-5803
7. Lease Name or Unit Agreement Name Puppy BPP State Com
8. Well Number 1Y
9. OGRID Number 025575
10. Pool name or Wildcat Empire; Wolfcamp, Northwest

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator
Yates Petroleum Corporation

3. Address of Operator
105 South Fourth Street, Artesia, NM 88210

4. Well Location
Unit Letter D : 390 feet from the North line and 200 feet from the West line
Unit Letter A : 960 feet from the North line and 330 feet from the East line
Section 2 Township 17S Range 27E NMPM Eddy County

11. Elevation (Show whether DR, RKB, RT, GR, etc)
3425'GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND A ☐
CASING/CEMENT JOB ☐

OTHER: Intermediate casing ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

2/3/12 - TD 12-1/4" hole to 1666'.

2/4/12 - Set 9-5/8" 36# K-55 LT&C casing at 1666'. Cemented with 350 sx Class "C" + 4% D20 + 1% S001 + .1125 PPS D130 + 3 PPS D42 + .2% D46 (yld 1.97, wt 12.9). Circulated 24 sx cement. Tested casing to 1200 psi for 30 min. WOC. Reduced hole to 8-3/4" and resumed drilling.

RECEIVED

FEB 17 2012

NMOCD ARTESIA

Spud Date:

9/28/11

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Tina Huerta

TITLE

Regulatory Compliance Supervisor

DATE

February 16, 2012

Type or print name

Tina Huerta

E-mail address:

tinah@yatespetroleum.com

PHONE:

575-748-4168

For State Use Only

APPROVED BY:

R. Dade

TITLE

Dist. H Supervisor

DATE

02/16/2012

Conditions of Approval (if any):