

Submit 3 Copies To Appropriate District
Office
District I
1625 N French Dr , Hobbs, NM 87240
District II
1301 W Grand Ave , Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S St Francis Dr , Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103

June 19, 2008

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)		WELL API NO. 30-015-39505
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>		5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
2. Name of Operator EOG Resources, Inc.		6. State Oil & Gas Lease No.
3. Address of Operator P.O. Box 2267 Midland, TX 79702		7. Lease Name or Unit Agreement Name: Parkway 23 State Com
4. Well Location Unit Letter D : 930 feet from the North line and 220 feet from the West line Section 23 Township 19S Range 29E NMPM County Eddy		8. Well Number 5H
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3310' GR		9. OGRID Number 7377
		10. Pool name or Wildcat Turkey Track; Bone Spring

12. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPLETIONS ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☒

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

2/24/12 Ran 82 jts 8-5/8", 32#, J55 LTC casing set at 3334'.
Cement lead w/ 600 sx Class C, 12.7 ppg, 2.217 yield; tail w/ 200 sx Class C, 14.8 ppg, 1.334 yield. Did not circulate to surface. Notified Randy Dade - NMOCD. Ordered to run temp survey and 1" cement to surface. TOC found at 403' TS.
2/25/12 Pumped 26 bbls Class C, 14.8 ppg to top off. 14 bbls circulated to surface. WOC 30 hrs. Tested casing to 2000 psi for 30 minutes. Test good. Resumed drilling 7-7/8" hole.

Spud Date:

2/19/2012

Rig Release Date:

RECEIVED
MAR -1 2012
NMOCD ARTESIA

Hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Stan Wagner TITLE Regulatory Analyst DATE 2/28/12

Type or print name Stan Wagner E-mail address: _____ PHONE 432-686-3689

For State Use Only

APPROVED BY JC Shepard TITLE Geologist DATE 3/5/2012

Conditions of Approval (if any):