

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S St Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised August 1, 2011

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-005-61765
1. Type of Well: Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other: P & A		5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
2. Name of Operator Yates Petroleum Corporation		6. State Oil & Gas Lease No.
3. Address of Operator 105 South Fourth Street, Artesia, NM 88210		7. Lease Name or Unit Agreement Name Geraldine VG Com
4. Well Location Unit Letter <u>G</u> : <u>1980</u> feet from the <u>North</u> line and <u>1980</u> feet from the <u>East</u> line Section <u>29</u> Township <u>6S</u> Range <u>26E</u> NMPM Chaves County		8. Well Number 1
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3660' GR		9. OGRID Number 025575
		10. Pool name or Wildcat Pecos Slope Abo

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☒
CASING/CEMENT JOB ☐

OTHER: ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

- 4-10-12 MIRU, bled well off for 15 min, pull prod equip, set CIBP at 3668 feet, tag CIBP at 3668 feet, circ well with 64 bbls of MLF, spot 25 SX Class "C" cement on top of CIBP, perf at 1600 feet, RIH w/workstring and pkr to 1200 feet, sqz 40 SX Class "C" Cement into perfs, PUH to 1500 feet.
- 4-11-12 Tag plug at 1483 feet, POOH w/pkr, RIH open ended to 1012 feet to spot 25 SX Class "C" cement, WOC 4 hrs, tag plug at 665 feet, perf at 60 feet, close BOP, attempt to sqz, pressure up to 400 PSI, held, bled well off, RIH to 130 feet, pump 10 SX Class "C" cement to surface.
- 4-17-12 Dig out cellar, cutoff wellhead, install dry hole marker, fill cellar and cut anchors. **WELL IS PLUGGED AND ABANDONED.**

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE SColl TITLE Regulatory Reporting Technician DATE April 18, 2012

Type or print name Sharon Coll E-mail address: scoll@yatespetroleum.com PHONE: 575-748-4507

For State Use Only

APPROVED BY: [Signature] TITLE DATE 4/23/2012

Conditions of Approval (if any):

Approved for plugging of well bore only.
Liability under bond is retained pending receipt
of C-103 (Subsequent Report of Well Plugging)
which may be found at OCD Web Page under
Forms. www.emnrd.state.nm.us/oed.

