Consideration (Assessment Services) Consideration Consid	District I - (575) 393-6161	State of New Mexico	Form C-103
165 N. Froeth P., 180bs, N. 86340 Solid September 120 South St. Francis Dr. Solid September 120 Solid Septe		Energy, Minerals and Natural Resource	Revised August 1, 2011
Signature Color	1625 N. French Dr., Hobbs, NM 88240		i
1. Check Appropriate Box to Indicate Part of Notice, Report or Other Data 1. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data 1. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data 1. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data 1. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data 1. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data 1. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data 1. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data 1. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data 1. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data 1. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data 1. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data 1. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data 1. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data 1. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data 1. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data 1. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data 1. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data 1. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data 1. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data 1. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data 1. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data 1. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data 1. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data 1. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data 1. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data 1. Check Appropria		OIL CONSERVATION DIVISION	
1002 Ris brase Rd, Artes, NM 87410 Sarifa Fe, NM 87505 Sarifa Fe, NM 97505 Sarifa Fe, NM 87505 Sarif			5. Indicate Type of Lease
1208 St. Fancis Dr., Sants Fe, NM 73785 7. Lesse Name or Unit Agrocomoti Name 7. Lesse	· · · · · · · · · · · · · · · · · · ·		
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS PORM POR PROPOSALS TO DRILL OR TO DEPPEN OR PLUG BACK TO A (DO NOT USE THIS PORM POR PROPOSALS TO DRILL OR TO DEPPEN OR PLUG BACK TO A (DO NOT USE THIS PORM POR PROPOSALS TO DRILL OR TO DEPPEN OR PLUG BACK TO A (DO NOT USE THIS PORM POR PROPOSALS TO DRILL OR TO DEPPEN OR PLUG BACK TO A (DO NOT USE THIS PORM POR PROPOSALS TO DRILL OR TO DEPPEN OR PLUG BACK TO A (DO NOT USE THIS PORM POR PROPOSALS TO DRILL OR TO DEPPEN OR PLUG BACK TO A (DO NOT USE THIS PORM POR PROPOSALS TO DRILL OR TO DEPPEN OR PLUG BACK TO A (DO NOT USE THIS PORM POR PROPOSALS TO DRILL OR TO DEPPEN OR PLUG BACK TO A (DO NOT USE THIS PORM POR PROPOSALS TO DRILL OR TO DEPPEN OR PLUG BACK TO A (DO NOT USE THIS PORM POR PROPOSALS TO DRILL OR TO DEPPEN OR PLUG BACK TO A (DO NOT USE THIS PORM POR PROPOSALS TO DRILL OR TO DEPPEN OR PLUG BACK TO A (DO NOT USE THIS PORM POR PROPOSALS TO DRILL OR TO DEPPEN OR PROPOSALS TO DRILL OR TO THE BACK TO A (DO NOT USE THIS PORM POR PROPOSALS TO DRILL OR TO THE BACK TO A (DO NOT USE THIS PORM POR PROPOSALS TO DRILL OR TO THE BACK TO A (DO NOT USE THIS PORM POR PROPOSALS TO DRILL OR TO THE BACK TO A (DO NOT USE THIS PORM POR PROPOSALS TO DRILL OR TO THE BACK TO A (DO NOT USE THIS PORM POR PROPOSALS TO DRILL OR TO THE BACK TO A (DO NOT USE THIS PORM POR PROPOSALS TO DRILL OR TO THE BACK TO A (DO NOT USE THIS PORM POR PROPOSALS TO DRILL OR TO THE BACK TO BA		Santa Fe, INIVI 8/303	6. State Oil & Gas Lease No.
SUNDRY NOTICES AND REPORTS ON WELLS T. Lease Name or Unit Agreement Name DO NOT USE THIS PORM FOR PROPOSALS 10 DIVIDENCE NOT ROBBERT RESERVOR. USE "APPLICATION FOR REMMIT" (ORM C-10) FOR SUCI PALMILLO 14 STATE R. Well Number #1H			
DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEFINENCY FOR MC-101) FOR SUCI PALMILLO 14 STATE		CES AND REPORTS ON WELLS	7. Lease Name or Unit Agreement Name
PROPOSALS) 1. Type of Well: Oil Well			,
1. Type of Well: Oil Well Giss Well Other S. Well Number #1H		CATION FOR PERMIT" (FORM C-101) FOR SUCII	PALMILLO 14 STATE
2. Name of Operator APACHE CORPORATION 9. OGRID Number \$73 3. Address of Operator 303 VETERANS AIRPARK LN #3000 10. Pool name or Wildex! PALMILLO,BONESPRING, SW 4. Weil Location Unit Letter L: 2080 feet from the SOUTH bine and 330 feet from the WEST line Socion 14 Township 19S Range 28E NMPM County EDDY 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON ALTER CASING MULTIPLE COMPL. COMMENCE PRILLING OPNS. ALTERING CASING OF ALTER CASING MULTIPLE COMPL. COMMENCE PRILLING OPNS. PAND A CASING/CEMENT JOB AND ASSING/CEMENT JOB ASSING/CEMENT JOB AND ASSING/CEMENT JOB ASSING/CEMENT JOB AND ASSING/CEMENT JOB ASSING/CEMENT JOB AND ASSING/CEMENT JOB ASSING/CEMENT JOB AND ASSING/CEMENT JOB AND ASSING/CEMENT JOB ASSING/CEMENT JOB AND ASSING/CEMENT JOB ASSING		Gas Well	8. Well Number #1H
3. Address of Operator 303 VETERANS AIRPARK LN #3000 4. Well Location Unit Letter L: 2080 feet from the SOUTH bine and 330 feet from the WEST line Socion 14 Township 198 Range 28E NMPM County EDDY 11. Elevation (Nione whether DR, RKB, RT, GR, etc.) 3454 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO. PERFORM REMEDIAL WORK PLUG AND ABANDON COMMENCE DRILLING OPNS PAND A CASING/CEMENT JOB PAND A CASING/CEMENT JOB PAND A CASING/CEMENT JOB PAND A CASING/CEMENT JOB PAND A PROVED By: 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 7/5/12: After drilling the planned 8-3/4" pilot hole as per the approved APD, Apache requests approval to change the planned setting of 7" 26# casing at 7000" (above the KOP") to a contingency string that will be set in the pilot hole to 1D (9000"), if hole problems are encountered. However, if the pilot hole is stable, a cement kick-off play will be set in open hole from 7800" to 800" (approx. 450sx). Then an 8-3/4" curve will be drilled. If hole problems are concuntered in the curve, then the "2" 26# casing will be set at the bolid of the out of the curve and ecmented back to about 2000" from surface. However, if no hole problems are seen, then a 7-7/8" lateral will be drilled as opposed to the planned 6-1/8" hole. Then 5-1/2" 17# casing will be ran from 17D back to surface and cemented to about 2000" from surface. In the event that the 7" contingency string is set in the well, then a 6-1/8" hole will be drilled after that point and a 4-1/2" 11.6# liner will be set. PECEIVED JUL 05 2012 NMCCD ARTESIA Thereby certify that the information above is true and complete to the best of my knowledge and			9 OGRID Number
4. Well Location Unit Letter L: 2080 feet from the SOUTH line and 330 feet from the WEST line Section 14 Township 19S Range 28E NMPM County EDDY 11. Elevation (Show whether DR, RKB, RT, GR, etc.) 34549 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON COMMENCE DRILLING OPNS PAND A PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMENT JOB DATE 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Atlach wellbore diagram of proposed completion or recompletion. 7/5/12: After drilling the planned 8-3/4" pilot hole as per the approved APD, Apache requests approval to change the planned setting of 7" 26# Casing at 7000" (above the KOP') to a contingency string that will be set in the pilot hole to TD (9000"), if hole problems are encountered. However, if the pilot hole is stable, a cement kick-off plug will be set in open hole from 7800" to 6800" (approx. 450sx). Then an 8-34" curve will be drilled at fiber problems are encountered in the curve, then the "2" 26ff casing will be set at from 61-1/8" hole. Then 5-1/2" 17# casing will be ran from TD back to surface and cemented to about 2000" from surface. In the event that the 7" contingency string is set in the well, then a 6-1/8" hole will be drilled after that point and a 4-1/2" 11.6# liner will be set. RECEIVED In the event that the 7" contingency string is set in the well, then a 6-1/8" hole will be drilled after that point and a 4-1/2" 11.6# liner will be set. RECEIVED In the contingency string is set in the well, then a 6-1/8" hole will be drilled after that point and a 4-1/2" 11.6# liner will be set. PHONE:	2. Name of operator /11/10114		
4. Well Location Unit Letter L: 2080 feet from the SOUTH line and 330 feet from the WEST line Section 14 Township 19S Range 28E NMFM County EDDY 11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3454' 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON TEMPORARILY ABANDON CHANGE PLANS COMMENCE DEPORT OF COMME	3. Address of Operator 303 VETERANS AIRPARK LN #3000		10. Pool name or Wildcat
Unit Letter L: 2080 feet from the SOUTH line and 330 feet from the WEST line Section 14 Township 198 Range 28E NMPM County EDDY 11. Elevation (Show whether DR, RKB, RT, GR, etc.) 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON TEMPORARILY ABANDON CHANGE PLANS SUBSEQUENT REPORT OF: REMEDIAL WORK ALTERING CASING PAND A CASING/CEMENT JOB PAND A PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMENT JOB PAND A OTHER: OTHER: OTHER: OTHER: The Proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion error recompletion or recompletion or recompletion or recompletion of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion of the curve will be drilled as per the approved APD, Apache requests approval to change the planned setting of 7" 26# casing at 7000" (above the KOP") to a contingency string that will be set in the pilot hole to TD (9000"), if hole problems are encountered. However, if the pilot hole is stuble, a cement kick-off plug will be set in the pilot hole to TD (9000"), if hole problems are encountered. However, if the pilot hole is stuble, a cement kick-off plug will be set in open hole from 7800 to 6800" (approx. 450sx). Then an 8-34" in the every that the 7" contingency string is set in the well, then a 6-1/8" hole will be drilled after that point and a 4-1/2" 11.6# liner will be set. RECEIVED INDUCED ARTESIA Thereby certify that the information above is true and complete to the best of my knowledge and belief. SIGNATURE Remedia. The plant hole and description and a 4-1/2" 11.6# liner will be set. PHONE: PHONE: PLANT APPROVED BY: PHONE: P	MIDI	LAND, TX 79705	PALMILLO;BONESPRING, SW
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3454*	4. Well Location		
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING PLUG AND ABANDON CHANGE PLANS COMMENCE BRILLING OPNS. PAND A PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMENT JOB PAND A POWNHOLE COMMINGLE OTHER: OTHER:	Unit Letter L: 2080	_feet from the _SOUTH line and330	feet from theWESTline
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING COMMENCE DRILLING OPNS PAND A PAND A PAND A CASING/CEMENT JOB CASING/CEMENT JOB DOWNHOLE COMMINGLE DOWNHOLE C	Section 14	Township 19S Range 28E	NMPM County EDDY
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING COMMENCE ORILLING OPNS P AND A PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMENT JOB P AND A CASING/CEMENT JOB DOWNHOLE COMMINGLE OTHER: OTHER: OTHER: OTHER: OTHER: Isomorphism or recompletion or		11. Elevation (Show whether DR, RKB, RT, GF	R, etc.)
NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON CHANGE PLANS ALTERING CASING ALTERING CASING COMMENCE DRILLING OPNS. PAND A DULL OR ALTER CASING MULTIPLE COMPL CASING/CEMENT JOB PAND A CASING/CEMENT JOB OTHER: 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 7/5/12: After drilling the planned 8-3/4" pilot hole as per the approved APD, Apache requests approval to change the planned setting of 7" 26# casing at 7000' (above the KOP') to a contingency string that will be set in the pilot hole to TD (9000'), if hole problems are encountered. However, if the pilot hole is stable, a cement kick-off plug will be set in open hole from 7800' to 6800' (approx. 450sx). Then an 8-3/4" curve will be drilled. If hole problems are encountered in the curve, then the 7" 26# casing will be set at the bottom of the curve and comented back to about 2000' from surface. However, if no hole problems are seen, then a 7-7/8" lateral will be drilled as opposed to the planned 6-1/8" hole. Then 5-1/2" 17# casing will be ran from TD back to surface and cemented to about 2000' from surface. In the event that the 7" contingency string is set in the well, then a 6-1/8" hole will be drilled after that point and a 4-1/2" 11.6# liner will be set. Rig Release Date: Rig Release Date: PHONE: TITLE SUPV OF DRILLING SERVICES DATE 7/5/12 Type of print name E-mail address: PHONE: POTE TITLE SUPV OF DRILLING SERVICES DATE 7/5/12 Type of print name E-mail address: PHONE: PATE 1/5/12		3454'	
NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON CHANGE PLANS ALTERING CASING ALTERING CASING COMMENCE DRILLING OPNS. PAND A DULL OR ALTER CASING MULTIPLE COMPL CASING/CEMENT JOB PAND A CASING/CEMENT JOB OTHER: 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 7/5/12: After drilling the planned 8-3/4" pilot hole as per the approved APD, Apache requests approval to change the planned setting of 7" 26# casing at 7000' (above the KOP') to a contingency string that will be set in the pilot hole to TD (9000'), if hole problems are encountered. However, if the pilot hole is stable, a cement kick-off plug will be set in open hole from 7800' to 6800' (approx. 450sx). Then an 8-3/4" curve will be drilled. If hole problems are encountered in the curve, then the 7" 26# casing will be set at the bottom of the curve and comented back to about 2000' from surface. However, if no hole problems are seen, then a 7-7/8" lateral will be drilled as opposed to the planned 6-1/8" hole. Then 5-1/2" 17# casing will be ran from TD back to surface and cemented to about 2000' from surface. In the event that the 7" contingency string is set in the well, then a 6-1/8" hole will be drilled after that point and a 4-1/2" 11.6# liner will be set. Rig Release Date: Rig Release Date: PHONE: TITLE SUPV OF DRILLING SERVICES DATE 7/5/12 Type of print name E-mail address: PHONE: POTE TITLE SUPV OF DRILLING SERVICES DATE 7/5/12 Type of print name E-mail address: PHONE: PATE 1/5/12			
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PAND A PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMENT JOB PAND A PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMENT JOB PAND A PAND A DOWNHOLE COMMINGLE OTHER: OTHER: OTHER: OTHER: The pull of Starting any proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 7/5/12: After drilling the planned 8-3/4" pilot hole as per the approved APD, Apache requests approval to change the planned setting of 7" 26# casing at 7000" (above the KOP") to a contingency string that will be set in open hole from 7800" to 6800" (approx. 450sx). Then an 8-3/4" curve will be drilled. If hole problems are encountered in the curve, then the 7" 26# casing will be read to about 2000" from surface. However, if no hole problems are seen, then a 7-7/8" lateral will be drilled as opposed to the planned 6-1/8" hole. Then 5-1/2" 17# casing will be ran from TD back to surface and cemented to about 2000" from surface. In the event that the 7" contingency string is set in the well, then a 6-1/8" hole will be drilled after that point and a 4-1/2" 11.6# liner will be set. RECEIVED JUL 05-2012 NMOCD ARTESIA TITLE SUPV OF DRILLING SERVICES DATE 7/5/12 Type or print name E-mail address: PHONE: PHONE: PHONE: PHONE: PHONE: PHONE: PHONE: PHONE: PHONE: DATE 1/5/12	12. Check A	Appropriate Box to Indicate Nature of No	tice, Report or Other Data
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PAND A PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMENT JOB PAND A PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMENT JOB PAND A PAND A DOWNHOLE COMMINGLE OTHER: OTHER: OTHER: OTHER: The pull of Starting any proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 7/5/12: After drilling the planned 8-3/4" pilot hole as per the approved APD, Apache requests approval to change the planned setting of 7" 26# casing at 7000" (above the KOP") to a contingency string that will be set in open hole from 7800" to 6800" (approx. 450sx). Then an 8-3/4" curve will be drilled. If hole problems are encountered in the curve, then the 7" 26# casing will be read to about 2000" from surface. However, if no hole problems are seen, then a 7-7/8" lateral will be drilled as opposed to the planned 6-1/8" hole. Then 5-1/2" 17# casing will be ran from TD back to surface and cemented to about 2000" from surface. In the event that the 7" contingency string is set in the well, then a 6-1/8" hole will be drilled after that point and a 4-1/2" 11.6# liner will be set. RECEIVED JUL 05-2012 NMOCD ARTESIA TITLE SUPV OF DRILLING SERVICES DATE 7/5/12 Type or print name E-mail address: PHONE: PHONE: PHONE: PHONE: PHONE: PHONE: PHONE: PHONE: PHONE: DATE 1/5/12	NOTICE OF IN	TENTION TO:	SUBSEQUENT REPORT OF
TEMPORARILY ABANDON CHANGE PLANS CASING MULTIPLE COMPL CASING/CEMENT JOB DOWNHOLE COMMINGLE MULTIPLE COMPL CASING/CEMENT JOB CASING/CEMENT JOB COMMENCE COMMINGLE COMMINGLE COMPLET CASING COMMENCE COMMINGLE COMPLET CASING CASING/CEMENT JOB CASING/			
PULL OR ALTER CASING DOWNHOLE COMMINGLE OTHER: OTHE		1	
DOWNHOLE COMMINGLE OTHER: OTHER: 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 7/5/12: After drilling the planned 8-3/4" pilot hole as per the approved APD, Apache requests approval to change the planned setting of 7" 26# casing at 7000' (above the KOP') to a contingency string that will be set in the pilot hole to TD (9000'), if hole problems are encountered. However, if the pilot hole is stable, a cement kick-off plug will be set in open hole from 7800' to 6800' (approx. 450sx). Then an 8-3/4" curve will be drilled. If hole problems are encountered in the curve, then the 7" 26# casing will be set at the bottom of the curve and cemented back to about 2000' from surface. However, if no hole problems are seen, then a 7-7/8" lateral will be drilled as opposed to the planned 6-1/8" hole. Then 5-1/2" 17# casing will be ran from TD back to surface and cemented to about 2000' from surface. In the event that the 7" contingency string is set in the well, then a 6-1/8" hole will be drilled after that point and a 4-1/2" 11.6# liner will be set. Rig Release Date: Rig Release Date: Rig Release Date: Rig Release Date: PHONE: TITLE SUPV OF DRILLING SERVICES DATE 7/5/12 Type or print name E-mail address: PHONE:		1	
OTHER: 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 7/5/12: After drilling the planned 8-3/4" pilot hole as per the approved APD, Apache requests approval to change the planned setting of 7" 26# casing at 7000" (above the KOP") to a contingency string that will be set in the pilot hole to TD (9000"), if hole problems are encountered. However, if the pilot hole is stable, a cement kick-off plug will be set in othe photo from 7800" to 6800" (approx. 450sx). Then an 8-3/4" curve will be drilled. If hole problems are encountered in the curve, then the 7" 26# casing will be set at the bottom of the curve and cemented back to about 2000" from surface. However, if no hole problems are seen, then a 7-7/8" lateral will be drilled as opposed to the planned 6-1/8" hole. Then 5-1/2" 17# casing will be ran from TD back to surface and cemented to about 2000' from surface. In the event that the 7" contingency string is set in the well, then a 6-1/8" hole will be drilled after that point and a 4-1/2" 11.6# liner will be set. Rig Release Date: Rig Release Date:			
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 7/5/12: After drilling the planned 8-3/4" pilot hole as per the approved APD, Apache requests approval to change the planned setting of 7" 26# casing at 7000' (above the KOP') to a contingency string that will be set in the pilot hole to TD (9000'), if hole problems are encountered. However, if the pilot hole is stable, a cement kick-off plug will be set in open hole from 7800' to 6800' (approx. 450sx). Then an 8-3/4" curve will be drilled. If hole problems are encountered in the curve, then the 7" 26# casing will be set at the bottom of the curve and cemented back to about 2000' from surface. However, if no hole problems are seen, then a 7-7/8" lateral will be drilled as opposed to the planned 6-1/8" hole. Then 5-1/2" 17# casing will be ran from TD back to surface and cemented to about 2000' from surface. In the event that the 7" contingency string is set in the well, then a 6-1/8" hole will be drilled after that point and a 4-1/2" 11.6# liner will be set. RECEIVED JUL 05-2012 NMCCD ARTESIA Thereby certify that the information above is true and complete to the best of my knowledge and belief. SIGNATURE SIGNATURE TITLE SUPV OF DRILLING SERVICES DATE 7/5/12 Type or print name E-mail address: PHONE: PHO			
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 7/5/12: After drilling the planned 8-3/4" pilot hole as per the approved APD, Apache requests approval to change the planned setting of 7" 26# casing at 7000' (above the KOP') to a contingency string that will be set in the pilot hole to TD (9000'), if hole problems are encountered. However, if the pilot hole is stable, a cement kick-off plug will be set in open hole from 7800' to 6800' (approx. 450sx). Then an 8-3/4" curve will be drilled. If hole problems are encountered in the curve, then the 7" 26# casing will be set at the bottom of the curve and cemented back to about 2000' from surface. However, if no hole problems are seen, then a 7-7/8" lateral will be drilled as opposed to the planned 6-1/8" hole. Then 5-1/2" 17# casing will be ran from TD back to surface and cemented to about 2000' from surface. In the event that the 7" contingency string is set in the well, then a 6-1/8" hole will be drilled after that point and a 4-1/2" 11.6# liner will be set. RECEIVED In the event that the information above is true and complete to the best of my knowledge and belief. RECEIVED In the planned B-1/2" 11.6# liner will be set. In the event that the information above is true and complete to the best of my knowledge and belief. SIGNATURE Suproceed B-1/2" In the suproc			
proposed completion or recompletion. 7/5/12: 7/5/12: 7/5/12: 7/5/12: 1			
After drilling the planned 8-3/4" pilot hole as per the approved APD, Apache requests approval to change the planned setting of 7" 26# casing at 7000' (above the KOP') to a contingency string that will be set in the pilot hole to TD (9000'), if hole problems are encountered. However, if the pilot hole is stable, a cement kick-off plug will be set in open hole from 7800' to 6800' (approx. 450sx). Then an 8-3/4" curve will be drilled. If hole problems are encountered in the curve, then the 7" 26# casing will be set at the bottom of the curve and cemented back to about 2000' from surface. However, if no hole problems are seen, then a 7-7/8" lateral will be drilled as opposed to the planned 6-1/8" hole. Then 5-1/2" 17# casing will be ran from TD back to surface and cemented to about 2000' from surface. In the event that the 7" contingency string is set in the well, then a 6-1/8" hole will be drilled after that point and a 4-1/2" 11.6# liner will be set. RECEIVED IJL 05 2012 NMOCD ARTESIA			le Completions: Attach wellbore diagram of
After drilling the planned 8-3/4" pilot hole as per the approved APD, Apache requests approval to change the planned setting of 7" 26# casing at 7000" (above the KOP") to a contingency string that will be set in the pilot hole to TD (9000"), if hole problems are encountered. However, if the pilot hole is stable, a cement kick-off plug will be set in open hole from 7800" to 6800" (approx. 450sx). Then an 8-3/4" curve will be drilled. If hole problems are encountered in the curve, then the 7" 26# casing will be set at the bottom of the curve and cemented back to about 2000' from surface. However, if no hole problems are seen, then a 7-7/8" lateral will be drilled as opposed to the planned 6-1/8" hole. Then 5-1/2" 17# casing will be ran from TD back to surface and cemented to about 2000' from surface. In the event that the 7" contingency string is set in the well, then a 6-1/8" hole will be drilled after that point and a 4-1/2" 11.6# liner will be set. RECEIVED III		ansulation .	
casing at 7000' (above the KOP') to a contingency string that will be set in the pilot hole to TD (9000'), if hole problems are encountered. However, if the pilot hole is stable, a cement kick-off plug will be set in open hole from 7800' to 6800' (approx. 450sx). Then an 8-3/4" curve will be drilled. If hole problems are encountered in the curve, then the 7" 26# casing will be set at the bottom of the curve and cemented back to about 2000' from surface. However, if no hole problems are seen, then a 7-7/8" lateral will be drilled as opposed to the planned 6-1/8" hole. Then 5-1/2" 17# casing will be ran from TD back to surface and cemented to about 2000' from surface. In the event that the 7" contingency string is set in the well, then a 6-1/8" hole will be drilled after that point and a 4-1/2" 11.6# liner will be set. RECEIVED UL 05-2012 NMCCD ARTESIA PRECEIVED PRILLING SERVICES DATE 7/5/12 Type or print name E-mail address: PHONE: PHONE: TITLE SUPV OF DRILLING SERVICES DATE 7/5/12 APPROVED BY: TITLE SUPV OF DATE DATE 7/5/12 TITLE TI		ompicuon.	
However, if the pilot hole is stable, a cement kick-off plug will be set in open hole from 7800' to 6800' (approx. 450sx). Then an 8-3/4" curve will be drilled. If hole problems are encountered in the curve, then the 7" 26# casing will be set at the bottom of the curve and cemented back to about 2000' from surface. However, if no hole problems are seen, then a 7-7/8" lateral will be drilled as opposed to the planned 6-1/8" hole. Then 5-1/2" 17# casing will be ran from TD back to surface and cemented to about 2000' from surface. In the event that the 7" contingency string is set in the well, then a 6-1/8" hole will be drilled after that point and a 4-1/2" 11.6# liner will be set. RECEIVED UL 05 2012 NMOCD ARTESIA	7/5/12:	•	
curve will be drilled. If hole problems are encountered in the curve, then the 7" 26# casing will be set at the bottom of the curve and comented back to about 2000' from surface. However, if no hole problems are seen, then a 7-7/8" lateral will be drilled as opposed to the planned 6-1/8" hole. Then 5-1/2" 17# casing will be ran from TD back to surface and cemented to about 2000' from surface. In the event that the 7" contingency string is set in the well, then a 6-1/8" hole will be drilled after that point and a 4-1/2" 11.6# liner will be set. RECEIVED In the event that the information above is true and complete to the best of my knowledge and belief. Signature Signature Signature Signature E-mail address: PHONE: PHONE: PHONE: TITLE SUPV OF DRILLING SERVICES DATE 7/5/12 DATE 75/12	7/5/12: After drilling the planned 8-3/4" pilo	ot hole as per the approved APD, Apache requests	
comented back to about 2000' from surface. However, if no hole problems are seen, then a 7-7/8" lateral will be drilled as opposed to the planned 6-1/8" hole. Then 5-1/2" 17# casing will be ran from TD back to surface and cemented to about 2000' from surface. In the event that the 7" contingency string is set in the well, then a 6-1/8" hole will be drilled after that point and a 4-1/2" 11.6# liner will be set. RECEIVED JUL 05 2012 NMOCD ARTESIA I hereby certify that the information above is true and complete to the best of my knowledge and belief. SIGNATURE TITLE SUPV OF DRILLING SERVICES DATE 7/5/12 Type or print name For State Use Only APPROVED BY: TITLE TITLE TITLE TITLE TITLE DATE TITLE DATE TITLE DATE DATE DATE	7/5/12: After drilling the planned 8-3/4" pilocasing at 7000' (above the KOP') to	ot hole as per the approved APD, Apache requests a contingency string that will be set in the pilot h	ole to TD (9000'), if hole problems are encountered.
planned 6-1/8" hole. Then 5-1/2" 17# casing will be ran from TD back to surface and cemented to about 2000' from surface. In the event that the 7" contingency string is set in the well, then a 6-1/8" hole will be drilled after that point and a 4-1/2" 11.6# liner will be set. RECEIVED Rig Release Date: Rig Release Date: NMOCD ARTESIA I hereby certify that the information above is true and complete to the best of my knowledge and belief. SIGNATURE SIGNATURE TITLE SUPV OF DRILLING SERVICES DATE 7/5/12 Type or print name For State Use Only APPROVED BY: TITLE	7/5/12: After drilling the planned 8-3/4" pilo casing at 7000' (above the KOP') to However, if the pilot hole is stable, a	ot hole as per the approved APD, Apache requests a contingency string that will be set in the pilot he coment kick-off plug will be set in open hole fro	ole to TD (9000'), if hole problems are encountered. in 7800' to 6800' (approx. 450sx). Then an 8-3/4"
In the event that the 7" contingency string is set in the well, then a 6-1/8" hole will be drilled after that point and a 4-1/2" 11.6# liner will be set. RECEIVED	7/5/12: After drilling the planned 8-3/4" pilo casing at 7000' (above the KOP') to However, if the pilot hole is stable, a curve will be drilled. If hole problem	ot hole as per the approved APD, Apache requests a contingency string that will be set in the pilot has coment kick-off plug will be set in open hole from are encountered in the curve, then the 7" 26# c	ole to TD (9000'), if hole problems are encountered. on 7800' to 6800' (approx. 450sx). Then an 8-3/4" casing will be set at the bottom of the curve and
Spud Date: Rig Release Date: Rig Release Date: NMOCD ARTESIA I hereby certify that the information above is true and complete to the best of my knowledge and belief. SIGNATURE SIGNATURE TITLE SUPV OF DRILLING SERVICES DATE 7/5/12 Type or print name For State Use Only APPROVED BY: TITLE TITLE TITLE TYPE TITLE TI	7/5/12: After drilling the planned 8-3/4" pilo casing at 7000' (above the KOP') to However, if the pilot hole is stable, a curve will be drilled. If hole problem comented back to about 2000' from s	ot hole as per the approved APD, Apache requests a contingency string that will be set in the pilot he cement kick-off plug will be set in open hole from are encountered in the curve, then the 7" 26# c surface. However, if no hole problems are seen, t	ole to TD (9000'), if hole problems are encountered. on 7800' to 6800' (approx. 450sx). Then an 8-3/4" casing will be set at the bottom of the curve and then a 7-7/8" lateral will be drilled as opposed to the
Spud Date: Rig Release Date: Rig Release Date: NMCCD ARTESIA I hereby certify that the information above is true and complete to the best of my knowledge and belief. SIGNATURE SIGNATURE TITLE SUPV OF DRILLING SERVICES DATE 7/5/12 Type or print name E-mail address: PHONE: APPROVED BY: TITLE TITLE TITLE TITLE TO AUST DATE	7/5/12: After drilling the planned 8-3/4" pilo casing at 7000' (above the KOP') to However, if the pilot hole is stable, a curve will be drilled. If hole problem cemented back to about 2000' from a planned 6-1/8" hole. Then 5-1/2" 17	ot hole as per the approved APD, Apache requests a contingency string that will be set in the pilot had coment kick-off plug will be set in open hole from are encountered in the curve, then the 7" 26# courface. However, if no hole problems are seen, the casing will be ran from TD back to surface and	ole to TD (9000'), if hole problems are encountered. on 7800' to 6800' (approx. 450sx). Then an 8-3/4" asing will be set at the bottom of the curve and then a 7-7/8" lateral will be drilled as opposed to the lemented to about 2000' from surface.
Spud Date: Rig Release Date: NMCCD ARTESIA I hereby certify that the information above is true and complete to the best of my knowledge and belief. SIGNATURE TITLE SUPV OF DRILLING SERVICES DATE 7/5/12 Type or print name For State Use Only APPROVED BY: TITLE FOOLOGIST DATE DATE	7/5/12: After drilling the planned 8-3/4" pilo casing at 7000' (above the KOP') to However, if the pilot hole is stable, a curve will be drilled. If hole problem comented back to about 2000' from a planned 6-1/8" hole. Then 5-1/2" 17 In the event that the 7" contingency as	ot hole as per the approved APD, Apache requests a contingency string that will be set in the pilot had coment kick-off plug will be set in open hole from are encountered in the curve, then the 7" 26# courface. However, if no hole problems are seen, the casing will be ran from TD back to surface and	ole to TD (9000'), if hole problems are encountered. on 7800' to 6800' (approx. 450sx). Then an 8-3/4" asing will be set at the bottom of the curve and then a 7-7/8" lateral will be drilled as opposed to the lemented to about 2000' from surface.
Spud Date: Rig Release Date: NMCCD ARTESIA I hereby certify that the information above is true and complete to the best of my knowledge and belief. SIGNATURE TITLE SUPV OF DRILLING SERVICES DATE 7/5/12 Type or print name For State Use Only APPROVED BY: TITLE	7/5/12: After drilling the planned 8-3/4" pilo casing at 7000' (above the KOP') to However, if the pilot hole is stable, a curve will be drilled. If hole problem comented back to about 2000' from a planned 6-1/8" hole. Then 5-1/2" 17 In the event that the 7" contingency as	ot hole as per the approved APD, Apache requests a contingency string that will be set in the pilot had coment kick-off plug will be set in open hole from are encountered in the curve, then the 7" 26# courface. However, if no hole problems are seen, the casing will be ran from TD back to surface and	ole to TD (9000'), if hole problems are encountered. on 7800' to 6800' (approx. 450sx). Then an 8-3/4' asing will be set at the bottom of the curve and then a 7-7/8" lateral will be drilled as opposed to the lemented to about 2000' from surface. drilled after that point and a 4-1/2" 11.6# liner will
Spud Date: Rig Release Date: NMCCD ARTESIA I hereby certify that the information above is true and complete to the best of my knowledge and belief. SIGNATURE TITLE SUPV OF DRILLING SERVICES DATE 7/5/12 Type or print name For State Use Only APPROVED BY: TITLE	7/5/12: After drilling the planned 8-3/4" pilo casing at 7000' (above the KOP') to However, if the pilot hole is stable, a curve will be drilled. If hole problem comented back to about 2000' from a planned 6-1/8" hole. Then 5-1/2" 17 In the event that the 7" contingency as	ot hole as per the approved APD, Apache requests a contingency string that will be set in the pilot had coment kick-off plug will be set in open hole from are encountered in the curve, then the 7" 26# courface. However, if no hole problems are seen, the casing will be ran from TD back to surface and	ole to TD (9000'), if hole problems are encountered. on 7800' to 6800' (approx. 450sx). Then an 8-3/4' asing will be set at the bottom of the curve and then a 7-7/8" lateral will be drilled as opposed to the lemented to about 2000' from surface. drilled after that point and a 4-1/2" 11.6# liner will
I hereby certify that the information above is true and complete to the best of my knowledge and belief. SIGNATURE	7/5/12: After drilling the planned 8-3/4" pilo casing at 7000' (above the KOP') to However, if the pilot hole is stable, a curve will be drilled. If hole problem comented back to about 2000' from a planned 6-1/8" hole. Then 5-1/2" 17 In the event that the 7" contingency as	ot hole as per the approved APD, Apache requests a contingency string that will be set in the pilot had coment kick-off plug will be set in open hole from are encountered in the curve, then the 7" 26# courface. However, if no hole problems are seen, the casing will be ran from TD back to surface and	ole to TD (9000'), if hole problems are encountered. In 7800' to 6800' (approx. 450sx). Then an 8-3/4" easing will be set at the bottom of the curve and then a 7-7/8" lateral will be drilled as opposed to the cemented to about 2000' from surface. drilled after that point and a 4-1/2" 11.6# liner will
I hereby certify that the information above is true and complete to the best of my knowledge and belief. SIGNATURE	7/5/12: After drilling the planned 8-3/4" pilo casing at 7000' (above the KOP') to However, if the pilot hole is stable, a curve will be drilled. If hole problem comented back to about 2000' from a planned 6-1/8" hole. Then 5-1/2" 17 In the event that the 7" contingency above.	of hole as per the approved APD, Apache requests a contingency string that will be set in the pilot has cement kick-off plug will be set in open hole from as are encountered in the curve, then the 7" 26# consurface. However, if no hole problems are seen, to the casing will be ran from TD back to surface and string is set in the well, then a 6-1/8" hole will be	ole to TD (9000'), if hole problems are encountered. In 7800' to 6800' (approx. 450sx). Then an 8-3/4" easing will be set at the bottom of the curve and then a 7-7/8" lateral will be drilled as opposed to the cemented to about 2000' from surface. drilled after that point and a 4-1/2" 11.6# liner will
SIGNATURE SUPV OF DRILLING SERVICES DATE 7/5/12 Type or print name E-mail address: PHONE: For State Use Only APPROVED BY: TITLE FOO/OUST DATE 7/5/12	7/5/12: After drilling the planned 8-3/4" pilo casing at 7000' (above the KOP') to However, if the pilot hole is stable, a curve will be drilled. If hole problem comented back to about 2000' from a planned 6-1/8" hole. Then 5-1/2" 17 In the event that the 7" contingency above.	of hole as per the approved APD, Apache requests a contingency string that will be set in the pilot has cement kick-off plug will be set in open hole from as are encountered in the curve, then the 7" 26# consurface. However, if no hole problems are seen, to the casing will be ran from TD back to surface and string is set in the well, then a 6-1/8" hole will be	ole to TD (9000'), if hole problems are encountered. on 7800' to 6800' (approx. 450sx). Then an 8-3/4' casing will be set at the bottom of the curve and then a 7-7/8" lateral will be drilled as opposed to the cemented to about 2000' from surface. drilled after that point and a 4-1/2" 11.6# liner will RECEIVED JUL 05 2012
SIGNATURE SUPV OF DRILLING SERVICES DATE 7/5/12 Type or print name E-mail address: PHONE: For State Use Only APPROVED BY: TITLE FOO/OUST DATE 7/5/12	7/5/12: After drilling the planned 8-3/4" pilo casing at 7000' (above the KOP') to However, if the pilot hole is stable, a curve will be drilled. If hole problem comented back to about 2000' from a planned 6-1/8" hole. Then 5-1/2" 17 In the event that the 7" contingency above.	of hole as per the approved APD, Apache requests a contingency string that will be set in the pilot has cement kick-off plug will be set in open hole from as are encountered in the curve, then the 7" 26# consurface. However, if no hole problems are seen, to the casing will be ran from TD back to surface and string is set in the well, then a 6-1/8" hole will be	ole to TD (9000'), if hole problems are encountered. on 7800' to 6800' (approx. 450sx). Then an 8-3/4' casing will be set at the bottom of the curve and then a 7-7/8" lateral will be drilled as opposed to the cemented to about 2000' from surface. drilled after that point and a 4-1/2" 11.6# liner will RECEIVED JUL 05 2012
Type or print name For State Use Only APPROVED BY: E-mail address: PHONE: DATE DATE	7/5/12: After drilling the planned 8-3/4" pilo casing at 7000' (above the KOP') to However, if the pilot hole is stable, a curve will be drilled. If hole problem comented back to about 2000' from a planned 6-1/8" hole. Then 5-1/2" 17 In the event that the 7" contingency abe set. Spud Date:	ot hole as per the approved APD, Apache requests a contingency string that will be set in the pilot has cement kick-off plug will be set in open hole from an are encountered in the curve, then the 7" 26# consurface. However, if no hole problems are seen, the casing will be ran from TD back to surface and string is set in the well, then a 6-1/8" hole will be Rig Release Date:	ole to TD (9000'), if hole problems are encountered. on 7800' to 6800' (approx. 450sx). Then an 8-3/4'' casing will be set at the bottom of the curve and then a 7-7/8" lateral will be drilled as opposed to the cemented to about 2000' from surface. drilled after that point and a 4-1/2" 11.6# liner will RECEIVED JUL 05 2012 NMOCD ARTESIA
Type or print name For State Use Only APPROVED BY: E-mail address: PHONE: DATE DATE	7/5/12: After drilling the planned 8-3/4" pilo casing at 7000' (above the KOP') to However, if the pilot hole is stable, a curve will be drilled. If hole problem comented back to about 2000' from a planned 6-1/8" hole. Then 5-1/2" 17 In the event that the 7" contingency abe set. Spud Date:	ot hole as per the approved APD, Apache requests a contingency string that will be set in the pilot has cement kick-off plug will be set in open hole from an are encountered in the curve, then the 7" 26# consurface. However, if no hole problems are seen, the casing will be ran from TD back to surface and string is set in the well, then a 6-1/8" hole will be Rig Release Date:	ole to TD (9000'), if hole problems are encountered. on 7800' to 6800' (approx. 450sx). Then an 8-3/4'' casing will be set at the bottom of the curve and then a 7-7/8" lateral will be drilled as opposed to the cemented to about 2000' from surface. drilled after that point and a 4-1/2" 11.6# liner will RECEIVED JUL 05 2012 NMOCD ARTESIA
APPROVED BY: APPROVED BY: TITLE FOR State Use Only DATE TELE TO DO COST DATE TO DE TO STATE USE ONLY DATE TO ST	7/5/12: After drilling the planned 8-3/4" pilo casing at 7000' (above the KOP') to However, if the pilot hole is stable, a curve will be drilled. If hole problem cemented back to about 2000' from a planned 6-1/8" hole. Then 5-1/2" 17 In the event that the 7" contingency abe set. Spud Date:	ot hole as per the approved APD, Apache requests a contingency string that will be set in the pilot he cement kick-off plug will be set in open hole from a cencountered in the curve, then the 7" 26# consurface. However, if no hole problems are seen, the casing will be ran from TD back to surface and string is set in the well, then a 6-1/8" hole will be Rig Release Date: Rig Release Date:	ole to TD (9000'), if hole problems are encountered. on 7800' to 6800' (approx. 450sx). Then an 8-3/4' casing will be set at the bottom of the curve and then a 7-7/8" lateral will be drilled as opposed to the cemented to about 2000' from surface. drilled after that point and a 4-1/2" 11.6# liner will RECEIVED JUL 05 2012 NMOCD ARTESIA wledge and belief.
APPROVED BY: APPROVED BY: TITLE FOR State Use Only DATE TELE TO DO COST DATE TO DE TO STATE USE ONLY DATE TO ST	7/5/12: After drilling the planned 8-3/4" pilo casing at 7000' (above the KOP') to However, if the pilot hole is stable, a curve will be drilled. If hole problem cemented back to about 2000' from a planned 6-1/8" hole. Then 5-1/2" 17 In the event that the 7" contingency abe set. Spud Date:	ot hole as per the approved APD, Apache requests a contingency string that will be set in the pilot he cement kick-off plug will be set in open hole from a cencountered in the curve, then the 7" 26# consurface. However, if no hole problems are seen, the casing will be ran from TD back to surface and string is set in the well, then a 6-1/8" hole will be Rig Release Date: Rig Release Date:	ole to TD (9000'), if hole problems are encountered. on 7800' to 6800' (approx. 450sx). Then an 8-3/4' casing will be set at the bottom of the curve and then a 7-7/8" lateral will be drilled as opposed to the cemented to about 2000' from surface. drilled after that point and a 4-1/2" 11.6# liner will RECEIVED JUL 05 2012 NMOCD ARTESIA wledge and belief.
	7/5/12: After drilling the planned 8-3/4" pilo casing at 7000' (above the KOP') to However, if the pilot hole is stable, a curve will be drilled. If hole problem comented back to about 2000' from a planned 6-1/8" hole. Then 5-1/2" 17 In the event that the 7" contingency is be set. Spud Date:	ot hole as per the approved APD, Apache requests a contingency string that will be set in the pilot has cement kick-off plug will be set in open hole from as are encountered in the curve, then the 7" 26# consurface. However, if no hole problems are seen, to the casing will be ran from TD back to surface and string is set in the well, then a 6-1/8" hole will be Rig Release Date: Rig Release Date: TITLE_SUPV OF DRIL	ole to TD (9000'), if hole problems are encountered. In 7800' to 6800' (approx. 450sx). Then an 8-3/4" reasing will be set at the bottom of the curve and then a 7-7/8" lateral will be drilled as opposed to the cemented to about 2000' from surface. drilled after that point and a 4-1/2" 11.6# liner will RECEIVED JUL 05 2012 NMCCD ARTESIA wledge and belief. LING SERVICES DATE 7/5/12
	7/5/12: After drilling the planned 8-3/4" pilo casing at 7000' (above the KOP') to However, if the pilot hole is stable, a curve will be drilled. If hole problem cemented back to about 2000' from a planned 6-1/8" hole. Then 5-1/2" 17 In the event that the 7" contingency abe set. Spud Date: I hereby certify that the information of SIGNATURE Type or print name	ot hole as per the approved APD, Apache requests a contingency string that will be set in the pilot has cement kick-off plug will be set in open hole from as are encountered in the curve, then the 7" 26# consurface. However, if no hole problems are seen, to the casing will be ran from TD back to surface and string is set in the well, then a 6-1/8" hole will be Rig Release Date: Rig Release Date: TITLE_SUPV OF DRIL	ole to TD (9000'), if hole problems are encountered. In 7800' to 6800' (approx. 450sx). Then an 8-3/4" reasing will be set at the bottom of the curve and then a 7-7/8" lateral will be drilled as opposed to the cemented to about 2000' from surface. drilled after that point and a 4-1/2" 11.6# liner will RECEIVED JUL 05 2012 NMCCD ARTESIA wledge and belief. LING SERVICES DATE 7/5/12
	7/5/12: After drilling the planned 8-3/4" pilo casing at 7000' (above the KOP') to However, if the pilot hole is stable, a curve will be drilled. If hole problem cemented back to about 2000' from a planned 6-1/8" hole. Then 5-1/2" 17 In the event that the 7" contingency abe set. Spud Date: I hereby certify that the information of SIGNATURE Type or print name For State Use Only	ot hole as per the approved APD, Apache requests a contingency string that will be set in the pilot has cement kick-off plug will be set in open hole from a concountered in the curve, then the 7" 26# consurface. However, if no hole problems are seen, to the casing will be ran from TD back to surface and string is set in the well, then a 6-1/8" hole will be ran from TD back to surface and string is set in the well, then a 6-1/8" hole will be above is true and complete to the best of my known that the surface and the string is set in the well and the string is set in the well. TITLE SUPV OF DRILE E-mail address:	ole to TD (9000'), if hole problems are encountered. In 7800' to 6800' (approx. 450sx). Then an 8-3/4" reasing will be set at the bottom of the curve and then a 7-7/8" lateral will be drilled as opposed to the cemented to about 2000' from surface. drilled after that point and a 4-1/2" 11.6# liner will RECEIVED JUL 05 2012 NMCCD ARTESIA wledge and belief. LING SERVICES DATE 7/5/12 PHONE: