

Submit 1 Copy To Appropriate District Office  
District I - (575) 393-6161  
1625 N French Dr., Hobbs, NM 88240  
District II - (575) 748-1283  
811 S. First St., Artesia, NM 88210  
District III - (505) 334-6178  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV - (505) 476-3460  
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103  
Revised August 1, 2011

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

WELL API NO. 30-015-38306
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Wyatt Draw 13 MD
8. Well Number 1H
9. OGRID Number 14744
10. Pool name or Wildcat North Seven Rivers Glorieta; Yeso
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3422 GL

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐  
2. Name of Operator  
Mewbourne Oil Company  
3. Address of Operator  
PO Box 5270 Hobbs, NM 88241  
4. Well Location  
Unit Letter D : 250 feet from the North line and 350 feet from the West line  
Section 24 Township 19S Range 25E NMPM Eddy County

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐  
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ P AND A ☐  
CASING/CEMENT JOB ☒


OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

06/30/12...TD'd 8 3/4" hole @ 3063'. Ran 3063' of 7" 26# J55 BT&C & LT&C Csg. Cemented with 200 sks BJ Lite Class C (35:65:4) with additives. Mixed @ 12.5 /g w/ 2.13 yd. Tail with 300 sks Class C w/additives. Mixed @ 14.8 #/g w/ 1.34 yd. Plug down @ 12:15 AM 07/01/12. Circ 137 sks of cmt to the pit. At 9:30 P.M. 07/01/12, tested BOPE & csg to 1500# for 30 min, held OK. Drilled out with 6 1/8" bit.

Spud Date: 06/24/2012

Rig Release Date:



I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Jackie Lathan TITLE Hobbs Regulatory DATE 07/13/12  
Type or print name Jackie Lathan E-mail address: jlathan@mewbourne.com PHONE: 575-393-5905

For State Use Only

APPROVED BY: JDade TITLE Dist Supervisor DATE 7/18/12  
Conditions of Approval (if any):