Office	State of New Mexico	Form C-103
District 1 - (575) 393-6161	Energy, Minerals and Natural Resources	Revised August 1, 2011
1625 N. French Dr., Hobbs, NM 88240 District II – (575) 748-1283		WELL API NO. 30-015-40371
811 S. First St., Artesia, NM 88210	OIL CONSERVATION DIVISION	5. Indicate Type of Lease
<u>District III</u> – (505) 334-6178 1000 Rio Brazos Rd., Aztec, NM 87410	1220 South St. Francis Dr.	STATE X FEE
<u>District IV</u> – (505) 476-3460 1220 S. St. Francis Dr., Santa Fe, NM	Santa Fe, NM 87505	6. State Oil & Gas Lease No.
87505		
(DO NOT USE THIS FORM FOR PROP DIFFERENT RESERVOIR. USE "APPL	TICES AND REPORTS ON WELLS OSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A LICATION FOR PERMIT" (FORM C-101) FOR SUCH	7. Lease Name or Unit Agreement Name LOS MEDANOS 36 23 30 STATE
PROPOSALS.) 1. Type of Well: Oil Well X	Gas Well Other SWD	8. Well Number 1H
2. Name of Operator Chevron U S		9. OGRID Number
Chevron U	S A, Inc.	4323
3. Address of Operator 15 Smith	Road TX 79705	10. Pool name or Wildcat
4. Well Location	17/03	WC-015 G-OG S233036D; BONE SPRING
	: 150 feet from the NORTH line and 60	60' feet from the WEST line
Section 36	Township 23S Range 30E	NMPM County EDDY
	11. Elevation (Show whether DR, RKB, RT, GR, et	5 -
	3350' GR	The state of the s
12. Check	Appropriate Box to Indicate Nature of Notice	e, Report or Other Data
NOTICE OF I	NTENTION TO: SU	BSEQUENT REPORT OF:
PERFORM REMEDIAL WORK		
TEMPORARILY ABANDON		RILLING OPNS. P AND A
PULL OR ALTER CASING		NT JOB 🔯
DOWNHOLE COMMINGLE	J	
	□ OTHER:	m
OTHER:	_	
13. Describe proposed or com	ppleted operations. (Clearly state all pertinent details,	
13. Describe proposed or com of starting any proposed v	npleted operations. (Clearly state all pertinent details, work). SEE RULE 19.15.7.14 NMAC. For Multiple C	
13. Describe proposed or com of starting any proposed v proposed completion or re	repleted operations. (Clearly state all pertinent details, work). SEE RULE 19.15.7.14 NMAC. For Multiple Completion.	Completions: Attach wellbore diagram of
13. Describe proposed or com of starting any proposed v proposed completion or re ON 10/25/12 DRILL TO 535' @	npleted operations. (Clearly state all pertinent details, work). SEE RULE 19.15.7.14 NMAC. For Multiple Cecompletion. 9 14:30 HOURS. T.O.H., RUN CSNG AS FOLLOW	Completions: Attach wellbore diagram of /S: F/S 1.50, 1 JNT 13 3/8 48# H-40 CSNG
13. Describe proposed or come of starting any proposed of proposed completion or responsed to the completion of the comp	npleted operations. (Clearly state all pertinent details, work). SEE RULE 19.15.7.14 NMAC. For Multiple Cecompletion. 14:30 HOURS. T.O.H., RUN CSNG AS FOLLOW E CSNG 495.26 SET @ 535' KB THREAD LOCK AIEW & R/U SCHLUMBERGER. CMT CSNG AS FOL	Completions: Attach wellbore diagram of /S: F/S 1.50, 1 JNT 13 3/8 48# H-40 CSNG LL FLOAT EQUIPMENT. CIRC W/ RIG JLOWS: LEAD - 525 SKS CLASS C 1.65
of starting any proposed or comproposed completion or responsed to the completion of the comprometry of the completion o	npleted operations. (Clearly state all pertinent details, work). SEE RULE 19.15.7.14 NMAC. For Multiple Cecompletion. 14:30 HOURS. T.O.H., RUN CSNG AS FOLLOW E CSNG 495.26 SET @ 535' KB THREAD LOCK AIEW & R/U SCHLUMBERGER. CMT CSNG AS FOLOW, TAIL - 225 SKS CLASS C, YIELD 1.33, MIX 6.35	Completions: Attach wellbore diagram of VS: F/S 1.50, 1 JNT 13 3/8 48# H-40 CSNG LL FLOAT EQUIPMENT. CIRC W/ RIG LLOWS: LEAD - 525 SKS CLASS C 1.65 (@ 14.8 PPG 80 BBL CMT BACK T/
13. Describe proposed or comof starting any proposed of proposed completion or responsed to the completion of the comple	npleted operations. (Clearly state all pertinent details, work). SEE RULE 19.15.7.14 NMAC. For Multiple Cecompletion. 14:30 HOURS. T.O.H., RUN CSNG AS FOLLOW E CSNG 495.26 SET @ 535' KB THREAD LOCK AIEW & R/U SCHLUMBERGER. CMT CSNG AS FOLOW, TAIL - 225 SKS CLASS C, YIELD 1.33, MIX 6.35, OW, 5000 HIGH. BOTH HYD CHOKES AND ALL MARCH AND ALL MEDICAL SETTING AS TOUR	Completions: Attach wellbore diagram of VS: F/S 1.50, 1 JNT 13 3/8 48# H-40 CSNG LL FLOAT EQUIPMENT. CIRC W/ RIG LLOWS: LEAD - 525 SKS CLASS C 1.65 @ 14.8 PPG 80 BBL CMT BACK T/ MANIFOLD VALVE . HCR VALVES AND
13. Describe proposed or comof starting any proposed of proposed completion or responsed to the completion of the comple	npleted operations. (Clearly state all pertinent details, work). SEE RULE 19.15.7.14 NMAC. For Multiple Cecompletion. 10 14:30 HOURS. T.O.H., RUN CSNG AS FOLLOW E CSNG 495.26 SET @ 535' KB THREAD LOCK AIEW & R/U SCHLUMBERGER. CMT CSNG AS FOLOW, TAIL - 225 SKS CLASS C, YIELD 1.33, MIX 6.35, OW, 5000 HIGH. BOTH HYD CHOKES AND ALL MONTH STORM, SOUND TEST CSNG TO UMULATOR. BREAK CIRC AND TEST CSNG TO	Completions: Attach wellbore diagram of VS: F/S 1.50, 1 JNT 13 3/8 48# H-40 CSNG LL FLOAT EQUIPMENT. CIRC W/ RIG LLOWS: LEAD - 525 SKS CLASS C 1.65 (@ 14.8 PPG 80 BBL CMT BACK T/ MANIFOLD VALVE . HCR VALVES AND TANDPIPE BACK TO PUMPS. PERFORM
of starting any proposed or comproposed completion or responsed to the proposed completion or responsed to the proposed completion or response to the proposed completion or response to the proposed completion or response to the proposed completion of the proposed compression of the proposed completion or response to the p	npleted operations. (Clearly state all pertinent details, work). SEE RULE 19.15.7.14 NMAC. For Multiple Cecompletion. 10 14:30 HOURS. T.O.H., RUN CSNG AS FOLLOW E CSNG 495.26 SET @ 535' KB THREAD LOCK AIEW & R/U SCHLUMBERGER. CMT CSNG AS FOLOW, TAIL - 225 SKS CLASS C, YIELD 1.33, MIX 6.35, OW, 5000 HIGH. BOTH HYD CHOKES AND ALL MONTH STORM, SOUND TEST CSNG TO UMULATOR. BREAK CIRC AND TEST CSNG TO	Completions: Attach wellbore diagram of /S: F/S 1.50, 1 JNT 13 3/8 48# H-40 CSNG LL FLOAT EQUIPMENT. CIRC W/ RIG LLOWS: LEAD - 525 SKS CLASS C 1.65 @ 14.8 PPG 80 BBL CMT BACK T/ MANIFOLD VALVE . HCR VALVES AND TANDPIPE BACK TO PUMPS. PERFORM 1200 PSI FOR 30 MINUTES. TEST OK,
13. Describe proposed or comof starting any proposed of proposed completion or responsed to the completion of the comple	npleted operations. (Clearly state all pertinent details, work). SEE RULE 19.15.7.14 NMAC. For Multiple Cecompletion. 10 14:30 HOURS. T.O.H., RUN CSNG AS FOLLOW E CSNG 495.26 SET @ 535' KB THREAD LOCK AIEW & R/U SCHLUMBERGER. CMT CSNG AS FOLOW, TAIL - 225 SKS CLASS C, YIELD 1.33, MIX 6.35, OW, 5000 HIGH. BOTH HYD CHOKES AND ALL MONTH STORM, SOUND TEST CSNG TO UMULATOR. BREAK CIRC AND TEST CSNG TO	Completions: Attach wellbore diagram of VS: F/S 1.50, 1 JNT 13 3/8 48# H-40 CSNG LL FLOAT EQUIPMENT. CIRC W/ RIG LLOWS: LEAD - 525 SKS CLASS C 1.65 (@ 14.8 PPG 80 BBL CMT BACK T/ MANIFOLD VALVE . HCR VALVES AND TANDPIPE BACK TO PUMPS. PERFORM
13. Describe proposed or comof starting any proposed of proposed completion or responsed to the completion of the comple	npleted operations. (Clearly state all pertinent details, work). SEE RULE 19.15.7.14 NMAC. For Multiple Cecompletion. 10 14:30 HOURS. T.O.H., RUN CSNG AS FOLLOW E CSNG 495.26 SET @ 535' KB THREAD LOCK AIEW & R/U SCHLUMBERGER. CMT CSNG AS FOLOW, TAIL - 225 SKS CLASS C, YIELD 1.33, MIX 6.35, OW, 5000 HIGH. BOTH HYD CHOKES AND ALL MONTH STORM, SOUND TEST CSNG TO UMULATOR. BREAK CIRC AND TEST CSNG TO	Completions: Attach wellbore diagram of VS: F/S 1.50, 1 JNT 13 3/8 48# H-40 CSNG LL FLOAT EQUIPMENT. CIRC W/ RIG LOWS: LEAD - 525 SKS CLASS C 1.65 @ 14.8 PPG 80 BBL CMT BACK T/ MANIFOLD VALVE . HCR VALVES AND TANDPIPE BACK TO PUMPS. PERFORM 1200 PSI FOR 30 MINUTES. TEST OK,
13. Describe proposed or comof starting any proposed of proposed completion or reconstruction of the proposed complete of the proposed c	npleted operations. (Clearly state all pertinent details, work). SEE RULE 19.15.7.14 NMAC. For Multiple Cecompletion. 10 14:30 HOURS. T.O.H., RUN CSNG AS FOLLOW E CSNG 495.26 SET @ 535' KB THREAD LOCK AIEW & R/U SCHLUMBERGER. CMT CSNG AS FOLOW, TAIL - 225 SKS CLASS C, YIELD 1.33, MIX 6.35, OW, 5000 HIGH. BOTH HYD CHOKES AND ALL MONTH STORM, SOUND TEST CSNG TO UMULATOR. BREAK CIRC AND TEST CSNG TO	Completions: Attach wellbore diagram of VS: F/S 1.50, 1 JNT 13 3/8 48# H-40 CSNG LL FLOAT EQUIPMENT. CIRC W/ RIG LLOWS: LEAD - 525 SKS CLASS C 1.65 (@ 14.8 PPG 80 BBL CMT BACK T/ MANIFOLD VALVE . HCR VALVES AND TANDPIPE BACK TO PUMPS. PERFORM 1200 PSI FOR 30 MINUTES. TEST OK, RECEIVED OCT 3 0 2012
13. Describe proposed or comof starting any proposed of proposed completion or reconstruction of the proposed complete of the proposed c	npleted operations. (Clearly state all pertinent details, work). SEE RULE 19.15.7.14 NMAC. For Multiple Cecompletion. 10 14:30 HOURS. T.O.H., RUN CSNG AS FOLLOW E CSNG 495.26 SET @ 535' KB THREAD LOCK AIEW & R/U SCHLUMBERGER. CMT CSNG AS FOLOW, TAIL - 225 SKS CLASS C, YIELD 1.33, MIX 6.35, OW, 5000 HIGH. BOTH HYD CHOKES AND ALL MONTH STORM, SOUND TEST CSNG TO UMULATOR. BREAK CIRC AND TEST CSNG TO	Completions: Attach wellbore diagram of VS: F/S 1.50, 1 JNT 13 3/8 48# H-40 CSNG LL FLOAT EQUIPMENT. CIRC W/ RIG LOWS: LEAD - 525 SKS CLASS C 1.65 @ 14.8 PPG 80 BBL CMT BACK T/ MANIFOLD VALVE . HCR VALVES AND TANDPIPE BACK TO PUMPS. PERFORM 1200 PSI FOR 30 MINUTES. TEST OK,
13. Describe proposed or comof starting any proposed of proposed completion or reconstruction of the proposed completion of the proposed complete c	npleted operations. (Clearly state all pertinent details, work). SEE RULE 19.15.7.14 NMAC. For Multiple Cecompletion. 10 14:30 HOURS. T.O.H., RUN CSNG AS FOLLOW E CSNG 495.26 SET @ 535' KB THREAD LOCK AIEW & R/U SCHLUMBERGER. CMT CSNG AS FOLOW, TAIL - 225 SKS CLASS C, YIELD 1.33, MIX 6.35, OW, 5000 HIGH. BOTH HYD CHOKES AND ALL MONTH STORM, SOUND TEST CSNG TO UMULATOR. BREAK CIRC AND TEST CSNG TO	Completions: Attach wellbore diagram of VS: F/S 1.50, 1 JNT 13 3/8 48# H-40 CSNG LL FLOAT EQUIPMENT. CIRC W/ RIG LLOWS: LEAD - 525 SKS CLASS C 1.65 (@ 14.8 PPG 80 BBL CMT BACK T/ MANIFOLD VALVE . HCR VALVES AND TANDPIPE BACK TO PUMPS. PERFORM 1200 PSI FOR 30 MINUTES. TEST OK, RECEIVED OCT 3 0 2012
13. Describe proposed or comof starting any proposed was proposed completion or responsed to the proposed completion or response of the proposed completion or response of the proposed completion or response of the proposed completion of	npleted operations. (Clearly state all pertinent details, awork). SEE RULE 19.15.7.14 NMAC. For Multiple Cecompletion. 14:30 HOURS. T.O.H., RUN CSNG AS FOLLOW E CSNG 495.26 SET @ 535' KB THREAD LOCK AIEW & R/U SCHLUMBERGER. CMT CSNG AS FOLOW, TAIL - 225 SKS CLASS C, YIELD 1.33, MIX 6.35 OW, 5000 HIGH. BOTH HYD CHOKES AND ALL FOOLOW, 3500 HIGH. ALL FLOOR VALVES AND SUMULATOR. BREAK CIRC AND TEST CSNG TO @ 21:00 HOURS.	Completions: Attach wellbore diagram of VS: F/S 1.50, 1 JNT 13 3/8 48# H-40 CSNG LL FLOAT EQUIPMENT. CIRC W/ RIG LLOWS: LEAD - 525 SKS CLASS C 1.65 (@ 14.8 PPG 80 BBL CMT BACK T/ MANIFOLD VALVE . HCR VALVES AND TANDPIPE BACK TO PUMPS. PERFORM 1200 PSI FOR 30 MINUTES. TEST OK, RECEIVED OCT 3 0 2012
13. Describe proposed or comof starting any proposed was proposed completion or responsed to the proposed completion or response to the proposed completion or response to the proposed completion or response to the proposed completion of response to the proposed complete the proposed complete to	npleted operations. (Clearly state all pertinent details, awork). SEE RULE 19.15.7.14 NMAC. For Multiple Cecompletion. 10 14:30 HOURS. T.O.H., RUN CSNG AS FOLLOW E CSNG 495.26 SET @ 535' KB THREAD LOCK AI EW & R/U SCHLUMBERGER. CMT CSNG AS FOLOW, TAIL - 225 SKS CLASS C, YIELD 1.33, MIX 6.35 OW, 5000 HIGH. BOTH HYD CHOKES AND ALL MODERN ALL FLOOR VALVES AND SUMULATOR. BREAK CIRC AND TEST CSNG TO @ 21:00 HOURS. Rig Release Date:	Completions: Attach wellbore diagram of VS: F/S 1.50, 1 JNT 13 3/8 48# H-40 CSNG LL FLOAT EQUIPMENT. CIRC W/ RIG LLOWS: LEAD - 525 SKS CLASS C 1.65 @ 14.8 PPG 80 BBL CMT BACK T/ MANIFOLD VALVE . HCR VALVES AND TANDPIPE BACK TO PUMPS. PERFORM 1200 PSI FOR 30 MINUTES. TEST OK, RECEIVED OCT 3 0 2012 NMOCD ARTESIA
13. Describe proposed or comof starting any proposed was proposed completion or responsed to the proposed completion or response to the proposed completion or response to the proposed completion or response to the proposed completion of response to the proposed complete the proposed complete to	npleted operations. (Clearly state all pertinent details, awork). SEE RULE 19.15.7.14 NMAC. For Multiple Cecompletion. 14:30 HOURS. T.O.H., RUN CSNG AS FOLLOW E CSNG 495.26 SET @ 535' KB THREAD LOCK AIEW & R/U SCHLUMBERGER. CMT CSNG AS FOLOW, TAIL - 225 SKS CLASS C, YIELD 1.33, MIX 6.35 OW, 5000 HIGH. BOTH HYD CHOKES AND ALL FOOLOW, 3500 HIGH. ALL FLOOR VALVES AND SUMULATOR. BREAK CIRC AND TEST CSNG TO @ 21:00 HOURS.	Completions: Attach wellbore diagram of VS: F/S 1.50, 1 JNT 13 3/8 48# H-40 CSNG LL FLOAT EQUIPMENT. CIRC W/ RIG LLOWS: LEAD - 525 SKS CLASS C 1.65 @ 14.8 PPG 80 BBL CMT BACK T/ MANIFOLD VALVE . HCR VALVES AND TANDPIPE BACK TO PUMPS. PERFORM 1200 PSI FOR 30 MINUTES. TEST OK, RECEIVED OCT 3 0 2012 NMOCD ARTESIA
13. Describe proposed or comof starting any proposed was proposed completion or responsed to the proposed completion or response to the proposed completion or response to the proposed completion or response to the proposed completion of response to the proposed complete the proposed complete to	npleted operations. (Clearly state all pertinent details, awork). SEE RULE 19.15.7.14 NMAC. For Multiple Cecompletion. 10 14:30 HOURS. T.O.H., RUN CSNG AS FOLLOW E CSNG 495.26 SET @ 535' KB THREAD LOCK AI EW & R/U SCHLUMBERGER. CMT CSNG AS FOLOW, TAIL - 225 SKS CLASS C, YIELD 1.33, MIX 6.35 OW, 5000 HIGH. BOTH HYD CHOKES AND ALL MODERN ALL FLOOR VALVES AND SUMULATOR. BREAK CIRC AND TEST CSNG TO @ 21:00 HOURS. Rig Release Date:	Completions: Attach wellbore diagram of VS: F/S 1.50, 1 JNT 13 3/8 48# H-40 CSNG LL FLOAT EQUIPMENT. CIRC W/ RIG LLOWS: LEAD - 525 SKS CLASS C 1.65 (@ 14.8 PPG 80 BBL CMT BACK T/ MANIFOLD VALVE . HCR VALVES AND TANDPIPE BACK TO PUMPS. PERFORM 1200 PSI FOR 30 MINUTES. TEST OK, RECEIVED OCT 3 0 2012 NMOCD ARTESIA
13. Describe proposed or comof starting any proposed was proposed completion or responsed to the proposed completion or response to the proposed completion or response to the proposed completion or response to the proposed completion of response to the proposed complete the proposed complete to	npleted operations. (Clearly state all pertinent details, awork). SEE RULE 19.15.7.14 NMAC. For Multiple Cecompletion. 10 14:30 HOURS. T.O.H., RUN CSNG AS FOLLOW E CSNG 495.26 SET @ 535' KB THREAD LOCK AI EW & R/U SCHLUMBERGER. CMT CSNG AS FOLOW, TAIL - 225 SKS CLASS C, YIELD 1.33, MIX 6.35 OW, 5000 HIGH. BOTH HYD CHOKES AND ALL MODERN ALL FLOOR VALVES AND SUMULATOR. BREAK CIRC AND TEST CSNG TO @ 21:00 HOURS. Rig Release Date:	Completions: Attach wellbore diagram of VS: F/S 1.50, 1 JNT 13 3/8 48# H-40 CSNG LL FLOAT EQUIPMENT. CIRC W/ RIG LLOWS: LEAD - 525 SKS CLASS C 1.65 @ 14.8 PPG 80 BBL CMT BACK T/ MANIFOLD VALVE . HCR VALVES AND TANDPIPE BACK TO PUMPS. PERFORM 1200 PSI FOR 30 MINUTES. TEST OK, RECEIVED OCT 3 0 2012 NMOCD ARTESIA
13. Describe proposed or comof starting any proposed was proposed completion or responsed completion or responsed completion or response to the proposed completion of response to the proposed completion of the proposed completio	npleted operations. (Clearly state all pertinent details, awork). SEE RULE 19.15.7.14 NMAC. For Multiple Clecompletion. 10 14:30 HOURS. T.O.H., RUN CSNG AS FOLLOW E CSNG 495.26 SET @ 535' KB THREAD LOCK AND EW & R/U SCHLUMBERGER. CMT CSNG AS FOLOW, 5000 HIGH. BOTH HYD CHOKES AND ALL MODERN SEARCH SEAR	Completions: Attach wellbore diagram of VS: F/S 1.50, 1 JNT 13 3/8 48# H-40 CSNG LL FLOAT EQUIPMENT. CIRC W/ RIG LLOWS: LEAD - 525 SKS CLASS C 1.65 @ 14.8 PPG 80 BBL CMT BACK T/ MANIFOLD VALVE. HCR VALVES AND TANDPIPE BACK TO PUMPS. PERFORM 1200 PSI FOR 30 MINUTES. TEST OK, RECEIVED OCT 3 0 2012 NMOCD ARTESIA dige and belief. DATE 10/29/2012
13. Describe proposed or comof starting any proposed was proposed completion or responsed completion or responsed completion or responsed completion or response to the proposed completion of the propos	npleted operations. (Clearly state all pertinent details, awork). SEE RULE 19.15.7.14 NMAC. For Multiple Clecompletion. 10 14:30 HOURS. T.O.H., RUN CSNG AS FOLLOW E CSNG 495.26 SET @ 535' KB THREAD LOCK AND EW & R/U SCHLUMBERGER. CMT CSNG AS FOLOW, 5000 HIGH. BOTH HYD CHOKES AND ALL MODERN SEARCH SEAR	Completions: Attach wellbore diagram of VS: F/S 1.50, 1 JNT 13 3/8 48# H-40 CSNG LL FLOAT EQUIPMENT. CIRC W/ RIG LLOWS: LEAD - 525 SKS CLASS C 1.65 @ 14.8 PPG 80 BBL CMT BACK T/ MANIFOLD VALVE. HCR VALVES AND TANDPIPE BACK TO PUMPS. PERFORM 1200 PSI FOR 30 MINUTES. TEST OK, RECEIVED OCT 3 0 2012 NMOCD ARTESIA dge and belief. DATE 10/29/2012
13. Describe proposed or comof starting any proposed was proposed completion or responsed completion or response of responsed completion of responsed completion or responsed	Propleted operations. (Clearly state all pertinent details, awork). SEE RULE 19.15.7.14 NMAC. For Multiple Clecompletion. 10 14:30 HOURS. T.O.H., RUN CSNG AS FOLLOW E CSNG 495.26 SET @ 535' KB THREAD LOCK AND EW & R/U SCHLUMBERGER. CMT CSNG AS FOLLOW, 5000 HIGH. BOTH HYD CHOKES AND ALL MORE AND SOLOW, 3500 HIGH. ALL FLOOR VALVES AND SUMULATOR. BREAK CIRC AND TEST CSNG TO @ 21:00 HOURS. Rig Release Date: Rig Release Date:	Completions: Attach wellbore diagram of VS: F/S 1.50, 1 JNT 13 3/8 48# H-40 CSNG LL FLOAT EQUIPMENT. CIRC W/ RIG LLOWS: LEAD - 525 SKS CLASS C 1.65 (@ 14.8 PPG 80 BBL CMT BACK T/ MANIFOLD VALVE. HCR VALVES AND TANDPIPE BACK TO PUMPS. PERFORM 1200 PSI FOR 30 MINUTES. TEST OK, RECEIVED OCT 3 0 2012 NMOCD ARTESIA dige and belief. DATE 10/29/2012 Chk.com PHONE: (405)935-3782
13. Describe proposed or comof starting any proposed was proposed completion or responsed completion or responsed completion or responsed completion or response to the proposed completion of the propos	npleted operations. (Clearly state all pertinent details, awork). SEE RULE 19.15.7.14 NMAC. For Multiple Clecompletion. 10 14:30 HOURS. T.O.H., RUN CSNG AS FOLLOW E CSNG 495.26 SET @ 535' KB THREAD LOCK AND EW & R/U SCHLUMBERGER. CMT CSNG AS FOLOW, 5000 HIGH. BOTH HYD CHOKES AND ALL MODERN SEARCH SEAR	Completions: Attach wellbore diagram of VS: F/S 1.50, 1 JNT 13 3/8 48# H-40 CSNG LL FLOAT EQUIPMENT. CIRC W/ RIG LLOWS: LEAD - 525 SKS CLASS C 1.65 @ 14.8 PPG 80 BBL CMT BACK T/ MANIFOLD VALVE. HCR VALVES AND TANDPIPE BACK TO PUMPS. PERFORM 1200 PSI FOR 30 MINUTES. TEST OK, RECEIVED OCT 3 0 2012 NMOCD ARTESIA dige and belief. DATE 10/29/2012