Submit 3 Copies To Appropriate District Office	State of New Mexico				Form C-103 June 19, 2008
<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240	Energy, Minerals and Natural Resources		WELL API NO.	June 17, 2000	
District II 1301 W. Grand Ave., Artesia, NM 88210	OIL CONSERVATION DIVISION		30-015-40783	of Looks	
District III 1000 Rio Brazos Rd., Aztec, NM 87410	1220 South St. Francis Dr.		5. Indicate Type STATE	FEE	
District IV	Santa Fe, NM 87505)5	6. State Oil & G	
1220 S. St. Francis Dr., Santa Fe, NM 87505					
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A					or Unit Agreement Name
DIFFERENT RESERVOIR. USE "APPLIC PROPOSALS.)		C-101) FOR SUCH		LOGAN 2C STA	
1. Type of Well: Oil Well	Gas Well Other	REC	CEIVED	8. Well Number	#4
2. Name of Operator LIME ROCK RESOURCES II-A	A T D	OCT	3 1 2012	9. OGRID Numl	per 277558
3. Address of Operator	perator		-	10. Pool name of	r Wildcat
c/o Mike Pippin LLC, 3104 N. Sullivan, Farmington, NM 8740NMOC			D ARTESIA		
4. Well Location					
Unit Letter C: 990 feet from the NORTH line and 1500 feet from the WEST line					
Section 2 Township 18-S Range 27-E NMPM Eddy County					
11. Elevation (Show whether DR, RKB, RT, GR, etc.)					
3587' GL					
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data					
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:					
					ALTERING CASING
TEMPORARILY ABANDON					P AND A
PULL OR ALTER CASING	MULTIPLE COMPL		ASING/CEMENT	JOB 🛛	
DOWNHOLE COMMINGLE		ŀ			
OTHER:				& Casings	
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.					
Spud well on 10/12/12. Drilled 12-1/4" hole to 357'. Landed 8-5/8" 24# J-55 csg @ 353'. Cmted w/280 sx (357 cf) "C" cmt w/2% Cacl2 & 0.25# CF. Circ 104 sx cmt to surface. On 10/13/12, PT 8-5/8" csg to 800 psi for 30 min-OK.					
Drilled 7-7/8" hole from 8-5/8" csg shoe to MD4776' on 10/23/12. Ran open hole logs. On 10/24/12, landed 5-1/2" 17# J-55 csg @ MD4776'. Cmted lead w/275 sx (523 cf) 35/65 poz "C" cmt w/1/4#/sx CF, 5% salt, 5# LCM-1 & 0.3% R-3. Tailed w/625 sx (831 cf) "C" cmt w/0.2% CD-32, 0.25#/sx CF, 0.25% R-3. Circ 121 sx cmt to pit. Released drilling rig on 10/25/12. On 10/27/12, PT 8-5/8" csg to 5000 psi for 30 min-OK.					
Bottom Hole Location is 946' FNL & 1668' FWL Sec.2, T18S R27E					
Spud Date: 10/12/12		Drilling	Rig Release Da	te: 10/25/	12
I hereby certify that the information above is true and complete to the best of my knowledge and belief.					
SIGNATURE Mile Lipsin TITLE Petroleum Engineer - Agent DATE 10/30/12					
Type or print nameMike Pippin	E-mail :	address:	mike@pippinllo	c.com PHO	NE: <u>505-327-4573</u>
For State Use Only		Λ			1. 1
APPROVED BY: Conditions of Approval (if any):	CL TITLE	Dest	et Sefle	DA DA	ATE 10/31/12