Form 3160-5 (August 1999)

## N.M. Oil Cons. DIV-Dist. 2

UNITED STATES 1301 W. Grand Avenue DEPARTMENT OF THE INTERNOTIA, NIV 88210 BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB No. 1004-0135 Expires November 30, 2000

## Lease Serial No. NM-69333

											WELLS	
Do	not	use	this	form	for	pro	posal	s to	drill	or to	re-enter	ar

abandoned w	ell. Use Form 3160-3 (A	to anii or to re-entei PD) for such proposa	an Ils.	6. If I	ndian, Allottee or Tribe Name
SUBMIT IN TH	RIPLIGATE - Other ins	tructions on revers	e side	7. If U	Init or CA/Agreement, Name and/or No.
1. Type of Well			RECEIVED		
Oil Well 🖾 Gas Well	Other		MAY 1 0 2005		ll Name and No. onesome Dove Federal #
2. Name of Operator Yates Energy	Corneration	·	NOD-AHTEDIA		Well No. #2
3a. Address	Corporation	3b. Phone No. (inclu			0-015-33873
P. O. Box 232  4. Location of Well (Footage, Sec	23, Roswell, NM 8		4935		d and Pool, or Exploratory Area less Morrow East
660' FNL and	660' FEL of Sect	lon 26, T-23-S,	R-23-E		mty or Parish, State
	,			_	ing and the second
					ddy, New Mexico
12. CHECK AI	PPROPRIATE BOX(ES)	TO INDICATE NATU	IRE OF NOTICE, RI	EPORT,	OR OTHER DATA
TYPE OF SUBMISSION		T	YPE OF ACTION	-	
V	Acidize	Deepen Deepen	Production (Start	/Resume)	Water Shut-Off
Notice of Intent	Alter Casing	Fracture Treat	. Reclamation		Well Integrity
Subsequent Report	Casing Repair	New Construction	Recomplete		Other
	Change Plans	Plug and Abandon	Temporarily Aba	ndon A	. 1
Final Abandonment Notice	Convert to Injection	Plug Back	Water Disposal		DWANTERNS VAUSING  d work and approximate duration thereo
Nipple up on casing rams and pressure ter the API DDR at the a Go in the hole with a pressure test the rams DDR at the rig.  If there should be a least to 3000 psig by made for a new bit be test the rams (blind a If there should be a least the rams)	for the intermediate (8.62) with a 3000 psig, annular st the rams, well head, killing collars and at least one joins, well head, killing manifold eak, correct and retest as an independent tester: A cut no later than 500' beform a casing), well head, killing eak, correct then retest as lid the BOP or annular presents.	type preventer and do I manifold and casing int of drill pipe. Close I and casing with 1000 needed. Iter drilling out the intre drilling into the Woll I manifold, and casing needed.	the pipe rams just about psig for 30 minutes; ermediate casing, confcamp formation est, with 3000 psig (use	ove a driver record retinue driver at 7076	es; record results on ill pipe tool joint; results on the API illing until a trip is 'KB. Pressure
					·
<ol> <li>I hereby certify that the foregoin Name (Printed/Typed)</li> </ol>	g is true and correct			_	MAY - 5 2005
Sheryl L. Jon	as /	Title A	gent for Yates	Energ	y Corporation
Signature Alley	(2.90mx		05-03	-05	LES BABYAK PETROLEUM ENGINEER
	Net mestile space	त्रीत्रेयस्थानस्थानस्थानस्	inservation and in		
Approved by	• •	) <sub>Ti</sub>	tle		Date
Conditions of approval, if any, are a certify that the applicant holds legal which would entitle the applicant to co	or equitable title to those righ	an in also muliosa longo l	fice		

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.