

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

N.M. Oil Cons. DIV-Dist. 2
1301 W. Grand Avenue
Artesia, NM 88210

FORM APPROVED
OMB No. 1004-0135
Expires January 31, 2004

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or re enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

SUBMIT IN TRIPLICATE - Other instructions on reverse side

1. Type of Well



Oil Well



Gas Well



Other

2. Name of Operator

Yates Petroleum Corporation

3a. Address

105 S. 4th Str., Artesia, NM 88210

3b. Phone No. (include area code)

505-748-1471

4. Location of Well (Footage, Sec., T., R., M., OR Survey Description)

710'FSL & 1980'FEL of Section 23-T20S-R24E (Unit O, SWSE)

5. Lease Serial No.

NM-86241

6. If Indian, Allottee or Tribe Name

7. If Unit or CA/Agreement, Name and/or No.

8. Well Name and No.

Hill View AHE Federal Com #17

9. API Well No.

30-015-27214

10. Field and Pool, or Exploratory Area

Dagger Draw Upper Penn, South

11. County or Parish, State

Eddy County, New Mexico

12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION



Notice of Intent



Subsequent Report



Final Abandonment Notice



Acidize



Alter Casing



Casing Repair



Change Plans



Convert to Injection



Deepen



Fracture Treat



New Construction



Plug and Abandon



Plug Back



Production (Start/Resume)



Reclamation



Recomplete



Temporarily Abandon



Water Disposal



Water Shut-Off



Well Integrity



Other

13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)

Yates Petroleum Corporation plans to plug and abandon this well as follows: CIBP at 7451'.

1. Rig up all safety equipment needed.
2. Circulate hole with 9.5# mud and spot 25 sx plug on top of CIBP at 7451'.
3. Spot 100' (25 sx) cement plug from 5612'-5512'.
4. Spot 100' (25 sx) cement plug from 2172'-2072'.
5. Spot 100' (25 sx) cement plug from 1170'-1070'. Tag plug.
6. Spot 60' cement plug inside casing to surface. Tag plug.
7. Cut off wellhead and install marker.

NOTE: Yates Petroleum Corporation will use steel pits and no earth pits

APPROVAL SUBJECT TO
GENERAL REQUIREMENTS AND
SPECIAL STIPULATIONS ATTACHED

14. I hereby certify that the foregoing is true and correct

Name (Printed/Typed)

Tina Huerta

Title

Regulatory Compliance Supervisor

Signature

Tina Huerta

Date

July 11, 2005

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by

(ORIG. SGD.) ALEXIS C. SWOBODA

Title

PETROLEUM ENGINEER

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

RFO

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

Accepted for record - NMOCD
JUL 14 2005

OPERATOR Yates Petroleum Corporation
WELL NAME: Hillview AHE #17 **FIELD:** Dagger Draw
LOCATION: Unit O, 710' FSL & 1980' FEL, Sec 23-20S-24E **COUNTY** Eddy
GL: 3652' **ZERO:** 18 **KB:** 3670
SPUD DATE: 3-8-93 **COMPLETION DATE:** 5-29-93
COMMENTS: _____

CASING PROGRAM

9 5/8" 36# J-55	1120'
7" 12jts 26# N-80 sb	482.64
5 jts 26# J-55 sb	185.73'
60 jts 26# J-55 V	2474.40'
89 jts 23# J-55 V	3729.42'
31 jts 26# J-55 V	1250.56'

Before

14 3/4." Hole

8 3/4." Hole

9 5/8"@1120'
w/1600 sx (circ)

DST #1- 5338-5420'

DV Tool @ 5630'

CIBP @ 7451'

239 jts. 2 7/8. J-55
sn @ 7528.81
Pkr @ 7529.91

RBP @ 7590'

PBTD @ 8058'

7551-7559' w/9 .42 "holes
Acidz: 5-93-1500 20%

7657-7732 w/36 holes
Acidz: 18000 20% NEFE
7780-7798' w/18 holes
Acidz: 3000 20% NEFE

7"@8120'w/1510 sx (circ)

TD 8120'

TOPS

San Andres 593'
 Glorieta 2122'
 Bone Spring Lime 3458'
 3rd. Bone Spring Sd 5562'
 Wolfcamp Lime 5579'
 Canyon Lime 7530'

Not to scale

N.M. Oil Cons. DIV-Dist. 2
1301 W. Grand Avenue
Artesia, NM 88210

OPERATOR Yates Petroleum Corporation
WELL NAME: Hill view AHE #17 FIELD: Dagger Draw
LOCATION: Unit O, 710' FSL & 1980' FEL, Sec 23-20S-24E COUNTY Eddy
GL: 3652' ZERO: 18 KB: 3670
SPUD DATE: 3-8-93 COMPLETION DATE: 5-29-93
COMMENTS: _____

After

14 3/4" Hole

8 3/4" Hole

CIBP @ 7451' 35'
cement on top

239 jts. 2 7/8. J-55
sn @ 7528.81
Pkr @ 7529.91

RBP @ 7590'

PBTD @ 8058'

TD 8120'

60' Surface Plug

9 5/8" @ 1120'
w/1600 sx (circ)

100' Cement Plug
1170' - 1070'
(TAG PLUG)

100' Cement Plug
2172' - 2072'

100' Cement Plug
5612' - 5512'

DV Tool @ 5630'

7551-7559' w/9 .42" holes
Acidz: 5-93-1500 20%

7657-7732 w/36 holes
Acidz: 18000 20% NEFE
7780-7798' w/18 holes
Acidz: 3000 20% NEFE

7" @ 8120' w/1510 sx (circ)

CASING PROGRAM

9 5/8" 36# J-55	1120'
7" 12jts 26# N-80 sb	482.64
5 jts 26# J-55 sb	185.73'
60 jts 26# J-55 V	2474.40'
89 jts 23# J-55 V	3729.42'
31 jts 26# J-55 V	1250.56'

TOPS

San Andres 593'
Glorieta 2122'
Bone Spring Lime 3458'
3rd. Bone Spring Sd 5562'
Wolfcamp Lime 5579'
Canyon Lime 7530'

Not to scale