Form 3160-5 (August 1999)

LINITED STATES N.M. Oil Cons. DIV-Diet 2

UNITED STATES	FORM APROVED
DEPARTMENT OF THE INTERIOR AND	OMB NO. 1004-0135
DEPARTMENT OF THE INTERIOR 1 W. Grand Avenue	EXPIRES: NOVEMBER 30, 200
SUNDRY NOTICES AND REPORTS ON WELLS not use this form for proposals to drill or to re-one Size, NIVI 88210	5. Lease Serial No.
not use this form for proposals to drill or to re-presalt. NV 88210	NMNM0503

Do not use this form	a Earm 2160 2 (ADIN tar cuab r	noposais			r Tribe Name
	e Form 3160-3 (APD) for such p JBMIT IN TRIPLICATE			o. v. maian, / monoco	
		REC	EIVED	7. Unit or CA Agreen	nent Name and No.
a. Type of Well Oil Well 🗹 Ga	s Well Other	AUG	1 2 2005	8 Well Name and No).
Name of Operator DEVON ENERGY PRODUCT	TION COMPANY I P	QQU-/	anteom	Cottor 9. API Well No.	n Draw Unit 68
Address and Telephone No.	TOR COMPART, LI			1	-015-20272
•	00, Oklahoma City, OK 73102	405-552-461	5	10. Field and Pool, o	
Location of Well (Report location clear				1	a South, Atoka
, ,	2 T25S R31E	,		12. County or Parish	
				EDDY	NM NM
	APPROPRIATE BOX(s) TO INC				
TYPE OS SUBMISSION			E OF ACTION		
☐ Notice of Intent	Acidize Alter Casing	☐ Deepen☐ Fracture Treat	Production Reclamat	on (Start/Resume)	
☑ Subsequent Report	Casing Repair	New Construction	✓ Recomple		Other
Final Abandonment Notice	Change Plans	Plug and Abandon		rily Abandon	
. Describe Proposed or Completed Operations (C	Convert to Injection	Plug Back	☐ Water Di		
epen directionally or recomplete horizontally, give su Bond No. on file with BLM/BIA. Required subseque erval, a Form 3160-4 shall be filed once testing has I termined that the site is ready for final inspection)	ent reports shall be filed within 30 days fol	lowing completion of the involved	operations. If the o	peration results in a multiple o	completion or recompletion in a new
ubsequent operations of recompletion 10/05: MIRU. Drilled out cement, CIBP disting Wolfcamp perforations at 12895 stainer and cement down to 14066'. Performing and packer. Set top of packer at 1 tell back to production. Tested 0 BOPD,	@ 12270', & milled out packer -12972' (approximately 25 sxs i forated Atoka interval at 13996'- 3912'. Turned well to sales on	nto formation). Squeeze 14000'; 14017'-14024'; 14 6/17/05. Acidized well on	oressure 5200 041'-14047' (3 7/17/05 with 2	 Drilled out cement shots). Run 2-3/8" p gallons of 15% HO 	production
10/05: MIRU. Drilled out cement, CIBP kisting Wolfcamp perforations at 12895' tainer and cement down to14066'. Perf bing and packer. Set top of packer at 1	@ 12270', & milled out packer -12972' (approximately 25 sxs i forated Atoka interval at 13996'- 3912'. Turned well to sales on	nto formation). Squeeze 14000'; 14017'-14024'; 14 6/17/05. Acidized well on	oressure 5200 041'-14047' (3 7/17/05 with 2	 Drilled out cement shots). Run 2-3/8" p gallons of 15% HO 	production
10/05: MIRU. Drilled out cement, CIBP isting Wolfcamp perforations at 12895' tainer and cement down to14066'. Perforg and packer. Set top of packer at 1	@ 12270', & milled out packer -12972' (approximately 25 sxs i forated Atoka interval at 13996'- 3912'. Turned well to sales on	nto formation). Squeeze 14000'; 14017'-14024'; 14 6/17/05. Acidized well on	oressure 5200 041'-14047' (3 7/17/05 with 2 R TEST on 8/1	 Drilled out cement shots). Run 2-3/8" p gallons of 15% HO 	R RECORD
10/05: MIRU. Drilled out cement, CIBP isting Wolfcamp perforations at 12895 tainer and cement down to14066'. Perforng and packer. Set top of packer at 1	@ 12270', & milled out packer -12972' (approximately 25 sxs i forated Atoka interval at 13996'- 13912'. Turned well to sales on 3624 MCFD, 2 BWPD, 2400 PS	nto formation). Squeeze 14000'; 14017'-14024'; 14 6/17/05. Acidized well on	oressure 5200 041'-14047' (3 7/17/05 with 2 R TEST on 8/1	#. Drilled out cement 4 shots). Run 2-3/8" p 000 gallons of 15% HO /05.	R RECORD
10/05: MIRU. Drilled out cement, CIBP isting Wolfcamp perforations at 12895' tainer and cement down to 14066'. Perforing and packer. Set top of packer at 1 left back to production. Tested 0 BOPD,	rue and correct Name Title	nto formation). Squeeze (14000'; 14017'-14024'; 146/17/05. Acidized well on SI FTP, 11/64" CHK, 24 HI	oressure 5200 041'-14047' (3 7/17/05 with 2 R TEST on 8/1	#. Drilled out cement 4 shots). Run 2-3/8" p 000 gallons of 15% HC /05. CCEPTED FOI AUG 1 0 LES BA PETROLEUM	R RECORD 2005 BYAK ENGINEER
10/05: MIRU. Drilled out cement, CIBP isting Wolfcamp perforations at 12895' tainer and cement down to 14066'. Perfoing and packer. Set top of packer at 1 ell back to production. Tested 0 BOPD,	rue and correct Name Title	nto formation). Squeeze (14000'; 14017'-14024'; 146/17/05. Acidized well on SI FTP, 11/64" CHK, 24 HI	oressure 5200 041'-14047' (3 7/17/05 with 2 R TEST on 8/1	#. Drilled out cement 4 shots). Run 2-3/8" p 000 gallons of 15% HC /05. CCEPTED FOI AUG 1 0 LES BA PETROLEUM	R RECORD 2005 BYAK ENGINEER