Form 3160-5 (April 2004)

> Type of Well X Oil Well

2. Name of Operator

Sec. 12, T198, R28E

327' FSL & 483' FWL

3a. Address

Gas Well

Stephens & Johnson Operating Co.

Final Abandonment Notice

P.O. Box 2249 Wichita Falls TX 76307-2249 4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Other

IM. Of Cons. Physica. 2 DEPARTMENT OF THE INTERIOR VV. GRANG AVENUE

BUREAU OF LAND MANAGEMENT SIA, NM 88210

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

SUBMIT IN TRIPLICATE - Other instructions on reverse side

	FORM APPROVED	
)	OMB NO. 1004-0137	
,	Expires March 31, 2007	
	5. Lease Serial No.	
	LC-069107	
	6. If Indian, Allottee or Tribe Name	
	7. If Unit or CA/Agreement, Name and/or N	o
	8910169240	
	East Millman Pool Unit	
)	8. Well Name and No.	
	East Millman Tr 5 #7	
	Pool Unit	
	9. API Well No.	
M	30-015-34124 S I	
	10. Field and Pool, or Exploratory Area	
	Millman QN-GB-SA, East	

11. County or Parish, State

Other New Well

July 2005 (State)

			Eddy	NM_		
12. CHECK APPROPE	HECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA					
TYPE OF SUBMISSION		TYPE OF ACTION				
Notice of Intent	Acidize	Deepen	Production (Start/Resume)	Water Shut-Off		
Subsequent Report	Alter Casing	Fracture Treat	Reclamation	Well Integrity		

New Construction

Plug and Abandon

Recomplete

Water Disposal

Temporarily Abandon

3b. Phone No. (include area collection)

(940) 723-2166

13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the final site is ready for final inspection.)

SEE ATTACHED

Casing Repair

Change Plans

Convert to Injection

Note: Well is a State well; however, Tract 6 is Federal. Therefore, we request BIM update database to include this well. ACCEPTED FOR RECORD

> AUG 2 3 2005 ALEXIS C. SWOBODA PETROLEUM ENGINEER

14. I hereby certify that the foregoing is true and correct Name (Printed/Typed)	Title
	Production Analyst
Weller Crawa	Date August 12, 2005

sture Crava	Date August 12, 200	D5							
THIS SPACE FOR FEDERAL OR STATE OFFICE USE									
Approved by	Title	Date	_						
Conditions of approval, if any, are attached. Approval of this notice does not warrant of certify that the applicant holds legal or equitable title to those rights in the subject least which would entitle the applicant to conduct operations thereon.	Office se								

Title 18 U.S.C. Section 1001, and Title 43 U.S.C. Section 1212, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

East Millman Pool Unit 5-7 API #30-015-34124

- 1. Spudded 12 1/4" hole 4:30 PM 7-6-05. Drilled to 345' KB & ran 8 jts 8 5/8" 24#/ft. surface csg and cemented w/225 sx of cement. Cement circulated to surface (circulate 34 sx to pit). WOC 18 hrs. Pressure test BOP and 8 5/8" surface casing to 1,000 psig for 30 minutes. Held OK.
- 2. Drilled 7 7/8" hole to 2737'. Ran 71 jts 5 1/2", 15.50#/ft. csg, set @ 2723' KB. Cemented w/800 sx of cement. Plug down @ 6:17 PM 7-12-05. Cement circulated to surface (circulate 179 sx to pit).
- 3. Test 5 1/2" production casing to 1,500 psig for 30 minutes. Held OK. Perforated Grayburg formation one shot at each of the following depths: 2309', 2312', 2315', 2318', 2339', 2342', 2345', 2348', 2351', 2354', 2388', 2391', 2394', 2424', 2427', 2430', 2433', 2444', 2447', 2450', 2453', 2466', 2469', 2472'.
- 4. On 7-18-05 acidized perforations w/3,000 gals 15% NEFE.
- 5. On 7-19-05 sand fraced perforations w/103,500 gals 10 lb brine water, 20,000 lbs of BJ LiteProp 125, and 5,000 lbs Super LC 16/30 sand.