District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 For drilling and production facilities, submit to appropriate NMOCD District Office.
For downstream facilities, submit to Santa Fe office

Form C-144

June 1, 2004

Pit or Below-Grade Tank Registration or Closure

Is pit or below-grade tank covered by a "general plan"? Yes No X Type of action: Registration of a pit or below-grade tank Closure of a pit or below-grade tank X		
	e: 432-684-4293 e-mail address:	2 29E
Pit Type: Drilling X Production Disposal Workover Emergency Lined X Unlined Liner type: Synthetic X Thickness 12/20 mil Clay Pit Volumebbl	Below-grade tank Volume:bbl Type of fluid: Construction material: Double-walled, with leak detection? Yes If not, explain why not	
Depth to ground water (vertical distance from bottom of pit to seasonal high water elevation of ground water.)	Less than 50 feet 50 feet or more, but less than 100 feet 100 feet or more	(20 points) (10 points) (0 points) X
Wellhead protection area: (Less than 200 feet from a private domestic water source, or less than 1000 feet from all other water sources.)	Yes No	(20 points) (0 points) X
Distance to surface water: (horizontal distance to all wetlands, playas, irrigation canals, ditches, and perennial and ephemeral watercourses.)	Less than 200 feet 200 feet or more, but less than 1000 feet 1000 feet or more	(20 points) (10 points) (0 points)X
If this is a pit closure: (1) Attach a diagram of the facility showing the pit's	Ranking Score (Total Points) relationship to other equipment and tanks. (2) Indica	0 Points te disposal location: (check the onsite box if
your are burying in place) onsite X offsite If offsite, name of facility		
Additional Comments: Work plan for closure pit. Pit contents will be mixed with earthen material to stiffen pit contents. Encapsulation trench will be constructed		
and lined with a 12 mil synthetic liner. Pit contents will be placed in a lined trench. A 20 mil synthetic liner will then be placed over the pit contents with a 3' over lap of the under lying pit area. The capping liner will then have a min. of 3' of top soil placed on top. A 48 hour notice will be provided to the Oil Conservation Division before		
pit closure actions are begun.		
I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that the above-described pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines X , a general permit , or an (attached) alternative OCD-approved plan . Date: 09/12/05 Printed Name/Title		
Approval: Printed Name/Title Mike Grafthar Alst II Signature Mile Brusewer Date: 9/13/15-		