

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

RE	P 18	Arte	 <u></u>
	Carlo Baro	-1 A)

FORM APPROVED OMB NO. 1004-0135 Expires: July 31, 2010

	Exp	pire	es:	Jul	y	3	ĺ,	
ease Seria	al N	lo.						

SUNDRY NOTICES AND REPORTS ON WELLS ^{NOV} 2 7 2012	
bandoned well. Use form 3160-3 (APD) for such proposals	

NMLC029395B

Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals ARTEQIA					6. If Indian, Allottee or Tribe Name		
SUBMIT IN TRIPLICATE - Other instructions on reverse side.					7. If Unit or CA/Agre	ement, Name and/or No.	
Type of Well ☐ Gas Well ☐ Other				8. Well Name and No. TURNER B 1			
Name of Operator Contact: TERRY B CALLAHAN LINN OPERATING INCORPORATED E-Mail: tcallahan@linnenergy.com				9. API Well No. 30-015-05181-00-S1			
3a. Address 600 TRAVIS STREET SUITE 5100 HOUSTON, TX 77002 3b. Ph Ph: 2			nclude area code 4272	e)	10. Field and Pool, or Exploratory GRAYBURG		
4. Location of Well (Footage, Sec., 7	., R., M., or Survey Description	n)	-		11. County or Parish, and State		
Sec 17 T17S R31E SESE 990FSL 330FEL					EDDY COUNTY, NM		
12. CHECK APPE	ROPRIATE BOX(ES) TO	O INDICATE N	ATURE OF	NOTICE, R	EPORT, OR OTHE	R DATA	
TYPE OF SUBMISSION	:	· .	ТҮРЕ О	F ACTION		· · · · · · · · · · · · · · · · · · ·	
- Notice of Intent	☐ Acidize	☐ Deeper	eepen Pro		ion (Start/Resume)	☐ Water Shut-Off	
□ Notice of Intent	☐ Alter Casing	Fractur	e Treat	☐ Reclam	ation	☐ Well Integrity	
Subsequent Report	☐ Casing Repair	□ New C	onstruction	☐ Recomp	olete	Other	
☐ Final Abandonment Notice	Change Plans	Plug ar	nd Abandon	Tempor	arily Abandon	_	
	☐ Convert to Injection	□ Plug B	ack	☐ Water Disposal			
Attach the Bond under which the wo following completion of the involved testing has been completed. Final Al determined that the site is ready for f	operations. If the operation repairs of the operation operation is operations.	esults in a multiple c	ompletion or rec	completion in a iding reclamation	new interval, a Form 310 in, have been completed, ccepted as to plugg	50-4 shall be filed once and the operator has	
MI RU; dug out cellar; NDWH	, LD 1 jt of tbg. NUBOP;	RU to run tbg, o	lose in well.	1	iability under bond in face restoration is	is retained until	
10/24/2012							
PU tbg, TIH tag BP @ 2770. Class C Neat cmt from 2416-2 2 w/ 35 sxs of cmt. POH, stoc started flowing. RIH w/ 5-1/2" Class C Neat cmt; displ cmt to	2770. Received OK from od back 1110' of tbg. LD pkr to 1110'. Set pkr, w o 1320'. Closed well in, r	Cheryl M/Jame the rest. Perf 5 aterflow isolated	s Amos w/ Bl -1/2" csg @ ′ @ 1420'. So	LM to combir 1420'. Well	RECLANDUE_4		
14. Thereby certify that the foregoing is	true and correct. Electronic Submission # For LINN OPERA	#160381 verified b	y the BLM We	ell Informatio	n System	•	
	nmitted to AFMSS for proc	essing by KURT	SIMMONS on	11/16/2012 (1	2KMS3183SE)		
Name (Printed/Typed) TERRY B	CALLAHAN	T	itle REGU	LATORY SP	ECIALIST III		
Signature (Electronic S	Submission)	D	ate 11/15/2	2012			
	THIS SPACE FO	OR FEDERAL	OR STATE	OFFICE U	SE		
Approved By ACCEPT	Lanca		JAMES A _{Fitle} SUPERV	AMOS ISOR EPS		Date 11/25/2012	
Conditions of approval, if any, are attache certify that the applicant holds legal or eq which would entitle the applicant to conditions.	uitable title to those rights in th uct operations thereon.	ne subject lease	Office Carlsba				
Title 18 U.S.C. Section 1001 and Title 43	U.S.C. Section 1212, make it	a crime for any pers	on knowingly ar	nd willfully to n	nake to any department o	r agency of the United	

** BLM REVISED ** BLM REVISED ** BLM REVISED ** BLM REVISED ** Accepted for record

| 1 | 1 | 28 | 2012 | NMOCD

Additional data for EC transaction #160381 that would not fit on the form

32. Additional remarks, continued

10/25/2012

Open well, no water flow. Pressure up on plug, held 500 psi 20 mins. POH w/ tbg, LD pkr, RIH open ended tag plug @ 1300', POH w/ tbg, stand back 10 jts tbg, LD rest. Perf 4 sqz holes at 645', POH WL. RIH w/ pkr on tbg to 309' set pkr. Sqz 65 sxs Class C cmt displaced cmt to 457'. WOC. RIse pkr, POH w/ tbg & pkr, RIH w/ tbg tag cmt plug @ 433'. POH tbg, LD. NDBOP. Perft 4 sqz holes @ 250', POH WL. NU WH w/ 2' tbg sub. Sqz 95 sxs Class C cmt from 250' to surface. SISD 50 psi on csg.

10/26/2012

Remove well head cap; cmt 6' down topped off. RD clean I.ocation.

11/7/2012

Dig up and cut off well head. Weld on ground level marker, dig up dead men. Clean location, job complete.