UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

arlesia	,] (E			
	5. Lease Serial NMNM67			

FORM APPROVED DMB NO. 1004-0135 Expires: July 31, 2010 I No. 102

	IO HOLO AND INLI O		' K	(V		
Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.		6. If Indian, Allottee or Tribe Name				
SUBMIT IN TRII	PLICATE - Other instruc	tions on reverse	side.		7. If Unit or CA/Agree	ment, Name and/or No.
Type of Well	ner				8. Well Name and No. PARKWAY 35 FED	DERAL COM 4H
Name of Operator SM ENERGY COMPANY		VICKIE MARTINE Z@SM-ENERGY.0			9. API Well No. 30-015-39839	
3a. Address 3300 N "A" STREET BLDG 7- MIDLAND, TX 79705	200	3b. Phone No. (incl Ph: 432-688-17 Fx: 432-688-170	09		10. Field and Pool, or E PARKWAY BON	
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)					11. County or Parish, a	nd State
Sec 35 T19S R29E 450FSL 330FWL				. •	EDDY COUNTY	, NM
12. CHECK APPF	ROPRIATE BOX(ES) TO	D INDICATE NA	TURE OF N	NOTICE, RI	EPORT, OR OTHER	DATA
TYPE OF SUBMISSION	TYPE OF ACTION					
➤ Notice of Intent	☐ Acidize	☐ Deepen		□ Product	ion (Start/Resume)	■ Water Shut-Off
	☐ Alter Casing	☐ Fracture Treat		□ Reclam	ation	
☐ Subsequent Report	□ Casing Repair	■ New Construction		☐ Recomp		Other
Final Abandonment Notice	Final Abandonment Notice Change Plans Plug and Abandon				orarily Abandon	
13. Describe Proposed or Completed Ope	Convert to Injection	☐ Plug Bac		☐ Water I		
If the proposal is to deepen directional Attach the Bond under which the wor following completion of the involved testing has been completed. Final Abdetermined that the site is ready for final and the site is ready for fi	k will be performed or provide operations. If the operation re- bandonment Notices shall be fil- inal inspection.)	The Bond No. on file s sults in a multiple com ed only after all requir	vith BLM/BIA pletion or reco ements, includ	Required sui impletion in a i ing reclamatio	bsequent reports shall be f new interval, a Form 3160 n, have been completed, a	iled within 30 days 0-4 shall be filed once and the operator has
DUE TO UNFAVORABLE WE REQUESTS TO PLUG AND A COM 4H. SM ENERGY COM OF THE SALT AT 1,100 FT, T COMBINATION OF CLASS H CEMENT WILL BE BROUGH' EQUIPMENT IS MOVED FRO	ABANDON THE SURFAC IPANY WILL ATTEMPT T TOP OF SALT AT 390 FT AND CLASS C CEMEN T UP TO SURFACE. A D	E AND FIRST INTO FILL THE WELD AND THE SURFAT WITH LCM ADD	TERMEDIAT LBORE AS ACE CASIN ITIVES. ON	FE SECTION DEEP AS F G SHOE AT NCE INSIDE	NS OF THE PARKW. POSSIBLE TO COVE F250 FT WITH A ETHE SURFACE CA	AY 35 FEDERAL ER THE BASE ASING
Egon MENT 10 MOVED THE	,				RECEIVE	D
SEE ATTACHED FOR					DEC 05 2012	t e
CONDITIONS OF API	PROVAL		:	N	MOCD ARTE	SIA
14. Thereby certify that the foregoing is	true and correct. Electronic Submission #	161056 verified by	he BI M We			
	For SM EN	ERGY COMPANY,	sent to the C	arlsbad	Oyolom	
Name (Printed/Typed) VICKIE M.	ARTINEZ	Title	ENGIN	EER TECH	" ONE	
Signature (Electronic S	Submission)	Date	11/26/2	012	APPROV	
•	THIS SPACE FO	OR FEDERAL O	R STATE	OFFICE U	SE 3	COLUMN TO THE REAL PROPERTY OF THE PERTY OF
Approved By		Tit	e		Shife	MANAGEMENT O MANAGENCE
Conditions of approval, if any, are attache certify that the applicant holds legal or equivalent would entitle the applicant to conductive the applicant to conduct the applicant the appl	uitable title to those rights in the	not warrant or e subject lease	ĭce		BUREAU OF LAN	FIELD
Fitle 18 U.S.C. Section 1001 and Title 43	U.S.C. Section 1212, make it a	crime for any person	nowingly and	willfully to m	ake to any department or a	agency of the United ·

** OPERATOR-SUBMITTED ** OPERATOR-SUBMITTED ** OPERATOR-SUBMITTED **

Accepted for record MMOCD

OPERATOR'S NAME: WELL NAME & NO.:

SURFACE HOLE FOOTAGE: BOTTOM HOLE FOOTAGE

LOCATION:

COUNTY:

SM ENERGY COMPANY

PARKWAY 35 FEDERAL #4H

450' FSL & 330' FWL 660' FSL & 330' FEL

Section 35, T.19 S., R.29 E., NMPM

Eddy County, New Mexico

Sundry dated 11/26/2012 - 30-015-39839

See various remarks in AFMSS operator did not PLUG the well as of 12/03/2012 current TD is 750' as of 12/02/2012

They had 9 attempts to set plug across the loss circulation zone and 5 times they were able to get cement back up into the surface casing. Their contingence plan is to attempt to re-drill the hole they have been working on this for 12 days.

EGF 12/03/2012

BUREAU OF LAND MANAGEMENT Carlsbad Field Office 620 East Greene Street Carlsbad, New Mexico 88220 575-234-5972

Permanent Abandonment of Federal Wells Conditions of Approval

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within <u>ninety (90)</u> days from the approval date of this Notice of Intent to Abandon.

If you are unable to plug the well by the 90th day provide this office, prior to the 90th day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.

The rig used for the plugging procedure cannot be released and moved off without the prior approval of the authorized officer. Failure to do so may result in enforcement action.

- 2. <u>Notification:</u> Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Eddy County, call 575-361-2822; <u>Lea County, call 575-393-3612</u>.
- 3. <u>Blowout Preventers</u>: A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The BOP must be installed and maintained as per API and manufacturer recommendations. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.
- 4. <u>Mud Requirement:</u> Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of **brine** water. Minimum nine (9) pounds per gallon.
- 5. <u>Cement Requirement</u>: Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. Any plug that requires a tag will have a minimum WOC time of 4 hours.

In lieu of a cement plug across perforations in a cased hole (not for any other plugs), a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient. Before pumping or bailing cement on top of CIBP, tag will be required to verify depth. Based on depth, a tag of the cement may be deemed necessary.

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

6. Dry Hole Marker: All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The BLM is to be notified a minimum of 4 hours prior to the wellhead being cut off to verify that cement is to surface in the casing and all annuluses. Wellhead cut off shall commence within ten (10) calendar days of the well being plugged. If the cut off cannot be done by the 10th day, the BLM is to be contacted with justification to receive an extension for completing the cut off.

The well bore shall then be capped with a 4-inch pipe, 10-feet in length, 4 feet above ground and embedded in cement, unless otherwise noted in COA (requirements will be attached). The following information shall be permanently inscribed on the dry hole marker: well name and number, name of the operator, lease serial number, surveyed location (quarter-quarter section, section, township and range or other authorized survey designation acceptable to the authorized officer such as metes and bounds).

- 7. <u>Subsequent Plugging Reporting:</u> Within 30 days after plugging work is completed, file one original and three copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. **Show date well was plugged.**
- 8. <u>Trash:</u> All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration will be required. See attached reclamation procedure.

EGF 101311



United States Department of the Interior

BUREAU OF LAND MANAGEMENT

Carlsbad Field Office 620 E. Greene St. Carlsbad, New Mexico 88220-6292 www.blm.gov/nm



In Reply Refer To: 1310

Reclamation Objectives and Procedures

Reclamation Objective: Oil and gas development is one of many uses of the public lands and resources. While development may have a short- or long-term effect on the land, successful reclamation can ensure the effect is not permanent. During the life of the development, all disturbed areas not needed for active support of production operations should undergo "interim" reclamation in order to minimize the environmental impacts of development on other resources and uses. At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and productivity of the land and water are restored.

The long-term objective of final reclamation is to set the course for eventual ecosystem restoration, including the restoration of the natural vegetation community, hydrology, and wildlife habitats. In most cases this means returning the land to a condition approximating or equal to that which existed prior to the disturbance. The final goal of reclamation is to restore the character of the land and water to its predisturbance condition. The operator is generally not responsible for achieving full ecological restoration of the site. Instead, the operator must achieve the short-term stability, visual, hydrological, and productivity objectives of the surface management agency and take steps necessary to ensure that long-term objectives will be reached through natural processes.

To achieve these objectives, remove any and all contaminants, scrap/trash, equipment, pipelines and powerlines. Strip and remove caliche, contour the location to blend with the surrounding landscape, redistribute the native soils, provide erosion control as needed, rip and seed as specified in the original APD COA. This will apply to well pads, facilities, and access roads. Barricade access road at the starting point. If reserve pits have not reclaimed due to salts or other contaminants, submit a plan for approval, as to how you propose to provide adequate restoration of the pit area.

- The Application for Permit to Drill or Reenter (APD, Form 3160-3), Surface Use Plan of
 Operations must include adequate measures for stabilization and reclamation of disturbed lands.
 Oil and Gas operators must plan for reclamation, both interim and final, up front in the APD
 process as per Onshore Oil and Gas Order No. 1.
- 2. For wells and/or access roads not having an approved plan, or an inadequate plan for surface reclamation (either interim or final reclamation), the operator must submit a proposal describing the procedures for reclamation. For interim reclamation, the appropriate time for submittal would be when filing the Well Completion or Recompletion Report and Log (Form 3160-4). For final reclamation, the appropriate time for submittal would be when filing the Notice of Intent, or the Subsequent Report of Abandonment, Sundry Notices and Reports on Wells (Form 3160-5). Interim reclamation is to be completed within 6 months of well completion, and final reclamation is to be completed within 6 months of well abandonment.
- 3. The operator must file a Subsequent Report Plug and Abandonment (Form 3160-5) following the plugging of a well.
- 4. Previous instruction had you waiting for a BLM specialist to inspect the location and provide you with reclamation requirements. If you have an approved Surface Use Plan of Operation and/or an approved Sundry Notice, you are free to proceed with reclamation as per approved APD. If you have issues or concerns, contact a BLM specialist to assist you. It would be in your interest to have a BLM specialist look at the location and access road prior to the removal of reclamation

equipment to ensure that it meets BLM objectives. Upon conclusion submit a Form 3160-5, Subsequent Report of Reclamation. This will prompt a specialist to inspect the location to verify work was completed as per approved plans.

- 5. The approved Subsequent Report of Reclamation will be your notice that the native soils, contour and seedbed have been reestablished. If the BLM objectives have not been met the operator will be notified and corrective actions may be required.
- 6. It is the responsibility of the operator to monitor these locations and/or access roads until such time as the operator feels that the BLM objective has been met. If after two growing seasons the location and/or access roads are not showing the potential for successful revegetation, additional actions may be needed. When you feel the BLM objectives have been met submit a Final Abandonment Notice (FAN), Form 3160-5, stating that all reclamation requirements have been achieved and the location and/or access road is ready for a final abandonment inspection.
- 7. At this time the BLM specialist will inspect the location and/or access road. If the native soils and contour have been restored, and the revegetation is successful, the FAN will be approved, releasing the operator of any further liability of the location and/or access road. If the location and/or access road have not achieved the objective, you will be notified as to additional work needed or additional time being needed to achieve the objective.

If there are any questions, please feel free to contact any of the following specialists:

Jim Amos Supervisory Environmental Protection Specialist 575-234-5909, 575-361-2648 (Cell)

Terry Gregston Environmental Protection Specialist 575-234-5958

Bobby Ballard Environmental Protection Specialist 575-234-2230

Randy Rust Environmental Protection Specialist 575-234-5943

Linda Denniston Environmental Protection Specialist 575-234-5974

Jennifer Van Curen Environmental Protection Specialist 575-234-5905

Justin Frye Environmental Protection Specialist 575-234-5922 Cody Layton Natural Resource Specialist 575-234-5959

Trishia Bad Bear Natural Resource Specialist 575-393-3612

Todd Suter Surface Protection Specialist 575-234-5987

Doug Hoag Civil Engineering Technician 575-234-5979