	UNITED STATE EPARTMENT OF THE	INTERIOR	ON	DRM APPROVED 4B NO. 1004-0135 pires: July 31, 2010	
SUNDRY	UREAU OF LAND MANA NOTICES AND REPO	ORTS ON WELLSCP Artesia	5. Lease Serial N NMNM2263		
Do not use th	is form for proposals to	o drill or to re-enter an PD) for such proposals.		ttee or Tribe Name	
SUBMIT IN TRIPLICATE - Other instructions on reverse side.			7. If Unit or CA/	7. If Unit or CA/Agreement, Name and/or No.	
f. Type of Well ⊠ Oil Well □ Gas Well □ Ot		8. Well Name and No. EAST PECOS FEDERAL 22 1H			
— — — — — — — — — — — — — — — — — — — —		CHARLES K AHN	9. API Well No. 30-015-405	9. API Well No. 30-015-40568-00-X1	
3a. Address 3817 NW EXPRESSWAY SUITE 950 OKLAHOMA CITY, OK 73112		3b. Phone No. (include area code Ph: 405-996-5771 Fx: 405-996-5772) 10. Field and Po UNDESIGN		
4. Location of Well (Footage, Sec., T., R., M., or Survey Descript			11. County or Pa	11. County or Parish, and State	
Sec 22 T26S R29E SESW 250FSL 1690FWL		*.	ÉDDY COL	INTY, NM	
				•	
12. CHECK APP	ROPRIATE BOX(ES) T	O INDICATE NATURE OF	NOTICE, REPORT, OR OT	THER DATA	
TYPE OF SUBMISSION	· · · · · · · · · · · · · · · · · · ·	TYPE O	F ACTION		
Notice of Intent	□ ^{Acidize}	Deepen	Production (Start/Resum	e) 🔲 Water Shut-Off	
—	Alter Casing	Fracture Treat	Reclamation	U Well Integrity	
Subsequent Report	Casing Repair	□ New Construction	Recomplete		
□ Final Abandonment Notice	Change Plans	$\square \frac{Plug}{Plug} \operatorname{Back}$	☐ Temporarily Abandon ☐ Water Disposal		
Attach the Bond under which the wo following completion of the involved testing has been completed. Final Al determined that the site is ready for f A bond log was ran on the Ea shoe is at 2840 feet). In orde	rk will be performed or provid d operations. If the operation r bandonment Notices shall be f final inspection.) Ist Pecos Fed 22-1H. TC r to provide cement	esults in a multiple completion or rec iled only after all requirements, inclu DC was indicated at 4160 feet	ured and true vertical depths of all A. Required subsequent reports sh ompletion in a new interval, a Forn ding reclamation, have been comp (9 5/8 inch casing	all be filed within 30 days n 3160-4 shall be filed once	
Attach the Bond under which the wo following completion of the involved testing has been completed. Final Al determined that the site is ready for f A bond log was ran on the Ea	rk will be performed or provid d operations. If the operation r bandonment Notices shall be f final inspection.) Inst Pecos Fed 22-1H. TC r to provide cement tandards, it is proposed f ktender), .25% PF46 (An	v, give subsurface locations and meas le the Bond No. on file with BLM/BL esults in a multiple completion or rec iled only after all requirements, inclu DC was indicated at 4160 feet to pump 250 sks of 35:65 Poz ti Foam), .2% PF13 (retarder)	ured and true vertical depths of all A. Required subsequent reports sh ompletion in a new interval, a Forn ding reclamation, have been comp (9 5/8 inch casing ?C? with 5% PF44 mixed at 12.6 ppg	all be filed within 30 days n 3160-4 shall be filed once leted, and the operator has	
Attach the Bond under which the wo following completion of the involved testing has been completed. Final Al determined that the site is ready for f A bond log was ran on the Ea shoe is at 2840 feet). In orde tie-back conforming to BLM si (Salt), 6% PF20 (Bentonite Ea	rk will be performed or provid d operations. If the operation r bandonment Notices shall be f final inspection.) ast Pecos Fed 22-1H. TC r to provide cement tandards, it is proposed t xtender), .25% PF46 (An ch x 9 5/8 inch casing. T	v, give subsurface locations and meas le the Bond No. on file with BLM/BL esults in a multiple completion or rec iled only after all requirements, inclu DC was indicated at 4160 feet to pump 250 sks of 35.65 Poz ti Foam), .2% PF13 (retarder) his slurry will be displaced to the second to pump 250 sks of 35.65 Poz	 ured and true vertical depths of all A. Required subsequent reports shompletion in a new interval, a Forn ding reclamation, have been comp (9 5/8 inch casing ?C? with 5% PF44 mixed at 12.6 ppg 2500 feet. 	all be filed within 30 days n 3160-4 shall be filed once leted, and the operator has	
Attach the Bond under which the wo following completion of the involved testing has been completed. Final Al determined that the site is ready for f A bond log was ran on the Ea shoe is at 2840 feet). In orde tie-back conforming to BLM si (Salt), 6% PF20 (Bentonite Ea	rk will be performed or provid d operations. If the operation r bandonment Notices shall be f final inspection.) ast Pecos Fed 22-1H. TC r to provide cement tandards, it is proposed t xtender), .25% PF46 (An ch x 9 5/8 inch casing. T	y, give subsurface locations and meas le the Bond No. on file with BLM/BL esults in a multiple completion or rec illed only after all requirements, inclu DC was indicated at 4160 feet to pump 250 sks of 35:65 Poz ti Foam), .2% PF13 (retarder) his slurry will be displaced to NCCOPICC L. ICCOICC	ured and true vertical depths of all A. Required subsequent reports sh ompletion in a new interval, a Forn ding reclamation, have been comp (9 5/8 inch casing ?C? with 5% PF44 mixed at 12.6 ppg 2500 feet.	all be filed within 30 days n 3160-4 shall be filed once leted, and the operator has ECEIVED DEC 1 2 2012	
Attach the Bond under which the wo following completion of the involved testing has been completed. Final Al determined that the site is ready for f A bond log was ran on the Ea shoe is at 2840 feet). In orde tie-back conforming to BLM si (Salt), 6% PF20 (Bentonite Ea	rk will be performed or provid d operations. If the operation r bandonment Notices shall be f final inspection.) ast Pecos Fed 22-1H. TC r to provide cement tandards, it is proposed t xtender), .25% PF46 (An ch x 9 5/8 inch casing. T	y, give subsurface locations and meas le the Bond No. on file with BLM/BL esults in a multiple completion or rec illed only after all requirements, inclu DC was indicated at 4160 feet to pump 250 sks of 35:65 Poz ti Foam), .2% PF13 (retarder) his slurry will be displaced to NCCOPICC L. ICCOICC	ured and true vertical depths of all A. Required subsequent reports sh ompletion in a new interval, a Forn ding reclamation, have been comp (9 5/8 inch casing ?C? with 5% PF44 mixed at 12.6 ppg 2500 feet.	all be filed within 30 days n 3160-4 shall be filed once leted, and the operator has ECEIVED DEC 1 2 2012	
Attach the Bond under which the wo following completion of the involvec testing has been completed. Final Al determined that the site is ready for f A bond log was ran on the Ea shoe is at 2840 feet). In orde tie-back conforming to BLM si (Salt), 6% PF20 (Bentonite Ex (2.03 cf/sk) down the 5 1/2 inc	rk will be performed or provid d operations. If the operation r bandonment Notices shall be f final inspection.) Ist Pecos Fed 22-1H. TC r to provide cement tandards, it is proposed f tandards, it is proposed f	y, give subsurface locations and meas le the Bond No. on file with BLM/BL esults in a multiple completion or rec illed only after all requirements, inclu DC was indicated at 4160 feet to pump 250 sks of 35:65 Poz ti Foam), .2% PF13 (retarder) his slurry will be displaced to NCCOPICC L. ICCOICC	ured and true vertical depths of all A. Required subsequent reports sh ompletion in a new interval, a Forn ding reclamation, have been comp (9 5/8 inch casing ?C? with 5% PF44 mixed at 12.6 ppg 2500 feet.	all be filed within 30 days n 3160-4 shall be filed once leted, and the operator has	
Attach the Bond under which the wo following completion of the involved testing has been completed. Final Al determined that the site is ready for f A bond log was ran on the Ea shoe is at 2840 feet). In orde tie-back conforming to BLM si (Salt), 6% PF20 (Bentonite Ex (2.03 cf/sk) down the 5 1/2 ind Run & CR and 4. Thereby certify that the foregoing is	rk will be performed or provid d operations. If the operation r bandonment Notices shall be f final inspection.) ist Pecos Fed 22-1H. TC r to provide cement tandards, it is proposed t tandards, it is proposed t	y, give subsurface locations and meas le the Bond No. on file with BLM/BL esults in a multiple completion or rec iled only after all requirements, inclu DC was indicated at 4160 feet to pump 250 sks of 35:65 Poz ti Foam), .2% PF13 (retarder) his slurry will be displaced to NOCOPICC L. FOCOTO NMOCD JCS D JA D JA D JA D JA D JA D JA D JA D JA	ured and true vertical depths of all A. Required subsequent reports sh ompletion in a new interval, a Forn ding reclamation, have been comp (9 5/8 inch casing ?C? with 5% PF44 mixed at 12.6 ppg 2500 feet. M - CFO II Information System the Carlsbad	all be filed within 30 days n 3160-4 shall be filed once leted, and the operator has ECEIVED DEC 1 2 2012	
Attach the Bond under which the wo following completion of the involved testing has been completed. Final Al determined that the site is ready for f A bond log was ran on the Ea shoe is at 2840 feet). In orde tie-back conforming to BLM si (Salt), 6% PF20 (Bentonite Ex (2.03 cf/sk) down the 5 1/2 ind Run a CR and 4. Thereby certify that the foregoing is	rk will be performed or provid d operations. If the operation r bandonment Notices shall be f final inspection.) Ist Pecos Fed 22-1H. TC r to provide cement tandards, it is proposed t tandards, it is proposed t	y, give subsurface locations and meas le the Bond No. on file with BLM/BL esults in a multiple completion or rec iled only after all requirements, inclu DC was indicated at 4160 feet to pump 250 sks of 35:65 Poz ti Foam), .2% PF13 (retarder) his slurry will be displaced to NMOCD JC D JC D JC D JC D JC D JC D JC D JC	ured and true vertical depths of all A. Required subsequent reports sh ompletion in a new interval, a Forn ding reclamation, have been comp (9 5/8 inch casing ?C? with 5% PF44 mixed at 12.6 ppg 2500 feet. M - CFO II Information System the Carlsbad	all be filed within 30 days n 3160-4 shall be filed once leted, and the operator has ECEIVED DEC 1 2 2012	
Attach the Bond under which the wo following completion of the involved testing has been completed. Final Al determined that the site is ready for f A bond log was ran on the Ea shoe is at 2840 feet). In orde tie-back conforming to BLM si (Salt), 6% PF20 (Bentonite Ex (2.03 cf/sk) down the 5 1/2 ind Run a CR and 4. Thereby certify that the foregoing is Con	rk will be performed or provid d operations. If the operation r bandonment Notices shall be f final inspection.) ast Pecos Fed 22-1H. TC r to provide cement tandards, it is proposed t xtender), .25% PF46 (An ch x 9 5/8 inch casing. T Fo NMOC Strue and correct. Electronic Submission a For RKI EXPLC nmitted to AFMSS for provide S K AHN	y, give subsurface locations and meas le the Bond No. on file with BLM/BL esults in a multiple completion or rec iled only after all requirements, inclu DC was indicated at 4160 feet to pump 250 sks of 35:65 Poz ti Foam), .2% PF13 (retarder) his slurry will be displaced to NMOCD JC D JC D JC D JC D JC D JC D JC D JC	ured and true vertical depths of all A. Required subsequent reports sh ompletion in a new interval, a Forn ding reclamation, have been comp (9 5/8 inch casing ?C? with 5% PF44 mixed at 12.6 ppg 2500 feet. M - CFO II Information System the Carlsbad 12/06/2012 (13KMS4039SE) REGULATORY MANAGER	all be filed within 30 days n 3160-4 shall be filed once leted, and the operator has ECEIVED DEC 1 2 2012	
Attach the Bond under which the wo following completion of the involved testing has been completed. Final Al determined that the site is ready for f A bond log was ran on the Ea shoe is at 2840 feet). In orde tie-back conforming to BLM si (Salt), 6% PF20 (Bentonite Ex (2.03 cf/sk) down the 5 1/2 ind A Thereby certify that the foregoing is Name (Printed/Typed) CHARLES	rk will be performed or provid d operations. If the operation r bandonment Notices shall be f final inspection.) ist Pecos Fed 22-1H. TC r to provide cement tandards, it is proposed f ktender), .25% PF46 (An ch x 9 5/8 inch casing. T Fo NMOC Submit and correct. Electronic Submission f For RKI EXPLC nmitted to AFMSS for prov S K AHN Submission)	y, give subsurface locations and meas le the Bond No. on file with BLM/BL esults in a multiple completion or rec iled only after all requirements, inclu DC was indicated at 4160 feet to pump 250 sks of 35:65 Poz ti Foam), .2% PF13 (retarder) his slurry will be displaced to NMOCD JC D JU D JU D JU D JU D JU D JU D JU D JU	ured and true vertical depths of all A. Required subsequent reports sh ompletion in a new interval, a Forn ding reclamation, have been completion (9 5/8 inch casing ?C? with 5% PF44 mixed at 12.6 ppg 2500 feet. M - CFC II Information System the Carlsbad 12/06/2012 (13KMS4039SE) REGULATORY MANAGER 2012	all be filed within 30 days n 3160-4 shall be filed once leted, and the operator has ECEIVED DEC 1 2 2012	
Attach the Bond under which the wo following completion of the involvec testing has been completed. Final Al determined that the site is ready for f A bond log was ran on the Ea shoe is at 2840 feet). In orde tie-back conforming to BLM si (Salt), 6% PF20 (Bentonite E) (2.03 cf/sk) down the 5 1/2 ind A Thereby certify that the foregoing is Con Name (Printed/Typed) CHARLES Signature (Electronic S	rk will be performed or provid d operations. If the operation r bandonment Notices shall be f final inspection.) Inst Pecos Fed 22-1H. TC r to provide cement tandards, it is proposed f tandards, it is proposed	y, give subsurface locations and meas le the Bond No. on file with BLM/BL esults in a multiple completion or rec iled only after all requirements, inclu DC was indicated at 4160 feet to pump 250 sks of 35:65 Poz ti Foam), 2% PF13 (retarder) his slurry will be displaced to NMOCD JC D JQ D JQ D JQ H61717 verified by the BLM We DRATION & PROD LLC, sent to cessing by KURT SIMMONS on Title HS&E/I Date 12/05/2	ured and true vertical depths of all A. Required subsequent reports sh ompletion in a new interval, a Forn ding reclamation, have been completion (9 5/8 inch casing ?C? with 5% PF44 mixed at 12.6 ppg 2500 feet. M - CFC II Information System the Carlsbad 12/06/2012 (13KMS4039SE) REGULATORY MANAGER 2012	all be filed within 30 days n 3160-4 shall be filed once leted, and the operator has DEC 1 2 2012 DCD ARTESIA	
Attach the Bond under which the wo following completion of the involved testing has been completed. Final Al determined that the site is ready for f A bond log was ran on the Ea shoe is at 2840 feet). In orde tie-back conforming to BLM si (Salt), 6% PF20 (Bentonite Ex (2.03 cf/sk) down the 5 1/2 ind 4. Thereby certify that the foregoing is Con Name (<i>Printed/Typed</i>) CHARLES Signature (Electronic S Approved By CHRISTOPHER W/ inditions of approval, if any, are attached tify that the applicant holds legal or equilibrium of the sector of the se	rk will be performed or provid d operations. If the operation r bandonment Notices shall be f final inspection.) Inst Pecos Fed 22-1H. TC r to provide cement tandards, it is proposed f tandards, it is proposed f for NMOC Submission f For RKI EXPLC nmitted to AFMSS for provide S K AHN Submission) THIS SPACE F	y, give subsurface locations and meas le the Bond No. on file with BLM/BL esults in a multiple completion or rec iled only after all requirements, inclu DC was indicated at 4160 feet to pump 250 sks of 35:65 Poz ti Foam), 2% PF13 (retarder) his slurry will be displaced to NMOCD JC D JQ D JQ D JQ H61717 verified by the BLM We DRATION & PROD LLC, sent to cessing by KURT SIMMONS on Title HS&E/I Date 12/05/2 OR FEDERAL OR STATE * TitlePETROLE es not warrant or	ured and true vertical depths of all A. Required subsequent reports sh ompletion in a new interval, a Forn ding reclamation, have been completed (9 5/8 inch casing ?C? with 5% PF44 mixed at 12.6 ppg 2500 feet. M - CFC M - CFC III Information System the Carlsbad 12/06/2012 (13KMS4039SE) REGULATORY MANAGER 2012 OFFICE USE	all be filed within 30 days n 3160-4 shall be filed once leted, and the operator has DEC 1 2 2012 DCD ARTESIA	
Attach the Bond under which the wo following completion of the involved testing has been completed. Final Al determined that the site is ready for f A bond log was ran on the Ea shoe is at 2840 feet). In orde tie-back conforming to BLM si (Salt), 6% PF20 (Bentonite Ex (2.03 cf/sk) down the 5 1/2 ind A Thereby certify that the foregoing is Name (Printed/Typed) CHARLES	rk will be performed or provid d operations. If the operation r bandonment Notices shall be f final inspection.) ist Pecos Fed 22-1H. TC r to provide cement tandards, it is proposed to ktender), .25% PF46 (An ch x 9 5/8 inch casing. T A <i>Lo NMOC</i> <i>Submit q</i> <i>Construction of the second construction</i> <i>Submit and correct</i> . Electronic Submission of For RKI EXPLC mmitted to AFMSS for provide S K AHN Submission) THIS SPACE F ALLS ed. Approval of this notice doo uitable title to those rights in the uct operations thereon. U.S.C. Section 1212, make it	A give subsurface locations and meas le the Bond No. on file with BLM/BL esults in a multiple completion or rec iled only after all requirements, inclu DC was indicated at 4160 feet to pump 250 sks of 35:65 Poz ti Foam), 2% PF13 (retarder) his slurry will be displaced to NMOCD JC D III D III D IIII D IIIII D IIII D IIIII D IIIIII D IIIII D IIIIII D IIIII D IIIIIIII	ured and true vertical depths of all A. Required subsequent reports sh ompletion in a new interval, a Forn ding reclamation, have been comp (9 5/8 inch casing ?C? with 5% PF44 mixed at 12.6 ppg 2500 feet. M - CFO II Information System the Carlsbad 12/06/2012 (13KMS4039SE) REGULATORY MANAGER 2012 OFFICE USE EUM ENGINEER d d d willfully to make to any departm	all be filed within 30 days n 3160-4 shall be filed once leted, and the operator has ECEIVED DEC 1 2 2012 DCD ARTESIA Date 12/10/20	
Attach the Bond under which the wo following completion of the involved testing has been completed. Final Al determined that the site is ready for f A bond log was ran on the Ea shoe is at 2840 feet). In orde tie-back conforming to BLM si (Salt), 6% PF20 (Bentonite Ex (2.03 cf/sk) down the 5 1/2 ind 4. Thereby certify that the foregoing is Con Name (<i>Printed/Typed</i>) CHARLES Signature (Electronic S Approved By CHRISTOPHER WA inditions of approval, if any, are attache tify that the applicant holds legal or equich would entitle the applicant to cond the 18 U.S.C. Section 1001 and Title 43 States any false, fictitious or fraudulent	rk will be performed or provid d operations. If the operation r bandonment Notices shall be f final inspection.) (ast Pecos Fed 22-1H. TC r to provide cement tandards, it is proposed ta tandards, it is proposed ta tandards, it is proposed to tandards, it is proposed to the tandards, it is proposed to tandards, it is prop	A give subsurface locations and meas le the Bond No. on file with BLM/BL esults in a multiple completion or rec iled only after all requirements, inclu DC was indicated at 4160 feet to pump 250 sks of 35:65 Poz ti Foam), 2% PF13 (retarder) his slurry will be displaced to NMOCD JC D III FOOD D IIII FOOD D IIII FOOD D IIII FOOD D IIIII FOOD D IIIII FOOD CESSING by KURT SIMMONS on Title HS&E/I Date 12/05/2 OR FEDERAL OR STATE es not warrant or he subject lease Office Carlsba a crime for any person knowingly an	ured and true vertical depths of all A. Required subsequent reports sh ompletion in a new interval, a Forn ding reclamation, have been comp (9 5/8 inch casing ?C? with 5% PF44 mixed at 12.6 ppg 2500 feet. M - CFO II Information System the Carlsbad 12/06/2012 (13KMS4039SE) REGULATORY MANAGER 2012 OFFICE USE EUM ENGINEER d d d willfully to make to any departm	all be filed within 30 days n 3160-4 shall be filed once leted, and the operator has ECEIVED DEC 1 2 2012 DCD ARTESIA Date 12/10/20 rent or agency of the United	