

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103
Revised August 1, 2011

WELL API NO. 30-015-40533	
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>	
6. State Oil & Gas Lease No. B0-1969	
7. Lease Name or Unit Agreement Name Roo 22 State	
8. Well Number #11	
9. OGRID Number 16696	
10. Pool name or Wildcat ARTESIA ; GLORIETA-YESO (O) - 96830	
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>	
2. Name of Operator OXY USA INC	
3. Address of Operator PO BOX 4294; HOUSTON, TX 77210	
4. Well Location Unit Letter <u>K</u> : 1907 feet from the <u>S</u> line and 1794 feet from the <u>W</u> line Section <u>22</u> Township <u>17S</u> Range <u>28E</u> NMPM County <u>EDDY</u>	
11. Elevation (Show whether DR, RKB, RT, GR, etc.) <u>3617' GR</u>	

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: COMPLETION ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

11/05/2012 -RU SCHLUMBERGER WIRELINE MAKE TWO RUNS WITH GR-CBL-VDL-CCL-LOGS, RUN ONE WITH 0 PSI AND ONE WITH 1000 PSI, TAG PBTD @ 4790' RUN BOTH LOGS FROM 4790' TO SURFACE, BOTH LOGS SHOW THAT WE HAVE GOOD CEMENT.

11/07/2012 -PERFORATIONS: 4761.3' TO 4770', 4564' to 4572.7', 4461.3' TO 4470', 4262' to 4270.7', 4082' TO 4090.7', 3816.3' to 3825', 3660' TO 3668.7', 3559' to 3567.7'


5 SPF & 0.48 EHD

11/07/2012 FRAC with 80,819 gal linear gel, 464,000 gal cross-linked gel, 7,500 gal 15% HCl acid, 16,000 lbs 100 mesh SD, and 720,000 lbs 16/30 resin coated SD. RD FRAC TANKS & WIRLINE.

11/13/2012 - MIRU CLEANOUT RIG. BEGIN AFTER FRAC CLEANOUT.

11/14/2012 - COMPLETE AFTER FRAC CLEANOUT TO PBTD.

11/15/2012 - Run ESP and production equipment. RDMO.



I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE [Signature] TITLE REGULATORY ANALYST DATE 12/11/2012

Type or print name JENNIFER DUARTE E-mail address: jennifer_duarte@oxy.com PHONE: 713-513-6640

For State Use Only

APPROVED BY: [Signature] TITLE Dir. & Supervisor DATE 12/13/2012

Conditions of Approval (if any):

Well:	Roo 22 St # 11
API:	30-015-40533
Surface Location	
Producing Method Code:	P
Well Completion Data:	
Spud Date:	10/19/2012
TD DATE:	10/25/2012
Ready Date (COMPLETED DATE):	11/16/2012
RIG RELEASE DATE:	10/26/2012
Date Frac setup:	11/7/2012
Date Frac rigdown:	11/7/2012
Date post-frac cleanout started:	11/13/2012
Date post-frac cleanout finished:	11/14/2012
TD:	4865'
PBTD:	4790'
Perforations: (INTERVALS, SPF, SIZE)	4761.3' TO 4770', 4564' to 4572.7', 4461.3' TO 4470', 4262' to 4270.7', 4082' TO 4090.7', 3816.3' to 3825', 3660' TO 3668.7', 3559' to 3567.7' 5 SPF & 0.48 EHD
Frac Details	FRAC with 80,819 gal linear gel, 464,000 gal cross-linked gel, 7,500 gal 15% HCl acid, 16,000 lbs 100 mesh SD, and 720,000 lbs 16/30 resin coated SD
DHC, MC:	-
Surface Casing - Date Set:	10/20/2012
Surface Casing - Hole Size:	12-1/4"
Surface Casing - Type & weight:	36# J-55 LTC
Surface Casing - Casing Size:	9-5/8"
Surface Casing - Depth Set:	425'
Surface Casing - Sacks Cement:	400 sx
Surface Casing - TOC:	Surface (circ'd)
Date & test data for Surface Casing:	10/21/12 - test to 2300 psi (test good)
Production Casing - Date Set:	10/26/2012
Production Casing - Hole Size:	7-7/8"
Production Casing - Type & Weight:	17# L-80 LTC
Production Casing - Casing Size:	5-1/2"
Production Casing - Depth Set:	4865'
Production Casing - Sacks Cement:	1310 sx
Production Casing - TOC:	Surface (circ'd)
Date & test data for Production Casing:	11/05/12; 5000 psi, held pressure for 30 min (test good).
Tubing Size:	2-7/8"
Tubing Depth:	3441'
Well Test Data:	
Date New Oil:	12/1/2012
Test Date:	12/2/2012
Test Length:	24
Tbg. Pressure:	330
Csg. Pressure:	126
Choke Size:	-
Oil:	140
Water:	1722
Gas:	215
GAS - OIL RATIO	1535 scf/bbl
OIL GRAVITY - API (CORR)	39
Test Method:	P
DISPOSITION OF GAS (SOLD, USED FOR FUEL, ETC)	SOLD (currently being flared but will be sold)

1907' FSL x 1794' FWL Sec 22, T17S - R28E Eddy Co, NM
Yeso West 60% WI

Spud date: 10/19/2012

Completion Date: 11/07/2012

☐ ACTUAL

OXY USA INC

Roo 22 State # 11

30-015-40533

Luis Tarazona 12/04/12

9 5/8", 36# J-55

@ 425'

w/400 sx-TOC-Surf-Circ

Top Glorieta @ 3404'

Top Paddock @ 3478'

Top Blinebry @ 3938'

Stage 4 Perforations

4b - 3,559' - 3,567.7'

4a - 3,660' - 3,668.7'

Stage 3 Perforations

3b - 3,816.3' - 3,825'

3a - 4,082' - 4,090.7'

Stage 2 Perforations


2b - 4,262' - 4,270.7'

2a - 4,461.3' - 4,470'

Stage 1 Perforations

1b - 4,564' - 4,572.7'

1a - 4,761.3' - 4,770'



PBDT @

4790'

TD 4858'

5 1/2", 17# L-80

@ 4865' Cement to surface
w/1310 sx TOC - Surf - Circ