Form 316(55' (August 2007)

UNITED STATES DEPARTMENT OF THE INTERIOR

FORM APPROVED OMB NO. 1004-0135

BUREAU OF LAND MANAGEMENT SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.					Expires: July 31, 2010		
					5. Lease Serial No. NMNM102917		
					6. If Indian, Allottee or	r Tribe Name	
					o. If maran, / monec of	The Pulle	
SUBMIT IN TRIE	PLICATE - Other ins	tructions	on reverse side.		7. If Unit or CA/Agree	ment, Name and/or No.	
1. Type of Well		<u> </u>		·	8. Well Name and No.		
☑ Oil Well ☐ Gas Well ☐ Other					RDX FEDERAL 21 12		
Name of Operator RKI EXPLORATION & PROD	ict: CHARLES K AHN Drkixp.com			9. API Well No. 30-015-40560-00-X1			
3a. Address 3817 NW EXPRESSWAY SUITE 950 OKLAHOMA CITY, OK 73112		3b. Phone No. (include area code) Ph: 405-996-5771			10. Field and Pool, or Exploratory BRUSHY DRAW		
		Fx: 405-996-5-42-IVED			DRUSHT DRAV	v	
4. Location of Well (Footage, Sec., T., R., M., or Survey Descr		iption)	TEULIVEL		11. County or Parish,	and State	
Sec 21 T26S R30E NENW 430FNL 1330FWL			DEC 31 2012		EDDY COUNTY	, NM	
	•		ARACCO ADTO			•	
12. CHECK APPE	ROPRIATE BOX(ES		CATE NATURE OF A		PORT, OR OTHE	R DATA	
TYPE OF SUBMISSION	TYPE OF ACTION						
Notice of Intent	□ Acidize		Deepen _	_	on (Start/Resume)	□ Water Shut-Off	
Subsequent Beneat			☐ Fracture Treat	☐ Reclamat		☐ Well Integrity	
Subsequent Report ☐ Casing Repair			☐ New Construction	Recomplete		Other Drilling Operations	
☐ Final Abandonment Notice	☐ Change Plans		☐ Plug and Abandon	_	rily Abandon	Drining Operations	
Convert to		tion	☐ Plug Back	☐ Water Di	sposal		
13. Describe Proposed or Completed Op- If the proposal is to deepen directions Attach the Bond under which the wo following completion of the involved testing has been completed. Final Al determined that the site is ready for f	ally or recomplete horizon rk will be performed or properations. If the operations and onment Notices shall	tally, give sub ovide the Bon on results in a	surface locations and measu d No. on file with BLM/BIA multiple completion or reco	ared and true ver A. Required subs completion in a ne	tical depths of all pertir sequent reports shall be ew interval, a Form 316	nent markers and zones. filed within 30 days 0-4 shall be filed once	
SPUDDED THE WELL ON OF OF 13-3/8 INCH 54.5#, J55, S	N 9/19/2012. DRILLI STC CASING WITH S	ED 17-1/2 I SHOE @ 93	NCH HOLE TO 940 FE 34.22 FEET, FLOAT CO	ET ON 9/20/ OLLAR @ 88	2012. RAN 23 JOII 9.10 FEET.	NTS	
Cementing:	·	•				٠.	
Lead: 675 SKS OF CLASS C (Class C +4%PF20 +		-2%PF1 +0.25 pps PF-46) YIELD = 1.75, DENSITY = 13.5					
	(0.000 0 770.7 = 0	 /0	o ppo	, 52			
TAIL: 200 SKS OF CLASS C	(Class C + 1%PF1))	/IELD = 1.3	4, DENSITY = 14.8				
CIRCULATED 215 SKS/67 BI	BLS BACK TO SURE	ACE		A.C.C.R	phod for recor	d	
	SEO DI IONI TO COM			/40~64	MMOCD		
	,			CRI	Jade 1/4/13	·	
14. Thereby certify that the foregoing is	true and correct. Electronic Submissi	on #164284	verified by the BLM Wel	I Information	System		
Con	For RKI EX	PLORATION	I & PROD LLC, sent to t by KURT SIMMONS on 1	he Carlsbad			
Name (Printed/Typed) CHARLES		processing	· 1	•	Y MANAGER	•	
	.		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,				
Signature (Electronic S	Submission)		Date 12/14/20	012		,	
	THIS SPAC	E FOR FE	DERAL OR STATE	OFFICE US	E		
Approved By ACCEPT	ED		JAMES A A	AMOS SOR EPS		Date 12/24/201	
THE TOTAL			I	and the second second		,	

OCD Artesia

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office Carlsbad

Additional data for EC transaction #164284 that would not fit on the form

32. Additional remarks, continued

ON 9/22/2012, TESTED SURFACE CASING TO 1500 PSI FOR 30 MINUTES = OK DRILLED OUT CEMENT 39.25 HOURS AFTER CEMENT IN PLACE.