	UNITED STA DEPARTMENT OF T	HE INTERIOR	OCD Artesia	E	FORM APPROVED OM B No. 1004-0137 xpires: March 31, 2007	
BUREAU OF LAND M SUNDRY NOTICES AND Do not use this form for proposa		REPORTS ON WELLS		 Lease Scrial No. SHL: NM 02447, BHL: NM 02447 If Indian, Allottee or Tribe Name 		
abandoned w	ell. Use Form 3160 -	3 (APD) for such	proposals.			
· · · · · · · · · · · · · · · · · · ·	IPLICATE- Other in	nstructions on rev	/erse side.		CA/Agreement, Name and/or 1	No.
1. Type of Well ✓ Oil Well□ □ [Gas Well 🗆 🔄 Oth	er		8. Well Name Big Eddy	e and No. 7 Unit 248H	
2. Name of Operator BOPCO, L. P.		3b. Phone No. (include area code)		9. API Well No. 30-015-40714		
P. O. Box 2760 Midland, TX 79702		432-683-2277		10. Field and Pool, or Exploratory Area		
 Location of Well (Footage, Sec., T., R. M., or Survey Description SHL: NENE, UL A, 1175' FNL, 10' FEL, Sec 35, T19S-I BHL: 380' FNL & 1155' FEL, Sec 34, T19S-R31E, Lat: 		R31E, Lat: N32.620864, Long: W103.830839		WC Williams Sink (Bone Spring) 11. County or Parish, State		
	PPROPRIATE BOX(ES)	· ·		l	unty, New Mexico	<u> </u>
TYPE OF SUBMISSION			TYPE OF ACTION		OTHER DATA	_
Notice of Intent	Acidize	Dcepen Fracture Treat	Production (Sta	rt/Resume)	Water Shut-Off Well Integrity	
Subsequent Report	Casing Repair Change Plans	Plug and Abando		andon	✓ Other Cement operation	ons
Attach the Bond under which t following completion of the in testing has been completed. Fi	he work will be performed or volved operations. If the opera inal Abandonment Notices sha	provide the Bond No. on f ation results in a multiple or	ile with BLM/BIA. Require completion or recompletion i	ed subsequent rep n a new interval,	a Form 3160-4 shall be filed o	iys nce
Attach the Bond under which t following completion of the in testing has been completed. Fi determined that the site is read BOPCO, L.P. respectfull Change the 9-5/8", 40#, J to surface across the Capi	he work will be performed or volved operations. If the opera- inal Abandonment Notices sha y for final inspection.) y requests to make the foll -55, LTC casing cement jo itan Reef. A DV tool and J	provide the Bond No. on f ation results in a multiple co Il be filed only after all req owing changes to the al b from one stage to two CCP will be set at appro	ile with BLM/BIA. Require ompletion or recompletion i uirements, including reclam bove captioned well: o stage. We believe this v oximately +/- 50' above t	d subsequent rep n a new interval, ation, have been vill increase th he top of the ro	orts shall be filed within 30 da a Form 3160-4 shall be filed o completed, and the operator have e chances of returning center fin a section of gauge have	nes. nys nce as nent ole as
Attach the Bond under which the following completion of the in testing has been completed. Find determined that the site is read BOPCO, L.P. respectfull Change the 9-5/8", 40#, J to surface across the Capit determined by physical capital are as follows:	he work will be performed or volved operations. If the opera inal Abandonment Notices sha y for final inspection.) y requests to make the foll -55, LTC casing cement jo itan Reef. A DV tool and I alliper log. Based on interp	provide the Bond No. on f ation results in a multiple or Il be filed only after all req owing changes to the all b from one stage to two SCP will be set at appro- retation and offsets, we	ile with BLM/BIA. Require ompletion or recompletion i uirements, including reclam bove captioned well: o stage. We believe this oximately +/- 50' above t e believe the top of the re	d subsequent rep n a new interval, ation, have been vill increase th he top of the ro	orts shall be filed within 30 da a Form 3160-4 shall be filed o completed, and the operator have e chances of returning center fin a section of gauge have	nes. nys nce as nent ole as
Attach the Bond under which the following completion of the in- testing has been completed. Fil determined that the site is ready BOPCO, L.P. respectfull Change the 9-5/8", 40#, J to surface across the Capit determined by physical ca- are as follows: Stage 1 - Tail: 625 sks Cla- Stage 2 - Lead: 525 sks Cla-	he work will be performed or volved operations. If the opera- inal Abandonment Notices sha y for final inspection.) y requests to make the foll -55, LTC casing cement jo itan Reef. A DV tool and J	provide the Bond No. on f ation results in a multiple or ll be filed only after all req owing changes to the all b from one stage to two CCP will be set at appro- retation and offsets, we s (13.6 ppg, 1.71 cu ft/sk es (12.7 ppg, 1.85 cu ft/s	ile with BLM/BIA. Require ompletion or recompletion i uirements, including reclam bove captioned well: stage. We believe this v oximately +/- 50' above to believe the top of the re stage of the recent	ed subsequent rep n a new interval, ation, have been will increase th he top of the re sef will be at 2,	orts shall be filed within 30 da a Form 3160-4 shall be filed o completed, and the operator ha e chances of returning cen sef in a section of gauge h 715'. Updated cement vol	nes. nys nce as nent ole as
Attach the Bond under which the following completion of the in- testing has been completed. Fil determined that the site is ready BOPCO, L.P. respectfull Change the 9-5/8", 40#, J to surface across the Capit determined by physical ca- are as follows: Stage 1 - Tail: 625 sks Cla- Stage 2 - Lead: 525 sks Cla-	he work will be performed or volved operations. If the opera- inal Abandonment Notices sha y for final inspection.) y requests to make the foll -55, LTC casing cement jo itan Reef. A DV tool and H alliper log. Based on interp ass "C" cement + additives ass "C" cement + additives	provide the Bond No. on f ation results in a multiple or ll be filed only after all req owing changes to the al b from one stage to two CCP will be set at appro- retation and offsets, we s (13.6 ppg, 1.71 cu ft/sk s (12.7 ppg, 1.85 cu ft/sk s (14.8 ppg, 1.33 cu ft/sk	ile with BLM/BIA. Require ompletion or recompletion i uirements, including reclam bove captioned well: stage. We believe this v oximately +/- 50' above to believe the top of the re believe the top of the re stage, SEE A7 (c) CONDI	ed subsequent rep n a new interval, ation, have been will increase th he top of the ro sef will be at 2, TACHEF FIONS [5]	orts shall be filed within 30 da a Form 3160-4 shall be filed o completed, and the operator has e chances of returning cent ef in a section of gauge has 715'. Updated cement vol	nnes. nys nce as nent ble as umes
Attach the Bond under which the following completion of the in- testing has been completed. Fil determined that the site is ready BOPCO, L.P. respectfull Change the 9-5/8", 40#, J to surface across the Capit determined by physical ca- are as follows: Stage 1 - Tail: 625 sks Cla- Stage 2 - Lead: 525 sks Cla-	he work will be performed or volved operations. If the opera- inal Abandonment Notices sha y for final inspection.) y requests to make the foll -55, LTC casing cement jo itan Reef. A DV tool and H alliper log. Based on interp ass "C" cement + additives ass "C" cement + additives ACCEPT	provide the Bond No. on f ation results in a multiple or ll be filed only after all req owing changes to the all b from one stage to two CCP will be set at appro- retation and offsets, we s (13.6 ppg, 1.71 cu ft/sk es (12.7 ppg, 1.85 cu ft/s	ile with BLM/BIA. Require ompletion or recompletion i uirements, including reclam bove captioned well: stage. We believe this v oximately +/- 50' above to believe the top of the re believe the top of the re stage, SEE A7 (c) CONDI	ed subsequent rep n a new interval, ation, have been will increase th he top of the ro sef will be at 2, TACHEF FIONS [5]	orts shall be filed within 30 da a Form 3160-4 shall be filed o completed, and the operator ha e chances of returning cen sef in a section of gauge h 715'. Updated cement vol	nnes. nys nce as nent ble as umes
Attach the Bond under which the following completion of the intesting has been completed. Findetermined that the site is reach BOPCO, L.P. respectfull Change the 9-5/8", 40#, J to surface across the Capi determined by physical car are as follows: Stage 1 - Tail: 625 sks Cla Stage 2 - Lead: 525 sks Cla Tail: 120 sks Cla	he work will be performed or volved operations. If the opera- inal Abandonment Notices sha y for final inspection.) y requests to make the foll -55, LTC casing cement jo itan Reef. A DV tool and I aliper log. Based on interp ass "C" cement + additives ass "C" cement + additives ACCEPTO N egoing is true and correct	provide the Bond No. on f ation results in a multiple or Il be filed only after all req owing changes to the all b from one stage to two CCP will be set at appro- retation and offsets, wo (13.6 ppg, 1.71 cu ft/sk (13.8 ppg, 1.85 cu ft/sk (14.8 ppg, 1.33 cu ft/sk CO fOr record	ile with BLM/BIA. Require ompletion or recompletion i uirements, including reclam bove captioned well: stage. We believe this v oximately +/- 50' above to believe the top of the re believe the top of the re stage, SEE A7 (c) CONDI	ed subsequent rep n a new interval, ation, have been will increase th he top of the ro sef will be at 2, TACHEF FIONS [5]	orts shall be filed within 30 da a Form 3160-4 shall be filed o completed, and the operator has e chances of returning cent ef in a section of gauge has 715'. Updated cement vol	nnes. nys nce as nent ble as umes
Attach the Bond under which the following completion of the in- testing has been completed. Fi determined that the site is read BOPCO, L.P. respectfull Change the 9-5/8", 40#, J- to surface across the Capi determined by physical ca- are as follows: Stage 1 - Tail: 625 sks Cla- Stage 2 - Lead: 525 sks Cla- Tail: 120 sks Cla- Tail: 120 sks Cla- Tail: 120 sks Cla-	he work will be performed or volved operations. If the opera- inal Abandonment Notices sha y for final inspection.) y requests to make the foll -55, LTC casing cement jo itan Reef. A DV tool and I aliper log. Based on interp ass "C" cement + additives ass "C" cement + additives ACCEPTO N egoing is true and correct	provide the Bond No. on f ation results in a multiple or ll be filed only after all req owing changes to the all b from one stage to two CCP will be set at appro- retation and offsets, wo (13.6 ppg, 1.71 cu ft/sk (13.8 ppg, 1.85 cu ft/sk (14.8 ppg, 1.33 cu ft/sk CO for record MOCD	ile with BLM/BIA. Require completion or recompletion i uirements, including reclam bove captioned well: e stage. We believe this volume to stage. We believe this volume e believe the top of the rec believe the top of the rec so k) SEE AT CONDI SEE AT	ed subsequent rep n a new interval, ation, have been will increase th he top of the ro eef will be at 2, TACHE FIONS	orts shall be filed within 30 da a Form 3160-4 shall be filed o completed, and the operator has the chances of returning center and the operator has the chances of returning center that the operator has the chances of returning center the chances of returning center that the operator has the operator	nnes. nys nce as nent ble as umes
Attach the Bond under which the following completion of the inin testing has been completed. Find determined that the site is read BOPCO, L.P. respectfull Change the 9-5/8", 40#, J to surface across the Capi determined by physical cr are as follows: Stage 1 - Tail: 625 sks Cla Stage 2 - Lead: 525 sks Cla Tail: 120 sks Cla 14. Thereby certify that the fore Name (Printed/Typed) Christopher Gie	he work will be performed or volved operations. If the opera- inal Abandonment Notices sha y for final inspection.) y requests to make the foll -55, LTC casing cement jo itan Reef. A DV tool and I aliper log. Based on interp ass "C" cement + additives lass "C" cement + additives ACCEPT N egoing is true and correct ase	provide the Bond No. on f ation results in a multiple or Il be filed only after all req owing changes to the all b from one stage to two CCP will be set at appro- retation and offsets, wo (13.6 ppg, 1.71 cu ft/sk (13.7 ppg, 1.85 cu ft/sk (14.8 ppg, 1.33 cu ft/sk OC for record MOCD	ile with BLM/BIA. Require completion or recompletion i uirements, including reclam bove captioned well: ostage. We believe this of communicately +/- 50' above t e believe the top of the re- solution $SEE AT$ (c) (c) (c) (c) (c) (c) (c) (c) (c) (c)	ed subsequent rep n a new interval, ation, have been will increase th he top of the ro eef will be at 2, TACHE FIONS	orts shall be filed within 30 da a Form 3160-4 shall be filed o completed, and the operator has e chances of returning cent ef in a section of gauge has 715'. Updated cement vol	nnes. nys nce as nent ble as umes
Attach the Bond under which the following completion of the in testing has been completed. Fil determined that the site is read BOPCO, L.P. respectfull Change the 9-5/8", 40#, J to surface across the Capi determined by physical ca are as follows: Stage 1 - Tail: 625 sks Cla Stage 2 - Lead: 525 sks Cla Stage 2 - Lead: 525 sks Cla Tail: 120 sks Cla 14. I hereby certify that the fore Name (<i>Printed/Typed</i>) Christopher Gie Signature	he work will be performed or volved operations. If the opera inal Abandonment Notices sha y for final inspection.) y requests to make the foll -55, LTC casing cement jo itan Reef. A DV tool and H aliper log. Based on interp itss "C" cement + additives lass "C" cement + additives Cement + additives ACCEPT N going is true and correct ise THIS SPACE FC attached. Approval of this no d or equitable title to those rig	provide the Bond No. on f ation results in a multiple or ll be filed only after all req owing changes to the all b from one stage to two SCP will be set at appro- retation and offsets, wo (13.6 ppg, 1.71 cu ft/sk (13.8 ppg, 1.71 cu ft/sk (14.8 ppg, 1.33 cu ft/sk (14.8 ppg, 1.33 cu ft/sk (14.8 ppg, 1.33 cu ft/sk (14.8 ppg, 1.33 cu ft/sk (14.8 ppg, 1.35 cu ft/sk (14.8 pp	ile with BLM/BIA. Require interpletion or recompletion i uirements, including reclam bove captioned well: o stage. We believe this violately +/- 50' above t e believe the top of the re- s) k) SEE AT CONDI SOURCE Drilling Engineer 12/37/2	ed subsequent rep n a new interval, ation, have been will increase th he top of the ro eef will be at 2, TACHE TIONS USE	orts shall be filed within 30 da a Form 3160-4 shall be filed o completed, and the operator has e chances of returning cent ref in a section of gauge h 715'. Updated cement vol REFERENCE APPROVAL MOCD ARTES MOCD ARTES ADDROVED eJAN 4 2013 75/ Chris Walls	nes. ays nce as nent ble as umes
Attach the Bond under which the following completion of the in- testing has been completed. Fi determined that the site is read BOPCO, L.P. respectfull Change the 9-5/8", 40#, J to surface across the Capi- determined by physical ca- are as follows: Stage 1 - Tail: 625 sks Cla- Stage 2 - Lead: 525 sks Cla- Tail: 120 sks Cla- Tail: 120 sks Cla- I4. I hereby certify that the fore Name (Printed/Typed) Christopher Gie Signature	he work will be performed or volved operations. If the opera inal Abandonment Notices sha y for final inspection.) y requests to make the foll -55, LTC casing cement jo itan Reef. A DV tool and I aliper log. Based on interp ass "C" cement + additives lass "C" cement + additives ACCEPT N egoing is true and correct ise THIS SPACE FC attached. Approval of this no l or equitable title to those rig o conduct operations thereon. e 43 U.S.C. Section 1212, mak	provide the Bond No. on f ation results in a multiple or ll be filed only after all req owing changes to the all b from one stage to two SCP will be set at appro- retation and offsets, wo (13.6 ppg, 1.71 cu ft/sk (13.8 ppg, 1.71 cu ft/sk (14.8 ppg, 1.33 cu ft/sk (14.8 ppg, 1.35 cu ft/sk (14.8 pp	ile with BLM/BIA. Require in power caption or recompletion i uirements, including reclam bove captioned well: o stage. We believe this violated with the top of the re- oximately +/- 50' above the top of the re- solution of the re- so	ed subsequent rep n a new interval, ation, have been will increase th he top of the ro eef will be at 2, TACHE TIONS USE USE Da BURE	orts shall be filed within 30 da a Form 3160-4 shall be filed o completed, and the operator has e chances of returning cen- ter in a section of gauge h 715'. Updated cement vol REFECEIVED FAPPROYAL FAPPROYAL FAPPROYAL FAPPROYAL FAPPROYAL FAPPROYAL FAPPROYAL FAPPROYAL FAPPROYAL FAPPROYED ADDED ARTESI	nnes. nys nce as nent ble as umes

Conditions of Approval

- 1. The minimum required fill of cement behind the 9-5/8 inch intermediate casing is:
 - a. First stage to DV tool:
 - Cement to circulate. If cement does not circulate, contact the appropriate BLM office before proceeding with second stage cement job. Operator should have plans as to how they will achieve circulation on the next stage.
 - b. Second stage above DV tool:
 - Cement to surface. If cement does not circulate, contact the appropriate BLM office. Wait on cement (WOC) time for a primary cement job is to include the lead cement slurry due to potash.