

RECEIVED

JAN 08 2013

ATS-12-816

FORM APPROVED
OMB No. 1004-0137
Expires October 31, 2014

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

MOCD ARTESIA

APPLICATION FOR PERMIT TO DRILL OR REENTER

1a. Type of work: ☒ DRILL ☐ REENTER		5. Lease Serial No. NM-12559	
1b. Type of Well: ☒ Oil Well ☐ Gas Well ☐ Other ☒ Single Zone ☐ Multiple Zone		6. If Indian, Allottee or Tribe Name JES 1/9/2013	
2. Name of Operator COG PRODUCTION LLC.		7. If Unit or CA Agreement, Name and No. -----	
3a. Address 2208 WEST MAIN STREET ARTESIA, NEW MEXICO 88210		8. Lease Name and Well No. <u>2(39625)</u> MOMBA "24" FED. COM. #3H	
3b. Phone No. (include area code) 575-748-6968		9. API Well No. <u>30-015-40946</u>	
4. Location of Well (Report location clearly and in accordance with any State requirements.) At surface 43' FNL & 2180' FEL SECTION 24 T26S-R28E At proposed prod. zone BHL 330' FSL & 2020' FEL SECTION 24 T26S-R28E		10. Field and Pool, or Exploratory <u>DELAWARE RIVER-BONE SPRING</u> <u>HAY HOLLOW</u>	
14. Distance in miles and direction from nearest town or post office* Approximately 14 miles South of Malaga New Mexico		11. Sec., T. R. M. or Blk. and Survey or Area SECTION 24 T26S-R28E	
15. Distance from proposed* location to nearest property or lease line, ft. (Also to nearest drig. unit line, if any) 43'		12. County or Parish EDDY	
16. No. of acres in lease 980		13. State NM	
17. Spacing Unit dedicated to this well 160			
18. Distance from proposed location* to nearest well, drilling, completed, applied for, on this lease, ft. 1400'		20. BLM/BIA Bond No. on file NMB-000845 NMB-000860	
21. Elevations (Show whether DF, KDB, RT, GL, etc.) 2923' GL		22. Approximate date work will start* WHEN APPROVED	
		23. Estimated duration 30 Days	
24. Attachments			

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No.1, must be attached to this form:

- | | |
|--|---|
| 1. Well plat certified by a registered surveyor. | 4. Bond to cover the operations unless covered by an existing bond on file (see Item 20 above). |
| 2. A Drilling Plan. | 5. Operator certification |
| 3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO must be filed with the appropriate Forest Service Office). | 6. Such other site specific information and/or plans as may be required by the BLM. |

25. Signature <i>Joe T. Janica</i>	Name (Printed/Typed) Joe T. Janica	Date 08/17/12
Title Permit Eng.		
Approved by (Signature) <i>/s/ James A. Amos</i>	Name (Printed/Typed)	Date JAN 4 2013
Title FIELD MANAGER	Office CARLSBAD FIELD OFFICE	

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Conditions of approval, if any, are attached.

APPROVAL FOR TWO YEARS

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Continued on page 2)

*(Instructions on page 2)

Carlsbad Controlled Water Basin

SEE ATTACHED FOR

CONDITIONS OF APPROVAL

Approval Subject to General Requirements
& Special Stipulations Attached

DISTRICT I
1625 N. French Dr., Hobbs, NM 88240
Phone (505) 393-6161 Fax: (505) 393-0720

DISTRICT II
811 S. First St., Artesia, NM 88210
Phone (505) 746-1283 Fax: (505) 746-9720

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410
Phone (505) 334-6176 Fax: (505) 334-6170

DISTRICT IV
1220 S. St. Francis Dr., Santa Fe, NM 87505
Phone (505) 476-3460 Fax: (505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-102
Revised August 1, 2011

Submit one copy to appropriate
District Office

OIL CONSERVATION DIVISION

1220 South St. Francis Dr.
Santa Fe, New Mexico 87505

WELL LOCATION AND ACREAGE DEDICATION PLAT

☐ AMENDED REPORT

API Number 302-015-40946	Pool Code 30215	Pool Name HAY HOLLOW; Wildcat, Bone Spring
Property Code 39619 39625	Property Name MOMBA 24 FEDERAL COM	Well Number 3H
OGRID No. 217955	Operator Name COG PRODUCTION LLC	Elevation 2923'

Surface Location

UL or lot No.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
B	24	26 S	28 E		43	NORTH	2180	EAST	EDDY

Bottom Hole Location If Different From Surface

UL or lot No.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
O	24	26 S	28 E		330	SOUTH	2020	EAST	EDDY

Dedicated Acres	Joint or Infill	Consolidation Code	Order No.
160			

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED
OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION


SURFACE LOCATION Lat - N 32°02'06.86" Long - W 104°02'21.25" NMSPCE- N 376682.606 E 632469.291 (NAD-83)	PROPOSED BOTTOM HOLE LOCATION Lat - N 32°01'18.67" Long - W 104°02'19.29" NMSPCE- N 371813.079 E 632651.173 (NAD-83)	OPERATOR CERTIFICATION I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division. <i>Melanie Parker</i> 8/27/12 Signature Date Printed Name Email Address <i>mparker@concho.com</i> SURVEYOR CERTIFICATION I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief. Date Surveyed Signature & Seal of Professional Surveyor Certificate No. Gary L. Jones 7977 BASIN SURVEYS 26791
---	--	--

CERTIFICATION:

I hereby certify that I, or persons under my direct supervision, have inspected the proposed drillsite and access route, that I am familiar with the conditions which presently exist; that the statements made in this plan are to the best of my knowledge, true and correct; and that the work associated with the operations proposed herein will be performed by COG Production LLC and its contractors and subcontractors in conformity with this plan and the terms and conditions under which it is approved. This statement is subject to the provisions of 18 U.S.C. 1001 for the filing of a false statement.

7-23-12
Date

COG PRODUCTION LLC


Rand French – Regulatory Advisor

COG Production LLC
DRILLING AND OPERATIONS PROGRAM
Momba 24 Fed Com #3H
SHL: 2180' FEL & 43' FNL of Section 24
BHL: 2020' FEL & 330' FSL of Section 24
Section 24 T26S R28E
Eddy County, New Mexico

In conjunction with Form 3160-3, Application for Permit to Drill subject well, COG Production LLC submits the following eleven items of pertinent information in accordance with BLM requirements.

1. Geological surface formation: Permian
2. The estimated tops of geologic markers & estimated depths at which anticipated water, oil or gas formations are expected to be encountered are as follows:

Rustler	57'	
Water	120'	
Top of Salt	843'	
Base of Salt	2,435'	
Delaware	2,625'	Oil
Bone Spring	6,326'	Oil
2 nd Bone Spring	7,966'	Oil
TD TVD	8,130'	
TD MD	12,798'	

No other formations are expected to give up oil, gas or fresh water in measurable quantities. The surface fresh water sands will be protected by setting 13-3/8" casing at 425' and circulating cement back to surface. All intervals will be isolated by setting 5 1/2" casing to total depth and tying back cement to a minimum of 500' into 9-5/8" csg.

3. Proposed Casing Program: All casing is new and API approved

Hole Size	Depths	Section	OD Casing	New/Used	Wt	Collar	Grade	Collapse Design Factor	Burst Design Factor	Tension Design Factor
17 1/2"	0' - 425'	Surface	13 3/8"	New	48#	STC	J-55	1.125	1.125	1.6
12 1/4"	0' - 2,645'	Intrmd	9 5/8"	New	36#	LTC	J-55	1.125	1.125	1.6
7 7/8"	0' - 12,798'	Production Curve & Lateral	5 1/2"	New	17#	LTC	P-110	1.125	1.125	1.6

- While running all casing strings, the pipe will be kept a minimum of 1/3 full at all times to avoid approaching the collapse pressure of casing.

4. Proposed Cement Program

a. 13-3/8" Surface

Slurry: 325 sx Class C + 2% CaCl₂
(14.8 ppg / 1.34 cuft/sx)

**Calculated w/50% excess on OH volumes

b. 9 5/8" Intermediate:

*See
Cort*

Lead: 425 sx Class C + 4% Gel + 2% CaCl₂
(13.5 ppg / 1.75 cuft/sx)

Tail: 250 sx Class C + 2% CaCl₂
(14.8 ppg / 1.34 cuft/sx)

**Calculated w/35% excess on OH volumes

d. 5 1/2" Production

Lead: 525 sx 50:50:10 H + Salt+Gilsonite+CFR-3+ HR601
(11.8 ppg / 2.5 cuft/sx)

Tail: 975 sx 50:50:2 H +Salt+GasStop +HR601 +CFR-3
(14.4 ppg / 1.25 cuft/sx)

**Calculated w/35% excess on OH volumes

- The above cement volumes could be revised pending the caliper measurement from the open hole logs.
- The 9-5/8" intermediate string is designed to circulate to surface.
- The production string will at least tie back 500' into 9-5/8" shoe

5. Minimum Specifications for Pressure Control:

Nipple up on 13 3/8 with annular preventer tested to 50% of rating working pressure by independent tester and the rest of the 2M system tested to 2000 psi.

Nipple up on 9 5/8 with 3M system tested 3000 psi to by independent tester.

Pipe rams will be operationally checked each 24 hour period. Blind rams will be operationally checked on each trip out of the hole. These checks will be noted on the daily tour sheets. A 2" kill line and a minimum 3" choke line will be included in the drilling spool located below the ram-type BOP. Other accessories to the BOP equipment will include a Kelly cock and floor safety valve (inside BOP) and choke lines and choke manifold with 3000 psi WP rating.

6. Estimated BHP:

Lateral TD = 3526 psi

7. Mud Program: The applicable depths and properties of this system are as follows:

Depth	Type System	Mud Weight	Viscosity (sec)	Waterloss (cc)
0' - 425'	Fresh Water	8.4	29	N.C.
425' - 2,645'	Brine	10	29	N.C.
2,645' - 12,798' (Lateral)	Cut Brine	8.8 - 9.2	29	N.C.

The necessary mud products for weight addition and fluid loss control will be on location at all times.

8. Auxiliary Well Control and Monitoring Equipment:

- a. A Kelly cock will be in the drill string at all times.
- b. A full opening drill pipe stabbing valve having the appropriate connections will be on the rig floor at all times.
- c. Hydrogen Sulfide detection equipment will be in operation after drilling out the 13 3/8" casing shoe until the 5 1/2" casing is cemented. Breathing equipment will be on location upon drilling the 13 3/8" shoe until total depth is reached.

9. Testing, Logging and Coring Program: *See COA*

- a. Drill stem tests will be based on geological sample shows.
- b. If open hole electrical logging is preformed, the program will be:
 - i. Total Depth to Intermediate Casing: Dual Laterolog-Micro Laterolog and Gamma Ray. Compensated Neutron – Z Density log with Gamma Ray and Caliper.
 - ii. Total Depth to Surface: Compensated Neutron with Gamma Ray
 - iii. No coring program is planned
 - iv. Additional testing will be initiated subsequent to setting the 5 1/2" production casing. Specific intervals will be targeted based on log evaluation, geological sample shows and drill stem tests.

10. Potential Hazards:

- a. No abnormal pressures or temperatures are expected. There is no known presence of H2S in this area. If H2S is encountered the operator will comply with the provisions of Onshore Oil and Gas Order No. 6. All personnel will be familiar with all aspects of safe operation of equipment being used to drill this well. No H2S is anticipated to be encountered.

11. Anticipated starting date and Duration of Operations:

- a. Road and location construction will begin after the BLM has approved the APD. Anticipated spud date will be as possible after BLM approval and as soon as a rig will be available. Move in operations and drilling is expected to take 30 days.

Production
COG Operating LLC

Eddy County, NM (NAD 83)

Momba 24 Federal Com 3H

Momba 24 Federal Com 3H

Wellbore #1

Plan: Plan #1

Standard Planning Report

12 July, 2012

Planning Report

Database:	Houston R5000 Database	Local Co-ordinate Reference:	Site Momba 24 Federal Com 3H
Company:	COG Operating LLC	TVD Reference:	WELL @ 2940'50ft (Original Well Elev)
Project:	Eddy County, NM (NAD 83)	MD Reference:	WELL @ 2940'50ft (Original Well Elev)
Site:	Momba 24 Federal Com 3H	North Reference:	Grid
Well:	Momba 24 Federal Com 3H	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Plan #1		

Project:	Eddy County, NM (NAD 83)	System Datum:	Mean Sea Level
Map System:	US State Plane 1983		
Geo Datum:	North American Datum 1983		
Map Zone:	New Mexico Eastern Zone		

Site:	Momba 24 Federal Com 3H		
Site Position:		Northing:	376,682.60 ft
From:	Map	Easting:	632,469.30 ft
Position Uncertainty:	0.00 ft	Slot Radius:	13.200 in
		Latitude:	32.03523736
		Longitude:	-104.03924062
		Grid Convergence:	0.16 °

Well	Momba 24 Federal Com 3H					
Well Position	+N-S	0.00 ft	Northing:	376,682.60 ft	Latitude:	32.03523736
	+E-W	0.00 ft	Easting:	632,469.30 ft	Longitude:	-104.03924062
Position Uncertainty		0.00 ft	Wellhead Elevation:		Ground Level:	2,923.00 ft

Wellbore	Wellbore #1				
Magnetics	Model Name	Sample Date	Declination (°)	Dip Angle (°)	Field Strength (nT)
	IGRF200510	7/12/2012	7.65	59.93	48,389

Design:	Plan #1			
Audit Notes:				
Version:	Phase:	PLAN	Tie On Depth:	0.00
Vertical Section:	Depth From (TVD) (ft)	+N-S (ft)	+E-W (ft)	Direction (°)
	0.00	0.00	0.00	177.86

Plan Sections											
Measured	Inclination	Azimuth	Vertical	+N-S	+E-W	Dogleg	Build	Turn	TFO	Target	
Depth	(°)	(°)	Depth	(ft)	(ft)	Rate	Rate	Rate	(°)		
(ft)			(ft)			(°/100ft)	(°/100ft)	(°/100ft)			
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		
7,652.54	0.00	0.00	7,652.54	0.00	0.00	0.00	0.00	0.00	0.00		
8,402.54	90.00	177.86	8,130.00	-477.13	17.82	12.00	12.00	0.00	177.86		
12,797.99	90.00	177.86	8,130.00	-4,869.53	181.88	0.00	0.00	0.00	0.00	PBHL (Momba 24 Fed	

Planning Report

Database:	Houston R5000 Database	Local Co-ordinate Reference:	Site Momba 24 Federal Com 3H
Company:	COG Operating LLC	TVD Reference:	WELL @ 2940:50ft (Original Well Elev)
Project:	Eddy County, NM (NAD 83)	MD Reference:	WELL @ 2940:50ft (Original Well Elev)
Site:	Momba 24 Federal Com 3H	North Reference:	Grid
Well:	Momba 24 Federal Com 3H	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Plan #1		

Planned Survey										
Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Vertical Section (ft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)	
7,652.54	0.00	0.00	7,652.54	0.00	0.00	0.00	0.00	0.00	0.00	
KOP - Start Build @ 12.00°/100'										
7,700.00	5.70	177.86	7,699.92	-2.36	0.09	2.36	12.00	12.00	0.00	
7,800.00	17.70	177.86	7,797.67	-22.58	0.84	22.59	12.00	12.00	0.00	
7,900.00	29.70	177.86	7,889.07	-62.66	2.34	62.71	12.00	12.00	0.00	
8,000.00	41.70	177.86	7,970.13	-120.86	4.51	120.95	12.00	12.00	0.00	
8,100.00	53.70	177.86	8,037.32	-194.64	7.27	194.77	12.00	12.00	0.00	
8,200.00	65.70	177.86	8,087.68	-280.75	10.49	280.95	12.00	12.00	0.00	
8,206.84	66.52	177.86	8,090.45	-287.00	10.72	287.20	12.00	12.00	0.00	
PP @ 8206.84 MD, 8090.45 TVD, 66.52 INC, 177.86 AZ, 287.20 VS										
8,300.00	77.70	177.86	8,119.03	-375.45	14.02	375.72	12.00	12.00	0.00	
8,400.00	89.70	177.86	8,129.99	-474.60	17.73	474.93	12.00	12.00	0.00	
8,402.54	90.00	177.86	8,130.00	-477.13	17.82	477.46	12.00	12.00	0.00	
Landing Point - Hold @ 90.00° INC, 177.86° AZ										
8,500.00	90.00	177.86	8,130.00	-574.53	21.46	574.93	0.00	0.00	0.00	
8,600.00	90.00	177.86	8,130.00	-674.46	25.19	674.93	0.00	0.00	0.00	
8,700.00	90.00	177.86	8,130.00	-774.39	28.92	774.93	0.00	0.00	0.00	
8,800.00	90.00	177.86	8,130.00	-874.32	32.66	874.93	0.00	0.00	0.00	
8,900.00	90.00	177.86	8,130.00	-974.25	36.39	974.93	0.00	0.00	0.00	
9,000.00	90.00	177.86	8,130.00	-1,074.18	40.12	1,074.93	0.00	0.00	0.00	
9,100.00	90.00	177.86	8,130.00	-1,174.11	43.85	1,174.93	0.00	0.00	0.00	
9,200.00	90.00	177.86	8,130.00	-1,274.04	47.59	1,274.93	0.00	0.00	0.00	
9,300.00	90.00	177.86	8,130.00	-1,373.97	51.32	1,374.93	0.00	0.00	0.00	
9,400.00	90.00	177.86	8,130.00	-1,473.90	55.05	1,474.93	0.00	0.00	0.00	
9,500.00	90.00	177.86	8,130.00	-1,573.83	58.78	1,574.93	0.00	0.00	0.00	
9,600.00	90.00	177.86	8,130.00	-1,673.76	62.52	1,674.93	0.00	0.00	0.00	
9,700.00	90.00	177.86	8,130.00	-1,773.69	66.25	1,774.93	0.00	0.00	0.00	
9,800.00	90.00	177.86	8,130.00	-1,873.62	69.98	1,874.93	0.00	0.00	0.00	
9,900.00	90.00	177.86	8,130.00	-1,973.55	73.71	1,974.93	0.00	0.00	0.00	
10,000.00	90.00	177.86	8,130.00	-2,073.48	77.45	2,074.93	0.00	0.00	0.00	
10,100.00	90.00	177.86	8,130.00	-2,173.41	81.18	2,174.93	0.00	0.00	0.00	
10,200.00	90.00	177.86	8,130.00	-2,273.34	84.91	2,274.93	0.00	0.00	0.00	
10,300.00	90.00	177.86	8,130.00	-2,373.27	88.64	2,374.93	0.00	0.00	0.00	
10,400.00	90.00	177.86	8,130.00	-2,473.21	92.38	2,474.93	0.00	0.00	0.00	
10,500.00	90.00	177.86	8,130.00	-2,573.14	96.11	2,574.93	0.00	0.00	0.00	
10,600.00	90.00	177.86	8,130.00	-2,673.07	99.84	2,674.93	0.00	0.00	0.00	
10,700.00	90.00	177.86	8,130.00	-2,773.00	103.57	2,774.93	0.00	0.00	0.00	
10,800.00	90.00	177.86	8,130.00	-2,872.93	107.31	2,874.93	0.00	0.00	0.00	
10,900.00	90.00	177.86	8,130.00	-2,972.86	111.04	2,974.93	0.00	0.00	0.00	
11,000.00	90.00	177.86	8,130.00	-3,072.79	114.77	3,074.93	0.00	0.00	0.00	
11,100.00	90.00	177.86	8,130.00	-3,172.72	118.50	3,174.93	0.00	0.00	0.00	
11,200.00	90.00	177.86	8,130.00	-3,272.65	122.24	3,274.93	0.00	0.00	0.00	
11,300.00	90.00	177.86	8,130.00	-3,372.58	125.97	3,374.93	0.00	0.00	0.00	
11,400.00	90.00	177.86	8,130.00	-3,472.51	129.70	3,474.93	0.00	0.00	0.00	
11,500.00	90.00	177.86	8,130.00	-3,572.44	133.43	3,574.93	0.00	0.00	0.00	
11,600.00	90.00	177.86	8,130.00	-3,672.37	137.17	3,674.93	0.00	0.00	0.00	
11,700.00	90.00	177.86	8,130.00	-3,772.30	140.90	3,774.93	0.00	0.00	0.00	
11,800.00	90.00	177.86	8,130.00	-3,872.23	144.63	3,874.93	0.00	0.00	0.00	
11,900.00	90.00	177.86	8,130.00	-3,972.16	148.36	3,974.93	0.00	0.00	0.00	
12,000.00	90.00	177.86	8,130.00	-4,072.09	152.10	4,074.93	0.00	0.00	0.00	
12,100.00	90.00	177.86	8,130.00	-4,172.02	155.83	4,174.93	0.00	0.00	0.00	
12,200.00	90.00	177.86	8,130.00	-4,271.95	159.56	4,274.93	0.00	0.00	0.00	
12,300.00	90.00	177.86	8,130.00	-4,371.88	163.29	4,374.93	0.00	0.00	0.00	

Planning Report

Database:	Houston R5000 Database	Local Co-ordinate Reference:	Site Momba 24 Federal Com 3H
Company:	COG Operating LLC	TVD Reference:	WELL @ 2940.50ft (Original Well Elev)
Project:	Eddy County, NM (NAD 83)	MD Reference:	WELL @ 2940.50ft (Original Well Elev)
Site:	Momba 24 Federal Com 3H	North Reference:	Grid
Well:	Momba 24 Federal Com 3H	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Plan #1		

Planned Survey									
Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Vertical Section (ft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)
12,400.00	90.00	177.86	8,130.00	-4,471.81	167.03	4,474.93	0.00	0.00	0.00
12,500.00	90.00	177.86	8,130.00	-4,571.74	170.76	4,574.93	0.00	0.00	0.00
12,600.00	90.00	177.86	8,130.00	-4,671.67	174.49	4,674.93	0.00	0.00	0.00
12,700.00	90.00	177.86	8,130.00	-4,771.60	178.22	4,774.93	0.00	0.00	0.00
12,797.99	90.00	177.86	8,130.00	-4,869.53	181.88	4,872.92	0.00	0.00	0.00
TD @ 12797.99' MD, 8130.00' TVD - PBHL (Momba 24 Federal Com 3H Plan 1)									

Design Targets									
Target Name	Dip Angle (°)	Dip Dir (°)	TVD (ft)	+N/-S (ft)	+E/-W (ft)	Northing (ft)	Easting (ft)	Latitude	Longitude
- hit/miss target									
- Shape									
PBHL (Momba 24 Feder	0.00	0.00	8,130.00	-4,869.53	181.88	371,813.08	632,651.18	32.02184991	-104.03869652
- plan hits target center									
- Point									

Plan Annotations					
Measured Depth (ft)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Comment	
7,652.54	7,652.54	0.00	0.00	KOP - Start Build @ 12.00°/100'	
8,206.84	8,090.45	-287.00	10.72	PP @ 8206.84 MD, 8090.45 TVD, 66.52 INC, 177.86 AZ, 287.20 VS	
8,402.54	8,130.00	-477.13	17.82	Landing Point - Hold @ 90.00° INC, 177.86° AZ	
12,797.99	8,130.00	-4,869.53	181.88	TD @ 12797.99' MD, 8130.00' TVD	




COG Operating LLC
Momba 24 Federal Com 3H
Eddy County, NM (NAD 83)
Plan #1



Surface Location		Ground Elev: 2923.00 WELL @ 2940.50ft (Original Well Elev)			
+N/-S	+E/-W	Northing	Easting	Latitude	Longitude
0.00	0.00	376682.61	632469.29	32.03523736	-104.03924062


TARGET DETAILS							
Name	TVD	+N/-S	+E/-W	Northing	Easting	Latitude	Longitude
PBHL (Momba 24 Federal Com 3H Plan 1)	8130.00	-4869.53	181.88	371813.08	632651.17	32.02184991	-104.03869852

SECTION DETAILS											
Sec	MD	Inc	Azi	TVD	+N/-S	+E/-W	Dleg	TFace	VSect	Annotation	
1	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		
2	7652.54	0.00	0.00	7652.54	0.00	0.00	0.00	0.00	0.00	KOP - Start Build @ 12.00°/100°	
3	8402.54	90.00	177.86	8130.00	-477.13	17.82	12.00	177.86	477.46	Landing Point - Hold @ 90.00° INC, 177.86° AZ	
4	12797.99	90.00	177.86	8130.00	-4869.53	181.88	0.00	0.00	4872.92	TD @ 12797.99' MD, 8130.00' TVD	




Azimuths to Grid North
True North: -0.16°
Magnetic North: 7.49°


Magnetic Field
Strength: 48389.0snT
Dip Angle: 59.93°
Date: 7/12/2012
Model: IGRF200510




2,000 psi BOP Schematic




3,000 psi BOP Schematic



2M Choke Manifold Equipment



3M Choke Manifold Equipment





New Mexico Office of the State Engineer **Water Column/Average Depth to Water**

No records found.

PLSS Search:

Section(s): 24

Township: 26S

Range: 28E

The data is furnished by the NMOSE/ISC and is accepted by the recipient with the expressed understanding that the OSE/ISC make no warranties, expressed or implied, concerning the accuracy, completeness, reliability, usability, or suitability for any particular purpose of the data.

7/23/12 8:06 AM

Page 1 of 1

WATER COLUMN/ AVERAGE
DEPTH TO WATER

COG Production LLC

Rig Plat & Closed Loop Equipment Diagram

Well pad will be 340' X ^{330'}~~3210'~~
with cellar in center of pad




Exhibit 1

COG PRODUCTION LLC
HYDROGEN SULFIDE DRILLING OPERATIONS PLAN

I. HYDROGEN SULFIDE TRAINING

All personnel, whether regularly assigned, contracted, or employed on an unscheduled basis, will receive training from a qualified instructor in the following areas prior to commencing drilling operations on this well:

- A. The hazards and characteristics of hydrogen sulfide (H₂S).
- B. The proper use and maintenance of personal protective equipment and life support systems.
- C. The proper use of H₂S detectors, alarms, warning systems, briefing areas, evacuation procedures, and prevailing winds.
- D. The proper techniques for first aid and rescue procedures.

In addition, supervisory personnel will be trained in the following areas:

- A. The effects of H₂S on metal components. If high tensile tubulars are to be used, personnel will be trained in their special maintenance requirements.
- B. Corrective action and shut-in procedures when drilling or reworking a well and blowout prevention and well control procedures.
- C. The contents and requirements of the H₂S Drilling Operations Plan and the Public Protection Plan.

There will be an initial training session just prior to encountering a known or probable H₂S zone (within 3 days or 500 feet) and weekly H₂S and well control drills for all personnel in each crew. The initial training session shall include a review of the site specific H₂S Drilling Operations Plan and the Public Protection Plan. This plan shall be available at the well site. All personnel will be required to carry documentation that they have received the proper training.

II. H₂S SAFETY EQUIPMENT AND SYSTEMS

Note: All H₂S safety equipment and systems will be installed, tested, and operational when drilling reaches a depth of 500 feet above, or three days prior to penetrating the first zone containing or reasonably expected to contain H₂S.

A. Well Control Equipment:

Flare line.

Choke manifold.

Blind rams and pipe rams to accommodate all pipe sizes with properly sized closing unit.

Auxiliary equipment to include: annular preventer, mud-gas separator, rotating head.

B. Protective equipment for essential personnel:

Mark II Surviveair 30-minute units located in the dog house and at briefing areas.

C. H₂S detection and monitoring equipment:

2 - portable H₂S monitor positioned on location for best coverage and response. These units have warning lights and audible sirens when H₂S levels of 20 ppm are reached.

D. Visual warning systems:

Caution/Danger signs shall be posted on roads providing direct access to location. Signs will be painted a high visibility yellow with black lettering of sufficient size to be readable at a reasonable distance from the immediate location. Bilingual signs will be used, when appropriate. See example attached.

E. Mud Program:

The mud program has been designed to minimize the volume of H₂S circulated to the surface.

F. Metallurgy:

All drill strings, casings, tubing, wellhead, blowout preventers, drilling spool, kill lines, choke manifold and lines, and valves shall be suitable for H₂S service.

G. Communication:

Company vehicles equipped with cellular telephone.

COG Production LLC has conducted a review to determine if an H₂S contingency plan is required for the above referenced well. We were able to conclude that any potential hazardous volume would be minimal. H₂S concentrations of wells in this area from surface to TD are low enough; therefore, we do not believe that an H₂S contingency plan is necessary.

W A R N I N G

**YOU ARE ENTERING AN H₂S AREA
AUTHORIZED PERSONNEL ONLY**

- 1. BEARDS OR CONTACT LENSES NOT ALLOWED**
- 2. HARD HATS REQUIRED**
- 3. SMOKING IN DESIGNATED AREAS ONLY**
- 4. BE WIND CONSCIOUS AT ALL TIMES**
- 5. CK WITH COG PRODUCTION LLC FOREMAN AT MAIN OFFICE**

COG PRODUCTION LLC

1-575-748-6940

EMERGENCY CALL LIST



	<u>OFFICE</u>	<u>MOBILE</u>	<u>HOME</u>
COG OPERATING LLC OFFICE	575-748-6940		
SHERYL BAKER	575-748-6940	432-934-1873	575-748-2396
RON BEASLEY	575-746-2010	432-254-9883	
SETH WILD	575-748-6940	432-528-3633	
DEAN CHUMBLEY	575-748-3303	575-748-5988	575-748-2426

EMERGENCY RESPONSE NUMBERS

	<u>OFFICE</u>
STATE POLICE	575-748-9718
EDDY COUNTY SHERIFF	575-746-2701
EMERGENCY MEDICAL SERVICES (AMBULANCE)	911 or 575-746-2701
EDDY COUNTY EMERGENCY MANAGEMENT (HARRY BURGESS)	575-887-9511
STATE EMERGENCY RESPONSE CENTER (SERC)	575-476-9620
CARLSBAD POLICE DEPARTMENT	575-885-2111
CARLSBAD FIRE DEPARTMENT	575-885-3125
NEW MEXICO OIL CONSERVATION DIVISION	575-748-1283
INDIAN FIRE & SAFETY	800-530-8693
HALLIBURTON SERVICES	800-844-8451

Well pad will be 330' X 340'
with cellar in center of pad

COG Production LLC
H₂S Equipment Schematic
Terrain: Shinnery sand hills.



 Briefing Area
w/SCBA

Location
Entry
Condition
Sign 

Prevailing Wind
Direction in SENM

 Primary Briefing
Area w/SCBA

Company Representative's Trailer

Secondary egress.




COG Production LLC
2208 West Main
Artesia, NM 88210

Exhibit 3

Production Facility Layout

Momba 24 Federal Com #3H
Section 24-T26S-R28E



PECOS DISTRICT CONDITIONS OF APPROVAL

OPERATOR'S NAME:	COG Production
LEASE NO.:	NM12559
WELL NAME & NO.:	3H Momba 24 Federal Com
SURFACE HOLE FOOTAGE:	43' FNL & 2180' FEL
BOTTOM HOLE FOOTAGE:	330' FSL & 2020 FEL
LOCATION:	Section 24, T.26 S., R.28 E., NMPM
COUNTY:	Eddy County, New Mexico

TABLE OF CONTENTS

Standard Conditions of Approval (COA) apply to this APD. If any deviations to these standards exist or special COAs are required, the section with the deviation or requirement will be checked below.

- ☐ **General Provisions**
- ☐ **Permit Expiration**
- ☐ **Archaeology, Paleontology, and Historical Sites**
- ☐ **Noxious Weeds**
- ☒ **Special Requirements**
 - River Watershed Protection
 - Tank Battery Requirements
 - Fence Requirement
 - Livestock Water Pipeline Requirement
 - Communitization Agreement
- ☒ **Construction**
 - Notification
 - Topsoil
 - Closed Loop System
 - Federal Mineral Material Pits
 - Well Pads
 - Roads
- ☐ **Road Section Diagram**
- ☒ **Drilling**
 - Medium Cave/Karst
 - Waste Material and Fluids
- ☐ **Production (Post Drilling)**
 - Well Structures & Facilities
- ☐ **Interim Reclamation**
- ☐ **Final Abandonment & Reclamation**